

A True System-on-Chip solution for 2.4 GHz IEEE 802.15.4 / ZigBee™


Applications

- 2.4 GHz IEEE 802.15.4 systems
- ZigBee™ systems
- Home/building automation
- Industrial Control and Monitoring
- Low power wireless sensor networks
- PC peripherals
- Set-top boxes and remote controls
- Consumer Electronics

Product Description

The **CC2430** comes in three different versions: CC2430-F32/64/128, with 32/64/128 KB of flash memory respectively. The **CC2430** is a true System-on-Chip (SoC) solution specifically tailored for IEEE 802.15.4 and ZigBee™ applications. It enables ZigBee™ nodes to be built with very low total bill-of-material costs. The **CC2430** combines the excellent performance of the leading **CC2420** RF transceiver with an industry-standard enhanced 8051 MCU, 32/64/128 KB flash memory, 8 KB RAM and many other powerful features. Combined with the industry leading ZigBee™ protocol stack (Z-Stack) from Figure 8 Wireless / Chipcon, the **CC2430** provides the market's most competitive ZigBee™ solution.

The **CC2430** is highly suited for systems where ultra low power consumption is required. This is ensured by various operating modes. Short transition times between operating modes further ensure low power consumption.



Key Features

- High performance and low power 8051 microcontroller core.
- 2.4 GHz IEEE 802.15.4 compliant RF transceiver (industry leading **CC2420** radio core).
- Excellent receiver sensitivity and robustness to interferers
- 32, 64 or 128 KB in-system programmable flash
- 8 KB RAM, 4 KB with data retention in all power modes
- Powerful DMA functionality
- Very few external components
- Only a single crystal needed for mesh network systems
- Low current consumption (RX: 27mA, TX: 27mA, microcontroller running at 32 MHz)
- Only 0.5 μ A current consumption in power-down mode, where external interrupts or the RTC can wake up the system
- 0.3 μ A current consumption in stand-by mode, where external interrupts can wake up the system
- Very fast transition times from low-power modes to active mode enables ultra low average power consumption in low duty-cycle systems
- CSMA/CA hardware support.
- Wide supply voltage range (2.0V – 3.6V)
- Digital RSSI / LQI support
- Battery monitor and temperature sensor
- ADC with up to eight inputs and configurable resolution
- AES security coprocessor
- Two powerful USARTs with support for several serial protocols
- Watchdog timer
- One IEEE 802.15.4 MAC Timer, one general 16-bit timer and two 8-bit timers
- Hardware debug support
- 21 general I/O pins, two with 20mA sink/source capability
- Powerful and flexible development tools available
- RoHS compliant 7x7mm QLP48 package

Table Of Contents

| | | |
|-----------|-------------------------------------------------------------------------|-----------|
| 1 | ABBREVIATIONS..... | 5 |
| 2 | REFERENCES | 7 |
| 3 | REGISTER CONVENTIONS..... | 8 |
| 4 | FEATURES (CONTINUED FROM FRONT PAGE)..... | 9 |
| 4.1 | HIGH-PERFORMANCE AND LOW-POWER 8051-COMPATIBLE MICROCONTROLLER | 9 |
| 4.2 | UP TO 128 KB NON-VOLATILE PROGRAM MEMORY AND 2 x 4 KB DATA MEMORY | 9 |
| 4.3 | HARDWARE AES ENCRYPTION/DECRYPTION..... | 9 |
| 4.4 | PERIPHERAL FEATURES | 9 |
| 4.5 | LOW POWER..... | 9 |
| 4.6 | 802.15.4 MAC HARDWARE SUPPORT | 9 |
| 4.7 | INTEGRATED 2.4GHz DSSS DIGITAL RADIO | 9 |
| 5 | ABSOLUTE MAXIMUM RATINGS..... | 10 |
| 6 | OPERATING CONDITIONS | 10 |
| 7 | ELECTRICAL SPECIFICATIONS | 11 |
| 7.1 | GENERAL CHARACTERISTICS | 12 |
| 7.2 | RF RECEIVE SECTION | 13 |
| 7.3 | RF TRANSMIT SECTION | 15 |
| 7.4 | 32 MHz CRYSTAL OSCILLATOR..... | 15 |
| 7.5 | 32.768 kHz CRYSTAL OSCILLATOR | 16 |
| 7.6 | 32 kHz RC OSCILLATOR..... | 16 |
| 7.7 | HIGH FREQUENCY RC OSCILLATOR..... | 17 |
| 7.8 | FREQUENCY SYNTHESIZER CHARACTERISTICS..... | 17 |
| 7.9 | ANALOG TEMPERATURE SENSOR | 18 |
| 7.10 | ADC..... | 19 |
| 7.11 | CONTROL AC CHARACTERISTICS | 20 |
| 7.12 | SPI AC CHARACTERISTICS..... | 21 |
| 7.13 | DEBUG INTERFACE AC CHARACTERISTICS | 22 |
| 7.14 | PORT OUTPUTS AC CHARACTERISTICS | 22 |
| 7.15 | TIMER INPUTS AC CHARACTERISTICS | 23 |
| 7.16 | DC CHARACTERISTICS | 23 |
| 8 | PIN AND I/O PORT CONFIGURATION | 24 |
| 9 | CIRCUIT DESCRIPTION | 26 |
| 9.1 | CPU AND PERIPHERALS | 26 |
| 9.2 | RADIO | 28 |
| 10 | POWER MANAGEMENT..... | 29 |
| 11 | APPLICATION CIRCUIT | 30 |
| 11.1 | INPUT / OUTPUT MATCHING | 30 |
| 11.2 | BIAS RESISTORS..... | 30 |
| 11.3 | CRYSTAL | 30 |
| 11.4 | VOLTAGE REGULATORS..... | 30 |
| 11.5 | DEBUG INTERFACE | 30 |
| 11.6 | POWER SUPPLY DECOUPLING AND FILTERING | 30 |
| 12 | 8051 CPU..... | 33 |
| 12.1 | 8051 CPU INTRODUCTION | 33 |
| 12.2 | RESET..... | 33 |
| 12.3 | MEMORY | 33 |
| 12.4 | SFR REGISTERS..... | 44 |
| 12.5 | CPU REGISTERS | 47 |
| 12.6 | INSTRUCTION SET SUMMARY | 49 |
| 12.7 | INTERRUPTS | 53 |

| | | |
|-----------|--------------------------------------------------------------|------------|
| 12.8 | OSCILLATORS AND CLOCKS | 63 |
| 12.9 | DEBUG INTERFACE | 64 |
| 12.10 | RAM | 68 |
| 12.11 | FLASH MEMORY | 68 |
| 12.12 | MEMORY ARBITER | 68 |
| 13 | PERIPHERALS..... | 71 |
| 13.1 | I/O PORTS | 71 |
| 13.2 | DMA CONTROLLER | 81 |
| 13.3 | 16-BIT TIMER, TIMER1 | 92 |
| 13.4 | MAC TIMER (TIMER 2) | 104 |
| 13.5 | SLEEP TIMER | 111 |
| 13.6 | 8-BIT TIMER 3 AND TIMER 4 | 113 |
| 13.7 | ADC..... | 122 |
| 13.8 | RANDOM NUMBER GENERATOR..... | 128 |
| 13.9 | AES COPROCESSOR..... | 130 |
| 13.10 | POWER MANAGEMENT | 135 |
| 13.11 | POWER ON RESET AND BROWN OUT DETECTOR..... | 141 |
| 13.12 | WATCHDOG TIMER..... | 142 |
| 13.13 | USART | 144 |
| 13.14 | FLASH CONTROLLER | 154 |
| 14 | RADIO..... | 161 |
| 14.1 | IEEE 802.15.4 MODULATION FORMAT | 162 |
| 14.2 | COMMAND STROBES | 163 |
| 14.3 | RF REGISTERS | 163 |
| 14.4 | INTERRUPTS | 163 |
| 14.5 | FIFO ACCESS..... | 166 |
| 14.6 | DMA..... | 167 |
| 14.7 | RECEIVE MODE..... | 167 |
| 14.8 | RXFIFO OVERFLOW | 167 |
| 14.9 | TRANSMIT MODE | 168 |
| 14.10 | GENERAL CONTROL AND STATUS | 169 |
| 14.11 | DEMODULATOR, SYMBOL SYNCHRONIZER AND DATA DECISION..... | 169 |
| 14.12 | FRAME FORMAT | 170 |
| 14.13 | SYNCHRONIZATION HEADER..... | 170 |
| 14.14 | LENGTH FIELD | 171 |
| 14.15 | MAC PROTOCOL DATA UNIT | 171 |
| 14.16 | FRAME CHECK SEQUENCE..... | 172 |
| 14.17 | RF DATA BUFFERING | 173 |
| 14.18 | ADDRESS RECOGNITION..... | 174 |
| 14.19 | ACKNOWLEDGE FRAMES | 174 |
| 14.20 | RADIO CONTROL STATE MACHINE | 176 |
| 14.21 | MAC SECURITY OPERATIONS (ENCRYPTION AND AUTHENTICATION)..... | 177 |
| 14.22 | LINEAR IF AND AGC SETTINGS | 178 |
| 14.23 | RSSI / ENERGY DETECTION | 178 |
| 14.24 | LINK QUALITY INDICATION..... | 178 |
| 14.25 | CLEAR CHANNEL ASSESSMENT | 179 |
| 14.26 | FREQUENCY AND CHANNEL PROGRAMMING | 179 |
| 14.27 | VCO AND PLL SELF-CALIBRATION | 180 |
| 14.28 | OUTPUT POWER PROGRAMMING | 180 |
| 14.29 | INPUT / OUTPUT MATCHING | 181 |
| 14.30 | TRANSMITTER TEST MODES | 181 |
| 14.31 | SYSTEM CONSIDERATIONS AND GUIDELINES | 183 |
| 14.32 | PCB LAYOUT RECOMMENDATION | 185 |
| 14.33 | ANTENNA CONSIDERATIONS | 186 |
| 14.34 | CSMA/CA STROBE PROCESSOR | 186 |
| 14.35 | RADIO REGISTERS | 198 |
| 15 | RADIO TEST OUTPUT SIGNALS..... | 218 |
| 16 | VOLTAGE REGULATORS | 219 |

| | | |
|-----------|---------------------------------------------------|------------|
| 16.1 | VOLTAGE REGULATORS POWER-ON | 219 |
| 17 | EVALUATION SOFTWARE | 219 |
| 18 | REGISTER OVERVIEW | 220 |
| 19 | PACKAGE DESCRIPTION (QLP 48)..... | 223 |
| 19.1 | RECOMMENDED PCB LAYOUT FOR PACKAGE (QLP 48) | 224 |
| 19.2 | PACKAGE THERMAL PROPERTIES | 224 |
| 19.3 | SOLDERING INFORMATION..... | 224 |
| 19.4 | TRAY SPECIFICATION..... | 224 |
| 19.5 | CARRIER TAPE AND REEL SPECIFICATION | 225 |
| 20 | ORDERING INFORMATION..... | 226 |
| 21 | GENERAL INFORMATION..... | 227 |
| 21.1 | DOCUMENT HISTORY | 227 |
| 21.2 | PRODUCT STATUS DEFINITIONS | 230 |
| 22 | ADDRESS INFORMATION..... | 230 |
| 23 | TI WORLDWIDE TECHNICAL SUPPORT..... | 230 |
| | IMPORTANT NOTICE..... | 233 |

1 Abbreviations

| | | | |
|---------|--------------------------------------------------------|--------|----------------------------------------------------------------------------------|
| ADC | Analog to Digital Converter | I/Q | In-phase / Quadrature-phase |
| AES | Advanced Encryption Standard | IEEE | Institute of Electrical and Electronics Engineers |
| AGC | Automatic Gain Control | IF | Intermediate Frequency |
| ARIB | Association of Radio Industries and Businesses | IOC | I/O Controller |
| BCD | Binary Coded Decimal | ISM | Industrial, Scientific and Medical |
| BER | Bit Error Rate | ITU-T | International Telecommunication Union – Telecommunication Standardization Sector |
| BOD | Brown Out Detector | IV | Initialization Vector |
| BOM | Bill of Materials | IRQ | Interrupt Request |
| CBC | Cipher Block Chaining | JEDEC | Joint Electron Device Engineering Council |
| CBC-MAC | Cipher Block Chaining Message Authentication Code | KB | 1024 bytes |
| CCA | Clear Channel Assessment | kbps | kilo bits per second |
| CCM | Counter mode + CBC-MAC | LC | Inductor-capacitor |
| CFB | Cipher Feedback | LFSR | Linear Feedback Shift Register |
| CFR | Code of Federal Regulations | LNA | Low-Noise Amplifier |
| CMOS | Complementary Metal Oxide Semiconductor | LO | Local Oscillator |
| CPU | Central Processing Unit | LQI | Link Quality Indication |
| CRC | Cyclic Redundancy Check | LSB | Least Significant Bit / Byte |
| CSMA-CA | Carrier Sense Multiple Access with Collision Avoidance | LSB | Least Significant Byte |
| CSP | CSMA/CA Strobe Processor | MAC | Medium Access Control |
| CTR | Counter mode (encryption) | MAC | Message Authentication Code |
| CW | Continuous Wave | MCU | Microcontroller Unit |
| DAC | Digital to Analog Converter | MFR | MAC Footer |
| DC | Direct Current | MHR | MAC Header |
| DMA | Direct Memory Access | MIC | Message Integrity Code |
| DSM | Delta Sigma Modulator | MISO | Master In Slave Out |
| DSSS | Direct Sequence Spread Spectrum | MPDU | MAC Protocol Data Unit |
| ECB | Electronic Code Book (encryption) | MOSI | Master Out Slave In |
| EM | Evaluation Module | MSB | Most Significant Byte |
| ESD | Electro Static Discharge | MSDU | MAC Service Data Unit |
| ESR | Equivalent Series Resistance | MUX | Multiplexer |
| ETSI | European Telecommunications Standards Institute | NA | Not Available |
| EVM | Error Vector Magnitude | NC | Not Connected |
| FCC | Federal Communications Commission | OFB | Output Feedback (encryption) |
| FCF | Frame Control Field | O-QPSK | Offset - Quadrature Phase Shift Keying |
| FCS | Frame Check Sequence | PA | Power Amplifier |
| FFCTRL | FIFO and Frame Control | PCB | Printed Circuit Board |
| FIFO | First In First Out | PER | Packet Error Rate |
| HF | High Frequency | PHR | PHY Header |
| HSSD | High Speed Serial Data | PHY | Physical Layer |
| I/O | Input / Output | PLL | Phase Locked Loop |

| | |
|---------|---------------------------------------------------------|
| PM{0-3} | Power Mode 0-3 |
| PMC | Power Management Controller |
| POR | Power On Reset |
| PSDU | PHY Service Data Unit |
| PWM | Pulse Width Modulator |
| QLP | Quad Leadless Package |
| RAM | Random Access Memory |
| RBW | Resolution Bandwidth |
| RC | Resistor-Capacitor |
| RCOSC | RC Oscillator |
| RF | Radio Frequency |
| RoHS | Restriction on Hazardous Substances |
| RSSI | Receive Signal Strength Indicator |
| RTC | Real-Time Clock |
| RX | Receive |
| SCK | Serial Clock |
| SFD | Start of Frame Delimiter |
| SFR | Special Function Register |
| SHR | Synchronization Header |
| SINAD | Signal-to-noise and distortion ratio |
| SPI | Serial Peripheral Interface |
| SRAM | Static Random Access Memory |
| ST | Sleep Timer |
| T/R | Transmit / Receive |
| T/R | Tape and reel |
| TBD | To Be Decided / To Be Defined |
| THD | Total Harmonic Distortion |
| TI | Texas Instruments |
| TX | Transmit |
| UART | Universal Asynchronous Receiver/Transmitter |
| USART | Universal Synchronous/Asynchronous Receiver/Transmitter |
| VCO | Voltage Controlled Oscillator |
| VGA | Variable Gain Amplifier |
| WDT | Watchdog Timer |
| XOSC | Crystal Oscillator |

2 References

- [1] IEEE std. 802.15.4 - 2003: Wireless Medium Access Control (MAC) and Physical Layer (PHY) specifications for Low Rate Wireless Personal Area Networks (LR-WPANs)

<http://standards.ieee.org/getieee802/download/802.15.4-2003.pdf>
- [2] NIST FIPS Pub 197: Advanced Encryption Standard (AES), Federal Information Processing Standards Publication 197, US Department of Commerce/N.I.S.T., November 26, 2001.
Available from the NIST website.

<http://csrc.nist.gov/publications/fips/fips197/fips-197.pdf>

3 Register conventions

Each SFR register is described in a separate table. The table heading is given in the following format:

REGISTER NAME (SFR Address) - Register Description.

Each RF register is described in a separate table. The table heading is given in the following format:

REGISTER NAME (XDATA Address)

In the register descriptions, each register bit is shown with a symbol indicating the access mode of the register bit. The register values are always given in binary notation unless prefixed by '0x' which indicates hexadecimal notation.

| Symbol | Access Mode |
|--------|----------------|
| R/W | Read/write |
| R | Read only |
| R0 | Read as 0 |
| R1 | Read as 1 |
| W | Write only |
| W0 | Write as 0 |
| W1 | Write as 1 |
| H0 | Hardware clear |
| H1 | Hardware set |

Table 1: Register bit conventions

4 Features (continued from front page)

4.1 High-Performance and Low-Power 8051-Compatible Microcontroller

- Optimized 8051 core, which typically gives 8x the performance of a standard 8051
- Dual data pointers
- In-circuit interactive debugging is supported for the IAR Embedded Workbench through a simple two-wire serial interface

4.2 Up to 128 KB Non-volatile Program Memory and 2 x 4 KB Data Memory

- 32/64/128 KB of non-volatile flash memory in-system programmable through a simple two-wire interface or by the 8051 core
- Worst-case flash memory endurance: 1000 write/erase cycles.
- Programmable read and write lock of portions of Flash memory for software security
- 4096 bytes of internal SRAM with data retention in all power modes.
- Additional 4096 bytes of internal SRAM with data retention in power modes 0 and 1.

4.3 Hardware AES Encryption/Decryption

- AES supported in hardware coprocessor

4.4 Peripheral Features

- Powerful DMA Controller
- Power On Reset/Brown-Out Detection
- Eight channel ADC with configurable resolution
- Programmable watchdog timer
- Real time clock with 32.768 kHz crystal oscillator
- Four timers: one general 16-bit timer, two general 8-bit timers, one MAC timer
- Two programmable USARTs for master/slave SPI or UART operation
- 21 configurable general-purpose digital I/O-pins

- True random number generator

4.5 Low Power

- Four flexible power modes for reduced power consumption
- System can wake up on external interrupt or real-time counter event
- Low-power fully static CMOS design
- System clock source can be 16 MHz RC oscillator or 32 MHz crystal oscillator. The 32 MHz oscillator is used when radio is active.
- Optional clock source for ultra-low power operation can be either low-power RC oscillator or an optional 32.768 kHz crystal oscillator.

4.6 802.15.4 MAC hardware support

- Automatic preamble generator
- Synchronization word insertion/detection
- CRC-16 computation and checking over the MAC payload
- Clear Channel Assessment
- Energy detection / digital RSSI
- Link Quality Indication
- CSMA/CA Coprocessor

4.7 Integrated 2.4GHz DSSS Digital Radio


- 2.4 GHz IEEE 802.15.4 compliant RF transceiver (based on industry leading **CC2420** radio core).
- Excellent receiver sensitivity and robustness to interferers
- 250 kbps data rate, 2 MChip/s chip rate
- Reference designs comply with worldwide radio frequency regulations covered by ETSI EN 300 328 and EN 300 440 class 2 (Europe), FCC CFR47 Part 15 (US) and ARIB STD-T66 (Japan). Operation on 2480MHz under FCC is supported by duty-cycling or by reducing output power.

5 Absolute Maximum Ratings

Under no circumstances must the absolute maximum ratings given in Table 2 be violated. Stress exceeding one or more of the limiting values may cause permanent damage to the device.

| Parameter | Min | Max | Units | Condition |
|-----------------------------------------------------|------|---------------------|-------|--------------------------------------------|
| Supply voltage | −0.3 | 3.6 | V | All supply pins must have the same voltage |
| Voltage on any digital pin | −0.3 | VDD+0.3, max 3.6 | V | |
| Voltage on the 1.8V pins (pin no. 22, 25-40 and 42) | −0.3 | 2.0 | V | |
| Input RF level | | 10 | dBm | |
| Storage temperature range | −50 | 150 | °C | Device not programmed |
| Reflow soldering temperature | | 260 | °C | According to IPC/JEDEC J-STD-020C |

Table 2: Absolute Maximum Ratings



Caution! ESD sensitive device.
 Precaution should be used when handling the device in order to prevent permanent damage.

6 Operating Conditions

The operating conditions for **CC2430** are listed in Table 3 .

| Parameter | Min | Max | Unit | Condition |
|-----------------------------------------------------|-----|-----|------|---------------------------------------------------------------------------------|
| Operating ambient temperature range, T _A | −40 | 85 | °C | |
| Operating supply voltage | 2.0 | 3.6 | V | The supply pins to the radio part must be driven by the 1.8 V on-chip regulator |

Table 3: Operating Conditions

7 Electrical Specifications

Measured on Texas Instruments **CC2430** EM reference design with $T_A=25^{\circ}\text{C}$ and $V_{DD}=3.0\text{V}$ unless stated otherwise.

| Parameter | Min | Typ | Max | Unit | Condition |
|---------------------------------------|-----|------|-----|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Current Consumption | | | | | |
| MCU Active Mode, 16 MHz | | 4.3 | | mA | Digital regulator on, High frequency (16 MHz) RCOSC running. No radio, crystals, or peripherals active. Code run with Cache hit. |
| MCU Active Mode, 32 MHz | | 9.5 | | mA | MCU running at full speed (32MHz), 32MHz XOSC running. No radio or peripherals active. Code run with Cache hit. |
| MCU Active and RX Mode | | 26.7 | | mA | MCU running at full speed (32MHz), 32MHz XOSC running, radio in RX mode, -50 dBm input power. No peripherals active. Code run with Cache hit. |
| MCU Active and TX Mode, 0dBm | | 26.9 | | mA | MCU running at full speed (32MHz), 32MHz XOSC running, radio in TX mode, 0dBm output power. No peripherals active. Code run with Cache hit. |
| Power mode 1 | | 190 | | μA | Digital regulator on, High frequency RCOSC and crystal oscillator off. 32.768 kHz XOSC, POR and ST active. RAM retention. |
| Power mode 2 | | 0.5 | | μA | Digital regulator off, High frequency RCOSC and crystal oscillator off. 32.768 kHz XOSC, POR and ST active. RAM retention. |
| Power mode 3 | | 0.3 | | μA | No clocks. RAM retention. POR active. |
| Peripheral Current Consumption | | | | | |
| | | | | | Adds to the figures above if the peripheral unit is activated |
| Timer 1 | | 150 | | μA | Timer running, 32MHz XOSC used. |
| Timer 2 | | 230 | | μA | Timer running, 32MHz XOSC used. |
| Timer 3 | | 50 | | μA | Timer running, 32MHz XOSC used. |
| Timer 4 | | 50 | | μA | Timer running, 32MHz XOSC used. |
| Sleep Timer | | 0.2 | | μA | Including 32 kHz RCOSC or 32.768 kHz XOSC |
| ADC | | 1.2 | | mA | When converting. |
| Flash write | | 3 | | mA | Estimated value |
| Flash erase | | 3 | | mA | Estimated value |

Table 4: Electrical Specifications

7.1 General Characteristics

Measured on Texas Instruments **CC2430** EM reference design with $T_A=25^{\circ}\text{C}$ and $V_{DD}=3.0\text{V}$ unless stated otherwise.

| Parameter | Min | Typ | Max | Unit | Condition/Note |
|-----------------------------------------------------------------------------------|------|------|--------|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Wake-Up and Timing | | | | | |
| Power mode 1 → power mode 0 | | 4.1 | | μs | Digital regulator on, High frequency RCOSC and crystal oscillator off. Start-up of High frequency RCOSC. |
| Power mode 2 or 3 → power mode 0 | | 89.2 | | μs | Digital regulator off, High frequency RCOSC and crystal oscillator off. Start-up of regulator and High frequency RCOSC. |
| Active → TX or RX 32MHz XOSC initially OFF. Voltage regulator initially OFF | | 525 | | μs | Time from enabling radio part in power mode 0, until TX or RX starts. Includes start-up of voltage regulator and crystal oscillator in parallel. Crystal ESR=16 Ω . |
| Active → TX or RX Voltage regulator initially OFF | | 320 | | μs | Time from enabling radio part in power mode 0, until TX or RX starts. Includes start-up of voltage regulator. |
| Active → RX or TX | | | 192 | μs | Radio part already enabled. Time until RX or TX starts. |
| RX/TX turnaround | | | 192 | μs | |
| Radio part | | | | | |
| RF Frequency Range | 2400 | | 2483.5 | MHz | Programmable in 1 MHz steps, 5 MHz between channels for compliance with [1] |
| Radio bit rate | | 250 | | kbps | As defined by [1] |
| Radio chip rate | | 2.0 | | MChip/s | As defined by [1] |

Table 5: General Characteristics

7.2 RF Receive Section

Measured on Texas Instruments **CC2430** EM reference design with $T_A=25^{\circ}\text{C}$ and $V_{DD}=3.0\text{V}$ unless stated otherwise.

| Parameter | Min | Typ | Max | Unit | Condition/Note |
|-----------------------------------------------------------------------|-----|----------|-----|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receiver sensitivity | | -91 | | dBm | PER = 1%, as specified by [1] Measured in 50 Ω single endedly through a balun. [1] requires -85 dBm |
| Saturation (maximum input level) | | 10 | | dBm | PER = 1%, as specified by [1] Measured in 50 Ω single endedly through a balun. [1] requires -20 dBm |
| Adjacent channel rejection + 5 MHz channel spacing | | 41 | | dB | Wanted signal -88dBm, adjacent modulated channel at +5 MHz, PER = 1 %, as specified by [1]. [1] requires 0 dB |
| Adjacent channel rejection - 5 MHz channel spacing | | 30 | | dB | Wanted signal -88dBm, adjacent modulated channel at -5 MHz, PER = 1 %, as specified by [1]. [1] requires 0 dB |
| Alternate channel rejection + 10 MHz channel spacing | | 55 | | dB | Wanted signal -88dBm, adjacent modulated channel at +10 MHz, PER = 1 %, as specified by [1] [1] requires 30 dB |
| Alternate channel rejection - 10 MHz channel spacing | | 53 | | dB | Wanted signal -88dBm, adjacent modulated channel at -10 MHz, PER = 1 %, as specified by [1] [1] requires 30 dB |
| Channel rejection $\geq + 15\text{ MHz}$ $\leq - 15\text{ MHz}$ | | 55 53 | | dB dB | Wanted signal @ -82 dBm. Undesired signal is an 802.15.4 modulated channel, stepped through all channels from 2405 to 2480 MHz. Signal level for PER = 1%. Values are estimated. |
| Co-channel rejection | | -6 | | dB | Wanted signal @ -82 dBm. Undesired signal is 802.15.4 modulated at the same frequency as the desired signal. Signal level for PER = 1%. |

| Parameter | Min | Typ | Max | Unit | Condition/Note |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|----------------------------------------------------------|------------|----------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Blocking / Desensitization + 5 MHz from band edge + 10 MHz from band edge + 20 MHz from band edge + 50 MHz from band edge - 5 MHz from band edge - 10 MHz from band edge - 20 MHz from band edge - 50 MHz from band edge | | -42 -45 -26 -22 -31 -36 -24 -25 | | dBm dBm dBm dBm dBm dBm dBm dBm | Wanted signal 3 dB above the sensitivity level, CW jammer, PER = 1%. Measured according to EN 300 440 class 2. |
| Spurious emission 30 – 1000 MHz 1 – 12.75 GHz | | | -64 -75 | dBm dBm | Conducted measurement in a 50 Ω single ended load. Complies with EN 300 328, EN 300 440 class 2, FCC CFR47, Part 15 and ARIB STD-T-66 |
| Frequency error tolerance | | ± 140 | | ppm | Difference between centre frequency of the received RF signal and local oscillator frequency. [1] requires minimum 80 ppm |
| Symbol rate error tolerance | | ± 900 | | ppm | Difference between incoming symbol rate and the internally generated symbol rate [1] requires minimum 80 ppm |

Table 6: RF Receive Parameters

7.3 RF Transmit Section

Measured on Texas Instruments **CC2430** EM reference design with $T_A=25^{\circ}\text{C}$ and $V_{DD}=3.0\text{V}$ unless stated otherwise.

| Parameter | Min | Typ | Max | Unit | Condition/Note |
|---------------------------------|-----|------------|-----|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Nominal output power | | 0 | | dBm | Delivered to a single ended 50 Ω load through a balun and output power control set to 0x5F (TXCTRL). [1] requires minimum -3 dBm |
| Programmable output power range | | 25.8 | | dB | The output power is programmable in 16 steps from approximately -25.2 to 0.6 dBm. |
| Harmonics | | | | | |
| 2 nd harmonic | | -50.7 | | dBm | Measurement conducted with 100 kHz resolution bandwidth on spectrum analyzer and output power control set to 0x5F (TXCTRL). Output Delivered to a single ended 50 Ω load through a balun. |
| 3 rd harmonic | | -55.8 | | dBm | |
| 4 th harmonic | | -54.2 | | dBm | |
| 5 th harmonic | | -53.4 | | dBm | |
| Spurious emission | | | | | Maximum output power. |
| 30 - 1000 MHz | | -47 | | dBm | The peak conducted spurious emission is -47dBm@192MHz which is in a EN300440 restricted band limited to -54dBm. All radiated spurious emissions are within the limits of ETSI/FCC/ARIB. Texas Instruments CC2430 EM reference design complies with EN 300 328, EN 300 440, FCC CFR47 Part 15 and ARIB STD-T-66 |
| 1– 12.75 GHz | | -43 | | dBm | |
| 1.8 – 1.9 GHz | | -58 | | dBm | |
| 5.15 – 5.3 GHz | | -56 | | dBm | |
| Error Vector Magnitude (EVM) | | 11 | | % | Measured as defined by [1] [1] requires max. 35 % |
| Optimum load impedance | | 115 + j180 | | Ω | Differential impedance as seen from the RF-port (RF_P and RF_N) towards the antenna. |

Table 7: RF Transmit Parameters**7.4 32 MHz Crystal Oscillator**

Measured on Texas Instruments **CC2430** EM reference design with $T_A=25^{\circ}\text{C}$ and $V_{DD}=3.0\text{V}$ unless stated otherwise.

| Parameter | Min | Typ | Max | Unit | Condition/Note |
|----------------------------------------|------|-----|-----|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Crystal frequency | | 32 | | MHz | |
| Crystal frequency accuracy requirement | - 40 | | 40 | ppm | Including aging and temperature dependency, as specified by [1] Accuracy requirements can be relaxed by optional built-in tuning of load capacitance through software ¹ |
| ESR | 6 | 16 | 60 | Ω | |
| C_0 | 1 | 1.9 | 7 | pF | |
| C_L | 10 | 13 | 16 | pF | Load capacitance is optionally tunable through software |
| Start-up time | | 212 | | μs | |

Table 8: 32 MHz Crystal Oscillator Parameters

¹ Only for devices with Chip Version register, CHVER.VERSION equal to 0x02 or greater

7.5 32.768 kHz Crystal Oscillator

Measured on Texas Instruments **CC2430** EM reference design with $T_A=25^{\circ}\text{C}$ and $V_{DD}=3.0\text{V}$ unless stated otherwise.

| Parameter | Min | Typ | Max | Unit | Condition/Note |
|----------------------------------------|-----|--------|-----|------------|-----------------------------------------------------------------|
| Crystal frequency | | 32.768 | | kHz | |
| Crystal frequency accuracy requirement | -40 | | 40 | ppm | Including aging and temperature dependency, as specified by [1] |
| ESR | | 40 | 130 | k Ω | |
| C_0 | | 0.9 | 2.0 | pF | |
| C_L | | 12 | 16 | pF | |
| Start-up time | | | 450 | ms | Value is estimated. |

Table 9: 32.768 kHz Crystal Oscillator Parameters**7.6 32 kHz RC Oscillator**

Measured on Texas Instruments **CC2430** EM reference design with $T_A=25^{\circ}\text{C}$ and $V_{DD}=3.0\text{V}$ unless stated otherwise.

| Parameter | Min | Typ | Max | Unit | Condition/Note |
|--------------------------------------|-----|-----------|-----|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Calibrated frequency | | 32.753 | | kHz | The calibrated 32 kHz RC Oscillator frequency is the 32 MHz XTAL frequency divided by 977 |
| Frequency accuracy after calibration | | ± 0.2 | | % | Value is estimated. |
| Temperature coefficient | | +0.4 | | % / $^{\circ}\text{C}$ | Frequency drift when temperature changes after calibration. Value is estimated. |
| Supply voltage coefficient | | +3 | | % / V | Frequency drift when supply voltage changes after calibration. Value is estimated. |
| Initial calibration time | | 1.7 | | ms | When the 32 kHz RC Oscillator is enabled, calibration is continuously done in the background as long as the 32 MHz crystal oscillator is running and SLEEP.OSC32K_CALDIS bit is cleared. |

Table 10: 32 kHz RC Oscillator parameters

7.7 High Frequency RC Oscillator

Measured on Texas Instruments **CC2430** EM reference design with $T_A=25^{\circ}\text{C}$ and $V_{DD}=3.0\text{V}$ unless stated otherwise.

| Parameter | Min | Typ | Max | Unit | Condition/Note |
|---------------------------------|-----|-----------|---------|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Frequency | | 16 | | MHz | The calibrated High Frequency RC Oscillator frequency is the 32 MHz XTAL frequency multiplied by 1/2 |
| Uncalibrated frequency accuracy | | ± 18 | | % | Measured on Texas Instruments CC2430 EM reference design. |
| Calibrated frequency accuracy | | ± 0.6 | ± 1 | % | |
| Start-up time | | | 10 | μs | |
| Temperature coefficient | | | -325 | ppm / $^{\circ}\text{C}$ | Frequency drift when temperature changes after calibration |
| Supply voltage coefficient | | | 28 | ppm / mV | Frequency drift when supply voltage changes after calibration |
| Initial calibration time | | 50 | | μs | When the High Frequency RC Oscillator is enabled, calibration is continuously done in the background as long as the crystal oscillator is running. |

Table 11: High Frequency RC Oscillator parameters**7.8 Frequency Synthesizer Characteristics**

Measured on Texas Instruments **CC2430** EM reference design with $T_A=25^{\circ}\text{C}$ and $V_{DD}=3.0\text{V}$ unless stated otherwise.

| Parameter | Min | Typ | Max | Unit | Condition/Note |
|---------------|-----|----------------------|-----|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Phase noise | | -116 -117 -118 | | dBc/Hz dBc/Hz dBc/Hz | Unmodulated carrier At ± 1.5 MHz offset from carrier At ± 3 MHz offset from carrier At ± 5 MHz offset from carrier |
| PLL lock time | | | 192 | μs | The startup time when the crystal oscillator is running and RX / TX turnaround time |

Table 12: Frequency Synthesizer Parameters

7.9 Analog Temperature Sensor

Measured on Texas Instruments **CC2430** EM reference design with $T_A=25^{\circ}\text{C}$ and $V_{DD}=3.0\text{V}$ unless stated otherwise.

| Parameter | Min | Typ | Max | Unit | Condition/Note |
|---------------------------------------------|-----|-------|-----|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Output voltage at -40°C | | 0.648 | | V | Values are estimated |
| Output voltage at 0°C | | 0.743 | | V | Values are estimated |
| Output voltage at $+40^{\circ}\text{C}$ | | 0.840 | | V | Values are estimated |
| Output voltage at $+80^{\circ}\text{C}$ | | 0.939 | | V | Values are estimated |
| Temperature coefficient | | 2.45 | | mV/ $^{\circ}\text{C}$ | Fitted from -20°C to $+80^{\circ}\text{C}$ on estimated values. |
| Absolute error in calculated temperature | | -8 | | $^{\circ}\text{C}$ | From -20°C to $+80^{\circ}\text{C}$ when assuming best fit for absolute accuracy on estimated values: 0.743V at 0°C and 2.45mV / $^{\circ}\text{C}$. |
| Error in calculated temperature, calibrated | -2 | 0 | 2 | $^{\circ}\text{C}$ | From -20°C to $+80^{\circ}\text{C}$ when using 2.45mV / $^{\circ}\text{C}$, after 1-point calibration at room temperature. Values are estimated. Indicated min/max with 1-point calibration is based on simulated values for typical process parameters |
| Current consumption increase when enabled | | 280 | | μA | |

Table 13: Analog Temperature Sensor Parameters

7.10 ADC

Measured on Texas Instruments **CC2430** EM reference design with $T_A=25^{\circ}\text{C}$, $V_{DD}=3.0\text{V}$. Preliminary characterized parameters.

| Parameter | Min | Typ | Max | Unit | Condition/Note |
|-----------------------------------------------------------------------|-----|------------|------|---------------|-------------------------------------------|
| Input voltage | 0 | | AVDD | V | AVDD is voltage on AVDD_SOC pin |
| External reference voltage | 0 | | AVDD | V | AVDD is voltage on AVDD_SOC pin |
| External reference voltage differential | 0 | | AVDD | V | AVDD is voltage on AVDD_SOC pin |
| Input resistance, ADC single-ended input | | 167 | | k Ω | AIN0 to AIN7 selected as ADC input |
| Input resistance, ADC differential input ² | | TBD | | | |
| Input resistance, single-ended reference | | 49 | | k Ω | AIN7 selected as external reference input |
| Input resistance, differential reference ¹ | | TBD | | | |
| Effective number of bits (ENOB) ² | | 5.5 | | bits | 8-bits setting. |
| | | 7.3 | | | 10-bits setting. |
| | | 9.0 | | | 12-bits setting. |
| | | 10.5 | | | 14-bits setting. |
| Effective number of bits (ENOB) Differential input ¹ | | TBD | | | |
| Offset ¹ | | TBD | | LSB | |
| Conversion time | | 20 | | μs | 8-bits setting. |
| | | 36 | | μs | 10-bits setting. |
| | | 68 | | μs | 12-bits setting. |
| | | 132 | | μs | 14-bits setting. |
| Differential nonlinearity (DNL) ³ | | ± 0.14 | 1.0 | LSB | 8-bits setting. |
| Integral nonlinearity (INL) ² | | ± 0.5 | 3.4 | LSB | 8-bits setting. |
| SINAD ² (sine input signal frequency 1 Hz and 1 kHz) | | 34 | | dB | 8-bits setting. |
| | | 46 | | dB | 10-bits setting. |
| | | 56 | | dB | 12-bits setting. |
| | | 65 | | dB | 14-bits setting. |

Table 14: ADC Characteristics


² Not characterized for this data sheet revision.

³ Single-ended input signal and AVDD used as reference. Sine input, tested at frequencies 1 Hz and 1 kHz

7.11 Control AC Characteristics

$T_A = -40^{\circ}\text{C}$ to 85°C , $V_{DD} = 3.0\text{V}$ if nothing else stated.


| Parameter | Min | Typ | Max | Unit | Condition/Note |
|-----------------------------------------------------------------------------------|---------------------|-----|-----|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| System clock, f_{SYSCLK} $t_{\text{SYSCLK}} = 1/f_{\text{SYSCLK}}$ | 16 | | 32 | MHz | System clock is when 32 MHz crystal oscillator is used. System clock is 16 MHz when high frequency RC oscillator is used. |
| RESET_N low width | 2.5 | | | ns | See item 1, Figure 1. This is the shortest pulse that is guaranteed to be recognized as a reset pin request. |
| Interrupt pulse width | t_{SYSCLK} | | | ns | See item 2, Figure 1. This is the shortest pulse that is guaranteed to be recognized as an interrupt request. In PM2/3 the internal synchronizers are bypassed so this requirement does not apply in PM2/3. |

Table 15: Control Inputs AC Characteristics**Figure 1: Control Inputs AC Characteristics**

7.12 SPI AC Characteristics

$T_A = -40^{\circ}\text{C}$ to 85°C , $V_{DD} = 3.0\text{V}$ if nothing else stated.


| Parameter | Min | Typ | Max | Unit | Condition/Note |
|-----------------|-----------------------------|---------------------|-----|------|-------------------------------------------|
| SCK period | | See section 13.13.3 | | ns | Master. See item 1 Figure 2 |
| SCK duty cycle | | 50% | | | Master. |
| SSN low to SCK | $2 \cdot t_{\text{SYSCLK}}$ | | | | See item 5 Figure 2 |
| SCK to SSN high | 30 | | | ns | See item 6 Figure 2 |
| MISO setup | 10 | | | ns | Master. See item 2 Figure 2 |
| MISO hold | 10 | | | ns | Master. See item 3 Figure 2 |
| SCK to MOSI | | | 25 | ns | Master. See item 4 Figure 2, load = 10 pF |
| SCK period | 100 | | | ns | Slave. See item 1 Figure 2 |
| SCK duty cycle | | 50% | | | Slave. |
| MOSI setup | 10 | | | ns | Slave. See item 2 Figure 2 |
| MOSI hold | 10 | | | ns | Slave. See item 3 Figure 2 |
| SCK to MISO | | | 25 | ns | Slave. See item 4 Figure 2, load = 10 pF |

Table 16: SPI AC Characteristics**Figure 2: SPI AC Characteristics**

7.13 Debug Interface AC Characteristics

$T_A = -40^{\circ}\text{C}$ to 85°C , $V_{DD} = 3.0\text{V}$ if nothing else stated.

| Parameter | Min | Typ | Max | Unit | Condition/Note |
|------------------------------------|-----|-----|-----|------|-----------------------------------|
| Debug clock period | 128 | | | ns | See item 1 Figure 3 |
| Debug data setup | 5 | | | ns | See item 2 Figure 3 |
| Debug data hold | 5 | | | ns | See item 3 Figure 3 |
| Clock to data delay | | | 10 | ns | See item 4 Figure 3, load = 10 pF |
| RESET_N inactive after P2_2 rising | 10 | | | ns | See item 5 Figure 3 |

Table 17: Debug Interface AC Characteristics**Figure 3: Debug Interface AC Characteristics****7.14 Port Outputs AC Characteristics**

$T_A = -40^{\circ}\text{C}$ to 85°C , $V_{DD} = 3.0\text{V}$ if nothing else stated.

| Parameter | Min | Typ | Max | Unit | Condition/Note |
|-------------------------------------------------|-----|-----|-----|------|---------------------------------------------------------------------------------------------|
| P0, P1, P2 Port output pins, rise and fall time | | 10 | | ns | Load = 10 pF Timing is with respect to 10% VDD and 90% VDD levels. Value is estimated |

Table 18: Port Outputs AC Characteristics

7.15 Timer Inputs AC Characteristics

$T_A = -40^{\circ}\text{C}$ to 85°C , $V_{DD} = 3.0\text{V}$ if nothing else stated.

| Parameter | Min | Typ | Max | Unit | Condition/Note |
|---------------------------|---------------------|-----|-----|------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Input capture pulse width | t_{SYSCLK} | | | ns | Synchronizers determine the shortest input pulse that can be recognized. The synchronizers operate at the current system clock rate (16 or 32 MHz) |

Table 19: Timer Inputs AC Characteristics**7.16 DC Characteristics**

The DC Characteristics of **CC2430** are listed in Table 20 below.

$T_A = 25^{\circ}\text{C}$, $V_{DD} = 3.0\text{V}$ if nothing else stated.

| Digital Inputs/Outputs | Min | Typ | Max | Unit | Condition |
|----------------------------------------|-----------------|-----|------|---------------|-------------------------------------------------------------------------------------|
| Logic "0" input voltage | 0 | 0.7 | 0.9 | V | |
| Logic "1" input voltage | $V_{DD} - 0.7$ | VDD | VDD | V | |
| Logic "0" output voltage | 0 | 0 | 0.25 | V | For up to 4mA output current on all pins except P1_0 and P1_1 which are up to 20 mA |
| Logic "1" output voltage | $V_{DD} - 0.25$ | VDD | VDD | V | For up to 4mA output current on all pins except P1_0 and P1_1 which are up to 20 mA |
| Logic "0" input current | NA | -1 | -1 | μA | Input equals 0V |
| Logic "1" input current | NA | 1 | 1 | μA | Input equals VDD |
| I/O pin pull-up and pull-down resistor | 17 | 20 | 23 | k Ω | |

Table 20: DC Characteristics

8 Pin and I/O Port Configuration

The **CC2430** pinout is shown in Figure 4 and Table 21. See section 13.1 for details on the configuration of digital I/O ports.





Figure 4: Pinout top view

Note: The exposed die attach pad **must** be connected to a solid ground plane as this is the ground connection for the chip.

| Pin | Pin name | Pin type | Description |
|-----|--------------|-----------------|----------------------------------------------------------------------------------------------------------------------------------------|
| - | GND | Ground | The exposed die attach pad must be connected to a solid ground plane |
| 1 | P1_7 | Digital I/O | Port 1.7 |
| 2 | P1_6 | Digital I/O | Port 1.6 |
| 3 | P1_5 | Digital I/O | Port 1.5 |
| 4 | P1_4 | Digital I/O | Port 1.4 |
| 5 | P1_3 | Digital I/O | Port 1.3 |
| 6 | P1_2 | Digital I/O | Port 1.2 |
| 7 | DVDD | Power (Digital) | 2.0V-3.6V digital power supply for digital I/O |
| 8 | P1_1 | Digital I/O | Port 1.1 – 20 mA drive capability |
| 9 | P1_0 | Digital I/O | Port 1.0 – 20 mA drive capability |
| 10 | RESET_N | Digital input | Reset, active low |
| 11 | P0_0 | Digital I/O | Port 0.0 |
| 12 | P0_1 | Digital I/O | Port 0.1 |
| 13 | P0_2 | Digital I/O | Port 0.2 |
| 14 | P0_3 | Digital I/O | Port 0.3 |
| 15 | P0_4 | Digital I/O | Port 0.4 |
| 16 | P0_5 | Digital I/O | Port 0.5 |
| 17 | P0_6 | Digital I/O | Port 0.6 |
| 18 | P0_7 | Digital I/O | Port 0.7 |
| 19 | XOSC_Q2 | Analog I/O | 32 MHz crystal oscillator pin 2 |
| 20 | AVDD_SOC | Power (Analog) | 2.0V-3.6V analog power supply connection |
| 21 | XOSC_Q1 | Analog I/O | 32 MHz crystal oscillator pin 1, or external clock input |
| 22 | RBIAS1 | Analog I/O | External precision bias resistor for reference current |
| 23 | AVDD_RREG | Power (Analog) | 2.0V-3.6V analog power supply connection |
| 24 | RREG_OUT | Power output | 1.8V Voltage regulator power supply output. Only intended for supplying the analog 1.8V part (power supply for pins 25, 27-31, 35-40). |
| 25 | AVDD_IF1 | Power (Analog) | 1.8V Power supply for the receiver band pass filter, analog test module, global bias and first part of the VGA |
| 26 | RBIAS2 | Analog output | External precision resistor, 43 k Ω , ± 1 % |
| 27 | AVDD_CHP | Power (Analog) | 1.8V Power supply for phase detector, charge pump and first part of loop filter |
| 28 | VCO_GUARD | Power (Analog) | Connection of guard ring for VCO (to AVDD) shielding |
| 29 | AVDD_VCO | Power (Analog) | 1.8V Power supply for VCO and last part of PLL loop filter |
| 30 | AVDD_PRE | Power (Analog) | 1.8V Power supply for Prescaler, Div-2 and LO buffers |
| 31 | AVDD_RF1 | Power (Analog) | 1.8V Power supply for LNA, front-end bias and PA |
| 32 | RF_P | RF I/O | Positive RF input signal to LNA during RX. Positive RF output signal from PA during TX |
| 33 | TXRX_SWITCH | Power (Analog) | Regulated supply voltage for PA |
| 34 | RF_N | RF I/O | Negative RF input signal to LNA during RX Negative RF output signal from PA during TX |
| 35 | AVDD_SW | Power (Analog) | 1.8V Power supply for LNA / PA switch |
| 36 | AVDD_RF2 | Power (Analog) | 1.8V Power supply for receive and transmit mixers |
| 37 | AVDD_IF2 | Power (Analog) | 1.8V Power supply for transmit low pass filter and last stages of VGA |
| 38 | AVDD_ADC | Power (Analog) | 1.8V Power supply for analog parts of ADCs and DACs |
| 39 | DVDD_ADC | Power (Digital) | 1.8V Power supply for digital parts of ADCs |
| 40 | AVDD_DGUARD | Power (Digital) | Power supply connection for digital noise isolation |
| 41 | AVDD_DREG | Power (Digital) | 2.0V-3.6V digital power supply for digital core voltage regulator |
| 42 | DCOUP | Power (Digital) | 1.8V digital power supply decoupling. Do not use for supplying external circuits. |
| 43 | P2_4/XOSC_Q2 | Digital I/O | Port 2.4/32.768 kHz XOSC |
| 44 | P2_3/XOSC_Q1 | Digital I/O | Port 2.3/32.768 kHz XOSC |
| 45 | P2_2 | Digital I/O | Port 2.2 |
| 46 | P2_1 | Digital I/O | Port 2.1 |
| 47 | DVDD | Power (Digital) | 2.0V-3.6V digital power supply for digital I/O |
| 48 | P2_0 | Digital I/O | Port 2.0 |

Table 21: Pinout overview

9 Circuit Description**Figure 5: CC2430 Block Diagram**

A block diagram of **CC2430** is shown in Figure 5. The modules can be roughly divided into one of three categories: CPU-related modules, radio-related modules and modules related to power, test and clock distribution. In the following subsections, a short description of

each module that appears in Figure 5 is given.

9.1 CPU and Peripherals

The **8051 CPU core** is a single-cycle 8051-compatible core. It has three different memory

access buses (SFR, DATA and CODE/XDATA), a debug interface and an 18-input extended interrupt unit. See section 12 for details on the CPU.

The **memory crossbar/arbitrator** is at the heart of the system as it connects the CPU and DMA controller with the physical memories and all peripherals through the SFR bus. The memory arbitrator has four memory access points, access at which can map to one of three physical memories: an 8 KB SRAM, flash memory or RF and SFR registers. The memory arbitrator is responsible for performing arbitration and sequencing between simultaneous memory accesses to the same physical memory.

The **SFR bus** is drawn conceptually in the block diagram as a common bus that connects all hardware peripherals to the memory arbitrator. The SFR bus in the block diagram also provides access to the radio registers in the radio register bank even though these are indeed mapped into XDATA memory space.

The **8 KB SRAM** maps to the DATA memory space and to parts of the XDATA memory spaces. 4 KB of the 8 KB SRAM is an ultra-low-power SRAM that retains its contents even when the digital part is powered off (power modes 2 and 3). The rest of the SRAM loses its contents when the digital part is powered off.

The **32/64/128 KB flash block** provides in-circuit programmable non-volatile program memory for the device and maps into the CODE and XDATA memory spaces. Table 22 shows the available devices in the **CC2430** family. The available devices differ only in flash memory size. Writing to the flash block is performed through a **flash controller** that allows page-wise (2048 byte) erasure and 4 byte-wise programming. See section 13.14 for details on the flash controller.

A versatile five-channel **DMA controller** is available in the system and accesses memory using a unified memory space (XDATA) and thus has access to all physical memories. Each channel is configured (trigger, priority, transfer mode, addressing mode, source and destination pointers, and transfer count) with DMA descriptors anywhere in memory. Many of the hardware peripherals rely on the DMA controller for efficient operation (AES core, flash write controller, USARTs, Timers, ADC interface) by performing data transfers between a single SFR address and flash/SRAM. See section 13.2 for details.

The **interrupt controller** services a total of 18 interrupt sources, divided into six *interrupt groups*, each of which is associated with one of four interrupt priorities. An interrupt request is serviced even if the device is in a sleep mode (power modes 1-3) by bringing the **CC2430** back to active mode (power mode 0).

The **debug interface** implements a proprietary two-wire serial interface that is used for in-circuit debugging. Through this debug interface it is possible to perform an erasure of the entire flash memory, control which oscillators are enabled, stop and start execution of the user program, execute supplied instructions on the 8051 core, set code breakpoints, and single step through instructions in the code. Using these techniques it is possible to elegantly perform in-circuit debugging and external flash programming. See section 12.9 for details.

The **I/O-controller** is responsible for all general-purpose I/O pins. The CPU can configure whether peripheral modules control certain pins or whether they are under software control, and if so whether each pin is configured as an input or output and if a pull-up or pull-down resistor in the pad is connected. Each peripheral that connects to the I/O-pins can choose between two different I/O pin locations to ensure flexibility in various applications. See section 13.1 for details.

The **sleep timer** is an ultra-low power timer that counts 32.768 kHz crystal oscillator or 32.768 kHz RC oscillator periods. The sleep timer runs continuously in all operating modes except power mode 3. Typical uses for it is as a real-time counter that runs regardless of operating mode (except power mode 3) or as a wakeup timer to get out of power mode 1 or 2. See section 13.5 for details.

A built-in **watchdog timer** allows the **CC2430** to reset itself in case the firmware hangs. When enabled by software, the watchdog timer must be cleared periodically, otherwise it will reset the device when it times out. See section 13.12 for details.

Timer 1 is a 16-bit timer with timer/counter/PWM functionality. It has a programmable prescaler, a 16-bit period value and three individually programmable counter/capture channels each with a 16-bit compare value. Each of the counter/capture channels can be used as PWM outputs or to capture the timing of edges on input signals. See section 13.3 for details.

Timer 2 (MAC timer) is specially designed for supporting an IEEE 802.15.4 MAC or other time-slotted protocols in software. The timer has a configurable timer period and an 8-bit overflow counter that can be used to keep track of the number of periods that have transpired. There is also a 16-bit capture register used to record the exact time at which a start of frame delimiter is received/transmitted or the exact time of which transmission ends, as well as a 16-bit output compare register that can produce various command strobes (start RX, start TX, etc) at specific times to the radio modules. See section 13.4 for details.

Timers 3 and 4 are 8-bit timers with timer/counter/PWM functionality. They have a programmable prescaler, an 8-bit period value and one programmable counter channel with a 8-bit compare value. Each of the counter channels can be used as PWM outputs. See section 13.6 for details.

USART 0 and 1 are each configurable as either an SPI master/slave or a UART. They provide double buffering on both RX and TX and hardware flow-control and are thus well suited to high-throughput full-duplex applications. Each has its own high-precision baud-rate generator thus leaving the ordinary timers free for other uses. When configured as

an SPI slave they sample the input signal using SCK directly instead of some over-sampling scheme and are thus well-suited to high data rates. See section 13.13 for details.

The **AES encryption/decryption core** allows the user to encrypt and decrypt data using the AES algorithm with 128-bit keys. The core is able to support the AES operations required by IEEE 802.15.4 MAC security, the ZigBee™ network layer and the application layer. See section 13.9 for details.

The **ADC** supports 8 to 14 bits of resolution in a 30 kHz to 4 kHz bandwidth respectively. DC and audio conversions with up to 8 input channels (Port 0) are possible. The inputs can be selected as single ended or differential. The reference voltage can be internal, AVDD, or a single ended or differential external signal. The ADC also has a temperature sensor input channel. The ADC can automate the process of periodic sampling or conversion over a sequence of channels. See Section 13.7 for details.

9.2 Radio

CC2430 features an IEEE 802.15.4 compliant radio based on the leading **CC2420** transceiver. See Section 14 for details.

| Device | Flash |
|-------------|--------|
| CC2430-F32 | 32 KB |
| CC2430-F64 | 64 KB |
| CC2430-F128 | 128 KB |

Table 22: CC2430 Flash Memory Options

10 Power Management

The **CC2430** has four major power modes, called PM0, PM1, PM2 and PM3. PM0 is the active mode while PM3 has the lowest power consumption. The power modes are shown in Table 23 together with voltage regulator and oscillator options.

| Power Mode | High frequency oscillator | Low- frequency oscillator | Voltage regulator (digital) |
|---------------|---------------------------|---------------------------|-----------------------------|
| Configuration | A None | A None | A Off |
| | B 32 MHz XOSC | B 32.768 kHz RCOSC | B On |
| | C HF RCOSC | C 32.768 kHz XOSC | |
| | D Both | | |
| PM0 | B, C, D | B, C | B |
| PM1 | A | B, C | B |
| PM2 | A | B, C | A |
| PM3 | A | A | A |

Table 23: Power Modes

PM0 : The full functional mode. The voltage regulator to the digital core is on and either the

High frequency RC oscillator or the 32 MHz crystal oscillator or both are running. Either the 32.768 kHz RC oscillator or the 32.768 kHz crystal oscillator is running.

PM1 : The voltage regulator to the digital part is on. Neither the 32 MHz crystal oscillator nor the High frequency RC oscillator are running. Either the 32.768 kHz RC oscillator or the 32.768 kHz crystal oscillator is running. The system will go to PM0 on reset or an external interrupt or when the sleep timer expires.

PM2 : The voltage regulator to the digital core is turned off. Neither the 32 MHz crystal oscillator nor the High frequency RC oscillator are running. Either the 32.768 kHz RC oscillator or the 32.768 kHz crystal oscillator is running. The system will go to PM0 on reset or an external interrupt or when the sleep timer expires.

PM3 : The voltage regulator to the digital core is turned off. None of the oscillators are running. The system will go to PM0 on reset or an external interrupt.

Refer to section 13.10 on page 135 for a detailed description of power management.

11 Application Circuit

Few external components are required for the operation of **CC2430**. A typical application circuit is shown in Figure 6. Typical values and description of external components are shown in Table 24

11.1 Input / output matching

The RF input/output is high impedance and differential. The optimum differential load for the RF port is $115 + j180 \Omega$.

When using an unbalanced antenna such as a monopole, a balun should be used in order to optimize performance. The balun can be implemented using low-cost discrete inductors and capacitors. The recommended balun shown, consists of C341, L341, L321 and L331 together with a PCB microstrip transmission line ($\lambda/2$ -dipole), and will match the RF input/output to 50Ω . An internal T/R switch circuit is used to switch between the LNA and the PA. See Input/output matching section on page 181 for more details.

If a balanced antenna such as a folded dipole is used, the balun can be omitted. If the antenna also provides a DC path from TXRX_SWITCH pin to the RF pins, inductors are not needed for DC bias.

Figure 6 shows a suggested application circuit using a differential antenna. The antenna type is a standard folded dipole. The dipole has a virtual ground point; hence bias is provided without degradation in antenna performance. Also refer to the section Antenna Considerations on page 186.

11.2 Bias resistors

The bias resistors are R221 and R261. The bias resistor R221 is used to set an accurate bias current for the 32 MHz crystal oscillator.

11.3 Crystal

An external 32 MHz crystal, XTAL1, with two loading capacitors (C191 and C211) is used for the 32 MHz crystal oscillator. See page 15 for details. The load capacitance seen by the 32 MHz crystal is given by:

$$C_L = \frac{1}{\frac{1}{C_{191}} + \frac{1}{C_{211}}} + C_{parasitic} + C_{tune}$$

The load capacitance is optionally tunable through software⁴ to improve the frequency accuracy. The tuning adds the capacitance, C_{tune} shown in the equation above. Hence initial crystal inaccuracy may be compensated for by tuning. See page 63 for details about tuning.

XTAL2 is an optional 32.768 kHz crystal, with two loading capacitors (C441 and C431), used for the 32.768 kHz crystal oscillator. The 32.768 kHz crystal oscillator is used in applications where you need both very low sleep current consumption and accurate wake up times. The load capacitance seen by the 32.768 kHz crystal is given by:

$$C_L = \frac{1}{\frac{1}{C_{441}} + \frac{1}{C_{431}}} + C_{parasitic}$$

11.4 Voltage regulators

The on chip voltage regulators supply all 1.8 V power supply pins and internal power supplies. C241 and C421 are required for stability of the regulators. A series resistor may be used to comply with the ESR requirement.


11.5 Debug interface

The debug interface pin P2_2 is connected through pull-up resistor R451 to the power supply. See section 13.1.6 on page 74.

11.6 Power supply decoupling and filtering

Proper power supply decoupling must be used for optimum performance. The placement and size of the decoupling capacitors and the power supply filtering are very important to achieve the best performance in an application. TI provides a compact reference design that should be followed very closely. Refer to the section PCB Layout Recommendation on page 185.

⁴ Only for devices with Chip Version register, CHVER.VERSION equal to 0x02 or greater



**Figure 6: CC2430 Application Circuit. (Digital I/O and ADC interface not connected).
Decoupling capacitors not shown.**

| Component | Description | Single Ended 50Ω Output | Differential Antenna |
|------------|---------------------------------------------------------------------------------------|-------------------------------------------------------|----------------------------------------|
| C191, C211 | 32 MHz crystal load capacitor | 22 pF, 5%, NP0, 0402 | 22 pF, 5%, NP0, 0402 |
| C241, C421 | Load capacitance for power supply voltage regulators | 220 nF, 10%, 0402 | 220 nF, 10%, 0402 |
| C341 | DC block to antenna and match | 5.6 pF, +/- 0.25pF, NP0, 0402 | Not used |
| C431, C441 | 32.768 kHz crystal load capacitor (if low-frequency crystal is needed in application) | 15 pF, 5%, NP0, 0402 | 15 pF, 5%, NP0, 0402 |
| L321 | Discrete balun and match | 6.8 nH ⁵ , 5%, Monolithic/multilayer, 0402 | 12 nH 5%, Monolithic/multilayer, 0402 |
| L331 | Discrete balun and match | 22 nH, 5%, Monolithic/multilayer, 0402 | 27 nH, 5%, Monolithic/multilayer, 0402 |
| L341 | Discrete balun and match | 1.8 nH, 5%, Monolithic/multilayer, 0402 | Not used |
| R221 | Precision resistor for current reference generator to system-on-chip part | 56 kΩ, 1%, 0402 | 56 kΩ, 1%, 0402 |
| R261 | Precision resistor for current reference generator to RF part | 43 kΩ, 1%, 0402 | 43 kΩ, 1%, 0402 |
| R451 | Pull-up resistor connected to 2.0V-3.6V power supply. | | |
| XTAL1 | 32 MHz Crystal | 32 MHz crystal, ESR < 60 Ω | 32 MHz crystal, ESR < 60 Ω |
| XTAL2 | Optional 32.768 kHz watch crystal (if low-frequency crystal is needed in application) | 32.768 kHz crystal, Epson MC 306. | 32.768 kHz crystal, Epson MC 306. |

Table 24: Overview of external components (excluding supply decoupling capacitors)

⁵ For devices with Chip Version register, CHVER.VERSION equal 0x03 or greater

12 8051 CPU

This section describes the 8051 CPU core, with interrupts, memory and instruction set.

12.1 8051 CPU Introduction

The **CC2430** includes an 8-bit CPU core which is an enhanced version of the industry standard 8051 core.

The enhanced 8051 core uses the standard 8051 instruction set. Instructions execute faster than the standard 8051 due to the following:

- One clock per instruction cycle is used as opposed to 12 clocks per instruction cycle in the standard 8051.
- Wasted bus states are eliminated.

Since an instruction cycle is aligned with memory fetch when possible, most of the single byte instructions are performed in a single clock cycle. In addition to the speed improvement, the enhanced 8051 core also includes architectural enhancements:

- A second data pointer.
- Extended 18-source interrupt unit

The 8051 core is object code compatible with the industry standard 8051 microcontroller. That is, object code compiled with an industry standard 8051 compiler or assembler executes on the 8051 core and is functionally equivalent. However, because the 8051 core uses a different instruction timing than many other 8051 variants, existing code with timing loops may require modification. Also because the peripheral units such as timers and serial ports differ from those on a other 8051 cores, code which includes instructions using the peripheral units SFRs will not work correctly.

12.2 Reset

The **CC2430** has three reset sources. The following events generate a reset:

- Forcing RESET_N input pin low
- A power-on reset condition
- Watchdog timer reset condition

The initial conditions after a reset are as follows:

- I/O pins are configured as inputs with pull-up

- CPU program counter is loaded with 0x0000 and program execution starts at this address
- All peripheral registers are initialized to their reset values (refer to register descriptions)
- Watchdog timer is disabled

12.3 Memory

The 8051 CPU architecture has four different memory spaces. The 8051 has separate memory spaces for program memory and data memory. The 8051 memory spaces are the following:

CODE. A read-only memory space for program memory. This memory space can be up to 64 KB in size.

DATA. A read/write data memory space, which can be directly or indirectly accessed by a single cycle CPU instruction, thus allowing fast access. This memory space can be up to 256 bytes. The lower 128 bytes of the DATA memory space can be addressed either directly or indirectly, the upper 128 bytes only indirectly.

XDATA. A read/write data memory space access to which usually requires 4-5 CPU instruction cycles, thus giving slow access. This memory space can be up to 64 KB in size. Access to XDATA memory is also slower in hardware than DATA access as the CODE and XDATA memory spaces share a common bus on the CPU core and instruction pre-fetch from CODE can thus not be performed in parallel with XDATA accesses.

SFR. A read/write register memory space which can be directly accessed by a single CPU instruction. This memory space consists of 128 bytes. For SFR registers whose address is divisible by eight, each bit is also individually addressable.

The four different memory spaces are distinct in the 8051 architecture, but are partly overlapping in the **CC2430** to ease DMA transfers and hardware debugger operation.

How the different memory spaces are mapped onto the three physical memories (flash program memory, 8 KB SRAM and memory-mapped registers) is described in sections 12.3.1 and 12.3.2.

12.3.1 Memory Map

This section gives an overview of the memory map.

The memory map differs from the standard 8051 memory map in two important aspects, as described below.

First, in order to allow the DMA controller access to all physical memory and thus allow DMA transfers between the different 8051 memory spaces, parts of SFR and CODE memory space is mapped into the XDATA memory space.

Secondly, two alternative schemes for CODE memory space mapping can be used. The first scheme is the standard 8051 mapping where only the program memory i.e. flash memory is mapped to CODE memory space. This mapping is the default used after a device reset.

The second scheme is an extension to the standard CODE space mapping in that all

physical memory is mapped to CODE space, by using a *unified mapping* of the CODE memory space.

Details about mapping of all 8051 memory spaces are given in the next section.

The memory map showing how the different physical memories are mapped into the CPU memory spaces is given in the figures on the following pages for each flash memory size option.

Note that for CODE memory space, the two alternative memory maps are shown; unified and non-unified (standard) mapping.

For users familiar with the 8051 architecture, the standard 8051 memory space is shown as “*8051 memory spaces*” in the figures.




Figure 7: CC2430-F32 XDATA memory space




Figure 8: CC2430-F32 Non-unified mapping of CODE Space




Figure 9: CC2430-F32 Unified mapping of CODE space






Figure 10: CC2430-F64 XDATA memory space






Figure 13: CC2430-F128 XDATA memory space




Figure 14: CC2430-F128 Non-unified mapping of CODE Space




Figure 15: CC2430-F128 Unified mapping of CODE space

12.3.2 Memory Space

This section describes the details of each CPU memory space.

XDATA memory space. The XDATA memory map is given for each flash memory option in Figure 7, Figure 10 and Figure 13. For the devices with flash size above 32 KB, the lower 55 KB of the flash program memory is mapped into the address range 0x0000-0xDEFF. For the 32 KB flash size option, the 32 KB flash memory is mapped to 0x0000-0x7FFF in XDATA memory space.

Access to unimplemented areas shown as shaded in the memory map gives an undefined result.

For all device flash-options, the 8 KB SRAM is mapped into address range 0xE000-0xFFFF.

Also the SFR registers are mapped into address range 0xDF80-0xDFFF.

Another memory-mapped register area is the RF register area which is mapped into the address range 0xDF00-0xDF7F. These registers are associated with the radio (see sections 14 and 14.35).

The mapping of flash memory, SRAM and registers to XDATA allows the DMA controller and the CPU access to all the physical memories in a single unified address space.

One of the ramifications of this mapping is that the first address of usable SRAM starts at address 0xE000 instead of 0x0000, and therefore compilers/assemblers must take this into consideration.

In low-power modes PM2-3, with the lowest power consumption, the upper 4 KB of SRAM i.e. the memory locations in XDATA address range 0xF000-0xFFFF will retain their contents. There are some locations in this area that are excepted from retention. Refer to section 13.10 on page 135 for a detailed description of power modes and SRAM data retention.

CODE memory space. The CODE memory space uses either a *unified* or *non-unified* mapping (see section 12.3.1 on page 34) to the physical memories as shown in Figure 8 - Figure 9, Figure 11 - Figure 12 and Figure 14 - Figure 15. The unified mapping of the CODE memory space is similar to the XDATA mapping. Note that some SFR registers internal to the CPU can not be accessed in the

unified CODE memory space (see section 12.4 on page 44).

With flash memory sizes above 32 KB, the lower 55 KB of flash memory is mapped to CODE memory space when unified mapping is used. This is similar to the XDATA memory space.

The 8 KB SRAM is included in the CODE address space to allow program execution out of the SRAM.

Note: in order to use the unified memory mapping within CODE memory space, the SFR register bit `MEMCTR.MUNIF` must be 1.

For devices with flash memory size of 128 KB (CC2430-F128), a flash memory banking scheme is used for the CODE memory space. Since the physical flash memory size is 128 KB, the upper 32 KB area of CODE memory space is mapped to one out of the four 32 KB physical banks of flash memory through the flash bank select bits as shown in the non-unified CODE memory map. The flash bank select bits reside in the SFR register bits `MEMCTR.FMAP` (see section 12.12 on page 68). When unified CODE memory space mapping is used, the CODE memory is mapped to the flash memory in a similar manner to non-unified mapping, using memory banking, however 23 KB of the selected bank is available, as shown in the memory map.

Access to unimplemented areas shown as shaded in the memory map gives an undefined result.

DATA memory space. The 8-bit address range of DATA memory is mapped into the upper 256 bytes of the 8 KB SRAM. This area is also accessible through the unified CODE and XDATA memory spaces at the address range 0xFF00-0xFFFF.

SFR memory space. The 128 entry hardware register area is accessed through this memory space. The SFR registers are also accessible through the XDATA/DMA address space at the address range 0xDF80-0xDFFF. Some CPU-specific SFR registers reside inside the CPU core and can only be accessed using the SFR memory space and not through the duplicate mapping into XDATA memory space. These specific SFR registers are listed in section 12.4 on page 44.

12.3.3 Data Pointers

The **CC2430** has two data pointers, DPTR0 and DPTR1 to accelerate the movement of data blocks to/from memory. The data pointers are generally used to access CODE or XDATA space e.g.

```
MOVC A, @A+DPTR
```

```
MOV A, @DPTR.
```

The data pointer select bit, bit 0 in the Data Pointer Select register **DPS**, chooses which data pointer shall be the active one during execution of an instruction that uses the data pointer, e.g. in one of the above instructions.

The data pointers are two bytes wide consisting of the following SFRs:

- DPTR0 – DPH0 : DPL0
- DPTR1 – DPH1 : DPL1

DPH0 (0x83) – Data Pointer 0 High Byte

| Bit | Name | Reset | R/W | Description |
|-----|-----------|-------|-----|---------------------------|
| 7:0 | DPH0[7:0] | 0 | R/W | Data pointer 0, high byte |

DPL0 (0x82) – Data Pointer 0 Low Byte

| Bit | Name | Reset | R/W | Description |
|-----|-----------|-------|-----|--------------------------|
| 7:0 | DPL0[7:0] | 0 | R/W | Data pointer 0, low byte |

DPH1 (0x85) – Data Pointer 1 High Byte

| Bit | Name | Reset | R/W | Description |
|-----|-----------|-------|-----|---------------------------|
| 7:0 | DPH1[7:0] | 0 | R/W | Data pointer 1, high byte |

DPL1 (0x84) – Data Pointer 1 Low Byte

| Bit | Name | Reset | R/W | Description |
|-----|-----------|-------|-----|--------------------------|
| 7:0 | DPL1[7:0] | 0 | R/W | Data pointer 1, low byte |

DPS (0x92) – Data Pointer Select

| Bit | Name | Reset | R/W | Description |
|-----|------|-------|-----|-----------------------------------------------------------------------------|
| 7:1 | – | 0x00 | R0 | Not used |
| 0 | DPS | 0 | R/W | Data pointer select. Selects active data pointer. 0 : DPTR0 1 : DPTR1 |

12.3.4 XDATA Memory Access

The **CC2430** provides an additional SFR register **MPAGE**. This register is used during instructions **MOVX A, @Ri** and **MOVX @Ri, A**. **MPAGE** gives the 8 most significant address bits, while the register **Ri** gives the 8 least significant bits.

In some 8051 implementations, this type of XDATA access is performed using **P2** to give the most significant address bits. Existing software may therefore have to be adapted to make use of **MPAGE** instead of **P2**.

MPAGE (0x93) – Memory Page Select

| Bit | Name | Reset | R/W | Description |
|-----|------|-------|-----|-------------|
|-----|------|-------|-----|-------------|

| Bit | Name | Reset | R/W | Description |
|-----|----------------|-------|-----|-------------------------------------------------------------|
| 7:0 | MPAGE[7 : 0] | 0x00 | R/W | Memory page, high-order bits of address in MOVX instruction |

12.4 SFR Registers

The Special Function Registers (SFRs) control several of the features of the 8051 CPU core and/or peripherals. Many of the 8051 core SFRs are identical to the standard 8051 SFRs. However, there are additional SFRs that control features that are not available in the standard 8051. The additional SFRs are used to interface with the peripheral units and RF transceiver.

Table 25 shows the address to all SFRs in **CC2430**. The 8051 internal SFRs are shown with grey background, while the other SFRs are the SFRs specific to **CC2430**.

Note : all internal SFRs (shown with grey background in Table 25), can only be accessed through SFR space as these registers are not mapped into XDATA space.

Table 26 lists the additional SFRs that are not standard 8051 peripheral SFRs or CPU-internal SFRs. The additional SFRs are described in the relevant sections for each peripheral function.

| 8 bytes | | | | | | | | | |
|---------|--------|--------|----------|----------|----------|----------|----------|---------|----|
| 80 | P0 | SP | DPL0 | DPH0 | DPL1 | DPH1 | U0CSR | PCON | 87 |
| 88 | TCON | P0IFG | P1IFG | P2IFG | PICTL | P1IEN | - | P0INP | 8F |
| 90 | P1 | RFIM | DPS | MPAGE | T2CMP | ST0 | ST1 | ST2 | 97 |
| 98 | S0CON | - | IEN2 | S1CON | T2PEROF0 | T2PEROF1 | T2PEROF2 | FMAP | 9F |
| A0 | P2 | T2OF0 | T2OF1 | T2OF2 | T2CAPLPL | T2CAPHPH | T2TLD | T2THD | A7 |
| A8 | IEN0 | IP0 | - | FWT | FADDRH | FADDRH | FCTL | FWDATA | AF |
| B0 | - | ENC0I | ENC0D | ENCCS | ADCCON1 | ADCCON2 | ADCCON3 | - | B7 |
| B8 | IEN1 | IP1 | ADCL | ADCH | RNDL | RNDH | SLEEP | - | BF |
| C0 | IRCON | U0DBUF | U0BAUD | T2CNF | U0UCR | U0GCR | CLKCON | MEMCTR | C7 |
| C8 | - | WDCTL | T3CNT | T3CTL | T3CCTL0 | T3CC0 | T3CCTL1 | T3CC1 | CF |
| D0 | PSW | DMAIRQ | DMA1CFGH | DMA1CFGH | DMA0CFGH | DMA0CFGH | DMAARM | DMAREQ | D7 |
| D8 | TIMIF | RFD | T1CC0L | T1CC0H | T1CC1L | T1CC1H | T1CC2L | T1CC2H | DF |
| E0 | ACC | RFST | T1CNTL | T1CNTH | T1CTL | T1CCTL0 | T1CCTL1 | T1CCTL2 | E7 |
| E8 | IRCON2 | RFIF | T4CNT | T4CTL | T4CCTL0 | T4CC0 | T4CCTL1 | T4CC1 | EF |
| F0 | B | PERCFG | ADCCFG | P0SEL | P1SEL | P2SEL | P1INP | P2INP | F7 |
| F8 | U1CSR | U1DBUF | U1BAUD | U1UCR | U1GCR | P0DIR | P1DIR | P2DIR | FF |

Table 25: SFR address overview

Table 26: CC2430 specific SFR overview

| Register name | SFR Address | Module | Description |
|---------------|-------------|--------|----------------------------------|
| ADCCON1 | 0xB4 | ADC | ADC Control 1 |
| ADCCON2 | 0xB5 | ADC | ADC Control 2 |
| ADCCON3 | 0xB6 | ADC | ADC Control 3 |
| ADCL | 0xBA | ADC | ADC Data Low |
| ADCH | 0xBB | ADC | ADC Data High |
| RNDL | 0xBC | ADC | Random Number Generator Data Low |

| Register name | SFR Address | Module | Description |
|---------------|-------------|--------|--------------------------------------------|
| RNDH | 0xBD | ADC | Random Number Generator Data High |
| ENCDI | 0xB1 | AES | Encryption/Decryption Input Data |
| ENCDO | 0xB2 | AES | Encryption/Decryption Output Data |
| ENCCS | 0xB3 | AES | Encryption/Decryption Control and Status |
| DMAIRQ | 0xD1 | DMA | DMA Interrupt Flag |
| DMA1CFGL | 0xD2 | DMA | DMA Channel 1-4 Configuration Address Low |
| DMA1CFGH | 0xD3 | DMA | DMA Channel 1-4 Configuration Address High |
| DMA0CFGL | 0xD4 | DMA | DMA Channel 0 Configuration Address Low |
| DMA0CFGH | 0xD5 | DMA | DMA Channel 0 Configuration Address High |
| DMAARM | 0xD6 | DMA | DMA Channel Armed |
| DMAREQ | 0xD7 | DMA | DMA Channel Start Request and Status |
| FWT | 0xAB | FLASH | Flash Write Timing |
| FADDRH | 0xAC | FLASH | Flash Address Low |
| FADDRH | 0xAD | FLASH | Flash Address High |
| FCTL | 0xAE | FLASH | Flash Control |
| FWDATA | 0xAF | FLASH | Flash Write Data |
| P0IFG | 0x89 | IOC | Port 0 Interrupt Status Flag |
| P1IFG | 0x8A | IOC | Port 1 Interrupt Status Flag |
| P2IFG | 0x8B | IOC | Port 2 Interrupt Status Flag |
| PICTL | 0x8C | IOC | Port Pins Interrupt Mask and Edge |
| P1IEN | 0x8D | IOC | Port 1 Interrupt Mask |
| P0INP | 0x8F | IOC | Port 0 Input Mode |
| PERCFG | 0xF1 | IOC | Peripheral I/O Control |
| ADCCFG | 0xF2 | IOC | ADC Input Configuration |
| P0SEL | 0xF3 | IOC | Port 0 Function Select |
| P1SEL | 0xF4 | IOC | Port 1 Function Select |
| P2SEL | 0xF5 | IOC | Port 2 Function Select |
| P1INP | 0xF6 | IOC | Port 1 Input Mode |
| P2INP | 0xF7 | IOC | Port 2 Input Mode |
| P0DIR | 0xFD | IOC | Port 0 Direction |
| P1DIR | 0xFE | IOC | Port 1 Direction |
| P2DIR | 0xFF | IOC | Port 2 Direction |
| MEMCTR | 0xC7 | MEMORY | Memory System Control |
| FMAP | 0x9F | MEMORY | Flash Memory Bank Mapping |
| RFIM | 0x91 | RF | RF Interrupt Mask |
| RFD | 0xD9 | RF | RF Data |
| RFST | 0xE1 | RF | RF Command Strobe |
| RFIF | 0xE9 | RF | RF Interrupt flags |
| ST0 | 0x95 | ST | Sleep Timer 0 |
| ST1 | 0x96 | ST | Sleep Timer 1 |
| ST2 | 0x97 | ST | Sleep Timer 2 |
| SLEEP | 0xBE | PMC | Sleep Mode Control |

| Register name | SFR Address | Module | Description |
|---------------|-------------|--------|----------------------------------------------|
| CLKCON | 0xC6 | PMC | Clock Control |
| T1CC0L | 0xDA | Timer1 | Timer 1 Channel 0 Capture/Compare Value Low |
| T1CC0H | 0xDB | Timer1 | Timer 1 Channel 0 Capture/Compare Value High |
| T1CC1L | 0xDC | Timer1 | Timer 1 Channel 1 Capture/Compare Value Low |
| T1CC1H | 0xDD | Timer1 | Timer 1 Channel 1 Capture/Compare Value High |
| T1CC2L | 0xDE | Timer1 | Timer 1 Channel 2 Capture/Compare Value Low |
| T1CC2H | 0xDF | Timer1 | Timer 1 Channel 2 Capture/Compare Value High |
| T1CNTL | 0xE2 | Timer1 | Timer 1 Counter Low |
| T1CNTH | 0xE3 | Timer1 | Timer 1 Counter High |
| T1CTL | 0xE4 | Timer1 | Timer 1 Control and Status |
| T1CCTL0 | 0xE5 | Timer1 | Timer 1 Channel 0 Capture/Compare Control |
| T1CCTL1 | 0xE6 | Timer1 | Timer 1 Channel 1 Capture/Compare Control |
| T1CCTL2 | 0xE7 | Timer1 | Timer 1 Channel 2 Capture/Compare Control |
| T2CMP | 0x94 | Timer2 | Timer 2 Compare Value |
| T2PEROF0 | 0x9C | Timer2 | Timer 2 Overflow Capture/Compare 0 |
| T2PEROF1 | 0x9D | Timer2 | Timer 2 Overflow Capture/Compare 1 |
| T2PEROF2 | 0x9E | Timer2 | Timer 2 Overflow Capture/Compare 2 |
| T2OF0 | 0xA1 | Timer2 | Timer 2 Overflow Count 0 |
| T2OF1 | 0xA2 | Timer2 | Timer 2 Overflow Count 1 |
| T2OF2 | 0xA3 | Timer2 | Timer 2 Overflow Count 2 |
| T2CAPLPL | 0xA4 | Timer2 | Timer 2 Timer Period Low |
| T2CAPHPH | 0xA5 | Timer2 | Timer 2 Timer Period High |
| T2TLD | 0xA6 | Timer2 | Timer 2 Timer Value Low |
| T2THD | 0xA7 | Timer2 | Timer 2 Timer Value High |
| T2CNF | 0xC3 | Timer2 | Timer 2 Configuration |
| T3CNT | 0xCA | Timer3 | Timer 3 Counter |
| T3CTL | 0xCB | Timer3 | Timer 3 Control |
| T3CCTL0 | 0xCC | Timer3 | Timer 3 Channel 0 Compare Control |
| T3CC0 | 0xCD | Timer3 | Timer 3 Channel 0 Compare Value |
| T3CCTL1 | 0xCE | Timer3 | Timer 3 Channel 1 Compare Control |
| T3CC1 | 0xCF | Timer3 | Timer 3 Channel 1 Compare Value |
| T4CNT | 0xEA | Timer4 | Timer 4 Counter |
| T4CTL | 0xEB | Timer4 | Timer 4 Control |
| T4CCTL0 | 0xEC | Timer4 | Timer 4 Channel 0 Compare Control |
| T4CC0 | 0xED | Timer4 | Timer 4 Channel 0 Compare Value |
| T4CCTL1 | 0xEE | Timer4 | Timer 4 Channel 1 Compare Control |
| T4CC1 | 0xEF | Timer4 | Timer 4 Channel 1 Compare Value |
| TIMIF | 0xD8 | TMINT | Timers 1/3/4 Joint Interrupt Mask/Flags |
| U0CSR | 0x86 | USART0 | USART 0 Control and Status |
| U0DBUF | 0xC1 | USART0 | USART 0 Receive/Transmit Data Buffer |
| U0BAUD | 0xC2 | USART0 | USART 0 Baud Rate Control |
| U0UCR | 0xC4 | USART0 | USART 0 UART Control |

| Register name | SFR Address | Module | Description |
|---------------|-------------|--------|--------------------------------------|
| U0GCR | 0xC5 | USART0 | USART 0 Generic Control |
| U1CSR | 0xF8 | USART1 | USART 1 Control and Status |
| U1DBUF | 0xF9 | USART1 | USART 1 Receive/Transmit Data Buffer |
| U1BAUD | 0xFA | USART1 | USART 1 Baud Rate Control |
| U1UCR | 0xFB | USART1 | USART 1 UART Control |
| U1GCR | 0xFC | USART1 | USART 1 Generic Control |
| WDCTL | 0xC9 | WDT | Watchdog Timer Control |

12.5 CPU Registers

This section describes the internal registers found in the CPU.

12.5.1 Registers R0-R7

The **CC2430** provides four register banks of eight registers each. These register banks are mapped in the DATA memory space at addresses 0x00-0x07, 0x08-0x0F, 0x10-0x17 and 0x18-0x1F. Each register bank contains the eight 8-bit register R0-R7. The register bank to be used is selected through the Program Status Word `PSW.RS[1:0]`.

12.5.2 Program Status Word

The Program Status Word (PSW) contains several bits that show the current state of the CPU. The Program Status Word is accessible as an SFR and it is bit-addressable. `PSW` is shown below and contains the Carry flag, Auxiliary Carry flag for BCD operations, Register Select bits, Overflow flag and Parity flag. Two bits in `PSW` are uncommitted and can be used as user-defined status flags

.

PSW (0xD0) – Program Status Word

| Bit | Name | Reset | R/W | Description |
|-----|---------|-------|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | CY | 0 | R/W | Carry flag. Set to 1 when the last arithmetic operation resulted in a carry (during addition) or borrow (during subtraction), otherwise cleared to 0 by all arithmetic operations. |
| 6 | AC | 0 | R/W | Auxiliary carry flag for BCD operations. Set to 1 when the last arithmetic operation resulted in a carry into (during addition) or borrow from (during subtraction) the high order nibble, otherwise cleared to 0 by all arithmetic operations. |
| 5 | F0 | 0 | R/W | User-defined, bit-addressable |
| 4:3 | RS[1:0] | 00 | R/W | Register bank select bits. Selects which set of R7-R0 registers to use from four possible register banks in DATA space. 00 Bank 0, 0x00 – 0x07 01 Bank 1, 0x08 – 0x0F 10 Bank 2, 0x10 – 0x17 11 Bank 3, 0x18 – 0x1F |
| 2 | OV | 0 | R/W | Overflow flag, set by arithmetic operations. Set to 1 when the last arithmetic operation resulted in a carry (addition), borrow (subtraction), or overflow (multiply or divide). Otherwise, the bit is cleared to 0 by all arithmetic operations. |
| 1 | F1 | 0 | R/W | User-defined, bit-addressable |
| 0 | P | 0 | R/W | Parity flag, parity of accumulator set by hardware to 1 if it contains an odd number of 1's, otherwise it is cleared to 0 |

12.5.3 Accumulator

ACC is the accumulator. This is the source and destination of most arithmetic instructions,

data transfers and other instructions. The mnemonic for the accumulator (in instructions involving the accumulator) refers to A instead of ACC.

ACC (0xE0) – Accumulator

| Bit | Name | Reset | R/W | Description |
|-----|----------|-------|-----|-------------|
| 7:0 | ACC[7:0] | 0x00 | R/W | Accumulator |

12.5.4 B Register

The B register is used as the second 8-bit argument during execution of multiply and

divide instructions. When not used for these purposes it may be used as a scratch-pad register to hold temporary data.

B (0xF0) – B Register

| Bit | Name | Reset | R/W | Description |
|-----|--------|-------|-----|-------------------------------------------|
| 7:0 | B[7:0] | 0x00 | R/W | B register. Used in MUL/DIV instructions. |

12.5.5 Stack Pointer

The stack resides in DATA memory space and grows upwards. The `PUSH` instruction first increments the Stack Pointer (`SP`) and then copies the byte into the stack. The Stack Pointer is initialized to `0x07` after a reset and it

is incremented once to start from location `0x08` which is the first register (`R0`) of the second register bank. Thus, in order to use more than one register bank, the `SP` should be initialized to a different location not used for data storage.

SP (0x81) – Stack Pointer

| Bit | Name | Reset | R/W | Description |
|-----|---------|-------|-----|---------------|
| 7:0 | SP[7:0] | 0x07 | R/W | Stack Pointer |

12.6 Instruction Set Summary

The 8051 instruction set is summarized in Table 27. All mnemonics copyrighted © Intel Corporation, 1980.

The following conventions are used in the instruction set summary:

- `Rn` – Register `R7-R0` of the currently selected register bank.
- `direct` – 8-bit internal data location's address. This can be DATA area (`0x00 – 0x7F`) or SFR area (`0x80 – 0xFF`).
- `@Ri` – 8-bit internal data location, DATA area (`0x00 – 0xFF`) addressed indirectly through register `R1` or `R0`.
- `#data` – 8-bit constant included in instruction.
- `#data16` – 16-bit constant included in instruction.

- `addr16` – 16-bit destination address. Used by `LCALL` and `LJMP`. A branch can be anywhere within the 64 KB CODE memory space.
- `addr11` – 11-bit destination address. Used by `ACALL` and `AJMP`. The branch will be within the same 2 KB page of program memory as the first byte of the following instruction.
- `rel` – Signed (two's complement) 8-bit offset byte. Used by `SJMP` and all conditional jumps. Range is `-128` to `+127` bytes relative to first byte of the following instruction.
- `bit` – direct addressed bit in DATA area or SFR.

The instructions that affect CPU flag settings located in `PSW` are listed in Table 28 on page 53. Note that operations on the `PSW` register or bits in `PSW` will also affect the flag settings.

Table 27: Instruction Set Summary

| Mnemonic | Description | Hex Opcode | Bytes | Cycles |
|------------------------------|---------------------------------------------|------------|-------|--------|
| Arithmetic operations | | | | |
| ADD A,Rn | Add register to accumulator | 28-2F | 1 | 1 |
| ADD A,direct | Add direct byte to accumulator | 25 | 2 | 2 |
| ADD A,@Ri | Add indirect RAM to accumulator | 26-27 | 1 | 2 |
| ADD A,#data | Add immediate data to accumulator | 24 | 2 | 2 |
| ADDC A,Rn | Add register to accumulator with carry flag | 38-3F | 1 | 1 |
| ADDC A,direct | Add direct byte to A with carry flag | 35 | 2 | 2 |
| ADDC A,@Ri | Add indirect RAM to A with carry flag | 36-37 | 1 | 2 |
| ADDC A,#data | Add immediate data to A with carry flag | 34 | 2 | 2 |
| SUBB A,Rn | Subtract register from A with borrow | 98-9F | 1 | 1 |
| SUBB A,direct | Subtract direct byte from A with borrow | 95 | 2 | 2 |
| SUBB A,@Ri | Subtract indirect RAM from A with borrow | 96-97 | 1 | 2 |
| SUBB A,#data | Subtract immediate data from A with borrow | 94 | 2 | 2 |
| INC A | Increment accumulator | 04 | 1 | 1 |
| INC Rn | Increment register | 08-0F | 1 | 2 |
| INC direct | Increment direct byte | 05 | 2 | 3 |
| INC @Ri | Increment indirect RAM | 06-07 | 1 | 3 |
| INC DPTR | Increment data pointer | A3 | 1 | 1 |
| DEC A | Decrement accumulator | 14 | 1 | 1 |
| DEC Rn | Decrement register | 18-1F | 1 | 2 |
| DEC direct | Decrement direct byte | 15 | 2 | 3 |
| DEC @Ri | Decrement indirect RAM | 16-17 | 1 | 3 |
| MUL AB | Multiply A and B | A4 | 1 | 5 |
| DIV | Divide A by B | 84 | 1 | 5 |
| DA A | Decimal adjust accumulator | D4 | 1 | 1 |
| Logical operations | | | | |
| ANL A,Rn | AND register to accumulator | 58-5F | 1 | 1 |
| ANL A,direct | AND direct byte to accumulator | 55 | 2 | 2 |
| ANL A,@Ri | AND indirect RAM to accumulator | 56-57 | 1 | 2 |
| ANL A,#data | AND immediate data to accumulator | 54 | 2 | 2 |
| ANL direct,A | AND accumulator to direct byte | 52 | 2 | 3 |
| ANL direct,#data | AND immediate data to direct byte | 53 | 3 | 4 |
| ORL A,Rn | OR register to accumulator | 48-4F | 1 | 1 |
| ORL A,direct | OR direct byte to accumulator | 45 | 2 | 2 |
| ORL A,@Ri | OR indirect RAM to accumulator | 46-47 | 1 | 2 |
| ORL A,#data | OR immediate data to accumulator | 44 | 2 | 2 |
| ORL direct,A | OR accumulator to direct byte | 42 | 2 | 3 |
| ORL direct,#data | OR immediate data to direct byte | 43 | 3 | 4 |
| XRL A,Rn | Exclusive OR register to accumulator | 68-6F | 1 | 1 |
| XRL A,direct | Exclusive OR direct byte to accumulator | 65 | 2 | 2 |

| Mnemonic | Description | Hex Opcode | Bytes | Cycles |
|--------------------------|------------------------------------------------|------------|-------|--------|
| XRL A,@Ri | Exclusive OR indirect RAM to accumulator | 66-67 | 1 | 2 |
| XRL A,#data | Exclusive OR immediate data to accumulator | 64 | 2 | 2 |
| XRL direct,A | Exclusive OR accumulator to direct byte | 62 | 2 | 3 |
| XRL direct,#data | Exclusive OR immediate data to direct byte | 63 | 3 | 4 |
| CLR A | Clear accumulator | E4 | 1 | 1 |
| CPL A | Complement accumulator | F4 | 1 | 1 |
| RL A | Rotate accumulator left | 23 | 1 | 1 |
| RLC A | Rotate accumulator left through carry | 33 | 1 | 1 |
| RR A | Rotate accumulator right | 03 | 1 | 1 |
| RRC A | Rotate accumulator right through carry | 13 | 1 | 1 |
| SWAP A | Swap nibbles within the accumulator | C4 | 1 | 1 |
| Data transfers | | | | |
| MOV A,Rn | Move register to accumulator | E8-EF | 1 | 1 |
| MOV A,direct | Move direct byte to accumulator | E5 | 2 | 2 |
| MOV A,@Ri | Move indirect RAM to accumulator | E6-E7 | 1 | 2 |
| MOV A,#data | Move immediate data to accumulator | 74 | 2 | 2 |
| MOV Rn,A | Move accumulator to register | F8-FF | 1 | 2 |
| MOV Rn,direct | Move direct byte to register | A8-AF | 2 | 4 |
| MOV Rn,#data | Move immediate data to register | 78-7F | 2 | 2 |
| MOV direct,A | Move accumulator to direct byte | F5 | 2 | 3 |
| MOV direct,Rn | Move register to direct byte | 88-8F | 2 | 3 |
| MOV direct1,direct2 | Move direct byte to direct byte | 85 | 3 | 4 |
| MOV direct,@Ri | Move indirect RAM to direct byte | 86-87 | 2 | 4 |
| MOV direct,#data | Move immediate data to direct byte | 75 | 3 | 3 |
| MOV @Ri,A | Move accumulator to indirect RAM | F6-F7 | 1 | 3 |
| MOV @Ri,direct | Move direct byte to indirect RAM | A6-A7 | 2 | 5 |
| MOV @Ri,#data | Move immediate data to indirect RAM | 76-77 | 2 | 3 |
| MOV DPTR,#data16 | Load data pointer with a 16-bit constant | 90 | 3 | 3 |
| MOVC A,@A+DPTR | Move code byte relative to DPTR to accumulator | 93 | 1 | 3 |
| MOVC A,@A+PC | Move code byte relative to PC to accumulator | 83 | 1 | 3 |
| MOVX A,@Ri | Move external RAM (8-bit address) to A | E2-E3 | 1 | 3-10 |
| MOVX A,@DPTR | Move external RAM (16-bit address) to A | E0 | 1 | 3-10 |
| MOVX @Ri,A | Move A to external RAM (8-bit address) | F2-F3 | 1 | 4-11 |
| MOVX @DPTR,A | Move A to external RAM (16-bit address) | F0 | 1 | 4-11 |
| PUSH direct | Push direct byte onto stack | C0 | 2 | 4 |
| POP direct | Pop direct byte from stack | D0 | 2 | 3 |
| XCH A,Rn | Exchange register with accumulator | C8-CF | 1 | 2 |
| XCH A,direct | Exchange direct byte with accumulator | C5 | 2 | 3 |
| XCH A,@Ri | Exchange indirect RAM with accumulator | C6-C7 | 1 | 3 |
| XCHD A,@Ri | Exchange low-order nibble indirect. RAM with A | D6-D7 | 1 | 3 |
| Program branching | | | | |
| ACALL addr11 | Absolute subroutine call | xxx11 | 2 | 6 |

| Mnemonic | Description | Hex Opcode | Bytes | Cycles |
|------------------------------------|-----------------------------------------------------|------------|-------|--------|
| LCALL addr16 | Long subroutine call | 12 | 3 | 6 |
| RET | Return from subroutine | 22 | 1 | 4 |
| RETI | Return from interrupt | 32 | 1 | 4 |
| AJMP addr11 | Absolute jump | xxx01 | 2 | 3 |
| LJMP addr16 | Long jump | 02 | 3 | 4 |
| SJMP rel | Short jump (relative address) | 80 | 2 | 3 |
| JMP @A+DPTR | Jump indirect relative to the DPTR | 73 | 1 | 2 |
| JZ rel | Jump if accumulator is zero | 60 | 2 | 3 |
| JNZ rel | Jump if accumulator is not zero | 70 | 2 | 3 |
| JC rel | Jump if carry flag is set | 40 | 2 | 3 |
| JNC | Jump if carry flag is not set | 50 | 2 | 3 |
| JB bit,rel | Jump if direct bit is set | 20 | 3 | 4 |
| JNB bit,rel | Jump if direct bit is not set | 30 | 3 | 4 |
| JBC bit,direct rel | Jump if direct bit is set and clear bit | 10 | 3 | 4 |
| CJNE A,direct rel | Compare direct byte to A and jump if not equal | B5 | 3 | 4 |
| CJNE A,#data rel | Compare immediate to A and jump if not equal | B4 | 3 | 4 |
| CJNE Rn,#data rel | Compare immediate to reg. and jump if not equal | B8-BF | 3 | 4 |
| CJNE @Ri,#data rel | Compare immediate to indirect and jump if not equal | B6-B7 | 3 | 4 |
| DJNZ Rn,rel | Decrement register and jump if not zero | D8-DF | 2 | 3 |
| DJNZ direct,rel | Decrement direct byte and jump if not zero | D5 | 3 | 4 |
| NOP | No operation | 00 | 1 | 1 |
| Boolean variable operations | | | | |
| CLR C | Clear carry flag | C3 | 1 | 1 |
| CLR bit | Clear direct bit | C2 | 2 | 3 |
| SETB C | Set carry flag | D3 | 1 | 1 |
| SETB bit | Set direct bit | D2 | 2 | 3 |
| CPL C | Complement carry flag | B3 | 1 | 1 |
| CPL bit | Complement direct bit | B2 | 2 | 3 |
| ANL C,bit | AND direct bit to carry flag | 82 | 2 | 2 |
| ANL C,/bit | AND complement of direct bit to carry | B0 | 2 | 2 |
| ORL C,bit | OR direct bit to carry flag | 72 | 2 | 2 |
| ORL C,/bit | OR complement of direct bit to carry | A0 | 2 | 2 |
| MOV C,bit | Move direct bit to carry flag | A2 | 2 | 2 |
| MOV bit,C | Move carry flag to direct bit | 92 | 2 | 3 |

| Instruction | CY | OV | AC |
|-------------|----|----|----|
| ADD | x | x | x |
| ADDC | x | x | x |
| SUBB | x | x | x |
| MUL | 0 | x | - |
| DIV | 0 | x | - |
| DA | x | - | - |
| RRC | x | - | - |
| RLC | x | - | - |
| SETB C | 1 | - | - |
| CLR C | x | - | - |
| CPL C | x | - | - |
| ANL C,bit | x | - | - |
| ANL C,/bit | x | - | - |
| ORL C,bit | x | - | - |
| ORL C,/bit | x | - | - |
| MOV C,bit | x | - | - |
| CJNE | x | - | - |

"0"=set to 0, "1"=set to 1, "x"=set to 0/1, "-"=not affected

Table 28: Instructions that affect flag settings

12.7 Interrupts

The CPU has 18 interrupt sources. Each source has its own request flag located in a set of Interrupt Flag SFR registers. Each interrupt requested by the corresponding flag can be individually enabled or disabled. The definitions of the interrupt sources and the interrupt vectors are given in Table 29.

The interrupts are grouped into a set of priority level groups with selectable priority levels.

The interrupt enable registers are described in section 12.7.1 and the interrupt priority settings are described in section 12.7.3 on page 61.

12.7.1 Interrupt Masking

Each interrupt can be individually enabled or disabled by the interrupt enable bits in the Interrupt Enable SFRs *IEN0*, *IEN1* and *IEN2*. The Interrupt Enable SFRs are described below and summarized in Table 29.

Note that some peripherals have several events that can generate the interrupt request associated with that peripheral. This applies to

Port 0, Port 1, Port 2, DMA, Timer 1, Timer2, Timer 3, Timer 4 and Radio. These peripherals have interrupt mask bits for each internal interrupt source in the corresponding SFR registers.

In order to use any of the interrupts in the **CC2430**, the following steps must be taken

1. Clear interrupt flags
2. Enable global interrupt by setting the EA bit in *IEN0* to 1
3. Set the corresponding individual, interrupt enable bit in the *IEN0*, *IEN1* or *IEN2* registers to 1.
4. Set individual interrupt enable bit in the peripherals SFR register, if any.
5. Begin the interrupt service routine at the corresponding vector address of that interrupt. See Table 29 for addresses.

| Interrupt number | Description | Interrupt name | Interrupt Vector | Interrupt Mask | Interrupt Flag |
|------------------|--------------------------------------------|----------------|------------------|----------------|----------------|
| 0 | RF TX FIFO underflow and RX FIFO overflow. | RFERR | 03h | IEN0.RFERRIE | TCON.RFERRIF |
| 1 | ADC end of conversion | ADC | 0Bh | IEN0.ADCIE | TCON.ADCIF |
| 2 | USART0 RX complete | URX0 | 13h | IEN0.URX0IE | TCON.URX0IF |
| 3 | USART1 RX complete | URX1 | 1Bh | IEN0.URX1IE | TCON.URX1IF |
| 4 | AES encryption/decryption complete | ENC | 23h | IEN0.ENCIE | SOCON.ENCIF |
| 5 | Sleep Timer compare | ST | 2Bh | IEN0.STIE | IRCON.STIF |
| 6 | Port 2 inputs | P2INT | 33h | IEN2.P2IE | IRCON2.P2IF |
| 7 | USART0 TX complete | UTX0 | 3Bh | IEN2.UTX0IE | IRCON2.UTX0IF |
| 8 | DMA transfer complete | DMA | 43h | IEN1.DMAIE | IRCON.DMAIF |
| 9 | Timer 1 (16-bit) capture/compare/overflow | T1 | 4Bh | IEN1.T1IE | IRCON.T1IF |
| 10 | Timer 2 (MAC Timer) | T2 | 53h | IEN1.T2IE | IRCON.T2IF |
| 11 | Timer 3 (8-bit) compare/overflow | T3 | 5Bh | IEN1.T3IE | IRCON.T3IF |
| 12 | Timer 4 (8-bit) compare/overflow | T4 | 63h | IEN1.T4IE | IRCON.T4IF |
| 13 | Port 0 inputs | P0INT | 6Bh | IEN1.P0IE | IRCON.P0IF |
| 14 | USART1 TX complete | UTX1 | 73h | IEN2.UTX1IE | IRCON2.UTX1IF |
| 15 | Port 1 inputs | P1INT | 7Bh | IEN2.P1IE | IRCON2.P1IF |
| 16 | RF general interrupts | RF | 83h | IEN2.RFIE | S1CON.RFIF |
| 17 | Watchdog overflow in timer mode | WDT | 8Bh | IEN2.WDTIE | IRCON2.WDTIF |

Table 29: Interrupts Overview

IEN0 (0xA8) – Interrupt Enable 0

| Bit | Name | Reset | R/W | Description |
|-----|---------|-------|-----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | EA | 0 | R/W | Disables all interrupts. 0 No interrupt will be acknowledged 1 Each interrupt source is individually enabled or disabled by setting its corresponding enable bit |
| 6 | – | 0 | R0 | Not used. Read as 0 |
| 5 | STIE | 0 | R/W | STIE – Sleep Timer interrupt enable 0 Interrupt disabled 1 Interrupt enabled |
| 4 | ENCIE | 0 | R/W | ENCIE – AES encryption/decryption interrupt enable 0 Interrupt disabled 1 Interrupt enabled |
| 3 | URX1IE | 0 | R/W | URX1IE – USART1 RX interrupt enable 0 Interrupt disabled 1 Interrupt enabled |
| 2 | URX0IE | 0 | R/W | URX0IE - USART0 RX interrupt enable 0 Interrupt disabled 1 Interrupt enabled |
| 1 | ADCIE | 0 | R/W | ADCIE – ADC interrupt enable 0 Interrupt disabled 1 Interrupt enabled |
| 0 | RFERRIE | 0 | R/W | RFERRIE – RF TX/RX FIFO interrupt enable 0 Interrupt disabled 1 Interrupt enabled |

IEN1 (0xB8) – Interrupt Enable 1

| Bit | Name | Reset | R/W | Description |
|-----|-------|-------|-----|--------------------------------------------------------------------------------------|
| 7:6 | – | 00 | R0 | Not used. Read as 0 |
| 5 | P0IE | 0 | R/W | P0IE – Port 0 interrupt enable 0 Interrupt disabled 1 Interrupt enabled |
| 4 | T4IE | 0 | R/W | T4IE - Timer 4 interrupt enable 0 Interrupt disabled 1 Interrupt enabled |
| 3 | T3IE | 0 | R/W | T3IE - Timer 3 interrupt enable 0 Interrupt disabled 1 Interrupt enabled |
| 2 | T2IE | 0 | R/W | T2IE – Timer 2 interrupt enable 0 Interrupt disabled 1 Interrupt enabled |
| 1 | T1IE | 0 | R/W | T1IE – Timer 1 interrupt enable 0 Interrupt disabled 1 Interrupt enabled |
| 0 | DMAIE | 0 | R/W | DMAIE – DMA transfer interrupt enable 0 Interrupt disabled 1 Interrupt enabled |

IEN2 (0x9A) – Interrupt Enable 2

| Bit | Name | Reset | R/W | Description |
|-----|--------|-------|-----|----------------------------------------------------------------------------------------|
| 7:6 | – | 00 | R0 | Not used. Read as 0 |
| 5 | WDTIE | 0 | R/W | WDTIE – Watchdog timer interrupt enable 0 Interrupt disabled 1 Interrupt enabled |
| 4 | P1IE | 0 | R/W | P1IE– Port 1 interrupt enable 0 Interrupt disabled 1 Interrupt enabled |
| 3 | UTX1IE | 0 | R/W | UTX1IE – USART1 TX interrupt enable 0 Interrupt disabled 1 Interrupt enabled |
| 2 | UTX0IE | 0 | R/W | UTX0IE - USART0 TX interrupt enable 0 Interrupt disabled 1 Interrupt enabled |
| 1 | P2IE | 0 | R/W | P2IE – Port 2 interrupt enable 0 Interrupt disabled 1 Interrupt enabled |
| 0 | RFIE | 0 | R/W | RFIE – RF general interrupt enable 0 Interrupt disabled 1 Interrupt enabled |

12.7.2 Interrupt Processing

When an interrupt occurs, the CPU will vector to the interrupt vector address as shown in Table 29. Once an interrupt service has begun, it can be interrupted only by a higher priority interrupt. The interrupt service is terminated by a `RETI` (return from interrupt instruction). When an `RETI` is performed, the CPU will return to the instruction that would have been next when the interrupt occurred.

When the interrupt condition occurs, the CPU will also indicate this by setting an interrupt flag bit in the interrupt flag registers. This bit is set regardless of whether the interrupt is enabled or disabled. If the interrupt is enabled

when an interrupt flag is set, then on the next instruction cycle the interrupt will be acknowledged by hardware forcing an `LCALL` to the appropriate vector address.

Interrupt response will require a varying amount of time depending on the state of the CPU when the interrupt occurs. If the CPU is performing an interrupt service with equal or greater priority, the new interrupt will be pending until it becomes the interrupt with highest priority. In other cases, the response time depends on current instruction. The fastest possible response to an interrupt is seven machine cycles. This includes one machine cycle for detecting the interrupt and six cycles to perform the `LCALL`.

TCON (0x88) – Interrupt Flags

| Bit | Name | Reset | R/W | Description |
|-----|---------|-------|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | URX1IF | 0 | R/W H0 | URX1IF – USART1 RX interrupt flag. Set to 1 when USART1 RX interrupt occurs and cleared when CPU vectors to the interrupt service routine. 0 Interrupt not pending 1 Interrupt pending |
| 6 | – | 0 | R/W | Not used |
| 5 | ADCIF | 0 | R/W H0 | ADCIF – ADC interrupt flag. Set to 1 when ADC interrupt occurs and cleared when CPU vectors to the interrupt service routine. 0 Interrupt not pending 1 Interrupt pending |
| 4 | – | 0 | R/W | Not used |
| 3 | URX0IF | 0 | R/W H0 | URX0IF – USART0 RX interrupt flag. Set to 1 when USART0 interrupt occurs and cleared when CPU vectors to the interrupt service routine. 0 Interrupt not pending 1 Interrupt pending |
| 2 | IT1 | 1 | R/W | Reserved. Must always be set to 1. |
| 1 | RFERRIF | 0 | R/W H0 | RFERRIF – RF TX/RX FIFO interrupt flag. Set to 1 when RFERR interrupt occurs and cleared when CPU vectors to the interrupt service routine. 0 Interrupt not pending 1 Interrupt pending |
| 0 | IT0 | 1 | R/W | Reserved. Must always be set to 1. |

S0CON (0x98) – Interrupt Flags 2

| Bit | Name | Reset | R/W | Description |
|-----|---------|-------|-----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:2 | – | 0x00 | R/W | Not used |
| 1 | ENCIF_1 | 0 | R/W | ENCIF – AES interrupt. ENC has two interrupt flags, ENCIF_1 and ENCIF_0. Setting one of these flags will request interrupt service. Both flags are set when the AES co-processor requests the interrupt. 0 Interrupt not pending 1 Interrupt pending |
| 0 | ENCIF_0 | 0 | R/W | ENCIF – AES interrupt. ENC has two interrupt flags, ENCIF_1 and ENCIF_0. Setting one of these flags will request interrupt service. Both flags are set when the AES co-processor requests the interrupt. 0 Interrupt not pending 1 Interrupt pending |

S1CON (0x9B) – Interrupt Flags 3

| Bit | Name | Reset | R/W | Description |
|-----|--------|-------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:2 | – | 0x00 | R/W | Not used |
| 1 | RFIF_1 | 0 | R/W | RFIF – RF general interrupt. RF has two interrupt flags, RFIF_1 and RFIF_0. Setting one of these flags will request interrupt service. Both flags are set when the radio requests the interrupt. 0 Interrupt not pending 1 Interrupt pending |
| 0 | RFIF_0 | 0 | R/W | RFIF – RF general interrupt. RF has two interrupt flags, RFIF_1 and RFIF_0. Setting one of these flags will request interrupt service. Both flags are set when the radio requests the interrupt. 0 Interrupt not pending 1 Interrupt pending |

IRCON (0xC0) – Interrupt Flags 4

| Bit | Name | Reset | R/W | Description |
|-----|-------|-------|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | STIF | 0 | R/W | STIF – Sleep timer interrupt flag 0 Interrupt not pending 1 Interrupt pending |
| 6 | – | 0 | R/W | Not used |
| 5 | P0IF | 0 | R/W | P0IF – Port 0 interrupt flag 0 Interrupt not pending 1 Interrupt pending |
| 4 | T4IF | 0 | R/W H0 | T4IF – Timer 4 interrupt flag. Set to 1 when Timer 4 interrupt occurs and cleared when CPU vectors to the interrupt service routine. 0 Interrupt not pending 1 Interrupt pending |
| 3 | T3IF | 0 | R/W H0 | T3IF – Timer 3 interrupt flag. Set to 1 when Timer 3 interrupt occurs and cleared when CPU vectors to the interrupt service routine. 0 Interrupt not pending 1 Interrupt pending |
| 2 | T2IF | 0 | R/W H0 | T2IF – Timer 2 interrupt flag. Set to 1 when Timer 2 interrupt occurs and cleared when CPU vectors to the interrupt service routine. 0 Interrupt not pending 1 Interrupt pending |
| 1 | T1IF | 0 | R/W H0 | T1IF – Timer 1 interrupt flag. Set to 1 when Timer 1 interrupt occurs and cleared when CPU vectors to the interrupt service routine. 0 Interrupt not pending 1 Interrupt pending |
| 0 | DMAIF | 0 | R/W | DMAIF – DMA complete interrupt flag. 0 Interrupt not pending 1 Interrupt pending |

IRCON2 (0xE8) – Interrupt Flags 5

| Bit | Name | Reset | R/W | Description |
|-----|--------|-------|-----|------------------------------------------------------------------------------------------|
| 7:5 | – | 00 | R/W | Not used |
| 4 | WDTIF | 0 | R/W | WDTIF – Watchdog timer interrupt flag. 0 Interrupt not pending 1 Interrupt pending |
| 3 | P1IF | 0 | R/W | P1IF – Port 1 interrupt flag. 0 Interrupt not pending 1 Interrupt pending |
| 2 | UTX1IF | 0 | R/W | UTX1IF – USART1 TX interrupt flag. 0 Interrupt not pending 1 Interrupt pending |
| 1 | UTX0IF | 0 | R/W | UTX0IF – USART0 TX interrupt flag. 0 Interrupt not pending 1 Interrupt pending |
| 0 | P2IF | 0 | R/W | P2IF – Port2 interrupt flag. 0 Interrupt not pending 1 Interrupt pending |

12.7.3 Interrupt Priority

The interrupts are grouped into six interrupt priority groups and the priority for each group is set by the registers **IP0** and **IP1**. In order to assign a higher priority to an interrupt, i.e. to its interrupt group, the corresponding bits in **IP0** and **IP1** must be set as shown in Table 30 on page 62.

The interrupt priority groups with assigned interrupt sources are shown in Table 31. Each group is assigned one of four priority levels.

While an interrupt service request is in progress, it cannot be interrupted by a lower or same level interrupt.

In the case when interrupt requests of the same priority level are received simultaneously, the polling sequence shown in Table 32 is used to resolve the priority of each request.

IP1 (0xB9) – Interrupt Priority 1

| Bit | Name | Reset | R/W | Description |
|-----|-------|-------|-----|--------------------------------------------------------------|
| 7:6 | – | 00 | R/W | Not used. |
| 5 | IP1_5 | 0 | R/W | Interrupt group 5, priority control bit 1, refer to Table 30 |
| 4 | IP1_4 | 0 | R/W | Interrupt group 4, priority control bit 1, refer to Table 30 |
| 3 | IP1_3 | 0 | R/W | Interrupt group 3, priority control bit 1, refer to Table 30 |
| 2 | IP1_2 | 0 | R/W | Interrupt group 2, priority control bit 1, refer to Table 30 |
| 1 | IP1_1 | 0 | R/W | Interrupt group 1, priority control bit 1, refer to Table 30 |
| 0 | IP1_0 | 0 | R/W | Interrupt group 0, priority control bit 1, refer to Table 30 |

12.7.4**IP0 (0xA9) – Interrupt Priority 0**

| Bit | Name | Reset | R/W | Description |
|-----|-------|-------|-----|--------------------------------------------------------------|
| 7:6 | – | 00 | R/W | Not used. |
| 5 | IP0_5 | 0 | R/W | Interrupt group 5, priority control bit 0, refer to Table 30 |
| 4 | IP0_4 | 0 | R/W | Interrupt group 4, priority control bit 0, refer to Table 30 |
| 3 | IP0_3 | 0 | R/W | Interrupt group 3, priority control bit 0, refer to Table 30 |
| 2 | IP0_2 | 0 | R/W | Interrupt group 2, priority control bit 0, refer to Table 30 |
| 1 | IP0_1 | 0 | R/W | Interrupt group 1, priority control bit 0, refer to Table 30 |
| 0 | IP0_0 | 0 | R/W | Interrupt group 0, priority control bit 0, refer to Table 30 |

| IP1_x | IP0_x | Priority Level |
|-------|-------|----------------|
| 0 | 0 | 0 – lowest |
| 0 | 1 | 1 |
| 1 | 0 | 2 |
| 1 | 1 | 3 – highest |

Table 30: Priority Level Setting

| Group | Interrupts | | |
|-------|------------|-------|-------|
| IP0 | RFERR | RF | DMA |
| IP1 | ADC | P2INT | T1 |
| IP2 | URX0 | UTX0 | T2 |
| IP3 | URX1 | UTX1 | T3 |
| IP4 | ENC | P1INT | T4 |
| IP5 | ST | WDT | POINT |

Table 31: Interrupt Priority Groups


| Interrupt number | Interrupt name | |
|------------------|----------------|---------------------------------------------------------------------------------------------------------|
| 0 | RFERR | Polling sequence  |
| 16 | RF | |
| 8 | DMA | |
| 1 | ADC | |
| 9 | T1 | |
| 2 | URX0 | |
| 10 | T2 | |
| 3 | URX1 | |
| 11 | T3 | |
| 4 | ENC | |
| 12 | T4 | |
| 5 | ST | |
| 13 | POINT | |
| 6 | P2INT | |
| 7 | UTX0 | |
| 14 | UTX1 | |
| 15 | P1INT | |
| 17 | WDT | |

Table 32: Interrupt Polling Sequence

12.8 Oscillators and clocks

The **CC2430** has one internal system clock. The source for the system clock can be either a 16 MHz high-frequency RC oscillator or a 32 MHz crystal oscillator. Clock control is performed using the `CLKCON` SFR register described in section 13.10.

The system clock also feeds all 8051 peripherals (as described in section 6).

The choice of oscillator allows a trade-off between high-accuracy in the case of the crystal oscillator and low power consumption when the high-frequency RC oscillator is used. Note that operation of the RF transceiver requires that the crystal oscillator is used.

Optional tuning of the 32 MHz crystal oscillator load capacitance is supported. In most applications this is usually not needed. The tuning functionality is available in RF register `XOSC32M`, where a step-wise capacitance can be added from the `XOSC_Q1` and `XOSC_Q2` pins to ground (see Figure 6 on page 31). Adding more capacitance will lower the frequency. This can be used to tune away initial crystal inaccuracy. The oscillator frequency can be measured during production

and the result can be stored in the internal flash memory and used on power-up. Some applications may also use this to compensate for temperature drift in the crystal, by measuring the temperature and compensating accordingly. This must be handled by software.

By default, no additional capacitance is added to the oscillator pins. If tuning is necessary, the external capacitors (C211 and C191 in Figure 6) should be reduced such that the mid-value of the `XOSC32M` register corresponds to the nominal center frequency of the crystal.

12.9 Debug Interface

The **CC2430** includes a debug interface that provides a two-wire interface to an on-chip debug module. The debug interface allows programming of the on-chip flash and it provides access to memory and register contents and debug features such as breakpoints, single-stepping and register modification.

The debug interface uses the I/O pins P2_1 as Debug Data and P2_2 as Debug Clock during Debug mode. These I/O pins can be used as general purpose I/O only while the device is not in Debug mode. Thus the debug interface does not interfere with any peripheral I/O pins.

12.9.1 Debug Mode

Debug mode is entered by forcing two rising edge transitions on pin P2_2 (Debug Clock) while the RESET_N input is held low. See section 13.1.6 for pull-up resistor recommendation for pin P2_2.

While in Debug mode pin P2_1 is the Debug Data bi-directional pin and P2_2 is the Debug Clock input pin.

12.9.2 Debug Communication

The debug interface uses an SPI-like two-wire interface consisting of the Debug Data (P2_1) and Debug Clock (P2_2) pins. Data is driven on the bi-directional Debug Data pin at the positive edge of Debug Clock and data is sampled on the negative edge of this clock.

Debug commands are sent by an external host and consist of 1 to 4 output bytes (including command byte) from the host and an optional input byte read by the host. Command and data is transferred with MSB first. Figure 16 shows a timing diagram of data on the debug interface.

The first byte of the debug command is a command byte and is encoded as follows:

- bits 7 to 3 : instruction code
- bits 2 : return input byte to host byte when high
- bits 1 to 0 : number of output bytes from host following instruction code byte




Figure 16: Debug interface timing diagram

12.9.3 Debug Commands

The debug commands are shown in Note: x = don't care

Table 33. Some of the debug commands are described in further detail in the following sections.

12.9.4 Debug Lock Bit

For software code security the Debug Interface may be locked. When the Debug Lock bit, `DBGLOCK`, is set (see section 13.14.4) all debug commands except `CHIP_ERASE`, `READ_STATUS` and `GET_CHIP_ID` are

disabled and will not function. The status of the Debug Lock bit can read using the `READ_STATUS` command (see section 12.9.6).

Note that after the Debug Lock bit has been set, either a `HALT`, `RESUME`, `DEBUG_INSTR` or `STEP` command must be executed so that the Debug Lock value returned by `READ_STATUS` shows the updated Debug Lock. For example a dummy `NOP` `DEBUG_INSTR` command could be executed. After a device reset, the Debug Lock bit will be updated.

The CHIP_ERASE command is used to clear the Debug Lock bit.

12.9.5 Debug Configuration

The commands WR_CONFIG and RD_CONFIG are used to access the debug configuration data byte. The format and description of this configuration data is shown in Table 34.

12.9.6 Debug Status

A Debug status byte is read using the READ_STATUS command. The format and description of this debug status is shown in Table 35.

The READ_STATUS command is used e.g. for polling the status of flash chip erase after a CHIP_ERASE command or oscillator stable

status required for debug commands HALT, RESUME, DEBUG_INSTR, STEP_REPLACE and STEP_INSTR.

| Command | Instruction code | Description |
|---------------|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CHIP_ERASE | 0001 0x00 | Perform flash chip erase (mass erase) and clear lock bits. If any other command, except READ_STATUS, is issued, then the use of CHIP_ERASE is disabled. |
| WR_CONFIG | 0001 1x01 | Write configuration data. Refer to Table 34 |
| RD_CONFIG | 0010 0100 | Read configuration data. Returns value set by WR_CONFIG command. |
| GET_PC | 0010 1000 | Return value of 16-bit program counter. Returns 2 bytes regardless of value of bit 2 in instruction code |
| READ_STATUS | 0011 0x00 | Read status byte. Refer to Table 35 |
| SET_HW_BRKPNT | 0011 1x11 | Set hardware breakpoint |
| HALT | 0100 0100 | Halt CPU operation |
| RESUME | 0100 1100 | Resume CPU operation. The CPU must be in halted state for this command to be run. |
| DEBUG_INSTR | 0101 01xx | Run debug instruction. The supplied instruction will be executed by the CPU without incrementing the program counter. The CPU must be in halted state for this command to be run. |
| STEP_INSTR | 0101 1100 | Step CPU instruction. The CPU will execute the next instruction from program memory and increment the program counter after execution. The CPU must be in halted state for this command to be run. |
| STEP_REPLACE | 0110 01xx | Step and replace CPU instruction. The supplied instruction will be executed by the CPU instead of the next instruction in program memory. The program counter will be incremented after execution. The CPU must be in halted state for this command to be run. |
| GET_CHIP_ID | 0110 1000 | Return value of 16-bit chip ID and version number. Returns 2 bytes regardless of value of bit 2 of instruction code |

Note: x = don't care

Table 33: Debug Commands

| Bit | Name | Description |
|-----|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7-4 | – | Not used |
| 3 | TIMERS_OFF | Disable timers. Disable timer operation 0 Do not disable timers 1 Disable timers |
| 2 | DMA_PAUSE | DMA pause 0 Enable DMA transfers 1 Pause all DMA transfers |
| 1 | TIMER_SUSPEND | Suspend timers. Timer operation is suspended for debug instructions and if a step instruction is a branch. If not suspended these instructions would result an extra timer count during the clock cycle in which the branch is executed 0 Do not suspend timers 1 Suspend timers |
| 0 | SEL_FLASH_INFO_PAGE | Select flash information page 0 Select flash main page 1 Select flash information page |

Table 34: Debug Configuration

| Bit | Name | Description |
|-----|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | CHIP_ERASE_DONE | Flash chip erase done 0 Chip erase in progress 1 Chip erase done |
| 6 | PCON_IDLE | PCON idle 0 CPU is running 1 CPU is idle (clock gated) |
| 5 | CPU_HALTED | CPU halted 0 CPU running 1 CPU halted |
| 4 | POWER_MODE_0 | Power Mode 0 0 Power Mode 1-3 selected 1 Power Mode 0 selected |
| 3 | HALT_STATUS | Halt status. Returns cause of last CPU halt 0 CPU was halted by HALT debug command 1 CPU was halted by hardware breakpoint |
| 2 | DEBUG_LOCKED | Debug locked. Returns value of DBGLOCK bit 0 Debug interface is not locked 1 Debug interface is locked |
| 1 | OSCILLATOR_STABLE | Oscillators stable. This bit represents the status of the CLKCON.XSOC_STB and CLKCON.HFRC_STB register bits. 0 Oscillators not stable 1 Oscillators stable |
| 0 | STACK_OVERFLOW | Stack overflow. This bit indicates when the CPU writes to DATA memory space at address 0xFF which is possibly a stack overflow 0 No stack overflow 1 Stack overflow |

Table 35: Debug Status**12.9.7 Hardware Breakpoints**

The debug command SET_HW_BRKPNT is used to set a hardware breakpoint. The **CC2430** supports up to four hardware breakpoints. When a hardware breakpoint is enabled it will compare the CPU address bus with the breakpoint.. When a match occurs, the CPU is halted.

When issuing the SET_HW_BRKPNT, the external host must supply three data bytes that define the hardware breakpoint. The hardware breakpoint itself consists of 18 bits while three bits are used for control purposes. The format of the three data bytes for the SET_HW_BRKPNT command is as follows.

The first data byte consists of the following:

- bits 7-5 : unused
- bits 4-3 : breakpoint number; 0-3
- bit 2 : 1=enable, 0=disable
- bits 1-0 : Memory bank bits. Bits 17-16 of hardware breakpoint.

The second data byte consists of bits 15-8 of the hardware breakpoint.

The third data byte consists of bits 7-0 of the hardware breakpoint.

12.9.8 Flash Programming

Programming of the on-chip flash is performed via the debug interface. The external host must initially send instructions using the DEBUG_INSTR debug command to perform the flash

programming with the Flash Controller as described in section 13.14 on page 154.

12.10 RAM

The **CC2430** contains static RAM. At power-on the contents of RAM is undefined. The RAM size is 8 KB in total. The upper 4 KB of the RAM (XDATA memory locations 0xF000-0xFFFF) retains data in all power modes (see exception below). The remaining lower 4 KB (XDATA memory locations 0xE000-0xEFFF) will lose its contents in PM2 and PM3 and contains undefined data when returning to PM0.

The memory locations 0xFD56-0xFEFF consisting of 426 bytes in XDATA memory space do not retain data when PM2/3 is entered.

12.11 Flash Memory

The on-chip flash memory consists of 32768, 65536 or 131072 bytes. The flash memory is primarily intended to hold program code. The flash memory has the following features:

- Flash page erase time: 20 ms
- Flash chip (mass) erase time: 20 ms
- Flash write time (4 bytes): 20 μ s
- Data retention⁶: 100 years
- Program/erase endurance: 1,000 cycles

The flash memory consists of the Flash Main Page which is where the CPU reads program code and data. The flash memory also contains a Flash Information Page which contains the Flash Lock Bits. The Flash Information Page and hence the Lock Bits is only accessed by first selecting this page through the Debug Interface. The Flash Controller (see

⁶ At room temperature

section 13.14) is used to write and erase the contents of the flash memory.

When the CPU reads instructions from flash memory, it fetches the next instruction through a cache. The instruction cache is provided mainly to reduce power consumption by reducing the amount of time the flash memory itself is accessed. The use of the instruction cache may be disabled with the `MEMCTR.CACHDIS` register bit.

12.12 Memory Arbiter

The **CC2430** includes a memory arbiter which handles CPU and DMA access to all memory space.

The control registers `MEMCTR` and `FMAP` are used to control various aspects of the memory sub-system. The `MEMCTR` and `FMAP` registers are described below.

`MEMCTR.MUNIF` controls unified mapping of CODE memory space as shown in

Figure 13 on page 39. Unified mapping is required when the CPU is to execute program stored in XDATA.

For the 128 KB flash version (CC2430-F128), the Flash Bank Map register, `FMAP`⁷, controls mapping of physical banks of the 128 KB flash to the program address region 0x8000-0xFFFF in CODE memory space as shown in Figure 14 on 24.

Please note, for backwards compatibility with previous chip versions, the `FMAP.MAP[1:0]` and `MEMCTR.FMAP[1:0]` bits are aliased. Writing to `FMAP.MAP[1:0]` will also change the contents of the `MEMCTR.FMAP[1:0]` bits, and vice versa.

⁷ Only for devices with Chip Version register, `CHVER.VERSION` equal to 0x02 or greater

MEMCTR (0xC7) – Memory Arbiter Control

| Bit | Name | Reset | R/W | Description |
|-----|-----------|-------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | – | 0 | R0 | Not used |
| 6 | MUNIF | 0 | R/W | Unified memory mapping. When unified mapping is enabled, all physical memories are mapped into the CODE memory space as far as possible, when uniform mapping is disabled only flash memory is mapped to CODE space 0 Disable unified mapping 1 Enable unified mapping |
| 5:4 | FMAP[1:0] | 01 | R/W | Flash bank map. These bits are supported by CC2430-F128 only. Controls which of the four 32 KB flash memory banks to map to program address 0x8000 – 0xFFFF in CODE memory space. These bits are aliased to FMAP, MAP[1:0] 00 Map program address 0x8000 – 0xFFFF to physical memory address 0x00000 – 0x07FFF 01 Map program address 0x8000 – 0xFFFF to physical memory address 0x08000 – 0x0FFFF 10 Map program address 0x8000 – 0xFFFF to physical memory address 0x10000 – 0x17FFF 11 Map program address 0x8000 – 0xFFFF to physical memory address 0x18000 – 0x1FFFF |
| 3:2 | – | 00 | R0 | Not used |
| 1 | CACHDIS | 0 | R/W | Flash cache disable. Invalidates contents of instruction cache and forces all instruction read accesses to read straight from flash memory. Disabling will increase power consumption and is provided for debug purposes. 0 Cache enabled 1 Cache disabled |
| 0 | – | 1 | R/W | Reserved. Always set to 1. ⁸ |

⁸ Reserved bits must always be set to the specified value. Failure to follow this will result in indeterminate behaviour.

FMAP (0x9F) – Flash Bank Map⁹

| Bit | Name | Reset | R/W | Description |
|-----|----------|-------|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:2 | – | 0x00 | R0 | Not used |
| 1:0 | MAP[1:0] | 01 | R/W | <p>Flash bank map. Controls which of the four 32 KB flash memory banks to map to program address 0x8000 – 0xFFFF in CODE memory space. These bits are aliased to FMAP . MAP[1:0]</p> <p>00 Map program address 0x8000 – 0xFFFF to physical memory address 0x00000 – 0x07FFF</p> <p>01 Map program address 0x8000 – 0xFFFF to physical memory address 0x08000– 0x0FFFF</p> <p>10 Map program address 0x8000 – 0xFFFF to physical memory address 0x10000 – 0x17FFF</p> <p>11 Map program address 0x8000 – 0xFFFF to physical memory address 0x18000 – 0x1FFFF</p> |

⁹ Only for devices with Chip Version register, CHVER.VERSION equal to 0x02 or greater. This register supported on CC2430-F128 only.

13 Peripherals

In the following sub-sections each **CC2430** peripheral is described in detail.

The **CC2430** has four timers. These timers all run on the tick frequency given by the Power Management Controller register `CLKCON.TICKSPD`.

13.1 I/O ports

The **CC2430** has 21 digital input/output pins that can be configured as general purpose digital I/O or as peripheral I/O signals connected to the ADC, Timers or USART peripherals. The usage of the I/O ports is fully configurable from user software through a set of configuration registers.

The I/O ports have the following key features:

- 21 digital input/output pins
- General purpose I/O or peripheral I/O
- Pull-up or pull-down capability on inputs
- External interrupt capability

The external interrupt capability is available on all 21 I/O pins. Thus external devices may generate interrupts if required. The external interrupt feature can also be used to wake up from sleep modes.

13.1.1 General Purpose I/O

When used as general purpose I/O, the pins are organized as three 8-bit ports, ports 0-2, denoted P0, P1 and P2. P0 and P1 are complete 8-bit wide ports while P2 has only five usable bits. All ports are both bit- and byte addressable through the SFR registers `P0`, `P1` and `P2`. Each port pin can individually be set to operate as a general purpose I/O or as a peripheral I/O.

The output drive strength is 4 mA on all outputs, except for the two high-drive outputs, `P1_0` and `P1_1`, which each have 20 mA output drive strength.

To use a port as a general purpose I/O pin the pin must first be configured. The registers `PxSEL` where `x` is the port number 0-2 are used to configure each pin in a port as either a general purpose I/O pin or as a peripheral I/O signal. By default, after a reset, all digital input/output pins are configured as general-purpose I/O pins.

By default all general-purpose I/O pins are configured as inputs. To change the direction of a port pin, at any time, the registers `PxDIR` are used to set each port pin to be either an input or an output. Thus by setting the appropriate bit within `PxDIR`, to 1 the corresponding pin becomes an output.

When reading the port registers `P0`, `P1` and `P2`, the logic values on the input pins are returned regardless of the pin configuration. This does not apply during the execution of read-modify-write instructions. The read-modify-write instructions when operating on a port registers are the following: `ANL`, `ORL`, `XRL`, `JBC`, `CPL`, `INC`, `DEC`, `DJNZ` and `MOV`, `CLR` or `SETB`, when the destination is an individual bit in a port register `P0`, `P1` or `P2`. For these read-modify-write instructions, the value of the register, not the value on the pin, is read, modified, and written back to the port register.

When used as an input, the general purpose I/O port pins can be configured to have a pull-up, pull-down or tri-state mode of operation. By default, after a reset, inputs are configured as inputs with pull-up. To deselect the pull-up or pull-down function on an input the appropriate bit within the `PxINP` must be set to 1. The I/O port pins `P1_0` and `P1_1` do not have pull-up/pull-down capability.

In power modes PM2 and PM3 the I/O pins retain the I/O mode and output value (if applicable) that was set when PM2/3 was entered.

13.1.2 General Purpose I/O Interrupts

General purpose I/O pins configured as inputs can be used to generate interrupts. The interrupts can be configured to trigger on either a rising or falling edge of the external signal. Each of the `P0`, `P1` and `P2` ports have separate interrupt enable bits common for all bits within the port located in the `IEN1-2` registers as follows:

- `IEN1.P0IE` : P0 interrupt enable
- `IEN2.P1IE` : P1 interrupt enable
- `IEN2.P2IE` : P2 interrupt enable

In addition to these common interrupt enables, the bits within each port have interrupt enables located in I/O port SFR registers. Each bit within `P1` has an individual interrupt enable. In

P0 the low-order nibble and the high-order nibble have their individual interrupt enables. For the P2_0 – P2_4 inputs there is a common interrupt enable.

When an interrupt condition occurs on one of the general purpose I/O pins, the corresponding interrupt status flag in the P0-P2 interrupt flag registers, P0IFG, P1IFG or P2IFG will be set to 1. The interrupt status flag is set regardless of whether the pin has its interrupt enable set. When an interrupt is serviced the interrupt status flag is cleared by writing to a 0 to that flag.

Note that when clearing the PxIFG interrupt status flags, only one active flag should be cleared at a time. Failure to do this may result in generation of false interrupt requests.

The I/O SFR registers used for interrupts are described in section 13.1.9 on page 75. The registers are summarized below:

- P1IEN : P1 interrupt enables
- PICTL : P0/P2 interrupt enables and P0-2 edge configuration
- P0IFG : P0 interrupt flags
- P1IFG : P1 interrupt flags
- P2IFG : P2 interrupt flags

13.1.3 General Purpose I/O DMA

When used as general purpose I/O pins, the P0 and P1 ports are each associated with one DMA trigger. These DMA triggers are IOC_0

for P0 and IOC_1 for P1 as shown in Table 37 on page 87.

The IOC_0 or IOC_1 DMA trigger is activated when an input transition occurs on one of the P0 or P1 pins respectively. Note input transitions on pins configured as general purpose I/O inputs only will produce the DMA trigger.

Note that port registers P0 and P1 are mapped to XDATA memory space (see Table 25 on page 44). Therefore these registers are reachable for DMA transfers¹⁰. Port register P2 is not reachable for DMA transfers.

13.1.4 Peripheral I/O

This section describes how the digital input/output pins are configured as peripheral I/Os. For each peripheral unit that can interface with an external system through the digital input/output pins, a description of how peripheral I/Os are configured is given in the following sub-sections.

In general, setting the appropriate PxSEL bits to 1 is required to select peripheral I/O function on a digital I/O pin.

Note that peripheral units have two alternative locations for their I/O pins, refer to Table 36.

¹⁰ Only for devices with Chip Version register, CHVER.VERSION equal to 0x02 or greater

Table 36: Peripheral I/O Pin Mapping

| Periphery / Function | P0 | | | | | | | | P1 | | | | | | | | P2 | | | | |
|----------------------|----|----|----|----|----|----|----|----|----|----|----|----|----|----|---|---|----|----|--------|--------|---|
| | 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 | 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 | 4 | 3 | 2 | 1 | 0 |
| ADC | A7 | A6 | A5 | A4 | A3 | A2 | A1 | A0 | | | | | | | | | | | | | |
| USART0 SPI | | | C | SS | MO | MI | | | | | | | | | | | | | | | |
| Alt. 2 | | | | | | | | | | | MO | MI | C | SS | | | | | | | |
| USART0 UART | | | RT | CT | TX | RX | | | | | | | | | | | | | | | |
| Alt. 2 | | | | | | | | | | | TX | RX | RT | CT | | | | | | | |
| USART1 SPI | | | MI | MO | C | SS | | | | | | | | | | | | | | | |
| Alt. 2 | | | | | | | | | MI | MO | C | SS | | | | | | | | | |
| USART1 UART | | | RX | TX | RT | CT | | | | | | | | | | | | | | | |
| Alt. 2 | | | | | | | | | RX | TX | RT | CT | | | | | | | | | |
| TIMER1 | | | | 2 | 1 | 0 | | | | | | | | | | | | | | | |
| Alt. 2 | | | | | | | | | | | | | | 0 | 1 | 2 | | | | | |
| TIMER3 | | | | | | | | | | | | 1 | 0 | | | | | | | | |
| Alt. 2 | | | | | | | | | 1 | 0 | | | | | | | | | | | |
| TIMER4 | | | | | | | | | | | | | | | 1 | 0 | | | | | |
| Alt. 2 | | | | | | | | | | | | | | | | | 1 | | | 0 | |
| 32.768 kHz XOSC | | | | | | | | | | | | | | | | | Q2 | Q1 | | | |
| DEBUG | | | | | | | | | | | | | | | | | | | D C | D D | |

13.1.4.1 USART0

The SFR register bit `PERCFG.U0CFG` selects whether to use alternative 1 or alternative 2 locations.

In Table 36, the USART0 signals are shown as follows:

UART:

- RX : RXDATA
- TX : TXDATA
- RT : RTS
- CT : CTS

SPI:

- MI : MISO
- MO : MOSI
- C : SCK
- SS : SSN

`P2DIR.PRI0` selects the order of precedence when assigning several peripherals to port 0. When set to 00, USART0

has precedence. Note that if UART mode is selected and hardware flow control is disabled, USART1 or timer 1 will have precedence to use ports P0_4 and P0_5.

`P2SEL.PRI3P1` and `P2SEL.PRI0P1` select the order of precedence when assigning several peripherals to port 1. USART0 has precedence when both are set to 0. Note that if UART mode is selected and hardware flow control is disabled, timer 1 or timer 3 will have precedence to use ports P1_2 and P1_3.

13.1.4.2 USART1

The SFR register bit `PERCFG.U1CFG` selects whether to use alternative 1 or alternative 2 locations.

In Table 36, the USART1 signals are shown as follows:

- RX : RXDATA
- TX : TXDATA
- RT : RTS
- CT : CTS

SPI:

- MI : MISO
- MO : MOSI
- C : SCK
- SS : SSN

P2DIR.PRI0 selects the order of precedence when assigning several peripherals to port 0. When set to 01, USART1 has precedence. Note that if UART mode is selected and hardware flow control is disabled, USART0 or timer 1 will have precedence to use ports P0_2 and P0_3.

P2SEL.PRI3P1 and P2SEL.PRI2P1 select the order of precedence when assigning several peripherals to port 1. USART1 has precedence when the former is set to 1 and the latter is set to 0. Note that if UART mode is selected and hardware flow control is disabled, USART0 or timer 3 will have precedence to use ports P2_4 and P2_5.

13.1.4.3 Timer 1

PERCFG.T1CFG selects whether to use alternative 1 or alternative 2 locations.

In Table 36, the Timer 1 signals are shown as the following:

- 0 : Channel 0 capture/compare pin
- 1 : Channel 1 capture/compare pin
- 2 : Channel 2 capture/compare pin

P2DIR.PRI0 selects the order of precedence when assigning several peripherals to port 0. When set to 10 or 11 the timer 1 channels have precedence.

P2SEL.PRI1P1 and P2SEL.PRI0P1 select the order of precedence when assigning several peripherals to port 1. The timer 1 channels have precedence when the former is set low and the latter is set high.

13.1.4.4 Timer 3

PERCFG.T3CFG selects whether to use alternative 1 or alternative 2 locations.

In Table 36, the Timer 3 signals are shown as the following:

- 0 : Channel 0 compare pin
- 1 : Channel 1 compare pin

P2SEL.PRI2P1 selects the order of precedence when assigning several peripherals to port 1. The timer 3 channels have precedence when the bit is set.

13.1.4.5 Timer 4

PERCFG.T4CFG selects whether to use alternative 1 or alternative 2 locations.

In Table 36, the Timer 4 signals are shown as the following:

- 0 : Channel 0 compare pin
- 1 : Channel 1 compare pin

P2SEL.PRI1P1 selects the order of precedence when assigning several peripherals to port 1. The timer 4 channels have precedence when the bit is set.

13.1.5 ADC

When using the ADC in an application, Port 0 pins must be configured as ADC inputs. Up to eight ADC inputs can be used. To configure a Port 0 pin to be used as an ADC input the corresponding bit in the ADCCFG register must be set to 1. The default values in this register select the Port 0 pins as non-ADC input i.e. digital input/outputs.

The settings in the ADCCFG register override the settings in P0SEL.

The ADC can be configured to use the general-purpose I/O pin P2_0 as an external trigger to start conversions. P2_0 must be configured as a general-purpose I/O in input mode, when being used for ADC external trigger.

Refer to section 13.7 on page 122 for a detailed description of use of the ADC.

13.1.6 Debug interface

Ports P2_1 and P2_2 are used for debug data and clock signals, respectively. These are shown as DD (debug data) and DC (debug clock) in Table 36. When the debug interface is in use, P2DIR should select these pins as inputs. The state of P2SEL is overridden by the debug interface. Also, the direction is overridden when the chip changes the direction to supply the external host with data.

Note: It is highly recommended to use an external pull-up resistor connected to the debug clock pin, P2_2. Omitting this pull-up resistor may lead to inadvertent entry into debug mode (see section 12.9.1) while the RESET_N input pin is low in the presence of noise on the debug clock pin.

13.1.7 32.768 kHz XOSC input

Ports P2_3 and P2_4 are used to connect an external 32.768 kHz crystal. These port pins will be used by the 32.768 kHz crystal oscillator when `CLKCON.OSC32K` is low, regardless of register settings. The port pins will be set in analog mode when `CLKCON.OSC32K` is low.

13.1.8 Unused I/O pins

Unused I/O pins should have a defined level and not be left floating. One way to do this is to leave the pin unconnected and configure the pin as a general purpose I/O input with pull-up resistor. This is also the state of all pins during reset. Alternatively the pin can be configured as a general purpose I/O output. In both cases the pin should not be connected directly to VDD or GND in order to avoid excessive power consumption.

13.1.9 Low I/O Supply Voltage

In applications where the digital I/O power supply voltage pin DVDD is below 2.6 V, the register bit `PICCTL.PADSC` should be set to 1 in order to obtain output DC characteristics specified in section 7.16.

13.1.10 I/O registers

The registers for the I/O ports are described in this section. The registers are:

- P0 Port 0

- P1 Port 1
- P2 Port 2
- PERCFG Peripheral control register
- ADCCFG ADC input configuration register
- P0SEL Port 0 function select register
- P1SEL Port 1 function select register
- P2SEL Port 2 function select register
- P0DIR Port 0 direction register
- P1DIR Port 1 direction register
- P2DIR Port 2 direction register
- P0INP Port 0 input mode register
- P1INP Port 1 input mode register
- P2INP Port 2 input mode register
- P0IFG Port 0 interrupt status flag register
- P1IFG Port 1 interrupt status flag register
- P2IFG Port 2 interrupt status flag register
- PICCTL Interrupt mask and edge register
- P1IEN Port 1 interrupt mask register

P0 (0x80) – Port 0

| Bit | Name | Reset | R/W | Description |
|-----|---------|-------|-----|----------------------------------------------------|
| 7:0 | P0[7:0] | 0xFF | R/W | Port 0. General purpose I/O port. Bit-addressable. |

P1 (0x90) – Port 1

| Bit | Name | Reset | R/W | Description |
|-----|---------|-------|-----|----------------------------------------------------|
| 7:0 | P1[7:0] | 0xFF | R/W | Port 1. General purpose I/O port. Bit-addressable. |

P2 (0xA0) – Port 2

| Bit | Name | Reset | R/W | Description |
|-----|---------|-------|-----|----------------------------------------------------|
| 7:5 | – | 000 | R0 | Not used |
| 4:0 | P2[4:0] | 0x1F | R/W | Port 2. General purpose I/O port. Bit-addressable. |

PERCFG (0xF1) – Peripheral Control

| Bit | Name | Reset | R/W | Description |
|-----|-------|-------|-----|------------------------------------------------------------------------------|
| 7 | – | 0 | R0 | Not used |
| 6 | T1CFG | 0 | R/W | Timer 1 I/O location 0 Alternative 1 location 1 Alternative 2 location |
| 5 | T3CFG | 0 | R/W | Timer 3 I/O location 0 Alternative 1 location 1 Alternative 2 location |
| 4 | T4CFG | 0 | R/W | Timer 4 I/O location 0 Alternative 1 location 1 Alternative 2 location |
| 3:2 | – | 00 | R0 | Not used |
| 1 | U1CFG | 0 | R/W | USART1 I/O location 0 Alternative 1 location 1 Alternative 2 location |
| 0 | U0CFG | 0 | R/W | USART0 I/O location 0 Alternative 1 location 1 Alternative 2 location |

ADCCFG (0xF2) – ADC Input Configuration

| Bit | Name | Reset | R/W | Description |
|-----|-------------|-------|-----|----------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | ADCCFG[7:0] | 0x00 | R/W | ADC input configuration. ADCCFG[7:0] select P0_7 - P0_0 as ADC inputs AIN7 – AIN0 0 ADC input disabled 1 ADC input enabled |

P0SEL (0xF3) – Port 0 Function Select

| Bit | Name | Reset | R/W | Description |
|-----|-------------|-------|-----|--------------------------------------------------------------------------------|
| 7:0 | SELP0_[7:0] | 0x00 | R/W | P0_7 to P0_0 function select 0 General purpose I/O 1 Peripheral function |

P1SEL (0xF4) – Port 1 Function Select

| Bit | Name | Reset | R/W | Description |
|-----|-------------|-------|-----|--------------------------------------------------------------------------------|
| 7:0 | SELP1_[7:0] | 0x00 | R/W | P1_7 to P1_0 function select 0 General purpose I/O 1 Peripheral function |

P2SEL (0xF5) – Port 2 Function Select

| Bit | Name | Reset | R/W | Description |
|-----|---------|-------|-----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | – | 0 | R0 | Not used |
| 6 | PRI3P1 | 0 | R/W | Port 1 peripheral priority control. These bits shall determine the order of priority in the case when PERCFG assigns USART0 and USART1 to the same pins. 0 USART0 has priority 1 USART1 has priority |
| 5 | PRI2P1 | 0 | R/W | Port 1 peripheral priority control. These bits shall determine the order of priority in the case when PERCFG assigns USART1 and timer 3 to the same pins. 0 USART1 has priority 1 Timer 3 has priority |
| 4 | PRI1P1 | 0 | R/W | Port 1 peripheral priority control. These bits shall determine the order of priority in the case when PERCFG assigns timer 1 and timer 4 to the same pins. 0 Timer 1 has priority 1 Timer 4 has priority |
| 3 | PRI0P1 | 0 | R/W | Port 1 peripheral priority control. These bits shall determine the order of priority in the case when PERCFG assigns USART0 and timer 1 to the same pins. 0 USART0 has priority 1 Timer 1 has priority |
| 2 | SELP2_4 | 0 | R/W | P2_4 function select 0 General purpose I/O 1 Peripheral function |
| 1 | SELP2_3 | 0 | R/W | P2_3 function select 0 General purpose I/O 1 Peripheral function |
| 0 | SELP2_0 | 0 | R/W | P2_0 function select 0 General purpose I/O 1 Peripheral function |

P0DIR (0xFD) – Port 0 Direction

| Bit | Name | Reset | R/W | Description |
|-----|-------------|-------|-----|---------------------------------------------------|
| 7:0 | DIRP0_[7:0] | 0x00 | R/W | P0_7 to P0_0 I/O direction 0 Input 1 Output |

P1DIR (0xFE) – Port 1 Direction

| Bit | Name | Reset | R/W | Description |
|-----|-------------|-------|-----|---------------------------------------------------|
| 7:0 | DIRP1_[7:0] | 0x00 | R/W | P1_7 to P1_0 I/O direction 0 Input 1 Output |

P2DIR (0xFF) – Port 2 Direction

| Bit | Name | Reset | R/W | Description |
|-----|-------------|-------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:6 | PRIP0[1:0] | 00 | R/W | Port 0 peripheral priority control. These bits shall determine the order of priority in the case when PERCFG assigns several peripherals to the same pins 00 USART0 – USART1 01 USART1 – USART0 10 Timer 1 channels 0 and 1 – USART1 11 Timer 1 channel 2 – USART0 |
| 5 | – | 0 | R0 | Not used |
| 4:0 | DIRP2_[4:0] | 00000 | R/W | P2_4 to P2_0 I/O direction 0 Input 1 Output |

P0INP (0x8F) – Port 0 Input Mode

| Bit | Name | Reset | R/W | Description |
|-----|------------|-------|-----|--------------------------------------------------------------------|
| 7:0 | MDP0_[7:0] | 0x00 | R/W | P0_7 to P0_0 I/O input mode 0 Pull-up / pull-down 1 Tristate |

P1INP (0xF6) – Port 1 Input Mode

| Bit | Name | Reset | R/W | Description |
|-----|------------|-------|-----|--------------------------------------------------------------------|
| 7:2 | MDP1_[7:2] | 0x00 | R/W | P1_7 to P1_2 I/O input mode 0 Pull-up / pull-down 1 Tristate |
| 1:0 | – | 00 | R0 | Not used |

P2INP (0xF7) – Port 2 Input Mode

| Bit | Name | Reset | R/W | Description |
|-----|------------|-------|-----|--------------------------------------------------------------------------------------------------------------------------------------|
| 7 | PDUP2 | 0 | R/W | Port 2 pull-up/down select. Selects function for all Port 2 pins configured as pull-up/pull-down inputs. 0 Pull-up 1 Pull-down |
| 6 | PDUP1 | 0 | R/W | Port 1 pull-up/down select. Selects function for all Port 1 pins configured as pull-up/pull-down inputs. 0 Pull-up 1 Pull-down |
| 5 | PDUP0 | 0 | R/W | Port 0 pull-up/down select. Selects function for all Port 0 pins configured as pull-up/pull-down inputs. 0 Pull-up 1 Pull-down |
| 4:0 | MDP2_[4:0] | 00000 | R/W | P2_4 to P2_0 I/O input mode 0 Pull-up / pull-down 1 Tristate |

P0IFG (0x89) – Port 0 Interrupt Status Flag

| Bit | Name | Reset | R/W | Description |
|-----|-----------|-------|------|------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | P0IF[7:0] | 0x00 | R/W0 | Port 0, inputs 7 to 0 interrupt status flags. When an input port pin has an interrupt request pending, the corresponding flag bit will be set. |

P1IFG (0x8A) – Port 1 Interrupt Status Flag

| Bit | Name | Reset | R/W | Description |
|-----|-----------|-------|------|------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | P1IF[7:0] | 0x00 | R/W0 | Port 1, inputs 7 to 0 interrupt status flags. When an input port pin has an interrupt request pending, the corresponding flag bit will be set. |

P2IFG (0x8B) – Port 2 Interrupt Status Flag

| Bit | Name | Reset | R/W | Description |
|-----|-----------|-------|------|------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:5 | – | 000 | R0 | Not used. |
| 4:0 | P2IF[4:0] | 0x00 | R/W0 | Port 2, inputs 4 to 0 interrupt status flags. When an input port pin has an interrupt request pending, the corresponding flag bit will be set. |

PICTL (0x8C) – Port Interrupt Control

| Bit | Name | Reset | R/W | Description |
|-----|--------|-------|-----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | – | 0 | R0 | Not used |
| 6 | PADSC | 0 | R/W | Drive strength control for I/O pins in output mode. Selects output drive capability to account for low I/O supply voltage on pin DVDD. 0 Minimum drive capability. DVDD equal or greater than 2.6V 1 Maximum drive capability. DVDD less than 2.6V |
| 5 | P2IEN | 0 | R/W | Port 2, inputs 4 to 0 interrupt enable. This bit enables interrupt requests for the port 2 inputs 4 to 0. 0 Interrupts are disabled 1 Interrupts are enabled |
| 4 | P0IENH | 0 | R/W | Port 0, inputs 7 to 4 interrupt enable. This bit enables interrupt requests for the port 0 inputs 7 to 4. 0 Interrupts are disabled 1 Interrupts are enabled |
| 3 | P0IENL | 0 | R/W | Port 0, inputs 3 to 0 interrupt enable. This bit enables interrupt requests for the port 0 inputs 3 to 0. 0 Interrupts are disabled 1 Interrupts are enabled |
| 2 | P2ICON | 0 | R/W | Port 2, inputs 4 to 0 interrupt configuration. This bit selects the interrupt request condition for all port 2 inputs 0 Rising edge on input gives interrupt 1 Falling edge on input gives interrupt |
| 1 | P1ICON | 0 | R/W | Port 1, inputs 7 to 0 interrupt configuration. This bit selects the interrupt request condition for all port 1 inputs 0 Rising edge on input gives interrupt 1 Falling edge on input gives interrupt |
| 0 | P0ICON | 0 | R/W | Port 0, inputs 7 to 0 interrupt configuration. This bit selects the interrupt request condition for all port 0 inputs 0 Rising edge on input gives interrupt 1 Falling edge on input gives interrupt |

P1IEN (0x8D) – Port 1 Interrupt Mask

| Bit | Name | Reset | R/W | Description |
|-----|-------------|-------|-----|---------------------------------------------------------------------------------------------|
| 7:0 | P1_[7:0]IEN | 0x00 | R/W | Port P1_7 to P1_0 interrupt enable 0 Interrupts are disabled 1 Interrupts are enabled |

13.2 DMA Controller

The **CC2430** includes a direct memory access (DMA) controller, which can be used to relieve the 8051 CPU core of handling data movement operations thus achieving high overall performance with good power efficiency. The DMA controller can move data from a peripheral unit such as ADC or RF transceiver to memory with minimum CPU intervention.

The DMA controller coordinates all DMA transfers, ensuring that DMA requests are prioritized appropriately relative to each other and CPU memory access. The DMA controller contains a number of programmable DMA channels for memory-memory data movement.

The DMA controller controls data transfers over the entire address range in XDATA memory space. Since most of the SFR registers are mapped into the DMA memory space, these flexible DMA channels can be used to unburden the CPU in innovative ways, e.g. feed a USART with data from memory or periodically transfer samples between ADC and memory, etc. Use of the DMA can also reduce system power consumption by keeping the CPU in a low-power mode without having to wake up to move data to or from a peripheral unit. Note that section 12.4 describes which SFR registers that are not mapped into XDATA memory space.

The main features of the DMA controller are as follows:

- Five independent DMA channels
- Three configurable levels of DMA channel priority
- 31 configurable transfer trigger events
- Independent control of source and destination address

- Single, block and repeated transfer modes
- Supports length field in transfer data setting variable transfer length
- Can operate in either word-size or byte-size mode

13.2.1 DMA Operation


There are five DMA channels available in the DMA controller numbered channel 0 to channel 4. Each DMA channel can move data from one place within the DMA memory space to another i.e. between XDATA locations.

In order to use a DMA channel it must first be configured as described in sections 13.2.2 and 13.2.3. Figure 17 shows the DMA state diagram.

Once a DMA channel has been configured it must be armed before any transfers are allowed to be initiated. A DMA channel is armed by setting the appropriate bit in the DMA Channel Arm register **DMAARM**.

When a DMA channel is armed a transfer will begin when the configured DMA trigger event occurs. There are 31 possible DMA trigger events, e.g. UART transfer, Timer overflow etc. The trigger event to be used by a DMA channel is set by the DMA channel configuration. The DMA trigger events are listed in Table 37.

In addition to starting a DMA transfer through the DMA trigger events, the user software may force a DMA transfer to begin by setting the corresponding **DMAREQ** bit.

**Figure 17: DMA Operation**

13.2.2 DMA Configuration Parameters

Setup and control of the DMA operation is performed by the user software. This section describes the parameters which must be configured before a DMA channel can be used. Section 13.2.3 on page 85 describes

how the parameters are set up in software and passed to the DMA controller.

The behavior of each of the five DMA channels is configured with the following parameters:

Source address. The first address from which the DMA channel should read data.

Destination address. The first address to which the DMA channel should write the data read from the source address. The user must ensure that the destination is writable.

Transfer count. The number of transfers to perform before rearming or disarming the DMA channel and alerting the CPU with an interrupt request. The length can be defined in the configuration or it can be defined as described next as VLEN setting.

VLEN setting. The DMA channel is capable of variable length transfers using the first byte or word to set the transfer length. When doing this, various options regarding how to count number of bytes to transfer are available.

Priority. The priority of the DMA transfers for the DMA channel in respect to the CPU and other DMA channels and access ports.

Trigger event. All DMA transfers are initiated by so-called DMA trigger events. This trigger either starts a DMA block transfer or a single DMA transfer. In addition to the configured trigger, a DMA channel can always be triggered by setting its designated `DMAREQ.DMAREQx` flag. The DMA trigger sources are described in Table 37 on page 87.

Source and Destination Increment. The source and destination addresses can be controlled to increment or decrement or not change, in order to give good flexibility for various types of transfers.

Transfer mode. The transfer mode determines whether the transfer should be a single transfer or a block transfer, or repeated versions of these.

Byte or word transfers. Determines whether each DMA transfer should be 8-bit (byte) or 16-bit (word).

Interrupt Mask. An interrupt request is generated upon completion of the DMA transfer. The interrupt mask bit controls if the interrupt generation is enabled or disabled.

M8: Decide whether to use seven or eight bits of length byte for transfer length. Only applicable when doing byte transfers.

A detailed description of all configuration parameters are given in the following sections.

13.2.2.1 Source Address

The address in XDATA memory where the DMA channel shall start to read data.

13.2.2.2 Destination Address

The first address to which the DMA channel should write the data read from the source address. The user must ensure that the destination is writable.

13.2.2.3 Transfer Count

The number of bytes/words needed to be transferred for the DMA transfer to be complete. When the transfer count is reached, the DMA controller rearms or disarms the DMA channel and alerts the CPU with an interrupt request. The transfer count can be defined in the configuration or it can be defined as a variable length described in the next section.

13.2.2.4 VLEN Setting

The DMA channel is capable of using the first byte or word (for word, bits 12:0 are used) in source data as the transfer length. This allows variable length transfers. When using variable length transfer, various options regarding how to count number of bytes to transfer is given. In any case, the transfer count (LEN) setting is used as maximum transfer count. If the transfer length specified by the first byte or word is greater than LEN, then LEN bytes/words will be transferred. When using variable length transfers, then LEN should be set to the largest allowed transfer length plus one.

Note that the M8 bit (see page 85) is only used when byte size transfers are chosen.

Options which can be set with VLEN are the following:

1. Transfer number of bytes/words commanded by first byte/word + 1 (transfers the length byte/word, and then as many bytes/words as dictated by length byte/word)
2. Transfer number of bytes/words commanded by first byte/word
3. Transfer number of bytes/words commanded by first byte/word + 2 (transfers the length byte/word, and then as many bytes/words as dictated by length byte/word + 1)
4. Transfer number of bytes/words commanded by first byte/word + 3 (transfers the length byte/word, and then as many bytes/words as dictated by length byte/word + 2)

Figure 18 shows the VLEN options.




Figure 18: Variable Length (VLEN) Transfer Options

13.2.2.5 Trigger Event

Each DMA channel can be set up to sense on a single trigger. This field determines which trigger the DMA channel shall sense.

13.2.2.6 Source and Destination Increment

When the DMA channel is armed or rearmed the source and destination addresses are transferred to internal address pointers. The possibilities for address increment are :

- *Increment by zero.* The address pointer shall remain fixed after each transfer.
- *Increment by one.* The address pointer shall increment one count after each transfer.
- *Increment by two.* The address pointer shall increment two counts after each transfer.
- *Decrement by one.* The address pointer shall decrement one count after each transfer.

13.2.2.7 DMA Transfer Mode

The transfer mode determines how the DMA channel behaves when it starts transferring data. There are four transfer modes described below:

Single. On a trigger a single DMA transfer occurs and the DMA channel awaits the next trigger. After the number of transfers specified by the transfer count, are completed, the CPU is notified and the DMA channel is disarmed.

Block. On a trigger the number of DMA transfers specified by the transfer count is performed as quickly as possible, after which the CPU is notified and the DMA channel is disarmed.

Repeated single. On a trigger a single DMA transfer occurs and the DMA channel awaits the next trigger. After the number of transfers specified by the transfer count are completed, the CPU is notified and the DMA channel is rearmed.

Repeated block. On a trigger the number of DMA transfers specified by the transfer count is performed as quickly as possible, after which the CPU is notified and the DMA channel is rearmed.

13.2.2.8 DMA Priority

A DMA priority is associated with each DMA access port and is configurable for each DMA channel. The DMA priority is used to determine the winner in the case of multiple simultaneous internal memory requests, and whether the DMA memory access should have priority or not over a simultaneous CPU memory access. In case of an internal tie, a

round-robin scheme is used to ensure access for all. There are three levels of DMA priority:

High. Highest internal priority. DMA access will always prevail over CPU access.

Normal. Second highest internal priority. Guarantees that DMA access prevails over CPU on at least every second try.

Low. Lowest internal priority. DMA access will always defer to a CPU access.

13.2.2.9 Byte or Word transfers

Determines whether 8-bit (byte) or 16-bit (word) are done.

13.2.2.10 Interrupt mask

Upon completing a DMA transfer, the channel can generate an interrupt to the processor. This bit will mask the interrupt.

13.2.2.11 Mode 8 setting

This field determines whether to use 7 or 8 bits of length byte for transfer length. Only applicable when doing byte transfers.

13.2.3 DMA Configuration Setup

The DMA channel parameters such as address mode, transfer mode and priority described in the previous section have to be configured before a DMA channel can be armed and activated. The parameters are not configured directly through SFR registers, but instead they are written in a special DMA configuration data structure in memory. Each DMA channel in use requires its own DMA configuration data structure. The DMA configuration data structure consists of eight bytes and is described in section 13.2.6 on page 86. A DMA configuration data structure may reside at any location decided upon by the user software, and the address location is passed to the DMA controller through a set of SFRs `DMAxCFGH:DMAxCFGL`. Once a channel has been armed, the DMA controller will read

the configuration data structure for that channel, given by the address in `DMAxCFGH:DMAxCFGL`.

It is important to note that the method for specifying the start address for the DMA configuration data structure differs between DMA channel 0 and DMA channels 1-4 as follows:

`DMA0CFGH:DMA0CFGL` gives the start address for DMA channel 0 configuration data structure.

`DMA1CFGH:DMA1CFGL` gives the start address for DMA channel 1 configuration data structure followed by channel 2-4 configuration data structures.

Thus the DMA controller expects the DMA configuration data structures for DMA channels 1-4 to lie in a contiguous area in memory starting at the address held in `DMA1CFGH:DMA1CFGL` and consisting of 32 bytes.

13.2.4 Stopping DMA Transfers

Ongoing DMA transfer or armed DMA channels will be aborted using the `DMAARM` register to disarm the DMA channel.

One or more DMA channels are aborted by writing the following to the `DMAARM` register.

- Writing a 1 to `DMAARM.ABORT`, and at the same time,
- Select which DMA channels to abort by setting the corresponding, `DMAARM.DMAARMx` bits to 1. When setting `DMAARM.ABORT` to 1, the `DMAARM.DMAARMx` bits for non-aborted channels shall be written as 0.

An example of DMA channel arm and disarm is shown in Figure 19.

```
MOV DMAARM, #0x03    ; arm DMA channel 0 and 1

MOV DMAARM, #0x81    ; disarm DMA channel 0,
                     ; channel 1 is still armed
```

Figure 19: DMA arm/disarm example

13.2.5 DMA Interrupts

Each DMA channel can be configured to generate an interrupt to the CPU upon completing a DMA transfer. This is accomplished with the IRQMASK bit in the channel configuration. The corresponding interrupt flag in the DMAIRQ SFR register will be set when the interrupt is generated.

Regardless of the IRQMASK bit in the channel configuration, the interrupt flag will be set upon DMA channel complete. Thus software should

always check (and clear) this register when rearming a channel with a changed IRQMASK setting. Failure to do so could generate an interrupt based on the stored interrupt flag.

13.2.6 DMA Configuration Data Structure

For each DMA channel, the DMA configuration data structure consists of eight bytes. The configuration data structure is described in Table 38.

| DMA Trigger number | DMA Trigger name | Functional unit | Description |
|--------------------|------------------|------------------|------------------------------------------------------------|
| 0 | NONE | DMA | No trigger, setting DMAREQ . DMAREQx bit starts transfer |
| 1 | PREV | DMA | DMA channel is triggered by completion of previous channel |
| 2 | T1_CH0 | Timer 1 | Timer 1, compare, channel 0 |
| 3 | T1_CH1 | Timer 1 | Timer 1, compare, channel 1 |
| 4 | T1_CH2 | Timer 1 | Timer 1, compare, channel 2 |
| 5 | T2_COMP | Timer 2 | Timer 2, compare |
| 6 | T2_OVFL | Timer 2 | Timer 2, overflow |
| 7 | T3_CH0 | Timer 3 | Timer 3, compare, channel 0 |
| 8 | T3_CH1 | Timer 3 | Timer 3, compare, channel 1 |
| 9 | T4_CH0 | Timer 4 | Timer 4, compare, channel 0 |
| 10 | T4_CH1 | Timer 4 | Timer 4, compare, channel 1 |
| 11 | ST | Sleep Timer | Sleep Timer compare |
| 12 | IOC_0 | IO Controller | Port 0 I/O pin input transition |
| 13 | IOC_1 | IO Controller | Port 1 I/O pin input transition |
| 14 | URX0 | USART0 | USART0 RX complete |
| 15 | UTX0 | USART0 | USART0 TX complete |
| 16 | URX1 | USART1 | USART1 RX complete |
| 17 | UTX1 | USART1 | USART1 TX complete |
| 18 | FLASH | Flash controller | Flash data write complete |
| 19 | RADIO | Radio | RF packet byte received/transmit |
| 20 | ADC_CHALL | ADC | ADC end of a conversion in a sequence, sample ready |
| 21 | ADC_CH11 | ADC | ADC end of conversion channel 0 in sequence, sample ready |
| 22 | ADC_CH21 | ADC | ADC end of conversion channel 1 in sequence, sample ready |
| 23 | ADC_CH32 | ADC | ADC end of conversion channel 2 in sequence, sample ready |
| 24 | ADC_CH42 | ADC | ADC end of conversion channel 3 in sequence, sample ready |
| 25 | ADC_CH53 | ADC | ADC end of conversion channel 4 in sequence, sample ready |
| 26 | ADC_CH63 | ADC | ADC end of conversion channel 5 in sequence, sample ready |
| 27 | ADC_CH74 | ADC | ADC end of conversion channel 6 in sequence, sample ready |
| 28 | ADC_CH84 | ADC | ADC end of conversion channel 7 in sequence, sample ready |
| 29 | ENC_DW | AES | AES encryption processor requests download input data |
| 30 | ENC_UP | AES | AES encryption processor requests upload output data |

Table 37: DMA Trigger Sources

Table 38: DMA Configuration Data Structure

| Byte Offset | Bit | Name | Description |
|-------------|-----|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 0 | 7:0 | SRCADDR[15:8] | The DMA channel source address, high |
| 1 | 7:0 | SRCADDR[7:0] | The DMA channel source address, low |
| 2 | 7:0 | DESTADDR[15:8] | The DMA channel destination address, high. Note that flash memory is not directly writeable. |
| 3 | 7:0 | DESTADDR[7:0] | The DMA channel destination address, low. Note that flash memory is not directly writeable. |
| 4 | 7:5 | VLEN[2:0] | Variable length transfer mode. In word mode, bits 12:0 of the first word is considered as the transfer length. 000/111 Use LEN for transfer count 001 Transfer the number of bytes/words specified by first byte/word + 1 (up to a maximum specified by LEN). Thus transfer count excludes length byte/word 010 Transfer the number of bytes/words specified by first byte/word (up to a maximum specified by LEN). Thus transfer count includes length byte/word. 011 Transfer the number of bytes/words specified by first byte/word + 2 (up to a maximum specified by LEN). 100 Transfer the number of bytes/words specified by first byte/word + 3 (up to a maximum specified by LEN). 101 reserved 110 reserved |
| 4 | 4:0 | LEN[12:8] | The DMA channel transfer count. Used as maximum allowable length when VLEN = 000/111. The DMA channel counts in words when in WORDSIZE mode, and in bytes otherwise. |
| 5 | 7:0 | LEN[7:0] | The DMA channel transfer count. Used as maximum allowable length when VLEN = 000/111. The DMA channel counts in words when in WORDSIZE mode, and in bytes otherwise. |
| 6 | 7 | WORDSIZE | Selects whether each DMA transfer shall be 8-bit (0) or 16-bit (1). |
| 6 | 6:5 | TMODE[1:0] | The DMA channel transfer mode: 00 : Single 01 : Block 10 : Repeated single 11 : Repeated block |
| 6 | 4:0 | TRIG[4:0] | Select DMA trigger to use 00000 : No trigger (writing to DMAREQ is only trigger) 00001 : The previous DMA channel finished 00010 – 11111 : Selects one of the triggers shown in Table 37. The trigger is selected in the order shown in the table. |
| 7 | 7:6 | SRCINC[1:0] | Source address increment mode (after each transfer): 00 : 0 bytes/words 01 : 1 bytes/words 10 : 2 bytes/words 11 : -1 bytes/words |
| 7 | 5:4 | DESTINC[1:0] | Destination address increment mode (after each transfer): 00 : 0 bytes/words 01 : 1 bytes/words 10 : 2 bytes/words 11 : -1 bytes/words |

| Byte Offset | Bit | Name | Description |
|-------------|-----|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | 3 | IRQMASK | Interrupt Mask for this channel. 0 : Disable interrupt generation 1 : Enable interrupt generation upon DMA channel done |
| 7 | 2 | M8 | Mode of 8 th bit for VLEN transfer length; only applicable when WORDSIZE=0. 0 : Use all 8 bits for transfer count 1 : Use 7 LSB for transfer count |
| 7 | 1:0 | PRIORITY[1:0] | The DMA channel priority: 00 : Low, CPU has priority. 01 : Guaranteed, DMA at least every second try. 10 : High, DMA has priority 11 : Highest, DMA has priority. Reserved for DMA port access. |

13.2.7 DMA registers

This section describes the SFR registers associated with the DMA Controller

DMAARM (0xD6) – DMA Channel Arm

| Bit | Name | Reset | R/W | Description |
|-----|---------|-------|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | ABORT | 0 | R / W | DMA abort. This bit is used to stop ongoing DMA transfers. Writing a 1 to this bit will abort all channels which are selected by setting the corresponding DMAARM bit to 1 0 : Normal operation 1 : Abort all selected channels |
| 6:5 | – | 00 | R / W | Not used |
| 4 | DMAARM4 | 0 | R / W | DMA arm channel 4 This bit must be set in order for any DMA transfers to occur on the channel. For non-repetitive transfer modes, the bit is automatically cleared upon completion. |
| 3 | DMAARM3 | 0 | R / W | DMA arm channel 3 This bit must be set in order for any DMA transfers to occur on the channel. For non-repetitive transfer modes, the bit is automatically cleared upon completion. |
| 2 | DMAARM2 | 0 | R / W | DMA arm channel 2 This bit must be set in order for any DMA transfers to occur on the channel. For non-repetitive transfer modes, the bit is automatically cleared upon completion. |
| 1 | DMAARM1 | 0 | R / W | DMA arm channel 1 This bit must be set in order for any DMA transfers to occur on the channel. For non-repetitive transfer modes, the bit is automatically cleared upon completion. |
| 0 | DMAARM0 | 0 | R / W | DMA arm channel 0 This bit must be set in order for any DMA transfers to occur on the channel. For non-repetitive transfer modes, the bit is automatically cleared upon completion. |

DMAREQ (0xD7) – DMA Channel Start Request and Status

| Bit | Name | Reset | R/W | Description |
|-----|---------|-------|------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:5 | – | 000 | R0 | Not used |
| 4 | DMAREQ4 | 0 | R/W1 H0 | <p>DMA transfer request, channel 4</p> <p>When set to 1 activate the DMA channel (has the same effect as a single trigger event.). Only by setting the armed bit to 0 in the DMAARM register, can the channel be stopped if already started.</p> <p>This bit is cleared when the DMA channel is granted access.</p> |
| 3 | DMAREQ3 | 0 | R/W1 H0 | <p>DMA transfer request, channel 3</p> <p>When set to 1 activate the DMA channel (has the same effect as a single trigger event.). Only by setting the armed bit to 0 in the DMAARM register, can the channel be stopped if already started.</p> <p>This bit is cleared when the DMA channel is granted access.</p> |
| 2 | DMAREQ2 | 0 | R/W1 H0 | <p>DMA transfer request, channel 2</p> <p>When set to 1 activate the DMA channel (has the same effect as a single trigger event.). Only by setting the armed bit to 0 in the DMAARM register, can the channel be stopped if already started.</p> <p>This bit is cleared when the DMA channel is granted access.</p> |
| 1 | DMAREQ1 | 0 | R/W1 H0 | <p>DMA transfer request, channel 1</p> <p>When set to 1 activate the DMA channel (has the same effect as a single trigger event.). Only by setting the armed bit to 0 in the DMAARM register, can the channel be stopped if already started.</p> <p>This bit is cleared when the DMA channel is granted access.</p> |
| 0 | DMAREQ0 | 0 | R/W1 H0 | <p>DMA transfer request, channel 0</p> <p>When set to 1 activate the DMA channel (has the same effect as a single trigger event.). Only by setting the armed bit to 0 in the DMAARM register, can the channel be stopped if already started.</p> <p>This bit is cleared when the DMA channel is granted access.</p> |

DMA0CFGH (0xD5) – DMA Channel 0 Configuration Address High Byte

| Bit | Name | Reset | R/W | Description |
|-----|---------------|-------|-----|-----------------------------------------------------|
| 7:0 | DMA0CFG[15:8] | 0x00 | R/W | The DMA channel 0 configuration address, high order |

DMA0CFGL (0xD4) – DMA Channel 0 Configuration Address Low Byte

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|----------------------------------------------------|
| 7:0 | DMA0CFG[7:0] | 0x00 | R/W | The DMA channel 0 configuration address, low order |

DMA1CFGH (0xD3) – DMA Channel 1-4 Configuration Address High Byte

| Bit | Name | Reset | R/W | Description |
|-----|---------------|-------|-----|-------------------------------------------------------|
| 7:0 | DMA1CFG[15:8] | 0x00 | R/W | The DMA channel 1-4 configuration address, high order |

DMA1CFGL (0xD2) – DMA Channel 1-4 Configuration Address Low Byte

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|------------------------------------------------------|
| 7:0 | DMA1CFG[7:0] | 0x00 | R/W | The DMA channel 1-4 configuration address, low order |

DMAIRQ (0xD1) – DMA Interrupt Flag

| Bit | Name | Reset | R/W | Description |
|-----|--------|-------|------|-------------------------------------------------------------------------------------------------------------------------------|
| 7:5 | – | 000 | R/W0 | Not used |
| 4 | DMAIF4 | 0 | R/W0 | DMA channel 4 interrupt flag. 0 : DMA channel transfer not complete 1 : DMA channel transfer complete/interrupt pending |
| 3 | DMAIF3 | 0 | R/W0 | DMA channel 3 interrupt flag. 0 : DMA channel transfer not complete 1 : DMA channel transfer complete/interrupt pending |
| 2 | DMAIF2 | 0 | R/W0 | DMA channel 2 interrupt flag. 0 : DMA channel transfer not complete 1 : DMA channel transfer complete/interrupt pending |
| 1 | DMAIF1 | 0 | R/W0 | DMA channel 1 interrupt flag. 0 : DMA channel transfer not complete 1 : DMA channel transfer complete/interrupt pending |
| 0 | DMAIF0 | 0 | R/W0 | DMA channel 0 interrupt flag. 0 : DMA channel transfer not complete 1 : DMA channel transfer complete/interrupt pending |

13.3 16-bit Timer, Timer1

Timer 1 is an independent 16-bit timer which supports typical timer/counter functions such as input capture, output compare and PWM functions. The timer has three independent capture/compare channels. The timer uses one I/O pin per channel. The timer is used for a wide range of control and measurement applications and the availability of up/down count mode with three channels will for example allow implementation of motor control applications.

The features of Timer 1 are as follows:

- Three capture/compare channels
- Rising, falling or any edge input capture
- Set, clear or toggle output compare
- Free-running, modulo or up/down counter operation
- Clock prescaler for divide by 1, 8, 32 or 128
- Interrupt request generated on each capture/compare and terminal count
- DMA trigger function

13.3.1 16-bit Timer Counter

The timer consists of a 16-bit counter that increments or decrements at each active clock edge. The period of the active clock edges is defined by the register bits `CLKCON.TICKSPD` which sets the global division of the system clock giving a variable clock tick frequency from 0.25 MHz to 32 MHz. This is further divided in Timer 1 by the prescaler value set by `T1CTL.DIV`. This prescaler value can be from 1 to 128. Thus the lowest clock frequency used by Timer 1 is 1953.125 Hz and the highest is 32 MHz when the 32 MHz crystal oscillator is used as system clock source. When the 16 MHz RC oscillator is used as system clock source then the highest clock frequency used by Timer 1 is 16 MHz.

The counter operates as either a free-running counter, a modulo counter or as an up/down counter for use in centre-aligned PWM.

It is possible to read the 16-bit counter value through the two 8-bit SFRs; `T1CNTH` and `T1CNTL`, containing the high-order byte and low-order byte respectively. When the `T1CNTL` is read, the high-order byte of the counter at that instant is buffered in `T1CNTH` so that the high-order byte can be read from `T1CNTH`. Thus `T1CNTL` shall always be read first before reading `T1CNTH`.

All write accesses to the `T1CNTL` register will reset the 16-bit counter.


The counter produces an interrupt request when the terminal count value (overflow) is reached. It is possible to clear and halt the counter with `T1CTL` control register settings. The counter is started when a value other than 00 is written to `T1CTL.MODE`. If 00 is written to `T1CTL.MODE` the counter halts at its present value.

13.3.2 Timer 1 Operation

In general, the control register `T1CTL` is used to control the timer operation. The various modes of operation are described below.

13.3.3 Free-running Mode


In the free-running mode of operation the counter starts from 0x0000 and increments at each active clock edge. When the counter reaches 0xFFFF the counter is loaded with 0x0000 and continues incrementing its value as shown in Figure 20. When the terminal count value 0xFFFF is reached, the flag `T1CTL.OVFIF` is set. An interrupt request is generated if the corresponding interrupt mask bit `TIMIF.OVFIM` is set. The free-running mode can be used to generate independent time intervals and output signal frequencies.

**Figure 20: Free-running mode**

13.3.4 Modulo Mode

When the timer operates in modulo mode the 16-bit counter starts at 0x0000 and increments at each active clock edge. When the counter reaches the terminal count value held in registers T1CC0H:T1CC0L, the counter is reset to 0x0000 and continues to increment.

The flag T1CTL.OVFIF is set when the terminal count value is reached. An interrupt request is generated if the corresponding interrupt mask bit TIMIF.OVFIM is set. The modulo mode can be used for applications where a period other than 0xFFFF is required. The counter operation is shown in Figure 21.

**Figure 21: Modulo mode**


13.3.5 Up/down Mode

In the up/down timer mode, the counter repeatedly starts from 0x0000 and counts up until the value held in T1CC0H:T1CC0L is reached and then the counter counts down until 0x0000 is reached as shown in Figure 22. This timer mode is used when symmetrical output pulses are required with a period other than 0xFFFF, and therefore allows implementation of centre-aligned PWM output applications. The flag T1CTL.OVFIF is set

when the counter value reaches 0x0000 in the up/down mode¹¹. An interrupt request is generated if the corresponding interrupt mask bit TIMIF.OVFIM is set.

Clearing the counter by writing to T1CNTL will also reset the count direction to the count up from 0x0000 mode.

¹¹ Only for devices with Chip Version register, CHVER.VERSION equal to 0x02 or greater

**Figure 22 : Up/down mode**

13.3.6 Channel Mode Control

The channel mode is set with each channel's control and status register `T1CCTLn`. The settings include input capture and output compare modes.

13.3.7 Input Capture Mode

When a channel is configured as an input capture channel, the I/O pin associated with that channel, is configured as an input. After the timer has been started, a rising edge, falling edge or any edge on the input pin will trigger a capture of the 16-bit counter contents into the associated capture register. Thus the timer is able to capture the time when an external event takes place.

Note: before an I/O pin can be used by the timer, the required I/O pin must be configured as a Timer 1 peripheral pin as described in section 13.1.3 on page 72 .

The channel input pin is synchronized to the internal system clock. Thus pulses on the input pin must have a minimum duration greater than the system clock period.

The contents of the 16-bit capture register is read out from registers `T1CCnH:T1CCnL`.

When the capture takes place the interrupt flag for the channel is set. This bit is `T1CTL.CH0IF` for channel 0, `T1CTL.CH1IF` for channel 1, and `T1CTL.CH2IF` for channel 2. An interrupt request is generated if the corresponding interrupt mask bit on `T1CCTL0.IM`, `T1CCTL1.IM`, or `T1CCTL2.IM`, respectively, is set.

13.3.8 Output Compare Mode

In output compare mode the I/O pin associated with a channel is set as an output. After the timer has been started, the contents of the counter is compared with the contents of the

channel compare register `T1CCnH:T1CCnL`. If the compare register equals the counter contents, the output pin is set, reset or toggled according to the compare output mode setting of `T1CCTLn.CMP`. Note that all edges on output pins are glitch-free when operating in a given output compare mode. Writing to the compare register `T1CCnL` is buffered so that a value written to `T1CCnL` does not take effect until the corresponding high order register, `T1CCnH` is written. For output compare modes 1-3, a new value written to the compare register `T1CCnH:T1CCnL` takes effect after the registers have been written. For other output compare modes the new value written to the compare register take effect when the timer reaches `0x0000`.

Note that channel 0 has fewer output compare modes because `T1CC0H:T1CC0L` has a special function in modes 6 and 7, meaning these modes would not be useful for channel 0.

When a compare occurs, the interrupt flag for the channel is set. This bit is `T1CTL.CH0IF` for channel 0, `T1CTL.CH1IF` for channel 1, and `T1CTL.CH2IF` for channel 2. An interrupt request is generated if the corresponding interrupt mask bit on `T1CCTL0.IM`, `T1CCTL1.IM`, or `T1CCTL2.IM`, respectively, is set. When operating in up-down mode, the interrupt flag for channel 0 is set when the counter reaches `0x0000` for the compare mode.

Examples of output compare modes in various timer modes are given in the following figures.

Edge-aligned PWM output signals can be generated using the timer modulo mode and channels 1 and 2 in output compare mode 6 or 7 as shown in Figure 23. The period of the PWM signal is determined by the setting `T1CC0` and the duty cycle for the channel output is determined by `T1CCn`. The timer free-

running mode may also be used. In this case `CLKCON.TICKSPD` and the prescaler divider value `T1CTL.DIV` set the period of the PWM signal. The polarity of the PWM signal is determined by whether output compare mode 6 or 7 is used. PWM output signals can also be generated using output compare modes 4 and 5 as shown in the same figure, or by using modulo mode as shown in Figure 24. Using output compare mode 4 and 5 is preferred for simple PWM.

Centre-aligned PWM outputs can be generated when the timer up/down mode is selected. The channel output compare mode 4 or 5 is selected depending on required polarity of the PWM signal. The period of the PWM signal is determined by `T1CC0` and the duty cycle for the channel output is determined by `T1CCn`.

The centre-aligned PWM mode is required by certain types of motor drive applications and typically less noise is produced than the edge-aligned PWM mode because the I/O pin

transitions are not lined up on the same clock edge.

In some types of applications, a defined delay or dead time is required between outputs. Typically this is required for outputs driving an H-bridge configuration to avoid uncontrolled cross-conduction in one side of the H-bridge. The delay or dead-time can be obtained in the PWM outputs by using `T1CCn` as shown in the following:

Assuming that channel 1 and channel 2 are used to drive the outputs using timer up/down mode and the channels use output compare modes 4 and 5 respectively, then the timer period (in Timer 1 clock periods) is:

$$T_P = T1CC0 \times 2$$

and the dead time, i.e. the time when both outputs are low, (in Timer 1 clock periods) is given by:

$$T_D = T1CC1 - T1CC2$$




Figure 23: Output compare modes, timer free-running mode





Figure 24: Output compare modes, timer modulo mode

**Figure 25: Output modes, timer up/down mode**

13.3.9 Timer 1 Interrupts

There is one interrupt vector assigned to the timer. An interrupt request is generated when one of the following timer events occur:

- Counter reaches terminal count value.
- Input capture event.
- Output compare event

The register bits `T1CTL.OVFIF`, `T1CTL.CH0IF`, `T1CTL.CH1IF`, and `T1CTL.CH2IF` contains the interrupt flags for the terminal count value event, and the three channel compare/capture events, respectively. An interrupt request is only generated when the corresponding interrupt mask bit is set. The interrupt mask bits are `T1CCTL0.IM`,

`T1CCTL1.IM`, `T1CCTL2.IM` and `TIMIF.OVFIM`. If there are other pending interrupts, the corresponding interrupt flag must be cleared by software before a new interrupt request is generated. Also, enabling an interrupt mask bit will generate a new interrupt request if the corresponding interrupt flag is set.

13.3.10 Timer 1 DMA Triggers

There are three DMA triggers associated with Timer 1. These are DMA triggers `T1_CH0`, `T1_CH1` and `T1_CH2` which are generated on timer compare events as follows:

- `T1_CH0` – channel 0 compare
- `T1_CH1` – channel 1 compare

- T1_CH2 – channel 2 compare

13.3.11 Timer 1 Registers

This section describes the Timer 1 registers which consist of the following registers:

- T1CNTH – Timer 1 Count High
- T1CNTL – Timer 1 Count Low
- T1CTL – Timer 1 Control and Status
- T1CCTLx – Timer 1 Channel x Capture/Compare Control
- T1CCxH – Timer 1 Channel x Capture/Compare Value High
- T1CCxL – Timer 1 Channel x Capture/Compare Value Low

T1CNTH (0xE3) – Timer 1 Counter High

| Bit | Name | Reset | R/W | Description |
|-----|-----------|-------|-----|----------------------------------------------------------------------------------------------------------------------|
| 7:0 | CNT[15:8] | 0x00 | R | Timer count high order byte. Contains the high byte of the 16-bit timer counter buffered at the time T1CNTL is read. |

T1CNTL (0xE2) – Timer 1 Counter Low

| Bit | Name | Reset | R/W | Description |
|-----|----------|-------|-----|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | CNT[7:0] | 0x00 | R/W | Timer count low order byte. Contains the low byte of the 16-bit timer counter. Writing anything to this register results in the counter being cleared to 0x0000. |

T1CTL (0xE4) – Timer 1 Control and Status

| Bit | Name | Reset | R/W | Description |
|-----|-----------|-------|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | CH2IF | 0 | R/W0 | Timer 1 channel 2 interrupt flag. Set when the channel 2 interrupt condition occurs. Writing a 1 has no effect. |
| 6 | CH1IF | 0 | R/W0 | Timer 1 channel 1 interrupt flag. Set when the channel 1 interrupt condition occurs. Writing a 1 has no effect. |
| 5 | CH0IF | 0 | R/W0 | Timer 1 channel 0 interrupt flag. Set when the channel 0 interrupt condition occurs. Writing a 1 has no effect. |
| 4 | OVFIF | 0 | R/W0 | Timer 1 counter overflow interrupt flag. Set when the counter reaches the terminal count value in free-running or modulo mode. Writing a 1 has no effect. |
| 3:2 | DIV[1:0] | 00 | R/W | Prescaler divider value. Generates the active clock edge used to update the counter as follows: 00 Tick frequency/1 01 Tick frequency/8 10 Tick frequency/32 11 Tick frequency/128 |
| 1:0 | MODE[1:0] | 00 | R/W | Timer 1 mode select. The timer operating mode is selected as follows: 00 Operation is suspended 01 Free-running, repeatedly count from 0x0000 to 0xFFFF 10 Modulo, repeatedly count from 0x0000 to T1CC0 11 Up/down, repeatedly count from 0x0000 to T1CC0 and from T1CC0 down to 0x0000 |

T1CCTL0 (0xE5) – Timer 1 Channel 0 Capture/Compare Control

| Bit | Name | Reset | R/W | Description |
|-----|----------|-------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | – | 0 | R/W | Reserved. Always set to 0 |
| 6 | IM | 1 | R/W | Channel 0 interrupt mask. Enables interrupt request when set. |
| 5:3 | CMP[2:0] | 000 | R/W | Channel 0 compare mode select. Selects action on output when timer value equals compare value in T1CC0 000 Set output on compare 001 Clear output on compare 010 Toggle output on compare 011 Set output on compare-up, clear on 0 (clear on compare-down in up/down mode) 100 Clear output on compare-up, set on 0 (set on compare-down in up/down mode) 101 Not used 110 Not used 111 Not used |
| 2 | MODE | 0 | R/W | Mode. Select Timer 1 channel 0 capture or compare mode 0 Capture mode 1 Compare mode |
| 1:0 | CAP[1:0] | 00 | R/W | Channel 0 capture mode select 00 No capture 01 Capture on rising edge 10 Capture on falling edge 11 Capture on all edges |

T1CC0H (0xDB) – Timer 1 Channel 0 Capture/Compare Value High

| Bit | Name | Reset | R/W | Description |
|-----|-------------|-------|-----|----------------------------------------------------------|
| 7:0 | T1CC0[15:8] | 0x00 | R/W | Timer 1 channel 0 capture/compare value, high order byte |

T1CC0L (0xDA) – Timer 1 Channel 0 Capture/Compare Value Low

| Bit | Name | Reset | R/W | Description |
|-----|------------|-------|-----|---------------------------------------------------------|
| 7:0 | T1CC0[7:0] | 0x00 | R/W | Timer 1 channel 0 capture/compare value, low order byte |

T1CCTL1 (0xE6) – Timer 1 Channel 1 Capture/Compare Control

| Bit | Name | Reset | R/W | Description |
|-----|----------|-------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | – | 0 | R/W | Reserved. Always set to 0. |
| 6 | IM | 1 | R/W | Channel 1 interrupt mask. Enables interrupt request when set. |
| 5:3 | CMP[2:0] | 000 | R/W | Channel 1 compare mode select. Selects action on output when timer value equals compare value in T1CC1 000 Set output on compare 001 Clear output on compare 010 Toggle output on compare 011 Set output on compare-up, clear on 0 (clear on compare-down in up/down mode) 100 Clear output on compare-up, set on 0 (set on compare-down in up/down mode) 101 Clear when equal T1CC0, set when equal T1CC1 110 Set when equal T1CC0, clear when equal T1CC1 111 Not used |
| 2 | MODE | 0 | R/W | Mode. Select Timer 1 channel 1 capture or compare mode 0 Capture mode 1 Compare mode |
| 1:0 | CAP[1:0] | 00 | R/W | Channel 1 capture mode select 00 No capture 01 Capture on rising edge 10 Capture on falling edge 11 Capture on all edges |

T1CC1H (0xDD) – Timer 1 Channel 1 Capture/Compare Value High

| Bit | Name | Reset | R/W | Description |
|-----|-------------|-------|-----|----------------------------------------------------------|
| 7:0 | T1CC1[15:8] | 0x00 | R/W | Timer 1 channel 1 capture/compare value, high order byte |

T1CC1L (0xDC) – Timer 1 Channel 1 Capture/Compare Value Low

| Bit | Name | Reset | R/W | Description |
|-----|------------|-------|-----|---------------------------------------------------------|
| 7:0 | T1CC1[7:0] | 0x00 | R/W | Timer 1 channel 1 capture/compare value, low order byte |

T1CCTL2 (0xE7) – Timer 1 Channel 2 Capture/Compare Control

| Bit | Name | Reset | R/W | Description |
|-----|----------|-------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | – | 0 | R/W | Reserved. Always set to 0. |
| 6 | IM | 1 | R/W | Channel 2 interrupt mask. Enables interrupt request when set. |
| 5:3 | CMP[2:0] | 000 | R/W | Channel 2 compare mode select. Selects action on output when timer value equals compare value in T1CC2 000 Set output on compare 001 Clear output on compare 010 Toggle output on compare 011 Set output on compare-up, clear on 0 (clear on compare-down in up/down mode) 100 Clear output on compare-up, set on 0 (set on compare-down in up/down mode) 101 Clear when equal T1CC0, set when equal T1CC2 110 Set when equal T1CC0, clear when equal T1CC2 111 Not used |
| 2 | MODE | 0 | R/W | Mode. Select Timer 1 channel 2 capture or compare mode 0 Capture mode 1 Compare mode |
| 1:0 | CAP[1:0] | 00 | R/W | Channel 2 capture mode select 00 No capture 01 Capture on rising edge 10 Capture on falling edge 11 Capture on all edges |

T1CC2H (0xDF) – Timer 1 Channel 2 Capture/Compare Value High

| Bit | Name | Reset | R/W | Description |
|-----|-------------|-------|-----|----------------------------------------------------------|
| 7:0 | T1CC2[15:8] | 0x00 | R/W | Timer 1 channel 2 capture/compare value, high order byte |

T1CC2L (0xDE) – Timer 1 Channel 2 Capture/Compare Value Low

| Bit | Name | Reset | R/W | Description |
|-----|------------|-------|-----|---------------------------------------------------------|
| 7:0 | T1CC2[7:0] | 0x00 | R/W | Timer 1 channel 2 capture/compare value, low order byte |

The TIMIF.OVFIM register bit resides in the TIMIF register, which is described together with Timer 3 and Timer 4 registers on page 114.

13.4 MAC Timer (Timer 2)

The MAC Timer is mainly used to provide timing for 802.15.4 CSMA-CA algorithms and for general timekeeping in the 802.15.4 MAC layer. When the MAC Timer is used together with the Sleep Timer described in section 13.5, the timing function is provided even when the system enters low-power modes.

The main features of the MAC Timer are the following:

- 16-bit timer up-counter providing symbol/frame period: 16µs/320µs
- Adjustable period with accuracy 31.25 ns
- 8-bit timer compare function
- 20-bit overflow count
- 20-bit overflow count compare function
- Start of Frame Delimiter capture function.
- Timer start/stop synchronous with 32.768 kHz clock and timekeeping maintained by Sleep Timer.
- Interrupts generated on compare and overflow
- DMA trigger capability

13.4.1 Timer Operation

This section describes the operation of the timer.

13.4.1.1 General

After a reset the timer is in the timer IDLE mode where it is stopped. The timer starts running when `T2CNF.RUN` is set to 1. The timer will then enter the timer RUN mode. The entry is either immediate or it is performed synchronous with the 32.768 kHz clock. See section 13.4.4 for a description of the synchronous start and stop mode.

Once the timer is running in RUN mode, it can be stopped by writing a 0 to `T2CNF.RUN`. The timer will then enter the timer IDLE mode. The stopping of the timer is performed either immediately or it is performed synchronous with the 32.768 kHz clock

13.4.1.2 Up Counter

The MAC Timer contains a 16-bit timer, which increments during each clock cycle.

13.4.1.3 Timer overflow

When the timer is about to *count* to a value that is equal to or greater than the timer period set by registers `T2CAPHPH:T2CAPLPL`, a timer overflow occurs. When the timer overflow occurs, the timer is set to the difference between the value it is about to count to and the timer period, e.g. if the next value of the timer would be 0x00FF and the timer period is 0x00FF then the timer is set to 0x000. If the overflow interrupt mask bit `T2PEROF2.PERIM` is 1, an interrupt request is generated. The interrupt flag bit `T2CNF.PERIF` is set to 1 regardless of the interrupt mask value.

13.4.1.4 Timer delta increment

The timer period may be adjusted once during a timer period by writing a timer delta value. When a timer delta value is written to the registers `T2THD:T2TLD`, the 16-bit timer halts at its current value and a delta counter starts counting. The delta counter starts counting from the delta value written, down to zero. Once the delta counter reaches zero, the 16-bit timer starts counting again.

The delta counter decrements by the same rate as the timer. When the delta counter has reached zero it will not start counting again until the delta value is written once again. In this way a timer period may be increased by the delta value in order to make adjustments to the timer overflow events over time.

13.4.1.5 Timer Compare

A timer compare occurs when the timer is about to *count* to a value that is equal or greater than the 8-bit compare value held in the `T2CMP` register. Note that the compare value is only 8 bits so the compare is made between the compare value and either the most significant byte or the least significant byte of the timer. The selection of which part of the timer is to be compared is set by the `T2CNF.CMSEL` bit.

When a timer compare occurs the interrupt flag `T2CNF.CMPIF` is set to 1. An interrupt request is also generated if the interrupt mask `T2PEROF2.CMPIM` is set to 1.

13.4.1.6 Capture Input

The MAC timer has a timer capture function which captures at the time when the start of frame delimiter (SFD) status in the radio goes high. Refer to sections 14.6 and 14.9 starting on page 167 for a description of the SFD.

When the capture event occurs the current timer value will be captured into the capture register. The capture value can be read from the registers `T2CAPHPH:T2CAPLPL`. The value of the overflow count is also captured (see section 13.4.1.7) at the time of the capture event and can be read from the registers `T2PEROF2:T2PEROF1:T2PEROF0`.

13.4.1.7 Overflow count

At each timer overflow, the 20-bit overflow counter is incremented by 1. The overflow counter value is read through the SFR registers `T2OF2:T2OF1:T2OF0`. Note that the register contents in `T2OF2:T2OF1` is latched when `T2OF0` is read, meaning that `T2OF0` must always be read first.

Overflow count update

The overflow count value may be updated by writing to the registers `T2OF2:T2OF1:T2OF0` when the timer is in the IDLE or RUN state.

Note that the last data written to registers `T2OF1:T2OF0` is latched when `T2OF2` is written, meaning that `T2OF2` must always be written last.

13.4.1.8 Overflow count compare

A compare value may be set for the overflow counter. The compare value is set by writing to `T2PEROF2:T2PEROF1:T2PEROF0`.

When the overflow count value is equal or greater than the set compare value an overflow compare event occurs. If the overflow compare interrupt mask bit `T2PEROF2.OFCMPIM` is 1, an interrupt request is generated. The interrupt flag bit `T2CNF.OFCMPIF` is set to 1 regardless of the interrupt mask value.

13.4.2 Interrupts

The Timer has three individually maskable interrupt sources. These are the following:

- Timer overflow
- Timer compare
- Overflow count compare

The interrupt flags are given in the `T2CNF` registers. The interrupt flag bits are set only by hardware and may be cleared only by writing to the SFR register.

Each interrupt source may be masked by the mask bits in the `T2PEROF2` register. An interrupt is generated when the corresponding mask bit is set, otherwise the interrupt will not be generated. The interrupt flag bit is set, however disregarding the state of the interrupt mask bit.

13.4.3 DMA Triggers

Timer 2 can generate two DMA triggers – `T2_COMP` and `T2_OVFL` which are activated as follows:

- `T2_COMP`: Timer 2 compare event
- `T2_OVFL`: Timer 2 overflow event

13.4.4 Timer start/stop synchronization

This section describes the synchronized timer start and stop.

13.4.4.1 General

The Timer can be started and stopped synchronously with the 32.768 kHz clock rising edge. Note this event is derived from a 32.768 kHz clock signal, but is synchronous with the 32 MHz system clock and thus has a period approximately equal the 32.768 kHz clock period.

At the time of a synchronous start the timer is reloaded with new calculated values for the timer and overflow count such that it appears that the timer has not been stopped.

13.4.4.2 Timer synchronous stop

After the timer has started running, i.e. entered timer RUN mode it is stopped synchronously by writing 0 to `T2CNF.RUN` when `T2CNF.SYNC` is 1. After `T2CNF.RUN` has been set to 0, the timer will continue running until the 32.768 kHz clock rising edge is sampled as 1. When this occurs

the timer is stopped and the current Sleep timer value is stored.

13.4.4.3 Timer synchronous start

When the timer is in the IDLE mode it is started synchronously by writing 1 to T2CNF.RUN when T2CNF.SYNC is 1. After T2CNF.RUN has been set to 1, the timer will remain in the IDLE mode until the 32.768 kHz clock rising edge is detected. When this occurs the timer will first calculate new values for the 16-bit timer value and for the 20-bit timer overflow count, based on the current and stored Sleep timer values and the current 16-bit timer values. The new MAC Timer and overflow count values are loaded into the timer and the timer enters the RUN mode. This synchronous start process takes 75 clock cycles from the time when the 32.768 kHz clock rising edge is sampled high. The synchronous start and stop function requires that the system clock frequency is selected to be 32 MHz. If the 16 MHz clock is selected, there will be an offset added to the new calculated value.

The method for calculating the new MAC Timer value and overflow count value is given below. Due to the fact that the MAC Timer clock and Sleep timer clocks are asynchronous with a non-integer clock ratio there will be an error of maximum ± 1 in calculated timer value compared to the ideal timer value.

Calculation of new timer value and overflow count value

$$N_c = \text{CurrentSleepTimerValue}$$

$$N_s = \text{StoredSleepTimerValue}$$

$$K_{ck} = \text{ClockRatio} = 976.5625^{12}$$

$$stw = \text{SleepTimerWidth} = 24$$

$$P = \text{Timer2Period}$$

¹² Clock ratio of MAC Timer clock frequency (32 MHz) and Sleep timer clock frequency (32.768 kHz)

$$O_c = \text{CurrentOverflowCountValue}$$

$$T_c = \text{CurrentTimerValue}$$

$$T_{OH} = \text{Overhead} = 75$$

$$N_t = N_c - N_s$$

$$N_t \leq 0 \Rightarrow N_d = 2^{stw} + N_t; N_t > 0 \Rightarrow N_d = N_t$$

$$C = N_d \cdot K_{ck} + T_c + T_{OH} \quad (\text{Rounded to nearest integer value})$$

$$T = C \bmod P$$

$$O = \frac{(C - T)}{P} + O_c$$

$$\text{Timer2Value} = T$$

$$\text{Timer2OverflowCount} = O$$

For a given Timer 2 period value, P, there is a maximum duration between Timer 2 synchronous stop and start for which the timer value is correctly updated after starting. The maximum value is given in terms of the number of Sleep Timer clock periods, i.e. 32.768 kHz clock periods, $T_{ST(max)}$

$$T_{ST(max)} \leq \frac{(2^{20} - 1) \times P + T_{OH}}{K_{ck}}$$

13.4.5 Timer 2 Registers

The SFR registers associated with Timer 2 are listed in this section. These registers are the following:

- T2CNF – Timer 2 Configuration
- T2HD – Timer 2 Count/Delta High
- T2LD – Timer 2 Count/Delta Low
- T2CMP – Timer 2 Compare
- T2OF2 – Timer 2 Overflow Count 2
- T2OF1 – Timer 2 Overflow Count 1
- T2OF0 – Timer 2 Overflow Count 0
- T2CAPHPH – Timer 2 Capture/Period High
- T2CAPLPL – Timer 2 Capture/Period Low
- T2PEROF2 – Timer 2 Overflow Capture/Compare 2

- T2PEROF1 – Timer 2 Overflow Capture/Compare 1
- T2PEROF0 – Timer 2 Overflow Capture/Compare 0

T2CNF (0xC3) – Timer 2 Configuration

| Bit | Name | Reset | R/W | Description |
|-----|---------|-------|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | CMPIF | 0 | R/W0 | Timer compare interrupt flag. This bit is set to 1 when a timer compare event occurs. Cleared by software only. Writing a 1 to this bit has no effect. |
| 6 | PERIF | 0 | R/W0 | Overflow interrupt flag. This bit is set to 1 when a period event occurs. Cleared by software only. Writing a 1 to this bit has no effect. |
| 5 | OFCMPIF | 0 | R/W0 | Overflow compare interrupt flag. This bit is set to 1 when a overflow compare occurs. Cleared by software only. Writing a 1 to this bit has no effect. |
| 4 | – | 0 | R0 | Not used. Read as 0 |
| 3 | CMSEL | 0 | R/W | Timer compare source select. 0 Compare with 16-bit Timer bits [15:8] 1 Compare with 16-bit Timer bits [7:0] |
| 2 | – | 0 | R/W | Reserved. Always set to 0 |
| 1 | SYNC | 1 | R/W | Enable synchronized start and stop. 0 start and stop of timer is immediate 1 start and stop of timer is synchronized with 32.768 kHz edge and new timer values are reloaded. |
| 0 | RUN | 0 | R/W | Dual function: timer start / timer status. Writing this bit will start or stop the timer. 0 stop timer 1 start timer Reading this bit the current state of the timer is returned. 0 timer is stopped (IDLE state) 1 timer is running (RUN state) Note when SYNC =1 (the reset condition), the timer status does not change immediately when the timer is started or stopped. Instead the timer status is changed when the actual synchronous start/stop takes place. Prior to the synchronous start/stop event, the read value of RUN will differ from the last value written. |

T2THD (0xA7) – Timer 2 Timer Value High Byte

| Bit | Name | Reset | R/W | Description |
|-----|----------|-------|-----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | THD[7:0] | 0x00 | R/W | <p>The value read from this register is the high-order byte of the timer value. The high-order byte read is from timer value at the last instant when T2TLD was read.</p> <p>The value written to this register while the timer is running is the high-order byte of the timer delta counter value. The low-order byte of this value is the value last written to T2TLD. The timer will halt for delta clock cycles.</p> <p>The value written to this register while the timer is idle will be written to the high-order byte of the timer.</p> |

T2TLD (0xA6) – Timer 2 Timer Value Low Byte

| Bit | Name | Reset | R/W | Description |
|-----|----------|-------|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | TLD[7:0] | 0x00 | R/W | <p>The value read from this register is the low-order byte of the timer value.</p> <p>The value written to this register while the timer is running is the low-order byte of the timer delta counter value. The timer will halt for delta clock cycles. The value written to T2TLD will not take effect until T2THD is written.</p> <p>The value written to this register while the timer is idle will be written to the low-order byte of the timer.</p> |

T2CMP (0x94) – Timer 2 Compare Value

| Bit | Name | Reset | R/W | Description |
|-----|----------|-------|-----|---------------------------------------------------------------------------------------------------------------------------|
| 7:0 | CMP[7:0] | 0x00 | R/W | Timer Compare value. A timer compare occurs when the compare source selected by T2CNF.CMSEL equals the value held in CMP. |

T2OF2 (0xA3) – Timer 2 Overflow Count 2

| Bit | Name | Reset | R/W | Description |
|-----|----------|-------|-----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:4 | - | 0000 | R0 | Not used, read as 0 |
| 3:0 | OF2[3:0] | 0x00 | R/W | Overflow count. High bits T2OF[19:16]. T2OF is incremented by 1 each time the timer overflows i.e. timer counts to a value greater or equal to period. When reading this register, the value read is the value latched when T2OF0 was read. Writing to this register when the timer is in IDLE or RUN states will force the overflow count to be set to the value written to T2OF2:T2OF1:T2OF0. If the count would otherwise be incremented by 1 when this register is written then 1 is added to the value written. |

T2OF1 (0xA2) – Timer 2 Overflow Count 1

| Bit | Name | Reset | R/W | Description |
|-----|----------|-------|-----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | OF1[7:0] | 0x00 | R/W | Overflow count. Middle bits T2OF[15:8]. T2OF is incremented by 1 each time the timer overflows i.e. timer counts to a value greater or equal to period. When reading this register, the value read is the value latched when T2OF0 was read. Writing to this register when the timer is in IDLE |

| | | | | |
|--|--|--|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | | | | or RUN states will force the overflow count to be set to the value written to T2OF2:T2OF1:T2OF0. If the count would otherwise be incremented by 1 when this register is written then 1 is added to the value written. The value written will not take effect until T2OF2 is written. |
|--|--|--|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

T2OF0 (0xA1) – Timer 2 Overflow Count 0

| Bit | Name | Reset | R/W | Description |
|-----|----------|-------|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | OF0[7:0] | 0x00 | R/W | Overflow count. Low bits T2OF[7:0]. T2OF is incremented by 1 each time the timer overflows i.e. timer counts to a value greater or equal to period. Writing to this register when the timer is in IDLE or RUN states will force the overflow count to be set to the value written to T2OF2:T2OF1:T2OF0. If the count would otherwise be incremented by 1 when this register is written then 1 is added to the value written. The value written will not take effect until T2OF2 is written. |

T2CAPHPH (0xA5) – Timer 2 Period High Byte

| Bit | Name | Reset | R/W | Description |
|-----|-------------|-------|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | CAPHPH[7:0] | 0xFF | R/W | Capture value high/timer period high. Writing this register sets the high order bits [15:8] of the timer period. Reading this register gives the high order bits [15:8] of the timer value at the last capture event. |

T2CAPLPL (0xA4) – Timer 2 Period Low Byte

| Bit | Name | Reset | R/W | Description |
|-----|-------------|-------|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | CAPLPL[7:0] | 0xFF | R/W | Capture value low/timer period low. Writing this register sets the low order bits [7:0] of the timer period. Reading this register gives the low order bits [7:0] of the timer value at the last capture event. |

T2PEROF2 (0x9E) – Timer 2 Overflow Capture/Compare 2

| Bit | Name | Reset | R/W | Description |
|-----|-------------|-------|-----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | CMPIM | 0 | R/W | Compare interrupt mask. 0: No interrupt is generated on compare event 1: Interrupt is generated on compare event. |
| 6 | PERIM | 0 | R/W | Overflow interrupt mask 0: No interrupt is generated on timer overflow 1: Interrupt is generated on timer overflow |
| 5 | OFCMPIM | 0 | R/W | Overflow count compare interrupt mask 0: No interrupt is generated on overflow count compare 1: Interrupt is generated on overflow count compare |
| 4 | - | 0 | R0 | Not used, read as 0 |
| 3:0 | PEROF2[3:0] | 0000 | R/W | Overflow count capture/Overflow count compare value. Writing these bits set the high bits [19:16] of the overflow count compare value. Reading these bits returns the high bits [19:16] of the overflow count value at the time of the last capture event. |

T2PEROF1 (0x9D) – Timer 2 Overflow Capture/Compare 1

| Bit | Name | Reset | R/W | Description |
|-----|-------------|-------|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | PEROF1[7:0] | 0x00 | R/W | Overflow count capture /Overflow count compare value. Writing these bits set the middle bits [15:8] of the overflow count compare value. Reading these bits returns the middle bits [15:8] of the overflow count value at the time of the last capture event. |

T2PEROF0 (0x9C) – Timer 2 Overflow Capture/Compare 0

| Bit | Name | Reset | R/W | Description |
|-----|-------------|-------|-----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | PEROF0[7:0] | 0x00 | R/W | Overflow count capture /Overflow count compare value. Writing these bits set the low bits [7:0] of the overflow count compare value. Reading these bits returns the low bits [7:0] of the overflow count value at the time of the last capture event. |

13.5 Sleep Timer

The Sleep timer is used to set the period between when the system enters and exits low-power sleep modes.

The Sleep timer is also used to maintain timing in Timer 2 (MAC Timer) when entering a low-power sleep mode.

The main features of the Sleep timer are the following:

- 24-bit timer up-counter operating at 32.768 kHz clock
- 24-bit compare
- Low-power mode operation in PM2
- Interrupt and DMA trigger

13.5.1 Timer Operation

This section describes the operation of the timer.

13.5.1.1 General

The Sleep timer is a 24-bit timer running on the 32.768 kHz clock. The timer starts running immediately after a reset and continues to run uninterrupted. The current value of the timer can be read from the SFR registers `ST2:ST1:ST0`.

13.5.1.2 Timer Compare

A timer compare occurs when the timer value is equal to the 24-bit compare value. The compare value is set by writing to the registers `ST2:ST1:ST0`. When a timer compare occurs the interrupt flag `STIF` (interrupt 5) is asserted.

The interrupt enable bit for the ST interrupt is `IEN0.STIE` and the interrupt flag is `IRCON.STIF`.

When operating in power modes PM1 or PM2, the Sleep timer will be running and the Sleep timer compare event is used to wake up the device and return to active operation in PM0.

The default value of the compare value after reset is 0xFFFFF.

The Sleep timer compare can also be used as a DMA trigger (DMA trigger 9 in Table 37).

13.5.1.3 Sleep Timer Registers

The registers used by the Sleep Timer are:

- `ST2` – Sleep Timer 2
- `ST1` – Sleep Timer 1
- `ST0` – Sleep Timer 0

ST2 (0x97) – Sleep Timer 2

| Bit | Name | Reset | R/W | Description |
|-----|-----------------------|-------|-----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | <code>ST2[7:0]</code> | 0x00 | R/W | Sleep timer count/compare value. When read, this register returns the high bits [23:16] of the sleep timer count. When writing this register sets the high bits [23:16] of the compare value. The value read is latched at the time of reading register <code>ST0</code> . The value written is latched when <code>ST0</code> is written. |

ST1 (0x96) – Sleep Timer 1

| Bit | Name | Reset | R/W | Description |
|-----|-----------------------|-------|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | <code>ST1[7:0]</code> | 0x00 | R/W | Sleep timer count/compare value. When read, this register returns the middle bits [15:8] of the sleep timer count. When writing this register sets the middle bits [15:8] of the compare value. The value read is latched at the time of reading register <code>ST0</code> . The value written is latched when <code>ST0</code> is written. |

ST0 (0x95) – Sleep Timer 0

| Bit | Name | Reset | R/W | Description |
|-----|-----------------------|-------|-----|----------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | <code>ST0[7:0]</code> | 0x00 | R/W | Sleep timer count/compare value. When read, this register returns the low bits [7:0] of the sleep timer count. When writing this register sets the |

| | | | | |
|--|--|--|--|--------------------------------------|
| | | | | low bits [7:0] of the compare value. |
|--|--|--|--|--------------------------------------|

13.6 8-bit Timer 3 and Timer 4

Timer 3 and 4 are 8-bit timers which support typical input capture and output compare operations using two compare channels each. The timer allows general purpose timer and waveform generation functions.

Features of Timer 3/4 are as follows:

- Dual channel operation
- Set, clear or toggle output compare
- Clock prescaler for divide by 1, 2, 4, 8, 16, 32, 64, 128
- Interrupt request generated on each compare and terminal count event
- DMA trigger function

13.6.1 8-bit Timer Counter

All timer functions are based on the main 8-bit counter found in Timer 3/4. The counter increments or decrements at each active clock edge. The period of the active clock edges is defined by the register bits `CLKCON.TICKSPD` which is further divided by the prescaler value set by `TxCTL.DIV` (where x refers to the timer number, 3 or 4). The counter operates as either a free-running counter, a down counter, a modulo counter or as an up/down counter.

It is possible to read the 8-bit counter value through the SFR `TxCNT` where x refers to the timer number, 3 or 4.

The possibility to clear and halt the counter is given with `TxCTL` control register settings. The counter is started when a 1 is written to `TxCTL.START`. If a 0 is written to `TxCTL.START` the counter halts at its present value.

13.6.2 Timer 3/4 Mode Control

In general the control register `TxCTL` is used to control the timer operation.

13.6.2.1 Free-running Mode

In the free-running mode of operation the counter starts from 0x00 and increments at each active clock edge. When the counter reaches 0xFF the counter is loaded with 0x00 and continues incrementing its value. When the terminal count value 0xFF is reached (i.e. an overflow occurs), the interrupt flag `TIMIF.TxOVFIF` is set. If the corresponding interrupt mask bit `TxCTL.OVFIM` is set, an interrupt request is generated. The free-

running mode can be used to generate independent time intervals and output signal frequencies.

13.6.2.2 Down mode

In the down mode, after the timer has been started, the counter is loaded with the contents in `TxCC`. The counter then counts down to 0x00. The flag `TIMIF.TxOVFIF` is set when 0x00 is reached. If the corresponding interrupt mask bit `TxCTL.OVFIM` is set, an interrupt request is generated. The timer down mode can generally be used in applications where an event timeout interval is required.

13.6.2.3 Modulo Mode

When the timer operates in modulo mode the 8-bit counter starts at 0x00 and increments at each active clock edge. When the counter reaches the terminal count value held in register `TxCC` the counter is reset to 0x00 and continues to increment. The flag `TIMIF.TxOVFIF` is set when on this event. If the corresponding interrupt mask bit `TxCTL.OVFIM` is set, an interrupt request is generated. The modulo mode can be used for applications where a period other than 0xFF is required.

13.6.2.4 Up/down Mode

In the up/down timer mode, the counter repeatedly starts from 0x00 and counts up until the value held in `TxCC` is reached and then the counter counts down until 0x00 is reached. This timer mode is used when symmetrical output pulses are required with a period other than 0xFF, and therefore allows implementation of centre-aligned PWM output applications.

Clearing the counter by writing to `TxCTL.CLR` will also reset the count direction to the count up from 0x00 mode.

13.6.3 Channel Mode Control

The channel modes for each channel; 0 and 1, are set by the control and status registers `TxCCTLn` where n is the channel number, 0 or 1. The settings include output compare modes.

13.6.4 Output Compare Mode

In output compare mode the I/O pin associated with a channel shall be set to an output. After the timer has been started, the contents of the

counter is compared with the contents of the channel compare register `TxCC0n`. If the compare register equals the counter contents, the output pin is set, reset or toggled according to the compare output mode setting of `TxCCTL.CMP1:0`. Note that all edges on output pins are glitch-free when operating in a given compare output mode.

For simple PWM use, output compare modes 4 and 5 are preferred.

Writing to the compare register `TxCC0` does not take effect on the output compare value until the counter value is 0x00. Writing to the compare register `TxCC1` takes effect immediately.

When a compare occurs the interrupt flag corresponding to the actual channel is set. This is `TIMIF.TxCHnIF`. An interrupt request is generated if the corresponding interrupt mask bit `TxCCTLn.IM` is set.

13.6.5 Timer 3 and 4 interrupts

There is one interrupt vector assigned to each of the timers. These are T3 (interrupt 11) and T4 (interrupt 12). An interrupt request is generated when one of the following timer events occur:

- Counter reaches terminal count value.

- Output compare event

The SFR register `TIMIF` contains all interrupt flags for Timer 3 and Timer 4. The register bits `TIMIF.TxOVFIF` and `TIMIF.TxCHnIF`, contains the interrupt flags for the two terminal count value events and the four channel compare events, respectively. An interrupt request is only generated when the corresponding interrupt mask bit is set. If there are other pending interrupts, the corresponding interrupt flag must be cleared by the CPU before a new interrupt request can be generated. Also, enabling an interrupt mask bit will generate a new interrupt request if the corresponding interrupt flag is set.

13.6.6 Timer 3 and Timer 4 DMA triggers

There are two DMA triggers associated with Timer 3 and two DMA triggers associated with Timer 4. These are the following:

- T3_CH0 : Timer 3 channel 0 compare
- T3_CH1 : Timer 3 channel 1 compare
- T4_CH0 : Timer 4 channel 0 compare
- T4_CH1 : Timer 4 channel 1 compare

Refer to section 13.2 on page 81 for a description on use of DMA channels.

13.6.7 Timer 3 and 4 registers

T3CNT (0xCA) – Timer 3 Counter

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|--------------------------------------------------------------------|
| 7:0 | CNT[7 : 0] | 0x00 | R | Timer count byte. Contains the current value of the 8-bit counter. |

T3CTL (0xCB) – Timer 3 Control

| Bit | Name | Reset | R/W | Description |
|-----|---------------|-------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:5 | DIV[2 : 0] | 000 | R/W | Prescaler divider value. Generates the active clock edge used to clock the timer from CLKCON . TICKSPD as follows: 000 Tick frequency /1 001 Tick frequency /2 010 Tick frequency /4 011 Tick frequency /8 100 Tick frequency /16 101 Tick frequency /32 110 Tick frequency /64 111 Tick frequency /128 |
| 4 | START | 0 | R/W | Start timer. Normal operation when set, suspended when cleared |
| 3 | OVFIM | 1 | R/W0 | Overflow interrupt mask 0 : interrupt is disabled 1 : interrupt is enabled |
| 2 | CLR | 0 | R0/W1 | Clear counter. Writing high resets counter to 0x00 |
| 1:0 | MODE[1 : 0] | 00 | R/W | Timer 3 mode. Select the mode as follows: 00 Free running, repeatedly count from 0x00 to 0xFF 01 Down, count from T3CC0 to 0x00 10 Modulo, repeatedly count from 0x00 to T3CC0 11 Up/down, repeatedly count from 0x00 to T3CC0 and down to 0x00 |

T3CCTL0 (0xCC) – Timer 3 Channel 0 Compare Control

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | – | 0 | R0 | Unused |
| 6 | IM | 1 | R/W | Channel 0 interrupt mask 0 : interrupt is disabled 1 : interrupt is enabled |
| 5:3 | CMP[2 : 0] | 000 | R/W | Channel 0 compare output mode select. Specified action on output when timer value equals compare value in T3CC0 000 Set output on compare 001 Clear output on compare 010 Toggle output on compare 011 Set output on compare-up, clear on 0 (clear on compare-down in up/down mode) 100 Clear output on compare-up, set on 0 (set on compare-down in up/down mode) 101 Set output on compare, clear on 0xFF 110 Clear output on compare, set on 0x00 111 Not used |
| 2 | MODE | 0 | R/W | Mode. Select Timer 3 channel 0 compare mode 0 Compare disabled 1 Compare enable |
| 1:0 | – | 00 | R/W | Reserved. Set to 00. |

T3CC0 (0xCD) – Timer 3 Channel 0 Compare Value

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|-------------------------------|
| 7:0 | VAL[7 : 0] | 0x00 | R/W | Timer compare value channel 0 |

T3CCTL1 (0xCE) – Timer 3 Channel 1 Compare Control

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | – | 0 | R0 | Unused |
| 6 | IM | 1 | R/W | Channel 1 interrupt mask 0 : interrupt is disabled 1 : interrupt is enabled |
| 5:3 | CMP[2 : 0] | 000 | R/W | Channel 1 compare output mode select. Specified action on output when timer value equals compare value in T3CC1 000 Set output on compare 001 Clear output on compare 010 Toggle output on compare 011 Set output on compare-up, clear on 0 (clear on compare-down in up/down mode) 100 Clear output on compare-up, set on 0 (set on compare-down in up/down mode) 101 Set output on compare, clear on T3CC0 110 Clear output on compare, set on T3CC0 111 Not used |
| 2 | MODE | 0 | R/W | Mode. Select Timer 3 channel 1 compare mode 0 Compare disabled 1 Compare enabled |
| 1:0 | – | 00 | R/W | Reserved. Set to 00. |

T3CC1 (0xCF) – Timer 3 Channel 1 Compare Value

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|-------------------------------|
| 7:0 | VAL[7 : 0] | 0x00 | R/W | Timer compare value channel 1 |

T4CNT (0xEA) – Timer 4 Counter

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|--------------------------------------------------------------------|
| 7:0 | CNT[7 : 0] | 0x00 | R | Timer count byte. Contains the current value of the 8-bit counter. |

T4CTL (0xEB) – Timer 4 Control

| Bit | Name | Reset | R/W | Description |
|-----|-----------|-------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:5 | DIV[2:0] | 000 | R/W | Prescaler divider value. Generates the active clock edge used to clock the timer from CLKCON.TICKSPD as follows: 000 Tick frequency /1 001 Tick frequency /2 010 Tick frequency /4 011 Tick frequency /8 100 Tick frequency /16 101 Tick frequency /32 110 Tick frequency /64 111 Tick frequency /128 |
| 4 | START | 0 | R/W | Start timer. Normal operation when set, suspended when cleared |
| 3 | OVFIM | 1 | R/W0 | Overflow interrupt mask |
| 2 | CLR | 0 | R0/W1 | Clear counter. Writing high resets counter to 0x00 |
| 1:0 | MODE[1:0] | 00 | R/W | Timer 4 mode. Select the mode as follows: 00 Free running, repeatedly count from 0x00 to 0xFF 01 Down, count from T4CC0 to 0x00 10 Modulo, repeatedly count from 0x00 to T4CC0 11 Up/down, repeatedly count from 0x00 to T4CC0 and down to 0x00 |

T4CCTL0 (0xEC) – Timer 4 Channel 0 Compare Control

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | – | 0 | R0 | Unused |
| 6 | IM | 1 | R/W | Channel 0 interrupt mask |
| 5:3 | CMP[2 : 0] | 000 | R/W | Channel 0 compare output mode select. Specified action on output when timer value equals compare value in T4CC0 000 Set output on compare 001 Clear output on compare 010 Toggle output on compare 011 Set output on compare-up, clear on 0 (clear on compare-down in up/down mode) 100 Clear output on compare-up, set on 0 (set on compare-down in up/down mode) 101 Set output on compare, clear on 0x00 110 Clear output on compare, set on 0x00 111 Not used |
| 2 | MODE | 0 | R/W | Mode. Select Timer 4 channel 0 compare mode 0 Compare disabled 1 Compare enabled |
| 1:0 | – | 00 | R/W | Reserved. Set to 00 |

T4CC0 (0xED) – Timer 4 Channel 0 Compare Value

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|-------------------------------|
| 7:0 | VAL[7 : 0] | 0x00 | R/W | Timer compare value channel 0 |

T4CCTL1 (0xEE) – Timer 4 Channel 1 Compare Control

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | – | 0 | R0 | Unused |
| 6 | IM | 1 | R/W | Channel 1 interrupt mask |
| 5:3 | CMP[2 : 0] | 000 | R/W | Channel 1 compare output mode select. Specified action on output when timer value equals compare value in T4CC1. 000 Set output on compare 001 Clear output on compare 010 Toggle output on compare 011 Set output on compare-up, clear on 0 (clear on compare-down in up/down mode) 100 Clear output on compare-up, set on 0 (set on compare-down in up/down mode) 101 Set output on compare, clear on T4CC0 110 Clear output on compare, set on T4CC0 111 Not used |
| 2 | MODE | 0 | R/W | Mode. Select Timer 4 channel 1 compare mode 0 Compare disabled 1 Compare enabled |
| 1:0 | – | 00 | R/W | Reserved. Set to 00. |

T4CC1 (0xEF) – Timer 4 Channel 1 Compare Value

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|-------------------------------|
| 7:0 | VAL[7 : 0] | 0x00 | R/W | Timer compare value channel 1 |

TIMIF (0xD8) – Timers 1/3/4 Interrupt Mask/Flag

| Bit | Name | Reset | R/W | Description |
|-----|---------|-------|------|---------------------------------------------------------------------------------------------|
| 7 | – | 0 | R0 | Unused |
| 6 | OVFIM | 1 | R/W | Timer 1 overflow interrupt mask |
| 5 | T4CH1IF | 0 | R/W0 | Timer 4 channel 1 interrupt flag 0 : no interrupt is pending 1 : interrupt is pending |
| 4 | T4CH0IF | 0 | R/W0 | Timer 4 channel 0 interrupt flag 0 : no interrupt is pending 1 : interrupt is pending |
| 3 | T4OVFIF | 0 | R/W0 | Timer 4 overflow interrupt flag 0 : no interrupt is pending 1 : interrupt is pending |
| 2 | T3CH1IF | 0 | R/W0 | Timer 3 channel 1 interrupt flag 0 : no interrupt is pending 1 : interrupt is pending |
| 1 | T3CH0IF | 0 | R/W0 | Timer 3 channel 0 interrupt flag 0 : no interrupt is pending 1 : interrupt is pending |
| 0 | T3OVFIF | 0 | R/W0 | Timer 3 overflow interrupt flag 0 : no interrupt is pending 1 : interrupt is pending |

13.7 ADC

13.7.1 ADC Introduction

The ADC supports up to 14-bit analog-to-digital conversion. The ADC includes an analog multiplexer with up to eight individually configurable channels, reference voltage generator and conversion results written to memory through DMA. Several modes of operation are available.

The main features of the ADC are as follows:

- Selectable decimation rates which also sets the resolution (8 to 14 bits).

- Eight individual input channels, single-ended or differential
- Reference voltage selectable as internal, external single ended, external differential or AVDD_SOC.
- Interrupt request generation
- DMA triggers at end of conversions
- Temperature sensor input
- Battery measurement capability




Figure 26: ADC block diagram.

13.7.2 ADC Operation

This section describes the general setup and operation of the ADC and describes the usage of the ADC control and status registers accessed by the CPU.

13.7.2.1 ADC Core

The ADC includes an ADC capable of converting an analog input into a digital representation with up to 14 bits resolution. The ADC uses a selectable positive reference voltage.

13.7.2.2 ADC Inputs

The signals on the P0 port pins can be used as ADC inputs. In the following these

port pin will be referred to as the AIN0-AIN7 pins. The input pins AIN0-AIN7 are connected to the ADC. The ADC can be set up to automatically perform a sequence of conversions and optionally perform an extra conversion from any channel when the sequence is completed.

It is possible to configure the inputs as single-ended or differential inputs. In the case where differential inputs are selected, the differential inputs consist of the input pairs AIN0-1, AIN2-3, AIN4-5 and AIN6-7.

In addition to the input pins AIN0-AIN7, the output of an on-chip temperature sensor can be selected as an input to the ADC for temperature measurements.

It is also possible to select a voltage corresponding to AVDD_SOC/3 as an ADC input. This input allows the implementation of e.g. a battery monitor in applications where this feature is required.

13.7.2.3 ADC conversion sequences

The ADC can perform a sequence of conversions, and move the results to memory (through DMA) without any interaction from the CPU.

The ADCCON2.SCH register bits are used to define an ADC conversion sequence, from the ADC inputs. A conversion sequence will contain a conversion from each channel from 0 up to and including the channel number programmed in ADCCON2.SCH when ADCCON2.SCH is set to a value less than 8.

The single-ended inputs AIN0 to AIN7 are represented by channel numbers 0 to 7 in ADCCON2.SCH. Channel numbers 8 to 11 represent the differential inputs consisting of AIN0-AIN1, AIN2-AIN3, AIN4-AIN5 and AIN6-AIN7. Channel numbers 12 to 15 represent GND, internal voltage reference, temperature sensor and AVDD_SOC/3, respectively.

When ADCCON2.SCH is set to a value between 8 and 12, the sequence will start at channel 8. For even higher settings, only single conversions are performed. In addition to this sequence of conversions, the ADC can be programmed to perform a single conversion from any channel as soon as the sequence has completed. This is called an extra conversion and is controlled with the ADCCON3 register.

The conversion sequence can also be influenced with the ADCCFG register (see section 13.1.5 on page 74). The eight analog inputs to the ADC comes from IO pins, which are not necessarily programmed to be analog inputs. If a channel should normally be part of a sequence, but the corresponding analog input is disabled in the ADCCFG, then that channel will be skipped. For channels 8 to 12, both input pins must be enabled.

13.7.2.4 ADC Operating Modes

This section describes the operating modes and initialization of conversions.

The ADC has three control registers: ADCCON1, ADCCON2 and ADCCON3.

These registers are used to configure the ADC and to report status.

The ADCCON1.EOC bit is a status bit that is set high when a conversion ends and cleared when ADCH is read.

The ADCCON1.ST bit is used to start a sequence of conversions. A sequence will start when this bit is set high, ADCCON1.STSEL is 11 and no conversion is currently running. When the sequence is completed, this bit is automatically cleared.

The ADCCON1.STSEL bits select which event that will start a new sequence of conversions. The options which can be selected are rising edge on external pin P2_0, end of previous sequence, a Timer 1 channel 0 compare event or ADCCON1.ST is 1.

The ADCCON2 register controls how the sequence of conversions is performed.

ADCCON2.SREF is used to select the reference voltage. The reference voltage should only be changed when no conversion is running.

The ADCCON2.SDIV bits select the decimation rate (and thereby also the resolution and time required to complete a conversion and sample rate). The decimation rate should only be changed when no conversion is running.

The last channel of a sequence is selected with the ADCCON2.SCH bits.

The ADCCON3 register controls the channel number, reference voltage and decimation rate for the extra conversion. The extra conversion will take place immediately after the ADCCON3 register is updated. The coding of the register bits is exactly as for ADCCON2.

13.7.2.5 ADC Conversion Results

The digital conversion result is represented in two's complement form. For 14-bit resolution the digital conversion result is 8191 when the analog input is equal to the VREF, and the conversion result is -8192 when the analog input is equal to -VREF, where VREF is the selected positive voltage reference.

The digital conversion result is available when ADCCON1.EOC is set to 1, in ADCH and ADCL.

When the `ADCCON2.SCH` bits are read, they will indicate the channel above the channel which the conversion result in `ADCL` and `ADCH` apply to. E.g. reading the value 0x1 from `ADCCON2.SCH`, means that the available conversion result is from input `AIN0`.

13.7.2.6 ADC Reference Voltage

The positive reference voltage for analog-to-digital conversions is selectable as either an internally generated 1.25V voltage, the `AVDD_SOC` pin, an external voltage applied to the `AIN7` input pin or a differential voltage applied to the `AIN6`-`AIN7` inputs.

It is possible to select the reference voltage as the input to the ADC in order to perform a conversion of the reference voltage e.g. for calibration purposes. Similarly, it is possible to select the ground terminal GND as an input.

13.7.2.7 ADC Conversion Timing

The ADC runs on the 32 MHz system clock, which is divided by 8 to give a 4 MHz clock. Both the delta sigma modulator and decimation filter use the 4 MHz clock for their calculations.

The time required to perform a conversion depends on the selected decimation rate. When the decimation rate is set to for instance 128, the decimation filter uses exactly 128 of the 4 MHz clock periods to

calculate the result. When a conversion is started, the input multiplexer is allowed 16 4 MHz clock cycles to settle in case the channel has been changed since the previous conversion. The 16 clock cycles settling time applies to all decimation rates. Thus in general, the conversion time is given by:

$$T_{\text{conv}} = (\text{decimation rate} + 16) \times 0.25 \mu\text{s}.$$

13.7.2.8 ADC Interrupts

The ADC will generate an interrupt when an extra conversion has completed. An interrupt is not generated when a conversion from the sequence is completed.

13.7.2.9 ADC DMA Triggers

The ADC will generate a DMA trigger every time a conversion from the sequence has completed. When an extra conversion completes, no DMA trigger is generated.

There is one DMA trigger for each of the eight channels defined by the first eight possible settings for `ADCCON2.SCH`. The DMA trigger is active when a new sample is ready from the conversion for the channel. The DMA triggers are named `ADC_CHx` in Table 37 on page 87.

In addition there is one DMA trigger, `ADC_CHALL`, which is active when new data is ready from any of the channels in the ADC conversion sequence.

13.7.2.10 ADC Registers

This section describes the ADC registers.

ADCL (0xBA) – ADC Data Low

| Bit | Name | Reset | R/W | Description |
|-----|-----------------------|-------|-----|--------------------------------------------------|
| 7:2 | <code>ADC[5:0]</code> | 0x00 | R | Least significant part of ADC conversion result. |
| 1:0 | - | 00 | R0 | Not used. Always read as 0 |

ADCH (0xBB) – ADC Data High

| Bit | Name | Reset | R/W | Description |
|-----|-----------|-------|-----|-------------------------------------------------|
| 7:0 | ADC[13:6] | 0x00 | R | Most significant part of ADC conversion result. |

ADCCON1 (0xB4) – ADC Control 1

| Bit | Name | Reset | R/W | Description |
|-----|------------|-------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | EOC | 0 | R H0 | End of conversion Cleared when both ADCH and ADCL has been read. If a new conversion is completed before the previous data has been read, the EOC bit will remain high. 0 conversion not complete 1 conversion completed |
| 6 | ST | 0 | R/W1 | Start conversion. Read as 1 until conversion has completed 0 no conversion in progress 1 start a conversion sequence if ADCCON1.STSEL = 11 and no sequence is running. |
| 5:4 | STSEL[1:0] | 11 | R/W | Start select. Selects which event that will start a new conversion sequence. 00 External trigger on P2_0 pin. 01 Full speed. Do not wait for triggers. 10 Timer 1 channel 0 compare event 11 ADCCON1.ST = 1 |
| 3:2 | RCTRL[1:0] | 00 | R/W | Controls the 16 bit random number generator. When written 01, the setting will automatically return to 00 when operation has completed. 00 Normal operation. (13x unrolling) 01 Clock the LFSR once (no unrolling). 10 Reserved 11 Stopped. Random number generator is turned off. |
| 1:0 | - | 11 | R/W | Reserved. Always set to 11. |

ADCCON2 (0xB5) – ADC Control 2

| Bit | Name | Reset | R/W | Description |
|-----|-----------|-------|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:6 | SREF[1:0] | 00 | R/W | Selects reference voltage used for the sequence of conversions 00 Internal 1.25V reference 01 External reference on AIN7 pin 10 AVDD_SOC pin 11 External reference on AIN6-AIN7 differential input |
| 5:4 | SDIV[1:0] | 01 | R/W | Sets the decimation rate for channels included in the sequence of conversions. The decimation rate also determines the resolution and time required to complete a conversion. 00 64 decimation rate (8 bits resolution) 01 128 decimation rate (10 bits resolution) 10 256 decimation rate (12 bits resolution) 11 512 decimation rate (14 bits resolution) |
| 3:0 | SCH[3:0] | 0000 | R/W | Sequence Channel Select. Selects the end of the sequence. A sequence can either be from AIN0 to AIN7 (SCH<=7) or from the differential input AIN0-AIN1 to AIN6-AIN7 (8<=SCH<=11). For other settings, only single conversions are performed. When read, these bits will indicate the channel number plus one of current conversion result. 0000 AIN0 0001 AIN1 0010 AIN2 0011 AIN3 0100 AIN4 0101 AIN5 0110 AIN6 0111 AIN7 1000 AIN0-AIN1 1001 AIN2-AIN3 1010 AIN4-AIN5 1011 AIN6-AIN7 1100 GND 1101 Positive voltage reference 1110 Temperature sensor 1111 VDD/3 |

ADCCON3 (0xB6) – ADC Control 3

| Bit | Name | Reset | R/W | Description |
|-----|-----------|-------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:6 | EREF[1:0] | 00 | R/W | Selects reference voltage used for the extra conversion 00 Internal 1.25V reference 01 External reference on AIN7 pin 10 AVDD_SOC pin 11 External reference on AIN6-AIN7 differential input |
| 5:4 | EDIV[1:0] | 00 | R/W | Sets the decimation rate used for the extra conversion. The decimation rate also determines the resolution and time required to complete the conversion. 00 64 dec rate (8 bits resolution) 01 128 dec rate (10 bits resolution) 10 256 dec rate (12 bits resolution) 11 512 dec rate (14 bits resolution) |
| 3:0 | ECH[3:0] | 0000 | R/W | Extra channel select. Selects the channel number of the extra conversion that is carried out after a conversion sequence has ended. This bit field must be written for an extra conversion to be performed. If the ADC is not running, writing to these bits will trigger an immediate single conversion from the selected extra channel. The bits are automatically cleared when the extra conversion has finished. 0000 AIN0 0001 AIN1 0010 AIN2 0011 AIN3 0100 AIN4 0101 AIN5 0110 AIN6 0111 AIN7 1000 AIN0-AIN1 1001 AIN2-AIN3 1010 AIN4-AIN5 1011 AIN6-AIN7 1100 GND 1101 Positive voltage reference 1110 Temperature sensor 1111 VDD/3 |

13.8 Random Number Generator

13.8.1 Introduction

The random number generator has the following features.

- Generate pseudo-random bytes which can be read by the CPU or used directly by the Command Strobe Processor.
- Calculate CRC16 of bytes that are written to RNDH.

- Seeded by value written to RNDL.

The random number generator is a 16-bit Linear Feedback Shift Register (LFSR) with polynomial $X^{16} + X^{15} + X^2 + 1$ (i.e. CRC16). It uses different levels of unrolling depending on the operation it performs. The basic version (no unrolling) is shown below.




Figure 27: Basic structure of the Random Number Generator

The random number generator is turned off when `ADCCON1.RCTRL = 11..`

13.8.2 Random Number Generator Operation

The operation of the random number generator is controlled through a combination of the `ADCCON1.RCTRL` bits and input signals from other modules. The current value of the 16-bit shift register in the LFSR can be read from the `RNDH` and `RNDL` registers.

13.8.2.1 Semi random sequence generation

The default operation (`ADCCON1.RCTRL` is 00) is to clock the LFSR once (13x unrolling) each time the Command Strobe Processor reads the random value. This leads to the availability of a fresh pseudo-random byte from the LSB end of the LFSR.

Another way to update the LFSR is to set `ADCCON1.RCTRL` is 01. This will clock the LFSR once (no unrolling) and the `ADCCON1.RCTRL` bits will automatically be cleared when the operation has completed.

13.8.2.2 Seeding

The LFSR can be seeded by writing to the `RNDL` register twice. Each time the `RNDL` register is written, the 8 LSB of the LFSR is copied to the 8 MSB and the 8 LSBs are replaced with the new data byte that was written to `RNDL`.

When a true random value is required, the LFSR can be seeded by writing `RNDL` with random values from the ADC in the RF receive path. To use this seeding method, the radio must first be powered on by enabling the voltage regulator as described in section 16.1. The radio should be placed in infinite TX state, to avoid possible sync detect in RX state. The random values from the ADC are read from the RF registers `ADCTSTH` and `ADCTSTL` (see page 212). The values read are used as the seed values to be written to the `RNDL` register as described above.

13.8.2.3 CRC16

The LFSR can also be used to calculate the CRC value of a sequence of bytes. Writing to the `RNDH` register will trigger a CRC calculation. The new byte is processed from the MSB end and an 8x unrolling is used, so that a new byte can be written to `RNDH` every clock cycle.

Note that the LFSR must be properly seeded by writing to `RNDL`, before the CRC calculations start. Usually the seed value should be 0x0000 or 0xFFFF.

13.8.3 Random Number Generator Registers

This section describes the Random Number Generator registers.

RNDL (0xBC) – Random Number Generator Data Low Byte

| Bit | Name | Reset | R/W | Description |
|-------|----------------|-------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [7:0] | RNDL [7 : 0] | 0xFF | R/W | <p>Random value/seed or CRC result, low byte</p> <p>When used for random number generation writing this register twice will seed the random number generator. Writing to this register copies the 8 LSBs of the LFSR to the 8 MSBs and replaces the 8 LSBs with the data value written.</p> <p>The value returned when reading from this register is the 8 LSBs of the LSFR.</p> <p>When used for random number generation, reading this register returns the 8 LSBs of the random number. When used for CRC calculations, reading this register returns the 8 LSBs of the CRC result.</p> |

RNDH (0xBD) – Random Number Generator Data High Byte

| Bit | Name | Reset | R/W | Description |
|-------|----------------|-------|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [7:0] | RNDH [7 : 0] | 0xFF | R/W | <p>Random value or CRC result/input data, high byte</p> <p>When written, a CRC16 calculation will be triggered, and the data value written is processed starting with the MSB bit.</p> <p>The value returned when reading from this register is the 8 MSBs of the LSFR.</p> <p>When used for random number generation, reading this register returns the 8 MSBs of the random number. When used for CRC calculations, reading this register returns the 8 MSBs of the CRC result.</p> |

13.9 AES Coprocessor

The **CC2430** data encryption is performed using a dedicated coprocessor which supports the Advanced Encryption Standard, AES. The coprocessor allows encryption/decryption to be performed with minimal CPU usage.

The coprocessor has the following features:

- Supports all security suites in IEEE 802.15.4
- ECB, CBC, CFB, OFB, CTR and CBC-MAC modes.
- Hardware support for CCM mode
- 128-bits key and IV/Nonce
- DMA transfer trigger capability

13.9.1 AES Operation

To encrypt a message, the following procedure must be followed:

- Load key
- Load initialization vector (IV)
- Download and upload data for encryption/decryption.

The AES coprocessor works on blocks of 128 bits. A block of data is loaded into the coprocessor, encryption is performed and the result must be read out before the next block can be processed. Before each block load, a dedicated start command must be sent to the coprocessor.

13.9.2 Key and IV

Before a key or IV/nonce load starts, an appropriate load key or IV/nonce command must be issued to the coprocessor. When loading the IV it is important to also set the correct mode.

A key load or IV load operation aborts any processing that could be running.

The key, once loaded, stays valid until a key reload takes place.

The IV must be downloaded before the beginning of each message (not block).

Both key and IV values are cleared by a reset of the **CC2430**.

13.9.3 Padding of input data

The AES coprocessor works on blocks of 128 bits. If the last block contains less than 128 bits, it must be padded with zeros when written to the coprocessor.

13.9.4 Interface to CPU

The CPU communicates with the coprocessor using three SFR registers:

- **ENCCS**, Encryption control and status register
- **ENCDI**, Encryption input register
- **ENCDO**, Encryption output register

Read/write to the status register is done directly by the CPU, while access to the input/output registers must be performed using direct memory access (DMA).

Two DMA channels must be used, one for input data and one for output data. The DMA channels must be initialized before a start command is written to the **ENCCS**. Writing a start command generates a DMA trigger and the transfer is started. After each block is processed, an interrupt is generated. The interrupt is used to issue a new start command to the **ENCCS**.

13.9.5 Modes of operation

ECB and CBC modes are performed as described in section 13.9.1

When using CFB, OFB and CTR mode, the 128 bits blocks are divided into four 32 bit blocks. 32 bits are loaded into the AES coprocessor and the resulting 32 bits are read out. This continues until all 128 bits have been encrypted. The only time one has to consider this is if data is loaded/read directly using the CPU. When using DMA, this is handled automatically by the DMA triggers generated by the AES coprocessor.

Both encryption and decryption are performed similarly.

The CBC-MAC mode is a variant of the CBC mode. When performing CBC-MAC, data is downloaded to the coprocessor one 128 bits block at a time, except for the last block. Before the last block is loaded, the mode must be changed to CBC. The

last block is then downloaded and the block uploaded will be the MAC value.

CCM is a combination of CBC-MAC and CTR. Parts of the CCM must therefore be done in software. The following section gives a short explanation of the necessary steps to be done.

13.9.5.1 CBC-MAC

When performing CBC-MAC encryption, data is downloaded to the coprocessor in CBC-MAC mode one block at a time, except for the last block. Before the last block is loaded, the mode is changed to CBC. The last block is downloaded and the block uploaded is the message MAC.

CBC-MAC decryption is similar to encryption. The message MAC uploaded

must be compared with the MAC to be verified.

13.9.5.2 CCM mode

To encrypt a message under CCM mode, the following sequence can be conducted (key is already loaded):

Message Authentication Phase

This phase takes place during steps 1-6 shown in the following.

- (1) The software loads the IV with zeros.
- (2) The software creates the block B0. The layout of block B0 is shown in Figure 28.

| | Name B0 | | | | | Designation First block for authentication in CCM mode | | | | | | | | | | |
|------|------------|-------|---|---|---|-----------------------------------------------------------|---|---|---|-----|----|----|----|----|----|----|
| Byte | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
| Name | Flag | NONCE | | | | | | | | L_M | | | | | | |

Figure 28: Message Authentication Phase Block 0

There is no restriction on the NONCE value. L_M is the message length in bytes.

For 802.15.4 the NONCE is 13 bytes and L_M is 2 bytes.

The content of the Authentication Flag byte is described in Figure 29.

L is set to 6 in this example. So, L-1 is set to 5. M and A_Data can be set to any value.

| | Name FLAG/B0 | | Designation Authentication Flag Field for CCM mode | | | | | |
|-------|-----------------|--------|-------------------------------------------------------|---|---|-----|---|---|
| Bit | 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
| Name | Reserved | A_Data | (M-2)/2 | | | L-1 | | |
| Value | 0 | x | x | x | x | 1 | 0 | 1 |

Figure 29: Authentication Flag Byte

(3) If some Additional Authentication Data (denoted a below) is needed (that is A_Data =1), the software creates the A_Data length field, called L(a) by :

- (3a) If l(a)=0, (that is A_Data =0), then L(a) is the empty string. We note l(a) the length of a in octets.

- **(3b)** If $0 < l(a) < 2^{16} - 2^8$, then $L(a)$ is the 2-octets encoding of $l(a)$.

The Additional Authentication Data is appended to the A_Data length field $L(a)$. The Additional Authentication Blocks is padded with zeros until the last Additional Authentication Block is full. There is no restriction on the length of a .

$AUTH-DATA = L(a) + \text{Authentication Data} + (\text{zero padding})$

(4) The last block of the message is padded with zeros until full (that is if its length is not a multiple of 128).

(5) The software concatenates the block $B0$, the Additional Authentication Blocks if any, and the message;

$\text{Input message} = B0 + AUTH-DATA + \text{Message} + (\text{zero padding of message})$

(6) Once the input message authentication by CBC-MAC is finished, the software leaves the uploaded buffer contents unchanged ($M=16$), or keeps only the buffer's higher M bytes unchanged, while setting the lower bits to 0 ($M \neq 16$).

The result is called T .

Message Encryption

(7) The software creates the key stream block $A0$. Note that $L=6$, with the current example of the CTR generation. The content is shown in Figure 30.

Note that any value but zero works for the CTR value.

The content of the Encryption Flag byte is described in Figure 31.

| | Name A0 | | | | | Designation First CTR value for CCM mode | | | | | | | | | | |
|------|------------|-------|---|---|---|---------------------------------------------|---|---|---|---|----|----|-----|----|----|----|
| Byte | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
| Name | Flag | NONCE | | | | | | | | | | | CTR | | | |

Figure 30: Message Encryption Phase Block 0

| | Name FLAG/A0 | | Designation Encryption Flag Field for CCM mode | | | | | |
|-------|-----------------|---|---------------------------------------------------|---|---|-----|---|---|
| Bit | 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
| Name | Reserved | | - | | | L-1 | | |
| Value | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 1 |

Figure 31: Encryption Flag Byte

Message Encryption (cont.)

(8) The software loads $A0$ by selecting a Load IV/Nonce command. To do so, it sets Mode to CFB or OFB at the same time it selects the Load IV/Nonce command.

(9) The software calls a CFB or an OFB encryption on the authenticated data T .

The uploaded buffer contents stay unchanged ($M=16$), or only its first M bytes stay unchanged, the others being set to 0 ($M-16$). The result is U , which will be used later.

(10) The software calls a CTR mode encryption right now on the still padded

message blocks. It does not have to reload the IV/CTR.

(11) The encrypted authentication data U is appended to the encrypted message. This gives the final result, c.

Result c = encrypted message(m) + U

Message Decryption

CCM Mode decryption

In the coprocessor, the automatic generation of CTR works on 32 bits, therefore the maximum length of a message is 128×2^{32} bits, that is 2^{36} bytes, which can be written in a six-bit word. So, the value L is set to 6. To decrypt a CCM mode processed message, the following sequence can be conducted (key is already loaded):

Message Parsing Phase

(1) The software parses the message by separating the M rightmost octets, namely U, and the other octets, namely string C.

(2) C is padded with zeros until it can fill an integer number of 128-bit blocks;

(3) U is padded with zeros until it can fill a 128-bit block.

(4) The software creates the key stream block A0. It is done the same way as for CCM encryption.

(5) The software loads A0 by selecting a Load IV/Nonce command. To do so, it sets Mode to CFB or OFB at the same time as it selects the IV load.

(6) The software calls a CFB or an OFB encryption on the encrypted authenticated data U. The uploaded buffer contents stay unchanged (M=16), or only its first M bytes stay unchanged, the others being set to 0 (M!=16). The result is T.

(7) The software calls a CTR mode decryption right now on the encrypted message blocks C. It does not have to reload the IV/CTR.

Reference Authentication tag generation

This phase is identical to the Authentication Phase of CCM encryption. The only difference is that the result is named MACTag (instead of T).

Message Authentication checking Phase

The software compares T with MACTag.

13.9.6 Sharing the AES coprocessor between layers

The AES coprocessor is a common resource shared by all layers. The AES coprocessor can only be used by one instance one at a time. It is therefore necessary to implement some kind of software semaphore to allocate and de-allocate the resource.

13.9.7 AES Interrupts

The AES interrupt, ENC, is produced when encryption or decryption of a block is completed. The interrupt enable bit is `IEN0.ENCIE` and the interrupt flag is `S0CON.ENCIF`.

13.9.8 AES DMA Triggers

There are two DMA triggers associated with the AES coprocessor. These are `ENC_DW` which is active when input data needs to be downloaded to the `ENCDI` register, and `ENC_UP` which is active when output data needs to be uploaded from the `ENCDO` register.

The `ENCDI` and `ENCDO` registers should be set as destination and source locations for DMA channels used to transfer data to or from the AES coprocessor.

13.9.9 AES Registers

The AES coprocessor registers have the layout shown in this section.

ENCCS (0xB3) – Encryption Control and Status

| Bit | Name | Reset | R/W | Description |
|-----|-----------|-------|------------|----------------------------------------------------------------------------------------------------------------------------------|
| 7 | – | 0 | R0 | Not used, always read as 0 |
| 6:4 | MODE[2:0] | 000 | R/W | Encryption/decryption mode 000 CBC 001 CFB 010 OFB 011 CTR 100 ECB 101 CBC MAC 110 Not used 111 Not used |
| 3 | RDY | 1 | R | Encryption/decryption ready status 0 Encryption/decryption in progress 1 Encryption/decryption is completed |
| 2:1 | CMD[1:0] | 0 | R/W | Command to be performed when a 1 is written to ST. 00 encrypt block 01 decrypt block 10 load key 11 load IV/nonce |
| 0 | ST | 0 | R/W1 H0 | Start processing command set by CMD. Must be issued for each command or 128 bits block of data. Cleared by hardware |

ENC DI (0xB1) – Encryption Input Data

| Bit | Name | Reset | R/W | Description |
|-----|----------|-------|-----|-----------------------|
| 7:0 | DIN[7:0] | 0x00 | R/W | Encryption input data |

ENC DO (0xB2) – Encryption Output Data

| Bit | Name | Reset | R/W | Description |
|-----|----------|-------|-----|------------------------|
| 7:0 | DOU[7:0] | 0x00 | R/W | Encryption output data |

13.10 Power Management

This section describes the Power Management Controller. The Power Management Controller controls the use of power modes and clock control to achieve low-power operation.

13.10.1 Power Management Introduction

The **CC2430** uses different operating modes, or power modes, to allow low-power operation. Ultra-low-power operation is obtained by turning off power supply to modules to avoid static (leakage) power consumption and also by using clock gating and turning off oscillators to reduce dynamic power consumption.

The various operating modes are enumerated and are designated as power modes (PMx). The power modes are:

- PM0
Clock oscillators on, voltage regulator on
- PM1
32.768 kHz oscillators on, voltage regulator on
- PM2
32.768 kHz oscillators on, voltage regulator off
- PM3
All clock oscillators off, voltage regulator off

Note: the voltage regulator above refers to the digital regulator. The analog voltage regulator must be disabled separately through the RF register RFPWR.

13.10.1.1 PM0

PM0 is the full functional mode of operation where the CPU, peripherals and RF transceiver are active. The voltage regulator is turned on.

PM0 is used for normal operation.

13.10.1.2 PM1

In PM1, the high-frequency oscillators are powered down. The voltage regulator and the 32.768 kHz oscillators are on. When PM1 is entered, a power down sequence is run. When the device is taken out of PM1 to PM0, the high-frequency oscillators are started. The device will run

on the high frequency RC oscillator until the high frequency crystal oscillator has settled and been selected.

PM1 is used when the expected time until a wakeup event is relatively short since PM1 uses a fast power down/up sequence.

13.10.1.3 PM2

PM2 has the second lowest power consumption. In PM2 the power-on reset, external interrupts, 32.768 kHz oscillator and sleep timer peripherals are active. I/O pins retain the I/O mode and output value set before entering PM2. All other internal circuits are powered down. The voltage regulator is also turned off. When PM2 is entered, a power down sequence is run.

PM2 is used when it is relatively long until the expected time for wakeup event, since the power up/down sequence is relatively long. PM2 is typically entered when using the sleep timer as the wakeup event.

13.10.1.4 PM3

PM3 is used to achieve the operating mode with the lowest power consumption. In PM3 all internal circuits that are powered from the voltage regulator are turned off. The internal voltage regulator and all oscillators are also turned off.

Power-on reset and external I/O port interrupts are the only functions that are operating in this mode. I/O pins retain the I/O mode and output value set before entering PM3. Only a reset or external interrupt condition will wake the device up and place it into PM0. The contents of RAM and registers is partially preserved in this mode (see section 13.10.7). PM3 uses the same power down/up sequence as PM2.

PM3 is used to achieve ultra low power consumption when waiting for an external event.

13.10.2 Power Management Control

The required power mode is selected by the **MODE** bits in the **SLEEP** control register. Setting the **SFR** register **PCON.IDLE** bit after setting the **MODE** bits, enters the selected sleep mode.

An enabled interrupt from port pins or sleep timer or a power-on reset will wake the device from other power modes and

bring it into PM0 by resetting the `MODE` bits.




Figure 32: Clock System Overview

13.10.3 High-frequency oscillators

Figure 32 gives an overview of the clock system with available clock sources.

Two high frequency oscillators are present in the device:

- High-frequency (32 MHz) crystal oscillator.
- High-frequency (16 MHz) RC oscillator.
-

The high-frequency crystal oscillator startup time may be too long for some applications, therefore the device can run on the high-frequency RC oscillator until crystal oscillator is stable. The high-frequency RC oscillator consumes less power than the crystal oscillator, but since it is not as accurate as the crystal oscillator it can not be used for RF transceiver operation.

13.10.4 System clock

The system clock is derived from the selected system clock source, which is the high-frequency (32 MHz) crystal oscillator or the high-frequency (16 MHz) RC

oscillator. The `CLKCON.OSC` bit selects the source of the system clock. Note that to use the RF transceiver the high frequency crystal oscillator must be selected and stable.

Note that each time the `CLKCON.OSC` bit is altered, then the `CLKCON.CLKSPD` bit must also be altered in order for the system to know the frequency of the system clock.

When the `SLEEP.XOSC_STB` is 1, the 32 MHz crystal oscillator is stable and can be used as the source for the system clock.

The oscillator not selected as the system clock source, will be set in power-down mode by setting `SLEEP.OSC_PD` to 1. Thus the high-frequency RC oscillator may be turned off when the high-frequency crystal oscillator has been selected as system clock source and vice versa. When `SLEEP.OSC_PD` is 0, both oscillators are powered up and running.

When the high-frequency crystal oscillator is selected as system clock source and the high-frequency RC oscillator is also powered up, the high-frequency RC oscillator will be continuously calibrated to ensure clock stability over supply voltage and operating temperature. This calibration is not performed when the high-frequency RC oscillator itself is chosen as system clock source.

13.10.5 32.768 kHz oscillators

Two 32.768 kHz oscillators are present in the device as clock sources for the 32 kHz clock:

- 32.768 kHz crystal oscillator
- 32 kHz RC oscillator

By default, after a reset, the 32 kHz RC oscillator is enabled and selected as the 32 kHz clock source. The RC oscillator consumes less power, but is less accurate than the 32.768 kHz crystal oscillator. Refer to Table 9 and Table 10 on page 16 for characteristics of these oscillators. The 32.768 kHz clock runs the Sleep Timer and Watchdog Timer. The selection of which oscillator source to use for this clock is performed with the `CLKCON.OSC32K` register bit.

The `CLKCON.OSC32K` register bit must only be changed while using the high-frequency RC oscillator as the system

clock source. When the high frequency crystal oscillator is selected and it is stable, i.e. `SLEEP.XOSC_STB` is 1, calibration of the 32. kHz RC oscillator is continuously performed. This calibration is not performed in other power modes than PM0.

The 32. kHz RC oscillator calibration may take up to 2 ms to complete. When entering low power modes PM1 or PM2 an ongoing calibration must be completed before the low power mode is entered. In some applications this extra delay may be unacceptable and therefore the calibration may be disabled¹³ by setting register bit `SLEEP.OSC32K_CALDIS` to 1. Note that any ongoing calibration will be completed when a 1 is written to `SLEEP.OSC32K_CALDIS`.

13.10.6 Timer Tick generation

The power management controller generates a tick or enable signal for the peripheral timers, thus acting as a prescaler for the timers. This is a global clock division for Timer 1, Timer 3 and Timer 4. The tick speed is programmed from 0.25 MHz to 32 MHz in the `CLKCON.TICKSPD` register.

13.10.7 Data Retention

In power modes PM2 and PM3, power is removed from most of the internal circuitry. However parts of SRAM will retain its contents. The content of internal registers is also retained in PM2 and PM3.

The XDATA memory locations 0xF000-0xFFFF (4096 bytes) retains data in PM2 and PM3. Please note the exception as given below.

The XDATA memory locations 0xE000-0xEFFF (4096 bytes) and the area 0xFD56-0xFEFF (426 bytes) will lose all data when PM2 or PM3 is entered. These locations will contain undefined data when PM0 is re-entered.

The registers which retain their contents are the CPU registers, peripheral registers and RF registers, unless otherwise is specified for a given register bit field. Therefore switching to the low-power

¹³ Only for devices with Chip Version register, `CHVER.VERSION` equal to 0x02 or greater

modes PM2 or PM3 appears transparent to software with the following exceptions:

- The RF TXFIFO/RXFIFO contents is not retained when entering PM2 or PM3.
- Watchdog timer 15-bit counter is reset to 0x0000 when entering PM2 or PM3.

13.10.8 Power Management Registers

This section describes the Power Management registers. All register bits retain their previous values when entering PM2 or PM3 unless otherwise stated..

PCON (0x87) – Power Mode Control

| Bit | Name | Reset | R/W | Description |
|-----|------|-------|------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:2 | – | 0x00 | R/W | Not used. |
| 1 | – | 0 | R0 | Not used, always read as 0. |
| 0 | IDLE | 0 | R0/W H0 | Power mode control. Writing a 1 to this bit forces CC2430 to enter the power mode set by <i>SLEEP . MODE</i> . This bit is always read as 0 Disable all interrupts before writing a 1 to this bit. If interrupts are enabled when setting this bit to 1, an active interrupt will prevent entry into the requested power mode and the CC2430 will remain in PM0. |

SLEEP (0xBE) – Sleep Mode Control

| Bit | Name | Reset | R/W | Description |
|-----|---------------|-------|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | OSC32K_CALDIS | 0 | R/W | Disable 32 kHz RC oscillator calibration ¹⁴ 0 – 32 kHz RC oscillator calibration is enabled 1 – 32 kHz RC oscillator calibration is disabled. The setting of this bit to 1 does not take effect until high-frequency RC oscillator is chosen as source for system clock, i.e. CLKCON.OSC set to 1. Note: this bit is not retained in PM2 and PM3. After re-entry to PM0 from PM2 or PM3 this bit will be at the reset value 0 |
| 6 | XOSC_STB | 0 | R | XOSC stable status: 0 – XOSC is not powered up or not yet stable 1 – XOSC is powered up and stable |
| 5 | HFRC_STB | 0 | R | High-frequency RC oscillator (HF RCOSC) stable status: 0 – HF RCOSC is not powered up or not yet stable 1 – HF RCOSC is powered up and stable |
| 4:3 | RST[1:0] | XX | R | Status bit indicating the cause of the last reset. If there are multiple resets, the register will only contain the last event. 00 – Power-on reset 01 – External reset 10 – Watchdog timer reset |
| 2 | OSC_PD | 1 | R/W H0 | High-frequency (32 MHz) crystal oscillator and High-frequency (16 MHz) RC oscillator power down setting.. If there is a calibration in progress and the CPU attempts to set this bit, the bit will be updated at the end of calibration: 0 – Both oscillators powered up 1 – Oscillator not selected by CLKCON.OSC bit powered down |
| 1:0 | MODE[1:0] | 00 | R/W | Power mode setting: 00 – Power mode 0 01 – Power mode 1 10 – Power mode 2 11 – Power mode 3 |

¹⁴ Only for devices with Chip Version register, CHVER.VERSION equal to 0x02 or greater

CLKCON (0xC6) – Clock Control

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | OSC32K | 1 | R/W | <p>32 kHz clock oscillator select. The 16 MHz high frequency RC oscillator must be selected as system clock source when this bit is to be changed.</p> <p>0 – 32.768 kHz crystal oscillator 1 – 32 kHz RC oscillator</p> <p>Note: this bit is not retained in PM2 and PM3. After re-entry to PM0 from PM2 or PM3 this bit will be at the reset value 1.</p> |
| 6 | OSC | 1 | R/W | <p>System clock oscillator select:</p> <p>0 – 32 MHz crystal oscillator 1 – 16 MHz high frequency RC oscillator</p> <p>This setting will only take effect when the selected oscillator is powered up and stable. If the selected oscillator is not powered up, then writing this bit will power it up.</p> |
| 5:3 | TICKSPD[2:0] | 001 | R/W | <p>Timer ticks output setting, can not be higher than system clock setting given by OSC bit setting</p> <p>000 – 32 MHz 001 – 16 MHz 010 – 8 MHz 011 – 4 MHz 100 – 2 MHz 101 – 1 MHz 110 – 500 kHz 111 – 250 kHz</p> |
| 2:1 | – | 00 | R | Reserved. |
| 0 | CLKSPD | 1 | R | <p>Clock Speed. Indicates current system clock frequency. The value of this bit is set by the OSC bit setting</p> <p>0 – 32 MHz 1 – 16 MHz</p> <p>This bit is updated when clock source selected with the OSC is stable</p> |

13.11 Power On Reset and Brown Out Detector

The **CC2430** includes a Power On Reset (POR) providing correct initialization during device power-on. Also includes is a Brown Out Detector (BOD) operating on the regulated 1.8V digital power supply only. The BOD will protect the memory contents during supply voltage variations which cause the regulated 1.8V power to drop below the minimum level required by flash memory and SRAM..

When power is initially applied to the **CC2430** the Power On Reset (POR) and Brown Out Detector (BOD) will hold the device in reset state until the supply

voltage reaches above the Power On Reset and Brown Out voltages as defined in Table 4 on page 11.

Figure 33 shows the POR/BOD operation with the 1.8V (typical) regulated supply voltage together with the active low reset signals BOD_RESET and POR_RESET shown in the bottom of the figure.

The cause of the last reset can read from the register bits `SLEEP.RST`.




Figure 33 : Power On Reset and Brown Out Detector Operation

13.12 Watchdog Timer

The watchdog timer (WDT) is intended as a recovery method in situations where the CPU may be subjected to a software upset. The WDT shall reset the system when software fails to clear the WDT within a selected time interval. The watchdog can be used in applications that are subject to electrical noise, power glitches, electrostatic discharge etc., or where high reliability is required. If the watchdog function is not needed in an application, it is possible to configure the watchdog timer to be used as an interval timer that can be used to generate interrupts at selected time intervals.

The features of the watchdog timer are as follows:

- Four selectable timer intervals
- Watchdog mode
- Timer mode
- Interrupt request generation in timer mode
- Clock independent from system clock

The WDT is configured as either a watchdog timer or as a timer for general-purpose use. The operation of the WDT module is controlled by the `WDCTL` register. The watchdog timer consists of an 15-bit counter clocked by the 32.768 kHz clock. Note that the contents of the 15-bit counter is not user-accessible. The contents of the 15-bit counter is reset to 0x0000 when power modes PM2 or PM3 is entered.

13.12.1 Watchdog mode

The watchdog timer is disabled after a system reset. To set the WDT in watchdog mode the `WDCTL.MODE` bit is set to 0. The watchdog timer counter starts incrementing when the enable bit `WDCTL.EN` is set to 1. When the timer is enabled in watchdog mode it is not possible to disable the timer. Therefore, writing a 0 to `WDCTL.EN` has no effect if a 1 was already written to this bit when `WDCTL.MODE` was 0.

The WDT operates with a watchdog timer clock frequency of 32.768 kHz. This clock frequency gives time-out periods equal to 1.9 ms, 15.625 ms, 0.25 s and 1 s corresponding to the count value settings 64, 512, 8192 and 32768 respectively.

If the counter reaches the selected timer interval value, the watchdog timer generates a reset signal for the system. If a watchdog clear sequence is performed before the counter reaches the selected timer interval value, the counter is reset to 0x0000 and continues incrementing its value. The watchdog clear sequence consists of writing 0xA to `WDCTL.CLR[3:0]` followed by writing 0x5 to the same register bits within one half of a watchdog clock period. If this complete sequence is not performed, the watchdog timer generates a reset signal for the system. Note that as long as a correct watchdog clear sequence begins within the selected timer interval, the counter is reset when the complete sequence has been received.

When the watchdog timer has been enabled in watchdog mode, it is not possible to change the mode by writing to the `WDCTL.MODE` bit. The timer interval value can be changed by writing to the `WDCTL.INT[1:0]` bits.

Note that it is recommended that user software clears the watchdog timer at the same time as the timer interval value is changed, in order to avoid an unwanted watchdog reset.

In watchdog mode, the WDT does not produce an interrupt request.

13.12.2 Timer mode

To set the WDT in normal timer mode, the `WDCTL.MODE` bit is set to 1. When register bit `WDCTL.EN` is set to 1, the timer is started and the counter starts incrementing. When the counter reaches the selected interval value, the timer will produce an interrupt request.

In timer mode, it is possible to clear the timer contents by writing a 1 to `WDCTL.CLR[0]`. When the timer is cleared the contents of the counter is set to 0x0000. Writing a 0 to the enable bit `WDCTL.EN` stops the timer and writing 1 restarts the timer from 0x0000.

The timer interval is set by the `WDCTL.INT[1:0]` bits. In timer mode, a reset will not be produced when the timer interval has been reached.

13.12.3 Watchdog Timer Example

Figure 34 shows an example of periodical clearing of an active watchdog timer.

```

; clear watchdog timer
ORL    WDCTL, #0A0h
ORL    WDCTL, #50h
  
```

Figure 34: WDT Example**13.12.4 Watchdog Timer Register**

This section describes the register, WDCTL, for the Watchdog Timer.

WDCTL (0xC9) – Watchdog Timer Control

| Bit | Name | Reset | R/W | Description |
|-----|----------|-------|-----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:4 | CLR[3:0] | 0000 | R/W | Clear timer. When 0xA followed by 0x5 is written to these bits, the timer is loaded with 0x0. Note the timer will only be cleared when 0x5 is written within 0.5 watchdog clock period after 0xA was written. Writing to these bits when EN is 0 have no effect. |
| 3 | EN | 0 | R/W | Enable timer. When a 1 is written to this bit the timer is enabled and starts incrementing. Writing a 0 to this bit in timer mode stops the timer. Writing a 0 to this bit in watchdog mode has no effect. 0 Timer disabled (stop timer) 1 Timer enabled |
| 2 | MODE | 0 | R/W | Mode select. This bit selects the watchdog timer mode. 0 Watchdog mode 1 Timer mode |
| 1:0 | INT[1:0] | 00 | R/W | Timer interval select. These bits select the timer interval defined as a given number of 32.768 kHz oscillator periods. 00 clock period x 32768 (typical 1 s) 01 clock period x 8192 (typical 0.25 s) 10 clock period x 512 (typical 15.625 ms) 11 clock period x 64 (typical 1.9 ms) |

13.13 USART

USART0 and USART1 are serial communications interfaces that can be operated separately in either asynchronous UART mode or in synchronous SPI mode. The two USARTs have identical function, and are assigned to separate I/O pins. Refer to section 13.1 for I/O configuration.

13.13.1 UART mode

For asynchronous serial interfaces, the UART mode is provided. In the UART mode the interface uses a two-wire or four-wire interface consisting of the pins RXD, TXD and optionally RTS and CTS. The UART mode of operation includes the following features:

- 8 or 9 data bits
- Odd, even or no parity
- Configurable start and stop bit level
- Configurable LSB or MSB first transfer
- Independent receive and transmit interrupts
- Independent receive and transmit DMA triggers
- Parity and framing error status

The UART mode provides full duplex asynchronous transfers, and the synchronization of bits in the receiver does not interfere with the transmit function. A UART byte transfer consists of a start bit, eight data bits, an optional ninth data or parity bit, and one or two stop bits. Note that the data transferred is referred to as a byte, although the data can actually consist of eight or nine bits.

The UART operation is controlled by the USART Control and Status registers, UxCSR and the UART Control register UxUCR where x is the USART number, 0 or 1.

The UART mode is selected when UxCSR.MODE is set to 1.

13.13.1.1 UART Transmit

A UART transmission is initiated when the USART Receive/transmit Data Buffer, UxDBUF register is written. The byte is transmitted on TXDx output pin. The UxDBUF register is double-buffered.

The UxCSR.ACTIVE bit goes high when the byte transmission starts and low when it ends. When the transmission ends, the UxCSR.TX_BYTE bit is set to 1. An interrupt request is generated when the UxDBUF register is ready to accept new transmit data. This happens immediately after the transmission has been started, hence a new data byte value can be loaded into the data buffer while the byte is being transmitted.

13.13.1.2 UART Receive

Data reception on the UART is initiated when a 1 is written to the UxCSR.RE bit. The UART will then search for a valid start bit on the RXDx input pin and set the UxCSR.ACTIVE bit high. When a valid start bit has been detected the received byte is shifted into the receive register. The UxCSR.RX_BYTE bit is set and a receive interrupt is generated when the operation has completed. At the same time UxCSR.ACTIVE will go low.

The received data byte is available through the UxDBUF register. When UxDBUF is read, UxCSR.RX_BYTE is cleared by hardware.

13.13.1.3 UART Hardware Flow Control

Hardware flow control is enabled when the UxUCR.FLOW bit is set to 1. The RTS output will then be driven low when the receive register is empty and reception is enabled. Transmission of a byte will not occur before the CTS input goes low.

13.13.1.4 UART Character Format

If the BIT9 and PARITY bits in register UxUCR are set high, parity generation and detection is enabled. The parity is computed and transmitted as the ninth bit, and during reception, the parity is computed and compared to the received ninth bit. If there is a parity error, the UxCSR.ERR bit is set high. This bit is cleared when UxCSR is read.

The number of stop bits to be transmitted is set to one or two bits determined by the register bit UxUCR.SPB. The receiver will always check for one stop bit. If the first stop bit received during reception is not at the expected stop bit level, a framing error

is signaled by setting register bit `UxCSR.FE` high. `UxCSR.FE` is cleared when `UxCSR` is read. The receiver will check both stop bits when `UxUCR.SPB` is set.

13.13.2 SPI Mode

This section describes the SPI mode of operation for synchronous communication. In SPI mode, the USART communicates with an external system through a 3-wire or 4-wire interface. The interface consists of the pins MOSI, MISO, SCK and SS_N. Refer to section 13.1 for description of how the USART pins are assigned to the I/O pins.

The SPI mode includes the following features:

- 3-wire (master) and 4-wire SPI interface
- Master and slave modes
- Configurable SCK polarity and phase
- Configurable LSB or MSB first transfer

The SPI mode is selected when `UxCSR.MODE` is set to 0.

In SPI mode, the USART can be configured to operate either as an SPI master or as an SPI slave by writing the `UxCSR.SLAVE` bit.

13.13.2.1 SPI Master Operation

An SPI byte transfer in master mode is initiated when the `UxDBUF` register is written. The USART generates the SCK serial clock using the baud rate generator (see section 13.13.3) and shifts the provided byte from the transmit register onto the MOSI output. At the same time the receive register shifts in the received byte from the MISO input pin.

The `UxCSR.ACTIVE` bit goes high when the transfer starts and low when the transfer ends. When the transfer ends, the `UxCSR.TX_BYTE` bits is set to 1. A receive interrupt is generated when new received data is ready in the `UxDBUF` USART Receive/Transmit Data register.

The polarity and clock phase of the serial clock SCK is selected by `UxGCR.CPOL` and `UxGCR.CPHA`. The order of the byte transfer is selected by the `UxGCR.ORDER` bit.

At the end of the transfer, the received data byte is available for reading from the `UxDBUF`.

A transmit interrupt is generated when the unit is ready to accept another data byte for transmission. Since `UxDBUF` is double-buffered, this happens just after the transmission has been initiated.

SPI master mode operation as described above is a 3-wire interface. No select input is used to enable the master. If the external slave requires a slave select signal this can be implemented through software using a general-purpose I/O pin.

13.13.2.2 SPI Slave Operation

An SPI byte transfer in slave mode is controlled by the external system. The data on the MOSI input is shifted into the receive register controlled by the serial clock SCK which is an input in slave mode. At the same time the byte in the transmit register is shifted out onto the MISO output.

The `UxCSR.ACTIVE` bit goes high when the transfer starts and low when the transfer ends. Then the `UxCSR.RX_BYTE` bit is set and a receive interrupt is generated.

The expected polarity and clock phase of SCK is selected by `UxGCR.CPOL` and `UxGCR.CPHA`. The expected order of the byte transfer is selected by the `UxGCR.ORDER` bit.

At the end of the transfer, the received data byte is available for reading from `UxDBUF`.

The transmit interrupt is generated at the start of the operation.

13.13.3 SSN Slave Select Pin

When the USART is operating in SPI mode, configured as an SPI slave, a 4-wire interface is used with the Slave Select (SSN) pin as an input to the SPI. When SSN is held low, the SPI slave is active and receives data on the MOSI input and outputs data on the MISO output. When SSN is held high, the SPI slave is inactive and will not receive data. Note that the MISO output is not tri-stated when SSN is held high.

In SPI master mode, the SSN pin is not used. When the USART operates as an

SPI master and a slave select signal is needed by an external SPI slave device, then a general purpose I/O pin should be used to implement the slave select signal function in software.

13.13.4 Baud Rate Generation

An internal baud rate generator sets the UART baud rate when operating in UART mode and the SPI master clock frequency when operating in SPI mode.

The `UxBAUD.BAUD_M[7:0]` and `UxGCR.BAUD_E[4:0]` registers define the baud rate used for UART transfers and the rate of the serial clock for SPI transfers. The baud rate is given by the following equation:

$$\text{Baudrate} = \frac{(256 + \text{BAUD_M}) * 2^{\text{BAUD_E}}}{2^{28}} * F$$

where F is the system clock frequency, 16 MHz or 32 MHz.

The register values required for standard baud rates are shown in Table 39 for a typical system clock set to 32 MHz. The table also gives the difference in actual baud rate to standard baud rate value as a percentage error.

The maximum baud rate for UART mode is F/16 when BAUD_E is 16 and BAUD_M is 0, and where F is the system clock frequency.

The maximum baud rate for SPI mode and thus SCK frequency on output, is F/2 when BAUD_E is 19 and BAUD_M is 0. The maximum SPI rate for input is F/8 where BAUD_E is 17 and BAUD_M is 0. Setting higher baud rates than this will give erroneous results.

Note that the baud rate must be set through the `UxBAUD` and registers `UxGCR` before any other UART or SPI operations take place.

| Baud rate (bps) | UxBAUD.BAUD_M | UxGCR.BAUD_E | Error (%) |
|-----------------|---------------|--------------|-----------|
| 2400 | 59 | 6 | 0.14 |
| 4800 | 59 | 7 | 0.14 |
| 9600 | 59 | 8 | 0.14 |
| 14400 | 216 | 8 | 0.03 |
| 19200 | 59 | 9 | 0.14 |
| 28800 | 216 | 9 | 0.03 |
| 38400 | 59 | 10 | 0.14 |
| 57600 | 216 | 10 | 0.03 |
| 76800 | 59 | 11 | 0.14 |
| 115200 | 216 | 11 | 0.03 |
| 230400 | 216 | 12 | 0.03 |

Table 39: Commonly used baud rate settings for 32 MHz system clock

13.13.5 USART flushing

The current operation can be aborted by setting the `UxUCR.FLUSH` register bit. This event will immediately stop the current operation and clear all data buffers.

13.13.6 USART Interrupts

Each USART has two interrupts. These are the RX complete interrupt (URXx) and the TX complete interrupt (UTXx).

The USART interrupt enable bits are found in the `IEN0` and `IEN2` registers. The interrupt flags are located in the `TCON` and `IRCON2` registers. Refer to section 12.7 on page 53 for details of these registers. The interrupt enables and flags are summarized below.

Interrupt enables:

- USART0 RX : `IEN0.URX0IE`
- USART1 RX : `IEN0.URX1IE`
- USART0 TX : `IEN2.UTX0IE`

- USART1 TX : IEN2.UTX1IE

Interrupt flags:

- USART0 RX : TCON.URX0IF
- USART1 RX : TCON.URX1IF
- USART0 TX : IRCON2.UTX0IF
- USART1 TX : IRCON2.UTX1IF

13.13.7 USART DMA Triggers

There are two DMA triggers associated with each USART. The DMA triggers are activated by RX complete and TX complete events i.e. the same events as the USART interrupt requests. A DMA channel can be configured using a USART Receive/transmit buffer, UxDBUF, as source or destination address.

Refer to Table 37 on page 87 for an overview of the DMA triggers.

13.13.8 USART Registers

The registers for the USART are described in this section. For each USART there are five registers consisting of the following (x refers to USART number i.e. 0 or 1):

- UxCSR USART x Control and Status
- UxUCR USART x UART Control
- UxGCR USART x Generic Control
- UxDBUF USART x Receive/Transmit data buffer
- UxBAUD USART x Baud Rate Control

U0CSR (0x86) – USART 0 Control and Status

| Bit | Name | Reset | R/W | Description |
|-----|---------|-------|------|------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | MODE | 0 | R/W | USART mode select 0 SPI mode 1 UART mode |
| 6 | RE | 0 | R/W | UART receiver enable 0 Receiver disabled 1 Receiver enabled |
| 5 | SLAVE | 0 | R/W | SPI master or slave mode select 0 SPI master 1 SPI slave |
| 4 | FE | 0 | R/W0 | UART framing error status 0 No framing error detected 1 Byte received with incorrect stop bit level |
| 3 | ERR | 0 | R/W0 | UART parity error status 0 No parity error detected 1 Byte received with parity error |
| 2 | RX_BYTE | 0 | R/W0 | Receive byte status. UART mode and SPI slave mode 0 No byte received 1 Received byte ready |
| 1 | TX_BYTE | 0 | R/W0 | Transmit byte status. UART mode and SPI master mode 0 Byte not transmitted 1 Last byte written to Data Buffer register transmitted |
| 0 | ACTIVE | 0 | R | USART transmit/receive active status 0 USART idle 1 USART busy in transmit or receive mode |

U0UCR (0xC4) – USART 0 UART Control

| Bit | Name | Reset | R/W | Description |
|-----|--------|-------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | FLUSH | 0 | R0/W1 | Flush unit. When set, this event will immediately stop the current operation and return the unit to idle state. |
| 6 | FLOW | 0 | R/W | UART hardware flow enable. Selects use of hardware flow control with RTS and CTS pins 0 Flow control disabled 1 Flow control enabled |
| 5 | D9 | 0 | R/W | UART data bit 9 contents. This value is used when 9 bit transfer is enabled. When parity is disabled, the value written to D9 is transmitted as the bit 9 when 9 bit data is enabled. If parity is enabled then this bit sets the parity level as follows. 0 Even parity 1 Odd parity |
| 4 | BIT9 | 0 | R/W | UART 9-bit data enable. When this bit is 1, data is 9 bits and the content of data bit 9 is given by D9 and PARITY. 0 8 bits transfer 1 9 bits transfer |
| 3 | PARITY | 0 | R/W | UART parity enable. 0 Parity disabled 1 Parity enabled |
| 2 | SPB | 0 | R/W | UART number of stop bits. Selects the number of stop bits to transmit 0 1 stop bit 1 2 stop bits |
| 1 | STOP | 1 | R/W | UART stop bit level 0 Low stop bit 1 High stop bit |
| 0 | START | 0 | R/W | UART start bit level. The polarity of the idle line is assumed the opposite of the selected start bit level. 0 Low start bit 1 High start bit |

U0GCR (0xC5) – USART 0 Generic Control

| Bit | Name | Reset | R/W | Description |
|-----|------------------|-------|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | CPOL | 0 | R/W | SPI clock polarity 0 Negative clock polarity 1 Positive clock polarity |
| 6 | CPHA | 0 | R/W | SPI clock phase 0 Data is output on <i>MOSI</i> when <i>SCK</i> goes from CPOL inverted to CPOL , and data input is sampled on <i>MISO</i> when <i>SCK</i> goes from CPOL to CPOL inverted. 1 Data is output on <i>MOSI</i> when <i>SCK</i> goes from CPOL to CPOL inverted, and data input is sampled on <i>MISO</i> when <i>SCK</i> goes from CPOL inverted to CPOL . |
| 5 | ORDER | 0 | R/W | Bit order for transfers 0 LSB first 1 MSB first |
| 4:0 | BAUD_E [4 : 0] | 0x00 | R/W | Baud rate exponent value. BAUD_E along with BAUD_M decides the UART baud rate and the SPI master SCK clock frequency |

U0DBUF (0xC1) – USART 0 Receive/Transmit Data Buffer

| Bit | Name | Reset | R/W | Description |
|-----|----------------|-------|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | DATA [7 : 0] | 0x00 | R/W | USART receive and transmit data. When writing this register the data written is written to the internal, transmit data register. When reading this register, the data from the internal read data register is read. |

U0BAUD (0xC2) – USART 0 Baud Rate Control

| Bit | Name | Reset | R/W | Description |
|-----|------------------|-------|-----|------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | BAUD_M [7 : 0] | 0x00 | R/W | Baud rate mantissa value. BAUD_E along with BAUD_M decides the UART baud rate and the SPI master SCK clock frequency |

U1CSR (0xF8) – USART 1 Control and Status

| Bit | Name | Reset | R/W | Description |
|-----|---------|-------|------|------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | MODE | 0 | R/W | USART mode select 0 SPI mode 1 UART mode |
| 6 | RE | 0 | R/W | UART receiver enable 0 Receiver disabled 1 Receiver enabled |
| 5 | SLAVE | 0 | R/W | SPI master or slave mode select 0 SPI master 1 SPI slave |
| 4 | FE | 0 | R/W0 | UART framing error status 0 No framing error detected 1 Byte received with incorrect stop bit level |
| 3 | ERR | 0 | R/W0 | UART parity error status 0 No parity error detected 1 Byte received with parity error |
| 2 | RX_BYTE | 0 | R/W0 | Receive byte status. UART mode and SPI slave mode 0 No byte received 1 Received byte ready |
| 1 | TX_BYTE | 0 | R/W0 | Transmit byte status. UART mode and SPI master mode 0 Byte not transmitted 1 Last byte written to Data Buffer register transmitted |
| 0 | ACTIVE | 0 | R | USART transmit/receive active status 0 USART idle 1 USART busy in transmit or receive mode |

U1UCR (0xFB) – USART 1 UART Control

| Bit | Name | Reset | R/W | Description |
|-----|--------|-------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | FLUSH | 0 | R0/W1 | Flush unit. When set, this event will immediately stop the current operation and return the unit to idle state. |
| 6 | FLOW | 0 | R/W | UART hardware flow enable. Selects use of hardware flow control with RTS and CTS pins 0 Flow control disabled 1 Flow control enabled |
| 5 | D9 | 0 | R/W | UART data bit 9 contents. This value is used 9 bit transfer is enabled. When parity is disabled, the value written to D9 is transmitted as the bit 9 when 9 bit data is enabled. If parity is enabled then this bit sets the parity level as follows. 0 Even parity 1 Odd parity |
| 4 | BIT9 | 0 | R/W | UART 9-bit data enable. When this bit is 1, data is 9 bits and the content of data bit 9 is given by D9 and PARITY. 0 8 bits transfer 1 9 bits transfer |
| 3 | PARITY | 0 | R/W | UART parity enable. 0 Parity disabled 1 Parity enabled |
| 2 | SPB | 0 | R/W | UART number of stop bits. Selects the number of stop bits to transmit 0 1 stop bit 1 2 stop bits |
| 1 | STOP | 1 | R/W | UART stop bit level 0 Low stop bit 1 High stop bit |
| 0 | START | 0 | R/W | UART start bit level. The polarity of the idle line is assumed the opposite of the selected start bit level. 0 Low start bit 1 High start bit |

U1GCR (0xFC) – USART 1 Generic Control

| Bit | Name | Reset | R/W | Description |
|-----|-----------------|-------|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | CPOL | 0 | R/W | SPI clock polarity 0 Negative clock polarity 1 Positive clock polarity |
| 6 | CPHA | 0 | R/W | SPI clock phase 0 Data is output on <i>MOSI</i> when <i>SCK</i> goes from CPOL inverted to CPOL , and data input is sampled on <i>MISO</i> when <i>SCK</i> goes from CPOL to CPOL inverted. 1 Data is output on <i>MOSI</i> when <i>SCK</i> goes from CPOL to CPOL inverted, and data input is sampled on <i>MISO</i> when <i>SCK</i> goes from CPOL inverted to CPOL . |
| 5 | ORDER | 0 | R/W | Bit order for transfers 0 LSB first 1 MSB first |
| 4:0 | BAUD_E[4 : 0] | 0x00 | R/W | Baud rate exponent value. BAUD_E along with BAUD_M decides the UART baud rate and the SPI master SCK clock frequency |

U1DBUF (0xF9) – USART 1 Receive/Transmit Data Buffer

| Bit | Name | Reset | R/W | Description |
|-----|---------------|-------|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | DATA[7 : 0] | 0x00 | R/W | USART receive and transmit data. When writing this register the data written is written to the internal, transmit data register. When reading this register, the data from the internal read data register is read. |

U1BAUD (0xFA) – USART 1 Baud Rate Control

| Bit | Name | Reset | R/W | Description |
|-----|-----------------|-------|-----|------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | BAUD_M[7 : 0] | 0x00 | R/W | Baud rate mantissa value. BAUD_E along with BAUD_M decides the UART baud rate and the SPI master SCK clock frequency |

13.14 Flash Controller

The **CC2430** contains 32, 64 or 128 KB flash memory for storage of program code. The flash memory is programmable from the user software. See Table 22 on page 28 for flash memory size options.

The Flash Controller handles writing and erasing the embedded flash memory. The embedded flash memory consists of 64 pages of 2048 bytes each (CC2430-F128). The flash memory is byte-addressable from the CPU and 32-bit word-addressable from the Flash Controller.

The flash controller has the following features:

- 32-bit word programmable
- Page erase
- Lock bits for write-protection and code security
- Flash page erase timing 20 ms
- Flash chip erase timing 200 ms
- Flash write timing (4 bytes) 20 μ s
- Auto power-down during low-frequency CPU clock read access

13.14.1 Flash Memory Organization

The flash memory is divided into 64 flash pages consisting of 2 KB each. A flash page is the smallest erasable unit in the memory, while a 32 bit word is the smallest writable unit that may be addressed through the flash controller.

When performing write operations, the flash memory is word-addressable using a 15-bit address written to the address registers `FADDRH:FADDRL`.

When performing page erase operations, the flash memory page to be erased is addressed through the register bits `FADDRH[6:1]`.

Note the difference in addressing the flash memory; when accessed by the CPU to read code or data, the flash memory is byte-addressable. When accessed by the Flash Controller, the flash memory is word-addressable, where a word consists of 32 bits.

The next sections describe the procedures for flash write and flash page erase in detail.

13.14.2 Flash Write

Data is written to the flash memory by using a program command initiated by writing the Flash Control register, `FCTL`. Flash write operations can program any number of locations in the flash memory at a time. Each location may be programmed twice before the next erase must take place. After a page erase or chip erase (through debug interface), the erased bits are set to 1.

A write operation is performed using one out of two methods;

- Through DMA transfer
- Through CPU SFR access.

The DMA transfer method is the preferred way to write to the flash memory.

A write operation is initiated by writing a 1 to `FCTL.WRITE`. The address of the 32-bit word to start writing at, is given by `FADDRH:FADDRL`. During each single, write operation `FCTL.SWBSY` is set high. During a write operation, the byte written to the `FWDATA` register is forwarded to the flash memory. The flash memory is 32-bit word-programmable, meaning data is written as 32-bit words. The first byte written to `FWDATA` is the LSB of the 32-bit word. The actual writing to flash memory takes place each time four bytes have been written to `FWDATA`.

The CPU will not be able to access the flash, e.g. to read program code, while a flash write operation is in progress. Therefore the program code executing the flash write must be executed from RAM, meaning that the program code must reside in the area 0xE000 to 0xFF00 in CODE memory space.

When a flash write operation is executed from RAM, the CPU continues to execute code from the next instruction after the write to `FWDATA`, which initiated the flash write operation.

The `FCTL.SWBSY` bit must be 0 before accessing the flash after a flash write, otherwise an access violation occurs. This also means that `FCTL.SWBSY` must be 0 before program execution can continue at a location in flash memory.

13.14.2.1 DMA Flash Write

When using DMA write operations, the data to be written into flash is stored in Data/XDATA memory. A DMA channel is configured to read the data to be written from memory and write this data to the Flash Write Data register, `FWDATA`, with the DMA trigger event `FLASH` enabled. Thus the Flash Controller will trigger a DMA transfer when the Flash Write Data register, `FWDATA`, is ready to receive new data. The DMA channel should be configured to perform a block to fixed, single mode, byte size transfers.

When the DMA channel is armed, starting a flash write will trigger the first DMA transfer.

Figure 36 shows an example of how a DMA channel is configured and how a DMA transfer is initiated to write a block of

data from a location in XDATA to flash memory, assuming the code is executed from RAM


DMA Flash Write from flash memory

When performing DMA flash write while executing code from within flash memory, the instruction that triggers the first DMA trigger event `FLASH` must be aligned on a 4-byte boundary. Figure 35 shows an example of code that correctly aligns the instruction for triggering DMA.

```
; Write flash and generate Flash DMA trigger
; Code is executed from flash memory
;
#include "ioCC2430.h"
MODULE flashDmaTrigger.s51
RSEG RCODE (2)
PUBLIC halFlashDmaTrigger
FUNCTION halFlashDmaTrigger, 0203H

halFlashDmaTrigger:
ORL FCTL, #0x02;
RET;
END;
```

Figure 35: Flash write using DMA from flash



```

; Write a consecutive block of data from XDATA to consecutive locations in
; flash memory using DMA.
; Assumes 32 MHz system clock is used and code is executed from RAM
;

```

```

    MOV    DPTR,#DMACFG          ;load data pointer with address for DMA
                                ;channel configuration and
                                ;start writing DMA configuration
    MOV    A,#SRC_HI             ;source data high address
    MOVX   @DPTR,A              ;
    INC    DPTR                  ;
    MOV    A,#SRC_LO             ;source data low address
    MOVX   @DPTR,A              ;
    INC    DPTR                  ;
    MOV    A,#0DFh               ;destination high address = HIGH(X_FWDATA)
    MOVX   @DPTR,A              ;
    INC    DPTR                  ;
    MOV    A,#0AFh               ;destination low address = LOW(X_FWDATA)
    MOVX   @DPTR,A              ;
    INC    DPTR                  ;
    MOV    A,#BLK_LEN            ;block length
    MOVX   @DPTR,A              ;
    INC    DPTR                  ;
    MOV    A,#012h               ;8 bits, single mode, use FLASH trigger
    MOVX   @DPTR,A              ;
    INC    DPTR                  ;
    MOV    A,#042h               ;increment source by 1, don't increment
    MOVX   @DPTR,A              ;destination, mask interrupt, high DMA
                                ;priority
    MOV    DMA0CFGL,#DMACFG_LO   ;setup start address for current DMA
    MOV    DMA0CFGH,#DMACFG_HI   ;configuration
    MOV    DMAARM,#01h           ;arm DMA channel 0
    MOV    FADDRH,#00h           ;setup flash address high
    MOV    FADDRL,#01h           ;setup flash address low
    MOV    FWT,#2Ah              ;setup flash timing
    MOV    FCTL,#02h             ;start flash page write => trigger DMA
    .
    .

```

Figure 36: Flash write using DMA

13.14.2.2 CPU Flash Write

The CPU can also write directly to the flash when executing program code from XDATA. The CPU writes data to the Flash Write Data register, FWDATA. The flash memory is written each time four bytes have been written to FWDATA. The CPU

can poll the FCTL.SWBSY status to determine when the flash is ready for four more bytes to be written to FWDATA

Performing flash write from XDATA

The steps required to start a flash write operation from XDATA are shown in Figure 37 on page 157.




Figure 37: Flash write performed from XDATA

13.14.3 Flash Page Erase

After a flash page erase, all bytes in the erased page are set to 1.

A page erase is initiated by setting FCTL.ERASE to 1. The page addressed by FADDRH[6:1] is erased when a page erase is initiated. Note that if a page erase is initiated simultaneously with a page write, i.e. FCTL.WRITE is set to 1, the page erase will be performed before the page write operation. The FCTL.BUSY bit

can be polled to see when the page erase has completed.

Note: if flash erase operations are performed from within flash memory and the watchdog timer is enabled, a watchdog timer interval must be selected that is longer than 20 ms, the duration of the flash erase operation, so that the CPU will manage to clear the watchdog timer.

Performing flash erase from flash memory.

The steps required to perform a flash page erase from within flash memory are outlined in Figure 38.

Note that, while executing program code from within flash memory, when a flash erase or write operation is initiated, program execution will resume from the next instruction when the flash controller

has completed the operation. The flash erase operation requires that the instruction that starts the erase i.e. writing to `FCTL.ERASE` is followed by a NOP instruction as shown in the example code. Omitting the NOP instruction after the flash erase operation will lead to undefined behaviour.

```

; Erase page in flash memory
; Assumes 32 MHz system clock is used
;
C1:   CLR     EA                      ;mask interrupts
      MOV     A,FCTL                 ;wait until flash controller is ready
      JB      ACC.7,C1
      MOV     FADDRH,#00h           ;setup flash address high
      MOV     FWT,#2Ah              ;setup flash timing
      MOV     FCTL,#01h             ;erase page
      NOP                                ;must always execute a NOP after erase
      RET                               ;continues here when flash is ready

```

Figure 38: Flash page erase performed from flash memory**13.14.4 Flash Lock Protection**

For software protection purposes a set of lock protection bits can be written once after each chip erase has been performed. The lock protect bits can only be written through the Debug Interface. There are three kinds of lock protect bits as described in this section. The flash lock bits reside at location 0x000 in the Flash Information page as described in section 12.11.

The `LSIZE[2:0]` lock protect bits are used to define a section of the flash memory which is write protected. The size of the write protected area can be set by the `LSIZE[2:0]` lock protect bits in sizes of eight steps from 0 to 128 KB.

The second type of lock protect bits is `BBLOCK`, which is used to lock the boot sector page (page 0 ranging from address 0 to 0x07FF). When `BBLOCK` is set to 0, the boot sector page is locked.

The third type of lock protect bit is `DBGLOCK`, which is used to disable hardware debug support through the Debug Interface. When `DBGLOCK` is set to 0, all debug commands are disabled.

The lock protect bits are written as a normal flash write to `FWDATA`, but the Debug Interface needs to select the Flash Information Page first instead of the Flash Main Page which is the default setting. The Information Page is selected through the Debug Configuration which is written through the Debug Interface only. Refer to section 12.9 on page 64 for details on how the Flash Information Page is selected using the Debug Interface.

Table 40 defines the byte containing the flash lock protection bits. Note that this is not an SFR register, but instead the byte stored at location 0x000 in Flash Information Page.

Table 40: Flash Lock Protection Bits Definition

| Bit | Name | Description |
|-----|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:5 | - | Reserved, write as 0 |
| 4 | BBLOCK | Boot Block Lock 0 Page 0 is write protected 1 Page 0 is writeable, unless LSIZE is 000 |
| 3:1 | LSIZE[2:0] | Lock Size. Sets the size of the upper Flash area which is write-protected. Byte sizes and page number are listed below 000 128k bytes (All pages) CC2430-F128 only 001 64k bytes (page 32 - 63) CC2430-F64/128 only 010 32k bytes (page 48 - 63) 011 16k bytes (page 56 - 63) 100 8k bytes (page 60 - 63) 101 4k bytes (page 62 - 63) 110 2k bytes (page 63) 111 0k bytes (no pages) |
| 0 | DBGLOCK | Debug lock bit 0 Disable debug commands 1 Enable debug commands |

13.14.5 Flash Write Timing

The Flash Controller contains a timing generator, which controls the timing sequence of flash write and erase operations. The timing generator uses the information set in the Flash Write Timing register, `FWT.FWT[5:0]`, to set the internal timing. `FWT.FWT[5:0]` must be set to a value according to the currently selected CPU clock frequency.

The value set in the `FWT.FWT[5:0]` shall be set according to the CPU clock frequency. The initial value held in `FWT.FWT[5:0]` after a reset is 0x2A which corresponds to 32 MHz CPU clock frequency.

The `FWT` values for the 16 MHz and 32 MHz CPU clock frequencies are given in Table 41.

| CPU clock frequency (MHz) | FWT |
|---------------------------|------|
| 16 | 0x15 |
| 32 | 0x2A |

Table 41: Flash timing (FWT) values**13.14.6 Flash DMA trigger**

The Flash DMA trigger is activated when flash data written to the `FWDATA` register has been written to the specified location in the flash memory, thus indicating that the flash controller is ready to accept new data to be written to `FWDATA`.

13.14.7 Flash Controller Registers

The Flash Controller registers are described in this section.

FCTL (0xAE) – Flash Control

| Bit | Name | Reset | R/W | Description |
|-----|--------|-------|------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | BUSY | 0 | R | Indicates that write or erase is in operation |
| 6 | SWBSY | 0 | R | Indicates that single write is busy; avoid writing to FWDATA register while this is true |
| 5 | – | 0 | R/W | Not used. |
| 4 | CONTRD | 0 | R/W | Continuous read enable mode 0 Avoid wasting power; turn on read enables to flash only when needed 1 Enable continuous read enables to flash when read is to be done. Reduces internal switching of read enables, but greatly increases power consumption. |
| 3:2 | | 0 | R/W | Not used. |
| 1 | WRITE | 0 | R0/W | Write. Start writing word at location given by FADDRH : FADDRL. If ERASE is set to 1, a page erase of the whole page addressed by FADDRH, is performed before the write. |
| 0 | ERASE | 0 | R0/W | Page Erase. Erase page that is given by FADDRH[6 : 1] |

FWDATA (0xAF) – Flash Write Data

| Bit | Name | Reset | R/W | Description |
|-----|-----------------|-------|-----|-------------------------------------------------------------------------------------------|
| 7:0 | FWDATA[7 : 0] | 0x00 | R/W | Flash write data. Data written to FWDATA is written to flash when FCTL.WRITE is set to 1. |

FADDRH (0xAD) – Flash Address High Byte


| Bit | Name | Reset | R/W | Description |
|-----|-----------------|-------|-----|----------------------------------------------------------------------------------------------|
| 7 | - | 0 | R/W | Not used |
| 6:0 | FADDRH[6 : 0] | 0x00 | R/W | Page address / High byte of flash word address Bits 6:1 will select which page to access. |

FADDRL (0xAC) – Flash Address Low Byte

| Bit | Name | Reset | R/W | Description |
|-----|-----------------|-------|-----|--------------------------------|
| 7:0 | FADDRL[7 : 0] | 0x00 | R/W | Low byte of flash word address |

FWT (0xAB) – Flash Write Timing

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|------------------------------------------------------|
| 7:6 | – | 00 | R/W | Not used |
| 5:0 | FWT[5 : 0] | 0x2A | R/W | Flash Write Timing. Controls flash timing generator. |

14 Radio**Figure 39: CC2430 Radio Module**

A simplified block diagram of the IEEE 802.15.4 compliant radio inside **CC2430** is shown in Figure 39. The radio core is based on the industry leading **CC2420** RF transceiver.

CC2430 features a low-IF receiver. The received RF signal is amplified by the low-noise amplifier (LNA) and down-converted in quadrature (I and Q) to the intermediate frequency (IF). At IF (2 MHz), the complex I/Q signal is filtered and amplified, and then digitized by the RF receiver ADCs. Automatic gain control, final channel filtering, de-spreading, symbol correlation and byte synchronization are performed digitally.

An interrupt indicates that a start of frame delimiter has been detected. **CC2430** buffers the received data in a 128 byte receive FIFO. The user may read the FIFO through an SFR interface. It is recommended to use direct memory access (DMA) to move data between memory and the FIFO.

CRC is verified in hardware. RSSI and correlation values are appended to the frame. Clear channel assessment, CCA, is available through an interrupt in receive mode.

The **CC2430** transmitter is based on direct up-conversion. The data is buffered in a 128 byte transmit FIFO (separate from the receive FIFO). The preamble and start of frame delimiter are generated in hardware. Each symbol (4 bits) is spread using the IEEE 802.15.4 spreading sequence to 32 chips and output to the digital-to-analog converters (DACs).

An analog low pass filter passes the signal to the quadrature (I and Q) up-conversion mixers. The RF signal is amplified in the power amplifier (PA) and fed to the antenna.

The internal T/R switch circuitry makes the antenna interface and matching easy. The RF connection is differential. A balun may be used for single-ended antennas. The biasing of the PA and LNA is done by connecting TXRX_SWITCH to RF_P and RF_N through an external DC path.

The frequency synthesizer includes a completely on-chip LC VCO and a 90 degrees phase splitter for generating the I and Q LO signals to the down-conversion mixers in receive mode and up-conversion mixers in transmit mode. The VCO operates in the frequency range 4800 – 4966 MHz, and the frequency is divided by two when split into I and Q signals.

The digital baseband includes support for frame handling, address recognition, data buffering, CSMA-CA strobe processor and MAC security.

An on-chip voltage regulator delivers the regulated 1.8 V supply voltage.

14.1 IEEE 802.15.4 Modulation Format

This section is meant as an introduction to the 2.4 GHz direct sequence spread spectrum (DSSS) RF modulation format defined in IEEE 802.15.4. For a complete description, please refer to [1].

The modulation and spreading functions are illustrated at block level in Figure 40 [1]. Each byte is divided into two symbols, 4 bits each. The least significant symbol is

transmitted first. For multi-byte fields, the least significant byte is transmitted first.

Each symbol is mapped to one out of 16 pseudo-random sequences, 32 chips each. The symbol to chip mapping is shown in Table 42. The chip sequence is then transmitted at 2 MChips/s, with the least significant chip (C_0) transmitted first for each symbol.




Figure 40: Modulation and spreading functions [1]

| Symbol | Chip sequence ($C_0, C_1, C_2, \dots, C_{31}$) |
|--------|-----------------------------------------------------------------|
| 0 | 1 1 0 1 1 0 0 1 1 1 0 0 0 0 1 1 0 1 0 1 0 0 1 0 0 0 1 0 1 1 1 0 |
| 1 | 1 1 1 0 1 1 0 1 1 0 0 1 1 1 0 0 0 0 1 1 0 1 0 1 0 0 1 0 0 0 1 0 |
| 2 | 0 0 1 0 1 1 1 0 1 1 0 1 1 0 0 1 1 1 0 0 0 0 1 1 0 1 0 1 0 0 1 0 |
| 3 | 0 0 1 0 0 0 1 0 1 1 1 0 1 1 0 1 1 0 0 1 1 1 0 0 0 0 1 1 0 1 0 1 |
| 4 | 0 1 0 1 0 0 1 0 0 0 1 0 1 1 1 0 1 1 0 1 1 0 0 1 1 1 0 0 0 0 1 1 |
| 5 | 0 0 1 1 0 1 0 1 0 0 1 0 0 0 1 0 1 1 1 0 1 1 0 1 1 0 0 1 1 1 0 0 |
| 6 | 1 1 0 0 0 0 1 1 0 1 0 1 0 0 1 0 0 0 1 0 1 1 1 0 1 1 0 1 1 0 0 1 |
| 7 | 1 0 0 1 1 1 0 0 0 0 1 1 0 1 0 1 0 0 1 0 0 0 1 0 1 1 1 0 1 1 0 1 |
| 8 | 1 0 0 0 1 1 0 0 1 0 0 1 0 1 1 0 0 0 0 0 0 1 1 1 0 1 1 1 1 0 1 1 |
| 9 | 1 0 1 1 1 0 0 0 1 1 0 0 1 0 0 1 0 1 1 0 0 0 0 0 0 1 1 1 0 1 1 1 |
| 10 | 0 1 1 1 1 0 1 1 1 0 0 0 1 1 0 0 1 0 0 1 0 1 1 0 0 0 0 0 0 1 1 1 |
| 11 | 0 1 1 1 0 1 1 1 1 0 1 1 1 0 0 0 1 1 0 0 1 0 0 1 0 1 1 0 0 0 0 0 |
| 12 | 0 0 0 0 0 1 1 1 0 1 1 1 1 0 1 1 1 0 0 0 1 1 0 0 1 0 0 1 0 1 1 0 |
| 13 | 0 1 1 0 0 0 0 0 0 1 1 1 0 1 1 1 1 0 1 1 1 0 0 0 1 1 0 0 1 0 0 1 |
| 14 | 1 0 0 1 0 1 1 0 0 0 0 0 0 1 1 1 0 1 1 1 1 0 1 1 1 0 0 0 1 1 0 0 |
| 15 | 1 1 0 0 1 0 0 1 0 1 1 0 0 0 0 0 0 1 1 1 0 1 1 1 1 0 1 1 1 0 0 0 |

Table 42: IEEE 802.15.4 symbol-to-chip mapping [1]

The modulation format is Offset – Quadrature Phase Shift Keying (O-QPSK) with half-sine chip shaping. This is equivalent to MSK modulation. Each chip

is shaped as a half-sine, transmitted alternately in the I and Q channels with one half chip period offset. This is illustrated for the zero-symbol in Figure 41.




Figure 41: I / Q Phases when transmitting a zero-symbol chip sequence, $T_c = 0.5 \mu s$

14.2 Command strobcs

The CPU uses a set of *command strobcs* to control operation of the radio in **CC2430**.

Command strobcs may be viewed as single byte instructions which each control some function of the radio. These command strobcs must be used to enable the frequency synthesizer, enable receive mode, enable transmit mode and other functions.

A total of nine command strobcs are defined for the radio and these can be written individually to the radio or they can be given in a sequence together with a set of dedicated software instructions making up a simple program. All command strobcs from the CPU to the radio pass through the CSMA-CA/Command Strobe Processor (CSP). Detailed description about the CSP and how command strobcs are used is given in section 14.34 on page 186.

14.3 RF Registers

The operation of the radio is configured through a set of RF registers. These RF registers are mapped to XDATA memory space as shown in

Figure 13 on page 39.

The RF registers also provide status information from the radio.

The RF registers control/status bits are referred to where appropriate in the following sections while section 14.35 on

page 198 gives a full description of all RF registers.

14.4 Interrupts

The radio is associated with two interrupt vectors on the CPU. These are the RFERR interrupt (interrupt 0) and the RF interrupt (interrupt 12) with the following functions

- RFERR : TXFIFO underflow, RXFIFO overflow
- RF : all other RF interrupts given by RFIF interrupt flags

The RF interrupt vector combines the interrupts in RFIF shown on page 165. Note that these RF interrupts are rising-edge triggered. Thus an interrupt is generated when e.g. the SFD status flag goes from 0 to 1.

The RFIF interrupt flags are described in the next section.

14.4.1 Interrupt registers

Two of the main interrupt control SFR registers are used to enable the RF and RFERR interrupts. These are the following:

- RFERR : IEN0.RFERRIE
- RF : IEN2.RFIE

Two main interrupt flag SFR registers hold the RF and RFERR interrupt flags. These are the following:

- RFERR : TCON.RFERRIF
- RF : S1CON.RFIF

Refer to section 12.7 on page 53 for details about the interrupts.

The RF interrupt is the combined interrupt from eight different sources in the radio. Two SFR registers are used for setting the eight individual RFIF radio interrupt flags and interrupt enables. These are the RFIF and RFIM registers.

The interrupt flags in SFR register RFIF show the status for each interrupt source for the RF interrupt vector.

The interrupt enable bits in RFIM are used to disable individual interrupt sources for the RF interrupt vector. Note that masking an interrupt source in RFIM does not affect the update of the status in the RFIF register.

Due to the use of the individual interrupt masks in RFIM, and the main interrupt mask for the RF interrupt given by IEN2.RFIE there is two-layered masking of this interrupt. Special attention needs to be taken when processing this type of interrupt as described below.

To clear the RF interrupt, S1CON.RFIF and the interrupt flag in RFIF need to be cleared. The order and method of doing this is shown in Figure 42. Note that S1CON is cleared after RFIF, otherwise S1CON.RFIF could be set once again due to the same interrupt.

```

MOV    RFIF,#00h           ;clear all interrupt flags
MOV    S1CON,#00h          ;clear main interrupt flags
MOV    RFIF,#0FFh          ;set interrupt mask
  
```

Figure 42: Clearing RF Interrupt

RFIF (0xE9) – RF Interrupt Flags

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | IRQ_RREG_ON | 0 | R/W0 | Voltage regulator for radio has been turned on 0 No interrupt pending 1 Interrupt pending |
| 6 | IRQ_TXDONE | 0 | R/W0 | TX completed with packet sent. Also set for acknowledge frames ¹⁵ if RF register IRQSRC.TXACK is 1 0 No interrupt pending 1 Interrupt pending |
| 5 | IRQ_FIFOP | 0 | R/W0 | Number of bytes in RXFIFO is above threshold set by IOCFG0.FIFOP_THR 0 No interrupt pending 1 Interrupt pending |
| 4 | IRQ_SFD | 0 | R/W0 | Start of frame delimiter (SFD) has been detected 0 No interrupt pending 1 Interrupt pending |
| 3 | IRQ_CCA | 0 | R/W0 | Clear channel assessment (CCA) indicates that channel is clear 0 No interrupt pending 1 Interrupt pending |
| 2 | IRQ_CSP_WT | 0 | R/W0 | CSMA-CA/strobe processor (CSP) wait condition is true 0 No interrupt pending 1 Interrupt pending |
| 1 | IRQ_CSP_STOP | 0 | R/W0 | CSMA-CA/strobe processor (CSP) program execution stopped 0 No interrupt pending 1 Interrupt pending |
| 0 | IRQ_CSP_INT | 0 | R/W0 | CSMA-CA/strobe processor (CSP) INT instruction executed 0 No interrupt pending 1 Interrupt pending |

¹⁵ Only for devices with Chip Version register, CHVER.VERSION equal to 0x02 or greater

RFIM (0x91) – RF Interrupt Mask

| Bit | Name | Reset | R/W | Description |
|-----|-------------|-------|-----|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | IM_RREG_PD | 0 | R/W | Voltage regulator for radio has been turned on 0 Interrupt disabled 1 Interrupt enabled |
| 6 | IM_TXDONE | 0 | R/W | TX completed with packet sent. Also for acknowledge frames ¹⁶ if RF register IRQSRC.TXACK is 1 0 Interrupt disabled 1 Interrupt enabled |
| 5 | IM_FIFOP | 0 | R/W | Number of bytes in RXFIFO is above threshold set by IOCFG0.FIFOP_THR 0 Interrupt disabled 1 Interrupt enabled |
| 4 | IM_SFD | 0 | R/W | Start of frame delimiter (SFD) has been detected 0 Interrupt disabled 1 Interrupt enabled |
| 3 | IM_CCA | 0 | R/W | Clear channel assessment (CCA) indicates that channel is clear 0 Interrupt disabled 1 Interrupt enabled |
| 2 | IM_CSP_WT | 0 | R/W | CSMA-CA/strobe processor (CSP) wait condition is true 0 Interrupt disabled 1 Interrupt enabled |
| 1 | IM_CSP_STOP | 0 | R/W | CSMA-CA/strobe processor (CSP) program execution stopped 0 Interrupt disabled 1 Interrupt enabled |
| 0 | IM_CSP_INT | 0 | R/W | CSMA-CA/strobe processor (CSP) INT instruction executed 0 Interrupt disabled 1 Interrupt enabled |

¹⁶ Only for devices with Chip Version register, CHVER.VERSION equal to 0x02 or greater

14.5 FIFO access

The TXFIFO and RXFIFO may be accessed through the SFR register RFD (0xD9).

Data is written to the TXFIFO when writing to the RFD register. Data is read from the RXFIFO when the RFD register is read.

The RF register bits RFSTATUS.FIFO and RFSTATUS.FIFOP provide information on the data in the receive FIFO, as described

in section 14.6 on page 167. Note that the RFSTATUS.FIFO and RFSTATUS.FIFOP only apply to the RXFIFO.

The TXFIFO may be flushed by issuing a SFLUSHTX command strobe. Similarly, a SFLUSHRX command strobe will flush the receive FIFO.

RFD (0xD9) – RF Data

| Bit | Name | Reset | R/W | Description |
|-----|----------|-------|-----|-----------------------------------------------------------------------------------------------------------------|
| 7:0 | RFD[7:0] | 0x00 | R/W | Data written to the register is written to the TXFIFO. When reading this register, data from the RXFIFO is read |

14.6 DMA

It is possible, and in most cases recommended, to use direct memory access (DMA) to move data between memory and the radio. The DMA controller is described in section 13.2. Refer to this section for a detailed description on how to setup and use DMA transfers.

To support the DMA controller there is one DMA trigger associated with the radio, this is the RADIO DMA trigger (DMA trigger 19). The RADIO DMA trigger is activated by two events. The first event to cause a RADIO DMA trigger, is when the first data is present in the RXFIFO, i.e. when the RXFIFO goes from the empty state to the non-empty state. The second event that causes a RADIO DMA trigger, is when data is read from the RXFIFO (through RFD SFR register) and there is still more data available in the RXFIFO.

14.7 Receive mode

In receive mode, the interrupt flag `RFIF.IRQ_SFD` goes high and the RF interrupt is requested after the start of frame delimiter (SFD) field has been completely received. If address recognition is disabled or is successful, the `RFSTATUS.SFD` bit goes low again only after the last byte of the MPDU has been received. If the received frame fails address recognition, the `RFSTATUS.SFD` bit goes low immediately. This is illustrated in Figure 43.

The `RFSTATUS.FIFO` bit is high when there is one or more data bytes in the RXFIFO. The first byte to be stored in the RXFIFO is the length field of the received frame, i.e. the `RFSTATUS.FIFO` bit is set high when the length field is written to the RXFIFO. The `RFSTATUS.FIFO` bit then remains high until the RXFIFO is empty. The RF register `RXFIFOCNT` contains the number of bytes present in the RXFIFO.

The `RFSTATUS.FIFOP` bit is high when the number of unread bytes in the RXFIFO exceeds the threshold programmed into `IOCFG0.FIFOP_THR`. When address recognition is enabled the `RFSTATUS.FIFOP` bit will not go high until the incoming frame passes address recognition, even if the number of bytes in the RXFIFO exceeds the programmed threshold.

The `RFSTATUS.FIFOP` bit will also go high when the last byte of a new packet is received, even if the threshold is not exceeded. If so the `RFSTATUS.FIFOP` bit will go back to low once one byte has been read out of the RXFIFO.

When address recognition is enabled, data should not be read out of the RXFIFO before the address is completely received, since the frame may be automatically flushed by **CC2430** if it fails address recognition. This may be handled by using the `RFSTATUS.FIFOP` bit, since this bit does not go high until the frame passes address recognition.

Figure 44 shows an example of status bit activity when reading a packet from the RXFIFO. In this example, the packet size is 8 bytes, `IOCFG0.FIFOP_THR = 3` and `MODEMCTRL0.AUTOCRC` is set. The length will be 8 bytes, RSSI will contain the average RSSI level during receiving of the packet and FCS/corr contain information of FCS check result and the correlation levels.

14.8 RXFIFO overflow

The RXFIFO can only contain a maximum of 128 bytes at a given time. This may be divided between multiple frames, as long as the total number of bytes is 128 or less. If an overflow occurs in the RXFIFO, this is signaled to the CPU by asserting the `RFERR` interrupt when enabled. In addition the radio will set

RFSTATUS.FIFO bit low while the RFSTATUS.FIFOP bit is high. Data already in the RXFIFO will not be affected by the overflow, i.e. frames already received may be read out.

A SFLUSHRX command strobe is required after a RXFIFO overflow to enable reception of new data.




Figure 43: SFD, FIFO and FIFOP activity examples during receive




Figure 44: Example of status activity when reading RXFIFO.

14.9 Transmit mode

During transmit, the RFSTATUS.FIFO and RFSTATUS.FIFOP bits are still only related to the RXFIFO. The RFSTATUS.SFD bit is however active

during transmission of a data frame, as shown in Figure 45.

The RFIF.IRQ_SFD interrupt flag goes high and the RF interrupt is requested when the SFD field has been completely transmitted. It goes low again when the complete MPDU (as defined by the length field) has been transmitted or if an

underflow is detected. The interrupt RFERR is asserted when enabled. See section 14.17.1 on page 173 for more information on TXFIFO underflow.

As can be seen from comparing Figure 43 and Figure 45, the `RFSTATUS.SFD` bit behaves very similarly during reception

and transmission of a data frame. If the `RFSTATUS.SFD` bits of the transmitter and the receiver are compared during the transmission of a data frame, a small delay between 3.076 μ s to 3.284 μ s can be seen because of bandwidth limitations in both the transmitter and the receiver.




Figure 45: SFD status activity example during transmit

14.10 General control and status

In receive mode, the `RFIF.IRQ_FIFO` interrupt flag and RF interrupt request can be used to interrupt the CPU when a threshold has been exceeded or a complete frame has been received.

In receive mode, the `RFSTATUS.FIFO` bit can be used to detect if there is data at all in the receive FIFO.

The `RFIF.IRQ_SFD` interrupt flag can be used to extract the timing information of transmitted and received data frames. The `RFIF.IRQ_SFD` bit will go high when a start of frame delimiter has been completely detected / transmitted.

For debug purposes, the `RFSTATUS.SFD`, `RFSTATUS.FIFO`, `RFSTATUS.FIFOP` and `RFSTATUS.CCA` bits can be output onto P1.7 – P1.4 I/O pins to monitor the status of these signals as selected by the `IOCFG0`, `IOCFG1` and `IOCFG2` register.

The polarity of these signals given on the debug outputs can also be controlled by the `IOCFG0–2` registers, if needed.

14.11 Demodulator, Symbol Synchronizer and Data Decision

The block diagram for the **CC2430** demodulator is shown in Figure 46. Channel filtering and frequency offset compensation is performed digitally. The signal level in the channel is estimated to generate the RSSI level (see the RSSI / Energy Detection section on page 178 for more information). Data filtering is also included for enhanced performance.

With the ± 40 ppm frequency accuracy requirement from [1], a compliant receiver must be able to compensate for up to 80 ppm or 200 kHz. The **CC2430** demodulator tolerates up to 300 kHz offset without significant degradation of the receiver performance.

Soft decision is used at the chip level, i.e. the demodulator does not make a decision for each chip, only for each received symbol. De-spreading is performed using over-sampling symbol correlators. Symbol synchronization is achieved by a continuous start of frame delimiter (SFD) search.

When an SFD is detected, data is written to the RXFIFO and may be read out by the

CPU at a lower bit rate than the 250 kbps generated by the receiver.

The **CC2430** demodulator also handles symbol rate errors in excess of 120 ppm without performance degradation. Resynchronization is performed

continuously to adjust for error in the incoming symbol rate.

The RF register `MDMCTRL1H.CORR_THR` control bits should be written to 20 to set the threshold for detecting IEEE 802.15.4 start of frame delimiters.




Figure 46: Demodulator Simplified Block Diagram

14.12 Frame Format

CC2430 has hardware support for parts of the IEEE 802.15.4 frame format. This section gives a brief summary to the IEEE 802.15.4 frame format, and describes how **CC2430** is set up to comply with this.

Figure 47 [1] shows a schematic view of the IEEE 802.15.4 frame format. Similar figures describing specific frame formats (data frames, beacon frames, acknowledgment frames and MAC command frames) are included in [1].




Figure 47: Schematic view of the IEEE 802.15.4 Frame Format [1]

14.13 Synchronization header

The synchronization header (SHR) consists of the preamble sequence followed by the start of frame delimiter (SFD). In [1], the preamble sequence is defined to be four bytes of 0x00. The SFD is one byte, set to 0xA7.

In **CC2430**, the preamble length and SFD is configurable. The default values are compliant with [1]. Changing these values

will make the system non-compliant to IEEE 802.15.4.

A synchronization header is always transmitted first in all transmit modes.

The preamble sequence length can be set with RF register bit `MDMCTRL0L.PREAMBLE_LENGTH`, while the SFD is programmed in the `SYNCWORDH:SYNCWORDL` registers. `SYNCWORDH:SYNCWORDL` is two bytes long, which gives the user some extra flexibility as described below. Figure 48

shows how the **CC2430** synchronization header relates to the IEEE 802.15.4 specification.

The programmable preamble length only applies to transmission, it does not affect receive mode. The preamble length should not be set shorter than the default value. Note that 2 of the 8 zero-symbols in the preamble sequence required by [1] are included in the SYNCWORDH:SYNCWORDL registers so that the **CC2430** preamble sequence is only 6 symbols long for compliance with [1]. Two additional zero symbols in SYNCWORDH:SYNCWORDL make **CC2430** compliant with [1].

In reception, **CC2430** synchronizes to received zero-symbols and searches for the SFD sequence defined by the SYNCWORDH:SYNCWORDL registers. The least significant symbols in

SYNCWORDH:SYNCWORDL set to 0xF will be ignored, while symbols different from 0xF will be required for synchronization. The default setting of 0xA70F thereby requires one additional zero-symbol for synchronization. This will reduce the number of false frames detected due to noise.

In receive mode **CC2430** uses the preamble sequence for symbol synchronization and frequency offset adjustments. The SFD is used for byte synchronization, and is not part of the data stored in the receive buffer (RXFIFO).




Figure 48: Transmitted Synchronization Header

14.14 Length field

The frame length field shown in Figure 47 defines the number of bytes in the MPDU. Note that the length field does not include the length field itself. It does however include the FCS (Frame Check Sequence), even if this is inserted automatically by **CC2430** hardware.

The length field is 7 bits and has a maximum value of 127. The most significant bit in the length field is reserved [1], and should be set to zero.

CC2430 uses the length field both for transmission and reception, so this field must always be included. In transmit

mode, the length field is used for underflow detection, as described in the FIFO access section on page 166.

14.15 MAC protocol data unit

The FCF, data sequence number and address information follows the length field as shown in Figure 47. Together with the MAC data payload and Frame Check Sequence, they form the MAC Protocol Data Unit (MPDU).

The format of the FCF is shown in Figure 49. Please refer to [1] for details.

There is no hardware support for the data sequence number, this field must be inserted and verified by software.

CC2430 includes hardware address recognition, as described in the Address

Recognition section on page 174.

| Bits: 0-2 | 3 | 4 | 5 | 6 | 7-9 | 10-11 | 12-13 | 14-15 |
|------------|------------------|---------------|---------------------|-----------|----------|-----------------------------|----------|------------------------|
| Frame Type | Security Enabled | Frame Pending | Acknowledge request | Intra PAN | Reserved | Destination addressing mode | Reserved | Source addressing mode |

Figure 49: Format of the Frame Control Field (FCF) [1]

14.16 Frame check sequence

A 2-byte frame check sequence (FCS) follows the last MAC payload byte as shown in Figure 47. The FCS is calculated over the MPDU, i.e. the length field is not part of the FCS. This field is automatically generated and verified by hardware when the RF register `MDMCTRL0L.AUTOCRC` control bit is set. It is recommended to always have this enabled, except possibly for debug purposes. If cleared, CRC generation and verification must be performed by software.

The FCS polynomial is [1]:

$$x^{16} + x^{12} + x^5 + 1$$

The **CC2430** hardware implementation is shown in Figure 50. Please refer to [1] for further details.

In transmit mode the FCS is appended at the correct position defined by the length field. The FCS is not written to the TXFIFO, but stored in a separate 16-bit register.

In receive mode the FCS is verified by hardware. The user is normally only interested in the correctness of the FCS,

not the FCS sequence itself. The FCS sequence itself is therefore not written to the RXFIFO during receive.

Instead, when `MDMCTRL0L.AUTOCRC` is set the two FCS bytes are replaced by the RSSI value, average correlation value (used for LQI) and CRC OK/not OK. This is illustrated in Figure 51.

The first FCS byte is replaced by the 8-bit RSSI value. See the RSSI section on page 178 for details.

The seven least significant bits in the last FCS byte are replaced by the average correlation value of the 8 first symbols of the received PHY header (length field) and PHY Service Data Unit (PSDU). This correlation value may be used as a basis for calculating the LQI. See the Link Quality Indication section on page 178 for details.

The most significant bit in the last byte of each frame is set high if the CRC of the received frame is correct and low otherwise.





Figure 50: CC2430 Frame Check Sequence (FCS) hardware implementation [1]

**Figure 51: Data in RXFIFO when MDMCTRL0L.AUTOCRC is set****14.17 RF Data Buffering**

CC2430 can be configured for different transmit and receive modes, as set in the MDMCTRL1L.TX_MODE and MDMCTRL1L.RX_MODE control bits. Buffered mode (mode 0) will be used for normal operation of **CC2430**, while other modes are available for test purposes.

14.17.1 Buffered transmit mode

In buffered transmit mode (TX_MODE 0), the 128 byte TXFIFO, located in **CC2430** RAM, is used to buffer data before transmission. A synchronization header is automatically inserted before the length field during transmission. The length field must always be the first byte written to the transmit buffer for all frames.

Writing one or multiple bytes to the TXFIFO is described in the FIFO access section on page 166. A DMA transfer can be configured to write transmit data to the TXFIFO.

Transmission is enabled by issuing a STXON or STXONCCA command strobe. See the Radio control state machine section on page 176 for an illustration of how the transmit command strobes affect the state of **CC2430**. The STXONCCA strobe is ignored if the channel is busy. See section 14.25 on page 179 for details on CCA.

The preamble sequence is started 12 symbol periods after the transmit command strobe. After the programmable start of frame delimiter has been transmitted, data is fetched from the TXFIFO.

The TXFIFO can only contain one data frame at a given time.

After complete transmission of a data frame, the TXFIFO is automatically refilled with the last transmitted frame. Issuing a new STXON or STXONCCA command strobe will then cause **CC2430** to retransmit the last frame.

Writing to the TXFIFO after a frame has been transmitted will cause the TXFIFO to be automatically flushed before the new byte is written. The only exception is if a TXFIFO underflow has occurred, when a SFLUSHTX command strobe is required.

14.17.2 Buffered receive mode

In buffered receive mode (RX_MODE 0), the 128 byte RXFIFO, located in **CC2430** RAM, is used to buffer data received by the demodulator. Accessing data in the RXFIFO is described in the FIFO access section on page 166.

The RF interrupt generated by RFSTATUS.FIFOP and also the RFSTATUS.FIFO and RFSTATUS.FIFOP register bits are used to assist the CPU in supervising the RXFIFO. Please note that these status bits are only related to the RXFIFO, even if **CC2430** is in transmit mode.

A DMA transfer should be used to read data from the RXFIFO. In this case a DMA channel can be setup to use the RADIO DMA trigger (see DMA triggers on page 87) to initiate a DMA transfer using the RFD register as the DMA source.

Multiple data frames may be in the RXFIFO simultaneously, as long as the total number of bytes does not exceed 128.

See the RXFIFO overflow section on page 167 for details on how a RXFIFO overflow is detected and signaled.

14.18 Address Recognition

CC2430 includes hardware support for address recognition, as specified in [1]. Hardware address recognition may be enabled or disabled using the `MDMCTRL0H.ADDR_DECODE` control bit. Address recognition uses the following RF registers

- `IEEE_ADDR7-IEEE_ADDR0`
- `PANIDH:PANIDL`
- `SHORTADDRH:SHORTADDRL`

Address recognition is based on the following requirements, listed from section 7.5.6.2 in [1]:

- The frame type subfield shall not contain an illegal frame type
- If the frame type indicates that the frame is a beacon frame, the source PAN identifier shall match `macPANId` unless `macPANId` is equal to `0xFFFF`, in which case the beacon frame shall be accepted regardless of the source PAN identifier.
- If a destination PAN identifier is included in the frame, it shall match `macPANId` or shall be the broadcast PAN identifier (`0xFFFF`).
- If a short destination address is included in the frame, it shall match either `macShortAddress` or the broadcast address (`0xFFFF`). Otherwise if an extended destination address is included in the frame, it shall match `aExtendedAddress`.
- If only source addressing fields are included in a data or MAC command frame, the frame shall only be accepted if the device is a

PAN coordinator and the source PAN identifier matches `macPANId`.

If any of the above requirements are not satisfied and address recognition is enabled, **CC2430** will disregard the incoming frame and flush the data from the RXFIFO. Only data from the rejected frame is flushed, data from previously accepted frames may still be in the RXFIFO.

Incoming frames are first subject to frame type filtering according to the setting of the `MDMCTRL0H.FRAME_T_FILT` register bit.

Following the required frame type filtering, incoming frames with reserved frame types (FCF frame type subfield is 4, 5, 6 or 7) are however accepted if the `RESERVED_FRAME_MODE` control bit in the RF register `MDMCTRL0H` is set. In this case, no further address recognition is performed on these frames. This option is included for future expansions of the IEEE 802.15.4 standard.

If a frame is rejected, **CC2430** will only start searching for a new frame after the rejected frame has been completely received (as defined by the length field) to avoid detecting false SFDs within the frame.

The `MDMCTRL0.PAN_COORDINATOR` control bit must be correctly set, since parts of the address recognition procedure requires knowledge about whether the current device is a PAN coordinator or not.

14.19 Acknowledge Frames

CC2430 includes hardware support for transmitting acknowledge frames, as specified in [1]. Figure 52 shows the format of the acknowledge frame.

If `MDMCTRL0L.AUTOACK` is enabled, an acknowledge frame is transmitted for all

incoming frames accepted by the address recognition with the acknowledge request flag set and a valid CRC. `AUTOACK` therefore does not make sense unless also `ADDR_DECODE` and `AUTOCRC` are enabled. The sequence number is copied from the incoming frame.

| | | | | | |
|------------------------------|--------------------------------|------------------|---------------------------|----------------------|----------------------------|
| Bytes: 4 | 1 | 1 | 2 | 1 | 2 |
| Preamble Sequence | Start of Frame Delimiter (SFD) | Frame Length | Frame Control Field (FCF) | Data Sequence Number | Frame Check Sequence (FCS) |
| Synchronisation Header (SHR) | | PHY Header (PHR) | MAC Header (MHR) | | MAC Footer (MFR) |

Figure 52: Acknowledge frame format [1]

Two command strobes, `SACK` and `SACKPEND` are defined to transmit acknowledge frames with the frame pending field cleared or set, respectively. The acknowledge frame is only transmitted if the CRC is valid.

For systems using beacons, there is an additional timing requirement that the acknowledge frame transmission may be started on the first backoff-slot boundary (20 symbol periods) at least 12 symbol periods after the last symbol of the incoming frame. When the RF register control bit `MDMCTRL1H.SLOTTED_ACK` is set to 1, the acknowledge frame is transmitted between 12 and 30 symbol periods after the incoming frame. The timing is defined such that there is an integer number of 20-symbol period backoff-slots between the incoming packet SFD and the transmitted acknowledge frame SFD. This timing is also illustrated in Figure 53.

Using `SACKPEND` will set the pending data flag for automatically transmitted acknowledge frames using `AUTOACK`. The pending flag will then be set also for future acknowledge frames, until a `SACK` command strobe is issued. The pending data flag that is transmitted will be logically OR'ed with the value of `FSMTC1.PENDING_OR`. Thus the pending flag can be set high using this register control bit.

When an acknowledge frame transmission completes, the RF Interrupt flag `RFIF.IRQ_TXDONE` will be set if this interrupt source is selected by setting RF register bit `IRQSRC.TXACK` to 1.

Acknowledge frames may be manually transmitted using normal data transmission if desired.




Figure 53: Acknowledge frame timing

14.20 Radio control state machine

CC2430 has a built-in state machine that is used to switch between different operation states (modes). The change of state is done either by using command strobes or by internal events such as SFD detected in receive mode.

The radio control state machine states are shown in Figure 54. The numbers in brackets refer to the state number readable in the `FSMSTATE` status register. Reading the `FSMSTATE` status register is primarily for test / debug purposes. The figure assumes that the device is already placed in the PM0 power mode.

Before using the radio in either RX or TX mode, the voltage regulator and crystal oscillator must be turned on and become stable. The voltage regulator and crystal oscillator startup times are given in the section 7.4 on page 15.

The voltage regulator for the radio is enabled by setting the RF register bit `RFPWR.RREG_RADIO_PD` to 0. The interrupt flag `RFIF.IRQ_RREG_ON` is set to 1 when the voltage regulator has powered-up.

The crystal oscillator is controlled through the Power Management Controller. The

`SLEEP.XOSC_STB` bit indicates whether the oscillator is running and stable or not (see page 139). This SFR register can be polled when waiting for the oscillator to start.

For test purposes, the frequency synthesizer (FS) can also be manually calibrated and started by using the `STXCALN` or `ISTXCALN` command strobe (see section 0 and 0). This will not start a transmission before a `STXON` command strobe is issued. This is not shown in Figure 54.

Enabling transmission is done by issuing a `STXON` or `STXONCCA` command strobe.

Turning off RF can be accomplished by using the `SRFOFF` command strobe.

After bringing the **CC2430** up to Power Mode 0 (PM0) from a low-power mode e.g. Power Mode 3 (PM3), all RF registers will retain their values thus placing the chip ready to operate at the correct frequency and mode. Due to the very fast start-up time, **CC2430** can remain in a low-power mode until a transmission session is requested.




Figure 54: Radio control 

14.21 MAC Security Operations (Encryption and Authentication)

CC2430 features hardware IEEE 802.15.4 MAC security operations. Refer to section

14.22 Linear IF and AGC Settings

CC2430 is based on a linear IF chain where the signal amplification is done in an analog VGA (variable gain amplifier). The gain of the VGA is digitally controlled.

The AGC (Automatic Gain Control) loop ensures that the ADC operates inside its

13.9 on page 130 for a description of the AES encryption unit.

dynamic range by using an analog/digital feedback loop.

The AGC characteristics are set through the `AGCCTRL:AGCCTRLH`, registers. The reset values should be used for all AGC control registers.

14.23 RSSI / Energy Detection

CC2430 has a built-in RSSI (Received Signal Strength Indicator) giving a digital value that can be read from the 8 bit, signed 2's complement `RSSIL.RSSI_VAL` register bits.

The RSSI value is always averaged over 8 symbol periods (128 μ s), in accordance with [1].

The RSSI register value `RSSIL.RSSI_VAL` can be referred to the power P at the RF pins by using the following equations:

$$P = \text{RSSI_VAL} + \text{RSSI_OFFSET} [\text{dBm}]$$

where the `RSSI_OFFSET` is found empirically during system development from the front end gain. `RSSI_OFFSET` is approximately -45 . E.g. if reading a value of -20 from the `RSSI` register, the RF input power is approximately -65 dBm.

A typical plot of the `RSSI_VAL` reading as function of input power is shown in Figure 55. It can be seen from the figure that the RSSI reading from **CC2430** is very linear and has a dynamic range of about 100 dB.




Figure 55: Typical RSSI value vs. input power

14.24 Link Quality Indication

The link quality indication (LQI) measurement is a characterization of the strength and/or quality of a received packet, as defined by [1].

The RSSI value described in the previous section may be used by the MAC software

to produce the LQI value. The LQI value is required by [1] to be limited to the range 0 through 255, with at least eight unique values. Software is responsible for generating the appropriate scaling of the LQI value for the given application.

Using the RSSI value directly to calculate the LQI value has the disadvantage that e.g. a narrowband interferer inside the

channel bandwidth will increase the LQI value although it actually reduces the true link quality. **CC2430** therefore also provides an average correlation value for each incoming packet, based on the eight first symbols following the SFD. This unsigned 7-bit value, which should be as high as possible, can be looked upon as an indication of the “chip error rate,” although **CC2430** does not perform chip decision.

As described in the Frame check sequence section on page 172, the average correlation value for the eight first symbols is appended to each received frame together with the RSSI and CRC OK/not OK when `MDMCTRL0L.AUTOCRC`

is set. A correlation value of approx. 110 indicates a maximum quality frame while a value of approx. 50 is typically the lowest quality frames detectable by **CC2430**.

Software must convert the correlation value to the range 0-255 defined by [1], e.g. by calculating:

$$\text{LQI} = (\text{CORR} - a) \cdot b$$

limited to the range 0-255, where *a* and *b* are found empirically based on PER measurements as a function of the correlation value.

A combination of RSSI and correlation values may also be used to generate the LQI value.

14.25 Clear Channel Assessment

The clear channel assessment signal is based on the measured RSSI value and a programmable threshold. The clear channel assessment function is used to implement the CSMA-CA functionality specified in [1]. CCA is valid when the receiver has been enabled for at least 8 symbol periods.

Carrier sense threshold level is programmed by `RSSI.CCA_THR`. The threshold value can be programmed in steps of 1 dB. A CCA hysteresis can also be programmed in the `MDMCTRL0H.CCA_HYST` control bits.

All three CCA modes specified by [1] are implemented in **CC2430**. These are set in `MDMCTRL0L.CCA_MODE`, as can be seen in the register description. The different modes are:

- 00 Reserved
- 01 Clear channel when received energy is below threshold.

14.26 Frequency and Channel Programming

The operating frequency is set by programming the 10 bit frequency word located in `FSCTRLH.FREQ[9:8]` and `FSCTRLH.FREQ[7:0]`. The operating frequency F_C in MHz is given by:

$$F_C = 2048 + \text{FREQ}[9:0] \text{ MHz}$$

- 10 Clear channel when not receiving valid IEEE 802.15.4 data.
- 11 Clear channel when energy is below threshold and not receiving valid IEEE 802.15.4 data

Clear channel assessment is available on the `RFSTATUS.CCA` RF register bit. `RFSTATUS.CCA` is active high. This register bit will also set the interrupt flag `RFIF.IRQ_CCA`.

Implementing CSMA-CA may easiest be done by using the `STXONCCA` command strobe given by the CSMA-CA/strobe processor, as shown in the Radio control state machine section on page 176. Transmission will then only start if the channel is clear. The `TX_ACTIVE` status bit in the `RFSTATUS` RF register may be used to detect the result of the CCA.

where `FREQ[9:0]` is the value given by `FSCTRLH.FREQ[9:8]:FSCTRLH.FREQ[7:0]`

In receive mode the actual LO frequency is $F_C - 2 \text{ MHz}$, since a 2 MHz IF is used. Direct conversion is used for transmission, so here the LO frequency equals F_C . The 2 MHz IF is automatically set by **CC2430**, so the frequency programming is equal for RX and TX.

IEEE 802.15.4 specifies 16 channels within the 2.4 GHz band, numbered 11

through 26. The RF frequency of channel k is given by [1] :

$$F_C = 2405 + 5 (k-11) \text{ MHz, } k=11, 12, \dots, 26$$

For operation in channel k, the `FSCTRLH.FREQ:FSCTRL.L.FREQ` register should therefore be set to:

$$\text{FSCTRLH.FREQ:FSCTRL.L.FREQ} = 357 + 5 (k-11)$$

14.27 VCO and PLL Self-Calibration

14.27.1 VCO

The VCO is completely integrated and operates at 4800 – 4966 MHz. The VCO frequency is divided by 2 to generate frequencies in the desired band (2400-2483.5 MHz).

14.27.2 PLL self-calibration

The VCO's characteristics will vary with temperature, changes in supply voltages, and the desired operating frequency.

In order to ensure reliable operation the VCO's bias current and tuning range are

automatically calibrated every time the RX mode or TX mode is enabled, i.e. in the `RX_CALIBRATE`, `TX_CALIBRATE` and `TX_ACK_CALIBRATE` control states in Figure 54 on page 177.

14.28 Output Power Programming

The RF output power of the device is programmable and is controlled by the `TXCTRL.L` RF register. Table 43 shows the output power for different settings, including the complete programming of the `TXCTRL.L` register and the current consumption in the whole device.

For optimum link quality it is recommended to set `TXCTRL.L` to 0x5F.

| TXCTRL.L register value | Output Power [dBm] | Device current consumption [mA] |
|-------------------------|--------------------|---------------------------------|
| 0xFF | 0.6 | 32.4 |
| 0xDF | 0.5 | 31.3 |
| 0xBF | 0.3 | 30.3 |
| 0x9F | 0.2 | 29.2 |
| 0x7F | -0.1 | 28.1 |
| 0x5F | -0.4 | 26.9 |
| 0x3F | -0.9 | 25.7 |
| 0x1F | -1.5 | 24.5 |
| 0x1B | -2.7 | 23.6 |
| 0x17 | -4.0 | 22.8 |
| 0x13 | -5.7 | 21.9 |
| 0x0F | -7.9 | 21.0 |
| 0x0B | -10.8 | 20.1 |
| 0x07 | -15.4 | 19.2 |
| 0x06 | -18.6 | 18.8 |
| 0x03 | -25.2 | 18.3 |

Table 43: Output power settings

14.29 Input / Output Matching

The RF input / output is differential (RF_N and RF_P). In addition there is supply switch output pin (TXRX_SWITCH) that must have an external DC path to RF_N and RF_P.

In RX mode the TXRX_SWITCH pin is at ground and will bias the LNA. In TX mode the TXRX_SWITCH pin is at supply rail voltage and will properly bias the internal PA.

The RF output and DC bias can be done using different topologies. Some are shown in Figure 6 on page 31.

Component values are given in Table 24 on page 32. If a differential antenna is implemented, no balun is required.

If a single ended output is required (for a single ended connector or a single ended antenna), a balun should be used for optimum performance.

14.30 Transmitter Test Modes


CC2430 can be set into different transmit test modes for performance evaluation. The test mode descriptions in the following sections requires that the chip is first reset, the crystal oscillator is selected using the CLKCON register and that the crystal oscillator has stabilized.

14.30.1 Unmodulated carrier

An unmodulated carrier may be transmitted by setting MDMCTRL1L.TX_MODE to 2, writing

0x1800 to the DACTSTH:DACTSTL registers and issue a STXON command strobe. The transmitter is then enabled while the transmitter I/Q DACs are overridden to static values. An unmodulated carrier will then be available on the RF output pins.

A plot of the single carrier output spectrum from **CC2430** is shown in Figure 56 below.

**Figure 56: Single carrier output**

14.30.2 Modulated spectrum

The **CC2430** has a built-in test pattern generator that can generate a pseudo random sequence using the CRC generator. This is enabled by setting `MDMCTRL1L.TX_MODE` to 3 and issuing a `STXON` command strobe. The modulated spectrum is then available on the RF pins. The low byte of the CRC word is transmitted and the CRC is updated with 0xFF for each new byte. The length of the transmitted data sequence is 65535 bits. The transmitted data-sequence is then:


[synchronization header] [0x00, 0x78, 0xb8, 0x4b, 0x99, 0xc3, 0xe9, ...]

Since a synchronization header (preamble and SFD) is transmitted in all TX modes, this test mode may also be used to transmit a known pseudorandom bit sequence for bit error testing. Please note

that **CC2430** requires symbol synchronization, not only bit synchronization, for correct reception. Packet error rate is therefore a better measurement for the true RF performance.

Another option to generate a modulated spectrum is to fill the TXFIFO with pseudo-random data and set `MDMCTRL1L.TX_MODE` to 2. **CC2430** will then transmit data from the FIFO disregarding a TXFIFO underflow. The length of the transmitted data sequence is then 1024 bits (128 bytes).

A plot of the modulated spectrum from **CC2430** is shown in Figure 57. Note that to find the output power from the modulated spectrum, the RBW must be set to 3 MHz or higher.

**Figure 57: Modulated spectrum plot**

14.31 System Considerations and Guidelines

14.31.1 SRD regulations

International regulations and national laws regulate the use of radio receivers and transmitters. SRDs (Short Range Devices) for license free operation are allowed to operate in the 2.4 GHz band worldwide. The most important regulations are ETSI EN 300 328 and EN 300 440 (Europe), FCC CFR-47 part 15.247 and 15.249 (USA), and ARIB STD-T66 (Japan).

14.31.2 Frequency hopping and multi-channel systems

The 2.4 GHz band is shared by many systems both in industrial, office and home environments. **CC2430** uses direct sequence spread spectrum (DSSS) as

defined by [1] to spread the output power, thereby making the communication link more robust even in a noisy environment.

With **CC2430** it is also possible to combine both DSSS and FHSS (frequency hopping spread spectrum) in a proprietary non-IEEE 802.15.4 system. This is achieved by reprogramming the operating frequency (see the Frequency and Channel Programming section on page 179) before enabling RX or TX. A frequency synchronization scheme must then be implemented within the proprietary MAC layer to make the transmitter and receiver operate on the same RF channel.

14.31.3 Data burst transmissions

The data buffering in **CC2430** lets the user have a lower data rate link between the CPU and the radio module than the RF bit rate of 250 kbps. This allows the CPU to

buffer data at its own speed, reducing the workload and timing requirements. DMA transfers may be used to efficiently move data to and from the radio FIFOs.

The relatively high data rate of **CC2430** also reduces the average power consumption compared to the 868 / 915 MHz bands defined by [1], where only 20 / 40 kbps are available. **CC2430** may be powered up a smaller portion of the time, so that the average power consumption is reduced for a given amount of data to be transferred.

14.31.4 Crystal accuracy and drift

A crystal accuracy of ± 40 ppm is required for compliance with IEEE 802.15.4 [1]. This accuracy must also take ageing and temperature drift into consideration.

A crystal with low temperature drift and low aging could be used without further compensation. A trimmer capacitor in the crystal oscillator circuit (in parallel with C191 in Figure 6) could be used to set the initial frequency accurately.

For non-IEEE 802.15.4 systems, the robust demodulator in **CC2430** allows up to 120 ppm total frequency offset between the transmitter and receiver. This could e.g. relax the accuracy requirement to 60 ppm for each of the devices.

Optionally in a star network topology, the full-function device (FFD) could be equipped with a more accurate crystal thereby relaxing the requirement on the reduced-function device (RFD). This can make sense in systems where the reduced-function devices ship in higher volumes than the full-function devices.

14.31.5 Communication robustness

CC2430 provides very good adjacent, alternate and co channel rejection, image frequency suppression and blocking properties. The **CC2430** performance is significantly better than the requirements imposed by [1]. These are highly important parameters for reliable operation in the 2.4 GHz band, since an increasing number of devices/systems are using this license free frequency band.

14.31.6 Communication security

The hardware encryption and authentication operations in **CC2430** enable

secure communication, which is required for many applications. Security operations require a lot of data processing, which is costly in an 8-bit microcontroller system. The hardware support within **CC2430** enables a high level of security with minimum CPU processing requirements.

14.31.7 Low cost systems

As the **CC2430** provides 250 kbps multi-channel performance without any external filters, a very low cost system can be made (e.g. two layer PCB with single-sided component mounting).

A differential antenna will eliminate the need for a balun, and the DC biasing can be achieved in the antenna topology.

14.31.8 Battery operated systems

In low power applications, the **CC2430** should be placed in the low-power modes PM2 or PM3 when not being active. Ultra low power consumption may be achieved since the voltage regulators are turned off.

14.31.9 BER / PER measurements

CC2430 includes test modes where data is received infinitely and output to pins. The required test modes are selected with the RF register bits MDMCTRL1L.TX_MODE[1:0] and MDMCTRL1L.RX_MODE[1:0]. These modes may be used for Bit Error Rate (BER) measurements. However, the following precautions must be taken to perform such a measurement:

- A preamble and SFD sequence must be used, even if pseudo random data is transmitted, since receiving the DSSS modulated signal requires symbol synchronization, not bit synchronization like e.g. in 2FSK systems. The SYNCWORDH:SYNCWORDL may be set to another value to fit to the measurement setup if necessary.
- The data transmitted over air must be spread according to [1] and the description on page 162. This means that the transmitter used during measurements must be able to do spreading of the bit data to chip data. Remember that the *chip* sequence transmitted by the test setup is not the same as

the *bit* sequence, which is output by **CC2430**.

- When operating at or below the sensitivity limit, **CC2430** may lose symbol synchronization in infinite receive mode. A new SFD and restart of the receiver may be required to re-gain synchronization.

In an IEEE 802.15.4 system, all communication is based on packets. The sensitivity limit specified by [1] is based on Packet Error Rate (PER) measurements instead of BER. This is a more realistic measurement of the true RF performance since it mirrors the way the actual system operates.

It is recommended to perform PER measurements instead of BER measurements to evaluate the performance of IEEE 802.15.4 systems. To do PER measurements, the following may be used as a guideline:

- A valid preamble, SFD and length field must be used for each packet.
- The PSDU (see Figure 47 on page 170) length should be 20 bytes for sensitivity measurements as specified by [1].
- The sensitivity limit specified by [1] is the RF level resulting in a 1% PER. The packet sample space for a given measurement must then be $\gg 100$ to have a sufficiently large sample space. E.g. at least 1000 packets should be used to measure the sensitivity.
- The data transmitted over air must be spread according to [1] and the

description on page 162. Pre-generated packets may be used, although [1] requires that the PER is averaged over random PSDU data.

- The **CC2430** receive FIFO may be used to buffer data received during PER measurements, since it is able to buffer up to 128 bytes.
- The `MDMCTRL1H.CORR_THR` control register should be set to 20, as described in the Demodulator, Symbol Synchronizer and Data Decision section.

The simplest way of making a PER measurement will be to use another **CC2430** as the reference transmitter. However, this makes it difficult to measure the exact receiver performance.

Using a signal generator, this may either be set up as O-QPSK with half-sine shaping or as MSK. If using O-QPSK, the phases must be selected according to [1]. If using MSK, the chip sequence must be modified such that the modulated MSK signal has the same phase shifts as the O-QPSK sequence previously defined.

For a desired symbol sequence s_0, s_1, \dots, s_{n-1} of length n symbols, the desired chip sequence $c_0, c_1, c_2, \dots, c_{32n-1}$ of length $32n$ is found using table lookup from Table 42 on page 162. It can be seen from comparing the phase shifts of the O-QPSK signal with the frequency of a MSK signal that the MSK chip sequence is generated as:

$(c_0 \text{ xnor } c_1), (c_1 \text{ xor } c_2), (c_2 \text{ xnor } c_3), \dots, (c_{32n-1} \text{ xor } c_{32n})$ where c_{32n} may be arbitrarily selected.

14.32 PCB Layout Recommendation

A four layer PCB is highly recommended.

In the Texas Instruments reference design, the top layer is used for signal routing, and the open areas are filled with metallization connected to ground using several vias. The area under the chip is used for grounding and must be well connected to the ground plane with several vias.

The ground pins should be connected to ground as close as possible to the

package pin using individual vias. The decoupling capacitors should also be placed as close as possible to the supply pins and connected to the ground plane by separate vias. Supply power filtering is very important.

The external components should be as small as possible (0402 is recommended) and surface mount devices must be used.

If using any external high-speed digital devices, caution should be used when

placing these in order to avoid interference with the RF circuitry.

A Development Kit, CC2430DK, with a fully assembled Evaluation Module is available. It is strongly advised that this

reference layout is followed very closely in order to obtain the best performance.

The schematic, BOM and layout Gerber files for the reference designs are all available from the TI website.

14.33 Antenna Considerations

CC2430 can be used together with various types of antennas. A differential antenna like a dipole would be the easiest to interface not needing a balun (balanced to un-balanced transformation network).

The length of the $\lambda/2$ -dipole antenna is given by:

$$L = 14250 / f$$

where f is in MHz, giving the length in cm. An antenna for 2450 MHz should be 5.8 cm. Each arm is therefore 2.9 cm.

Other commonly used antennas for short-range communication are monopole, helical and loop antennas. The single-ended monopole and helical would require a balun network between the differential output and the antenna.

Monopole antennas are resonant antennas with a length corresponding to one quarter of the electrical wavelength ($\lambda/4$). They are very easy to design and can be implemented simply as a "piece of wire" or even integrated into the PCB.

The length of the $\lambda/4$ -monopole antenna is given by:

$$L = 7125 / f$$

where f is in MHz, giving the length in cm. An antenna for 2450 MHz should be 2.9 cm.

Non-resonant monopole antennas shorter than $\lambda/4$ can also be used, but at the expense of range. In size and cost critical applications such an antenna may very well be integrated into the PCB.

Enclosing the antenna in high dielectric constant material reduces the overall size of the antenna. Many vendors offer such antennas intended for PCB mounting.

Helical antennas can be thought of as a combination of a monopole and a loop antenna. They are a good compromise in size critical applications. Helical antennas tend to be more difficult to optimize than the simple monopole.

Loop antennas are easy to integrate into the PCB, but are less effective due to difficult impedance matching because of their very low radiation resistance.

For low power applications the differential antenna is recommended giving the best range and because of its simplicity.

The antenna should be connected as close as possible to the IC. If the antenna is located away from the RF pins the antenna should be matched to the feeding transmission line (50 Ω).

14.34 CSMA/CA Strobe Processor

The Command Strobe/CSMA-CA Processor (CSP) provides the control interface between the CPU and the Radio module in the **CC2430**.

The CSP interfaces with the CPU through the SFR register `RFST` and the RF registers `CSPX`, `CSPY`, `CSPZ`, `CSPT` and `CSPCTRL`. The CSP produces interrupt requests to the CPU. In addition the CSP interfaces with the MAC Timer by observing MAC Timer overflow events.

The CSP allows the CPU to issue command strobes to the radio thus controlling the operation of the radio.

The CSP has two modes of operation as follows, which are described below.

- Immediate Command Strobe execution.
- Program execution

Immediate Command Strobes are written as an Immediate Command Strobe instruction to the CSP which are issued instantly to the Radio module. The Immediate Command Strobe instruction is also used only to control the CSP. The

Immediate Command Strobe instructions are described in section 1.1.1.

Program execution mode means that the CSP executes a sequence of instructions, from a program memory or instruction memory, thus constituting a short user-defined program. The available instructions are from a set of 14 instructions. The instruction set is defined in section 1.1.1. The required program is first loaded into the CSP by the CPU, then

the CPU instructs the CSP to start executing the program.

The program execution mode together with the MAC Timer allows the CSP to automate CSMA-CA algorithms and thus act as a co-processor for the CPU.

The operation of the CSP is described in detail in the following sections. The command strobes and other instructions supported by the CSP are given in section 14.34.8 on page 191.

RFST (0xE1) – RF CSMA-CA / Strobe Processor

| Bit | Name | Reset | R/W | Description |
|-----|------------|-------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | INSTR[7:0] | 0xC0 | R/W | Data written to this register will be written to the CSP instruction memory. Reading this register will return the CSP instruction currently being executed. |

14.34.1 Instruction Memory

The CSP executes single byte program instructions which are read from a 24 byte instruction memory. The instruction memory is written to sequentially through the SFR register RFST. An instruction write pointer is maintained within the CSP to hold the location within the instruction memory where the next instruction written to RFST will be stored. Following a reset the write pointer is reset to location 0. During each RFST register write, the write pointer will be incremented by 1 until the end of memory is reached when the write pointer will stop incrementing. The first instruction written to RFST will be stored in location 0, the location where program execution starts. Thus a complete 24 instruction program is written to the instruction memory by writing each instruction in the desired order to the RFST register.

The write pointer may be reset to 0 by writing the immediate command strobe instruction ISSTOP. In addition the write pointer will be reset to 0 when the command strobe SSTOP is executed in a program.

Following a reset, the instruction memory is filled with SNOP (No Operation) instructions (opcode value 0xC0).

While the CSP is executing a program, there shall be no attempts to write instructions to the instruction memory by

writing to RFST. Failure to observe this rule can lead to incorrect program execution and corrupt instruction memory contents. However, Immediate Command Strobe instructions may be written to RFST (see section 14.34.3).

14.34.2 Data Registers

The CSP has three data registers CSPT, CSPX, CSPY and CSPZ, which are read/write accessible for the CPU as RF registers. These registers are read or modified by some instructions, thus allowing the CPU to set parameters to be used by a CSP program or allowing the CPU to read CSP program status.

The CSPT data register is not modified by any instruction. The CSPT data register is used to set a MAC Timer overflow compare value. Once program execution has started on the CSP, the contents of this register is decremented by 1 each time the MAC timer overflows. When CSPT reaches zero, program execution is halted and the interrupt IRQ_CSP_STOP is asserted. The CSPT register will not be decremented if the CPU writes 0xFF to this register.

Note: If the CSPT register compare function is not used, this register must be set to 0xFF before the program execution is started.

14.34.3 Program Execution

After the instruction memory has been filled, program execution is started by writing the immediate command strobe instruction ISSTART to the RFST register. The program execution will continue until either the instruction at last location has been executed, the CSPT data register contents is zero, a SSTOP instruction has been executed, an immediate ISSTOP instruction is written to RFST or until a SKIP instruction returns a location beyond the last location in the instruction memory. The CSP runs at 8 MHz clock frequency.

Immediate Command Strobe instructions may be written to RFST while a program is being executed. In this case the Immediate instruction will bypass the instruction in the instruction memory, which will be completed once the Immediate instruction has been completed.

During program execution, reading RFST will return the current instruction being executed. An exception to this is the execution of immediate command strobes, during which RFST will return C0h.

14.34.4 Interrupt Requests

The CSP has three interrupts flags which can produce the RF interrupt vector. These are the following:

- IRQ_CSP_STOP: asserted when the processor has executed the last instruction in memory and when the processor stops due to a

SSTOP or ISSTOP instruction or CSPT register equal zero.

- IRQ_CSP_WT: asserted when the processor continues executing the next instruction after a WAIT W or WAITX instruction.
- IRQ_CSP_INT: asserted when the processor executes an INT instruction.


14.34.5 Random Number Instruction

There will be a delay in the update of the random number used by the RANDXY instruction. Therefore if an instruction, RANDXY, that uses this value is issued immediately after a previous RANDXY instruction, the random value read may be the same in both cases.

14.34.6 Running CSP Programs

The basic flow for loading and running a program on the CSP is shown in Figure 58.

When program execution stops due to end of program the current program remains in program memory so that the same program can be run again by starting execution once again with the ISSTART command. However, when program execution is stopped by the SSTOP or ISTOP instruction, the program memory will be cleared.

**Figure 58: Running a CSP program****14.34.7 Instruction Set Summary**

This section gives an overview of the instruction set. This is intended as a summary and definition of instruction opcodes. Refer to section 14.34.8 for a description of each instruction.

Each instruction consists of one byte which is written to the `RFST` register to be stored in the instruction memory.

The Immediate Strobe instructions (`ISxxx`) are not used in a program. When these instructions are written to the `RFST` register, they are executed immediately. If the CSP is already executing a program the current instruction will be delayed until the Immediate Strobe instruction has completed.

For undefined opcodes, the behavior of the CSP is defined as a No Operation Strobe Command (`SNOP`).

Table 44: Instruction Set Summary

| Mnemonic | Opcode Bit number | | | | | | | | Description |
|----------|-------------------|---|---|------|---|---|---|---|-----------------------------------------------------------------------------------------|
| | 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 | |
| SKIP C,S | 0 | S | | | N | C | | | Skip S instructions when condition (C xor N) is true ¹⁷ |
| WAIT W | 1 | 0 | 0 | W | | | | | Wait for W number of MAC Timer overflows. If W is zero, wait for 32 MAC Timer overflows |
| WEVENT | 1 | 0 | 1 | 1 | 1 | 0 | 0 | 0 | Wait until MAC Timer value is greater than or equal to compare value in T2CMP |
| WAITX | 1 | 0 | 1 | 1 | 1 | 0 | 1 | 1 | Wait for CSPX number of backoffs. When CSPX is zero there is no wait. |
| LABEL | 1 | 0 | 1 | 1 | 1 | 0 | 1 | 0 | Label next instruction as loop start |
| RPT | 1 | 0 | 1 | 0 | N | C | | | Repeat from start of loop if condition (C xor N) is true |
| INT | 1 | 0 | 1 | 1 | 1 | 0 | 0 | 1 | Assert interrupt |
| INCY | 1 | 0 | 1 | 1 | 1 | 1 | 0 | 1 | Increment CSPY |
| INCMAXY | 1 | 0 | 1 | 1 | 0 | M | | | Increment CSPY not greater than M |
| DECY | 1 | 0 | 1 | 1 | 1 | 1 | 1 | 0 | Decrement CSPY |
| DECZ | 1 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | Decrement CSPZ |
| RANDXY | 1 | 0 | 1 | 1 | 1 | 1 | 0 | 0 | Load CSPX with CSPY bit random value. |
| Sxxx | 1 | 1 | 0 | STRB | | | | | Command strobe instructions ¹⁸ |
| ISxxx | 1 | 1 | 1 | STRB | | | | | Immediate strobe instructions ¹⁹ |

¹⁷ Refer to section 14.34.8 for full description of each instruction¹⁸ The Command strobe instruction is divided into eleven sub-instructions as defined by the STRB field. See sections 14.34.8.13 to 14.34.8.23 for a description.¹⁹ The Immediate strobe instruction is divided into eleven sub-instructions as defined by the STRB field. See sections 0 to 14.34.8.34 for a description.

14.34.8 Instruction Set Definition

There are 14 basic instruction types. Furthermore the Command Strobe and Immediate Strobe instructions can each be divided into eleven sub-instructions giving an effective number of 34 different instructions. The following sub-sections describe each instruction.

Note: the following definitions are used in this section

PC = CSP program counter
 X = RF register CSPX
 Y = RF register CSPY
 Z = RF register CSPZ
 T = RF register CSPT

14.34.8.1 DECZ

Function: Decrement Z

Description: The Z register is decremented by 1. An original value of 0x00 will underflow to 0x0FF.

Operation: $Z := Z - 1$

Opcode: 0xBF

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 0 | 1 | 1 | 1 | 1 | 1 | 1 |

14.34.8.2 DECY

Function: Decrement Y

Description: The Y register is decremented by 1. An original value of 0x00 will underflow to 0x0FF.

Operation: $Y := Y - 1$

Opcode: 0xBE

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 0 | 1 | 1 | 1 | 1 | 1 | 0 |

14.34.8.3 INCY

Function: Increment Y

Description: The Y register is incremented by 1. An original value of 0x0FF will overflow to 0x00.

Operation: $Y := Y + 1$

Opcode: 0xBD

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 0 | 1 | 1 | 1 | 1 | 0 | 1 |

14.34.8.4 INCMAXY

Function: Increment Y not greater than M.

Description: The Y register is incremented by 1 if the result is less than M otherwise Y register is loaded with value M. An original value of Y equal 0x0FF will result in the value M

Operation: $Y := \min(Y + 1, M)$

Opcode: 0xB0 | M (M=0 – 7)

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 0 | 1 | 1 | 0 | M | | |

14.34.8.5 RANDXY

Function: Load random value into X

Description: The [Y] LSB bits of X register are loaded with random value. Note that if two RANDXY instructions are issued immediately after each other the same random value will be used in both cases. If Y equals 0 or if Y is greater than 8, then 8 LSB bits are loaded.

Operation: $X[Y-1:0] := \text{RNG_DOUT}[Y-1:0]$, $X[7:Y] := 0$

Opcode: 0xBC

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 0 | 1 | 1 | 1 | 1 | 0 | 0 |

14.34.8.6 INT**Function:** Interrupt.**Description:** The interrupt IRQ_CSP_INT is asserted when this instruction is executed.**Operation:** IRQ_CSP_INT=1**Opcode:** 0xB9

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 0 | 1 | 1 | 1 | 0 | 0 | 1 |

14.34.8.7 WAITX**Function:** Wait for X MAC Timer overflows**Description:** Wait until MAC Timer overflows the number of times equal to register X. The contents of register X is decremented each time a MAC Timer overflow is detected. Program execution continues with the next instruction and the interrupt flag IRQ_CSP_WT is asserted when the wait condition is true. If register X is zero when this instruction starts executing, there is no wait.**Operation:**

X := X-1 when MAC Timer overflow = true

PC := PC while number of MAC Timer overflow = true < X

PC := PC+1 when number of MAC Timer overflow = true = X

Opcode: 0xBB

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 0 | 1 | 1 | 1 | 0 | 1 | 1 |

14.34.8.8 WAIT W**Function:** Wait for W MAC Timer overflows**Description:** Wait until MAC Timer overflows number of times equal to value W. If W=0 the instruction will wait for 32 overflows. Program execution continues with the next instruction and the interrupt

flag IRQ_CSP_WT is asserted when the wait condition is true.

Operation:

PC := PC while number of MAC Timer overflow = true < W

PC := PC+1 when number of MAC Timer overflow = true = W

Opcode: 0x80 | W (W=0 – 31)

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 0 | 0 | W | | | | |

14.34.8.9 WEVENT**Function:** Wait until MAC Timer compare**Description:** Wait MAC Timer value is greater than or equal to the compare value in T2CMP. Program execution continues with the next instruction when the wait condition is true.**Operation:**

PC := PC while MAC Timer compare = false

PC := PC+1 when MAC Timer compare = true

Opcode: 0xB8

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 0 | 1 | 1 | 1 | 0 | 0 | 0 |

14.34.8.10 LABEL**Function:** Set loop label**Description:** Sets next instruction as start of loop. If the current instruction is the last instruction in the instruction memory then the current PC is set as start of loop. Only one level of loops is supported.**Operation:** LABEL := PC+1

Opcode: 0xBA

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 0 | 1 | 1 | 1 | 0 | 1 | 0 |

14.34.8.11 RPT C**Function:** Conditional repeat

Description: If condition C is true then jump to instruction defined by last LABEL instruction, i.e. jump to start of loop. If the condition is false or if a LABEL instruction has not been executed, then execution will continue from next instruction. The condition C may be negated by setting N=1 and is described in the table below.

| Condition code C | Description | Function |
|------------------|---------------------------|--------------------|
| 000 | CCA is true | CCA=1 |
| 001 | Receiving packet | SFD=1 |
| 010 | CPU control true | CSPCTRL.CPU_CTRL=1 |
| 011 | End of instruction memory | PC=23 |
| 100 | Register X=0 | X=0 |
| 101 | Register Y=0 | Y=0 |
| 110 | Register Z=0 | Z=0 |
| 111 | Not used | - |

Operation:

PC := LABEL when (C xor N)=true

PC := PC+1 when (C xor N) =false or LABEL=not set

Opcode: 0xA0 | N | C (N=0,8 C=0 – 7)

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 0 | 1 | 0 | N | C | | |

14.34.8.12 SKIP S, C**Function:** Conditional skip instruction

Description: If condition C is true then skip S instructions. The condition C may

be negated (N=1) and is described in the table below (note same conditions as RPT C instruction). Setting S=0, will cause a wait at current instruction until (C xor N) = true

| Condition code C | Description | Function |
|------------------|---------------------------|--------------------|
| 000 | CCA is true | CCA=1 |
| 001 | Receiving packet | SFD =1 |
| 010 | CPU control true | CSPCTRL.CPU_CTRL=1 |
| 011 | End of instruction memory | PC=23 |
| 100 | Register X=0 | X=0 |
| 101 | Register Y=0 | Y=0 |
| 110 | Register Z=0 | Z=0 |
| 111 | Not used | - |

Operation:

PC := PC+S+1 when (C xor N)=true

PC := PC+1 when (C xor N)=false

Opcode:

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 0 | S | | | N | C | | |

14.34.8.13 STOP**Function:** Stop program execution

Description: The SSTOP instruction stops the CSP program execution. The instruction memory is cleared, any loop start location set by the LABEL instruction is invalidated and the IRQ_CSP_STOP interrupt flag is asserted.

Operation: Stop execution, PC := 0, write pointer := 0

Opcode: 0xDF

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 0 | 1 | 1 | 1 | 1 | 1 |

14.34.8.14 *SNOP***Function:** No Operation**Description:** Operation continues at the next instruction.**Operation:** PC := PC+1**Opcode:** 0xC0

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |

14.34.8.15 *STXCALN***Function:** Enable and calibrate frequency synthesizer for TX.

Note this instruction is for test purposes only (see section 14.20).

Description: The STXCALN instruction enables and calibrate frequency synthesizer for TX. The instruction waits for the radio to acknowledge the command before executing the next instruction.**Operation:** STXCALN**Opcode:** 0xC1

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 0 | 0 | 0 | 0 | 0 | 1 |

14.34.8.16 *SRXON***Function:** Enable and calibrate frequency synthesizer for RX**Description:** The SRXON instruction asserts the output FFCTL_SRXON_STRB to enable and calibrate frequency synthesizer for RX. The instruction waits

for the radio to acknowledge the command before executing the next instruction.

Operation: SRXON**Opcode:** 0xC2

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 0 | 0 | 0 | 0 | 1 | 0 |

14.34.8.17 *STXON***Function:** Enable TX after calibration**Description:** The STXON instruction enables TX after calibration. The instruction waits for the radio to acknowledge the command before executing the next instruction.**Operation:** STXON**Opcode:** 0xC3

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 0 | 0 | 0 | 0 | 1 | 1 |

14.34.8.18 *STXONCCA***Function:** Enable calibration and TX if CCA indicates a clear channel**Description:** The STXONCCA instruction enables TX after calibration if CCA indicates a clear channel. The instruction waits for the radio to acknowledge the command before executing the next instruction.**Operation:** STXONCCA**Opcode:** 0xC4

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 0 | 0 | 0 | 1 | 0 | 0 |

14.34.8.19 *SRFOFF*

Function: Disable RX/TX and frequency synthesizer.

Description: The SRFOFF instruction asserts disables RX/TX and the frequency synthesizer. The instruction waits for the radio to acknowledge the command before executing the next instruction.

Operation: SRFOFF

Opcode: 0xC5

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 0 | 0 | 0 | 1 | 0 | 1 |

14.34.8.20 *SFLUSHRX*

Function: Flush RXFIFO buffer and reset demodulator

Description: The SFLUSHRX instruction flushes the RXFIFO buffer and resets the demodulator. The instruction waits for the radio to acknowledge the command before executing the next instruction.

Operation: SFLUSHRX

Opcode: 0xC6

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 0 | 0 | 0 | 1 | 1 | 0 |

14.34.8.21 *SFLUSHTX*

Function: Flush TXFIFO buffer

Description: The SFLUSHTX instruction flushes the TXFIFO buffer. The instruction waits for the radio to acknowledge the command before executing the next instruction.

Operation: SFLUSHTX

Opcode: 0xC7

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 0 | 0 | 0 | 1 | 1 | 1 |

14.34.8.22 *SACK*

Function: Send acknowledge frame with pending field cleared

Description: The SACK instruction sends an acknowledge frame. The instruction waits for the radio to acknowledge the command before executing the next instruction.

Operation: SACK

Opcode: 0xC8

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 0 | 0 | 1 | 0 | 0 | 0 |

14.34.8.23 *SACKPEND*

Function: Send acknowledge frame with pending field set

Description: The SACKPEND instruction sends an acknowledge frame with pending field set. The instruction waits for the radio to acknowledge the command before executing the next instruction.

Operation: SACKPEND

Opcode: 0xC9

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 0 | 0 | 1 | 0 | 0 | 1 |

14.34.8.24 *ISSTOP*

Function: Stop program execution

Description: The ISSTOP instruction stops the CSP program execution. The instruction memory is cleared, any loop

start location set be the LABEL instruction is invalidated and the IRQ_CSP_STOP interrupt flag is asserted.

Operation: Stop execution

Opcode: 0xFF

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |

14.34.8.25 ISSTART

Function: Start program execution

Description: The ISSTART instruction starts the CSP program execution from first instruction written to instruction memory.

Operation: PC := 0, start execution

Opcode: 0xFE

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 |

14.34.8.26 ISTXCALN

Function: Enable and calibrate frequency synthesizer for TX.

Note this instruction is for test purposes only (see section 14.20).

Description: The ISTXCALN instruction immediately enables and calibrates frequency synthesizer for TX. The instruction waits for the radio to acknowledge the command before executing the next instruction.

Operation: STXCALN

Opcode: 0xE1

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 1 | 0 | 0 | 0 | 0 | 1 |

14.34.8.27 ISRXON

Function: Enable and calibrate frequency synthesizer for RX

Description: The ISRXON instruction immediately enables and calibrates frequency synthesizer for RX. The instruction waits for the radio to acknowledge the command before executing the next instruction.

Operation: SRXON

Opcode: 0xE2

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 1 | 0 | 0 | 0 | 1 | 0 |

14.34.8.28 ISTXON

Function: Enable TX after calibration

Description: The ISTXON instruction immediately enables TX after calibration. The instruction waits for the radio to acknowledge the command before executing the next instruction.

Operation: STXON_STRB

Opcode: 0xE3

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 1 | 0 | 0 | 0 | 1 | 1 |

14.34.8.29 ISTXONCCA

Function: Enable calibration and TX if CCA indicates a clear channel

Description: The ISTXONCCA instruction immediately enables TX after calibration if CCA indicates a clear channel. The instruction waits for the radio to acknowledge the command before executing the next instruction.

Operation: STXONCCA

Opcode: 0xE4

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 1 | 0 | 0 | 1 | 0 | 0 |

14.34.8.30 *ISRFOFF*

Function: Disable RX/TX and frequency synthesizer.

Description: The ISRFOFF instruction immediately disables RX/TX and frequency synthesizer. The instruction waits for the radio to acknowledge the command before executing the next instruction.

Operation:
FFCTL_SRFOFF_STRB=1

Opcode: 0xE5

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 1 | 0 | 0 | 1 | 0 | 1 |

14.34.8.31 *ISFLUSHRX*

Function: Flush RXFIFO buffer and reset demodulator

Description: The ISFLUSHRX instruction immediately flushes the RXFIFO buffer and resets the demodulator. The instruction waits for the radio to acknowledge the command before executing the next instruction.

Operation: SFLUSHRX

Opcode: 0xE6

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 1 | 0 | 0 | 1 | 1 | 0 |

14.34.8.32 *ISFLUSHTX*

Function: Flush TXFIFO buffer

Description: The ISFLUSHTX instruction immediately flushes the

TXFIFO buffer. The instruction waits for the radio to acknowledge the command before executing the next instruction.

Operation: SFLUSHTX

Opcode: 0xE7

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 1 | 0 | 0 | 1 | 1 | 1 |

14.34.8.33 *ISACK*

Function: Send acknowledge frame with pending field cleared

Description: The ISACK instruction immediately sends an acknowledge frame. The instruction waits for the radio to receive and interpret the command before executing the next instruction.

Operation: SACK

Opcode: 0xE8

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 1 | 0 | 1 | 0 | 0 | 0 |

14.34.8.34 *ISACKPEND*

Function: Send acknowledge frame with pending field set

Description: The ISACKPEND instruction immediately sends an acknowledge frame with pending field set. The instruction waits for the radio to receive and interpret the command before executing the next instruction.

Operation: SACKPEND

Opcode: 0xE9

| 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---|---|---|---|---|---|---|
| 1 | 1 | 1 | 0 | 1 | 0 | 0 | 1 |

14.35 Radio Registers

This section describes all RF registers used for control and status for the radio. The RF registers reside in XDATA memory space. Table 45 gives an overview of

register addresses while the remaining tables in this section describe each register. Refer also to section 3 for Register conventions.

Table 45 : Overview of RF registers

| XDATA Address | Register name | Description |
|---------------|---------------|------------------------------------------------|
| 0xDF00-0xDF01 | - | Reserved |
| 0xDF02 | MDMCTRL0H | Modem Control 0, high |
| 0xDF03 | MDMCTRL0L | Modem Control 0, low |
| 0xDF04 | MDMCTRL1H | Modem Control 1, high |
| 0xDF05 | MDMCTRL1L | Modem Control 1, low |
| 0xDF06 | RSSIH | RSSI and CCA Status and Control, high |
| 0xDF07 | RSSIL | RSSI and CCA Status and Control, low |
| 0xDF08 | SYNCWORDH | Synchronisation Word Control, high |
| 0xDF09 | SYNCWORDL | Synchronisation Word Control, low |
| 0xDF0A | TXCTRLH | Transmit Control, high |
| 0xDF0B | TXCTRL | Transmit Control, low |
| 0xDF0C | RXCTRL0H | Receive Control 0, high |
| 0xDF0D | RXCTRL0L | Receive Control 0, low |
| 0xDF0E | RXCTRL1H | Receive Control 1, high |
| 0xDF0F | RXCTRL1L | Receive Control 1, low |
| 0xDF10 | FSCTRLH | Frequency Synthesizer Control and Status, high |
| 0xDF11 | FSCTRL | Frequency Synthesizer Control and Status, low |
| 0xDF12 | CSPX | CSP X Data |
| 0xDF13 | CSPY | CSP Y Data |
| 0xDF14 | CSPZ | CSP Z Data |
| 0xDF15 | CSPCTRL | CSP Control |
| 0xDF16 | CSPT | CSP T Data |
| 0xDF17 | RFPWR | RF Power Control |
| 0xDF20 | FSMTCH | Finite State Machine Time Constants, high |
| 0xDF21 | FSMTCL | Finite State Machine Time Constants, low |
| 0xDF22 | MANANDH | Manual AND Override, high |
| 0xDF23 | MANANDL | Manual AND Override, low |
| 0xDF24 | MANORH | Manual OR Override, high |
| 0xDF25 | MANORL | Manual OR Override, low |
| 0xDF26 | AGCCTRLH | AGC Control, high |
| 0xDF27 | AGCCTRL | AGC Control, low |
| 0xDF28- | - | Reserved |

| XDATA Address | Register name | Description |
|---------------|---------------|-----------------------------------|
| 0xDF38 | | |
| 0xDF39 | FSMSTATE | Finite State Machine State Status |
| 0xDF3A | ADCTSTH | ADC Test, high |
| 0xDF3B | ADCTSTL | ADC Test, low |
| 0xDF3C | DACTSTH | DAC Test, high |
| 0xDF3D | DACTSTL | DAC Test, low |
| 0xDF3E | - | Reserved |
| 0xDF3F | - | Reserved |
| 0xDF40 | - | Reserved |
| 0xDF41 | - | Reserved |
| 0xDF43 | IEEE_ADDR0 | IEEE Address 0 (LSB) |
| 0xDF44 | IEEE_ADDR1 | IEEE Address 1 |
| 0xDF45 | IEEE_ADDR2 | IEEE Address 2 |
| 0xDF46 | IEEE_ADDR3 | IEEE Address 3 |
| 0xDF47 | IEEE_ADDR4 | IEEE Address 4 |
| 0xDF48 | IEEE_ADDR5 | IEEE Address 5 |
| 0xDF49 | IEEE_ADDR6 | IEEE Address 6 |
| 0xDF4A | IEEE_ADDR7 | IEEE Address 7 (MSB) |
| 0xDF4B | PANIDH | PAN Identifier, high |
| 0xDF4C | PANIDL | PAN Identifier, low |
| 0xDF4D | SHORTADDRH | Short Address, high |
| 0xDF4E | SHORTADDRL | Short Address, low |
| 0xDF4F | IOCFG0 | I/O Configuration 0 |
| 0xDF50 | IOCFG1 | I/O Configuration 1 |
| 0xDF51 | IOCFG2 | I/O Configuration 2 |
| 0xDF52 | IOCFG3 | I/O Configuration 3 |
| 0xDF53 | RXFIFOCNT | RX FIFO Count |
| 0xDF54 | FSMTC1 | Finite State Machine Control |
| 0xDF55-0xDF5F | - | Reserved |
| 0xDF60 | CHVER | Chip Version |
| 0xDF61 | CHIPID | Chip Identification |
| 0xDF62 | RFSTATUS | RF Status |
| 0xDF63 | XOSC32M | 32 MHz Crystal Oscillator Control |
| 0xDF64 | IRQSRC | RF Interrupt Source |

The RF registers shown in Table 46 are reserved for test purposes. The values for these registers should be obtained from SmartRF[®] Studio (see section 17 on page 219) and should not be changed.

Table 46 : Overview of RF test registers

| XDATA Address | Register name | Reset value |
|---------------|---------------|-------------|
|---------------|---------------|-------------|

| XDATA Address | Register name | Reset value |
|---------------|---------------|-------------|
| 0xDF28 | AGCTST0H | 0x36 |
| 0xDF29 | AGCTST0L | 0x49 |
| 0xDF2A | AGCTST1H | 0x08 |
| 0xDF2B | AGCTST1L | 0x54 |
| 0xDF2C | AGCTST2H | 0x09 |
| 0xDF2D | AGCTST2L | 0x0A |
| 0xDF2E | FSTST0H | 0x10 |
| 0xDF2F | FSTST0L | 0x00 |
| 0xDF30 | FSTST1H | 0x40 |
| 0xDF31 | FSTST1L | 0x32 |
| 0xDF32 | FSTST2H | 0x20 |
| 0xDF33 | FSTST2L | 0x00 |
| 0xDF34 | FSTST3H | 0x92 |
| 0xDF35 | FSTST3L | 0xDD |
| 0xDF37 | RXBPFTSTH | 0x00 |
| 0xDF38 | RXBPFTSTL | 0x00 |
| 0xDF3F | TOPTST | 0x10 |
| 0xDF40 | RESERVEDH | 0x00 |
| 0xDF41 | RESERVEDL | 0x00 |

|

| Bit | Name | Reset | R/W | Function |
|-----|---------------------|-------|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:6 | FRAMET_FILT | 00 | R/W | <p>These bits are used to perform special operations on the frame type field of a received packet. These operations do not influence the packet that is written to the RXFIFO.</p> <p>00 : Leave frame type as it is.</p> <p>01 : Invert MSB of frame type.</p> <p>10 : Set MSB of frame type to 0.</p> <p>11 : Set MSB of frame type to 1.</p> <p>For IEEE 802.15.4 compliant operation these bits should always be set to 00.</p> |
| 5 | RESERVED_FRAME_MODE | 0 | R/W | <p>Mode for accepting reserved IEEE 802.15.4 frame types when address recognition is enabled (MDMCTRL0.ADDR_DECODE = 1).</p> <p>0 : Reserved frame types (100, 101, 110, 111) are rejected by address recognition.</p> <p>1 : Reserved frame types (100, 101, 110, 111) are always accepted by address recognition. No further address decoding is done.</p> <p>When address recognition is disabled (MDMCTRL0.ADDR_DECODE = 0), all frames are received and RESERVED_FRAME_MODE is don't care.</p> <p>For IEEE 802.15.4 compliant operation these bits should always be set to 00.</p> |
| 4 | PAN_COORDINATOR | 0 | R/W | <p>PAN Coordinator enable. Used for filtering packets with no destination address, as specified in section 7.5.6.2 in 802.15.4 [1]</p> <p>0 : Device is not a PAN Coordinator</p> <p>1 : Device is a PAN Coordinator</p> |
| 3 | ADDR_DECODE | 1 | R/W | <p>Hardware Address decode enable.</p> <p>0 : Address decoding is disabled</p> <p>1 : Address decoding is enabled</p> |
| 2:0 | CCA_HYST[2:0] | 010 | R/W | CCA Hysteresis in dB, values 0 through 7 dB |

Table 47: Register MDMCTRL0H (0xDF02)

| Bit | Name | Reset | R/W | Description |
|-----|----------------------|-------|-----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:6 | CCA_MODE[1:0] | 11 | R/W | Clear Channel Assessment mode select. 00 : Reserved 01 : CCA=1 when RSSI < CCA_THR-CCA_HYST CCA=0 when RSSI >= CCA_THR 10 : CCA=1 when not receiving a packet 11 : CCA=1 when RSSI < CCA_THR-CCA_HYST and not receiving a packet CCA=0 when RSSI >= CCA_THR or receiving a packet |
| 5 | AUTOCRC | 1 | R/W | In packet mode a CRC-16 (ITU-T) is calculated and is transmitted after the last data byte in TX. In RX CRC is calculated and checked for validity. |
| 4 | AUTOACK | 0 | R/W | If AUTOACK is enabled, all packets accepted by address recognition with the acknowledge request flag set and a valid CRC are acknowledged 12 symbol periods after being received if MDMCTRL1H.SLOTTED_ACK = 0. Acknowledgment is at the beginning of the first backoff slot more than 12 symbol periods after the end of the received frame if the MDMCTRL1H.SLOTTED_ACK = 1 0 : AUTOACK disabled 1 : AUTOACK enabled |
| 3:0 | PREAMBLE_LENGTH[3:0] | 0010 | R/W | The number of preamble bytes (2 zero-symbols) to be sent in TX mode prior to the SYNCWORD. The reset value of 0010 is compliant with IEEE 802.15.4, since the 4 th zero byte is included in the SYNCWORD. 0000 : 1 leading zero bytes (not recommended) 0001 : 2 leading zero bytes (not recommended) 0010 : 3 leading zero bytes (IEEE 802.15.4 compliant) 0011 : 4 leading zero bytes ... 1111 : 16 leading zero bytes |

Table 48: Register MDMCTRL0L (0xDF03)

| Bit | Name | Reset | R/W | Description |
|-----|---------------|-------|-----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | SLOTTED_ACK | 0 | R/W | SLOTTED_ACK defines the timing of automatically transmitted acknowledgment frames. 0 : The acknowledgment frame is transmitted 12 symbol periods after the incoming frame. 1 : The acknowledgment frame is transmitted between 12 and 30 symbol periods after the incoming frame. The timing is defined such that there is an integer number of 20-symbol periods between the received and the transmitted SFDs. This may be used to transmit slotted acknowledgment frames in a beacon enabled network. |
| 6 | – | 0 | R/W | Reserved |
| 5 | CORR_THR_SFD | 1 | R/W | CORR_THR_SFD defines the level at which the CORR_THR correlation threshold is used to filter out received frames. 0 : Same filtering as CC2420, should be combined with a CORR_THR of 0x14 1 : More extensive filtering is performed, which will result in less false frame detections e.g. caused by noise. |
| 4:0 | CORR_THR[4:0] | 0x10 | R/W | Demodulator correlator threshold value, required before SFD search. |

Table 49: Register MDMCTRL1H (0xDF04)

| Bit | Name | Reset | R/W | Description |
|-----|-----------------|-------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:6 | – | 00 | R0 | Reserved, read as 0. |
| 5 | DEMOD_AVG_MODE | 0 | R/W | DC average filter behavior. 0 : Lock DC level to be removed after preamble match 1 : Continuously update DC average level. |
| 4 | MODULATION_MODE | 0 | R/W | Set one of two RF modulation modes for RX / TX 0 : IEEE 802.15.4 compliant mode 1 : Reversed phase, non-IEEE compliant (could be used to set up a system which will not receive 802.15.4 packets) |
| 3:2 | TX_MODE[1:0] | 00 | R/W | Set test modes for TX 00 : Normal operation, transmit TXFIFO 01 : Serial mode, use transmit data on serial interface, infinite transmission. 10 : TXFIFO looping ignore underflow in TXFIFO and read cyclic, infinite transmission. 11 : Send random data from CRC, infinite transmission. |
| 1:0 | RX_MODE[1:0] | 00 | R/W | Set test mode of RX 00 : Normal operation, use RXFIFO 01 : Receive serial mode, output received data on pins. Infinite RX. 10 : RXFIFO looping ignore overflow in RXFIFO and write cyclic, infinite reception. 11 : Reserved |

Table 50: Register MDMCTRL1L (0xDF05)

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | CCA_THR[7:0] | 0xE0 | R/W | Clear Channel Assessment threshold value, signed number in 2's complement for comparison with the RSSI. The unit is 1 dB, offset is TBD [depends on the absolute gain of the RX chain, including external components and should be measured]. The CCA signal goes high when the received signal is below this value. The reset value is in the range of -70 dBm. |

Table 51: Register RSSIH (0xDF06)

| Bit | Name | Reset | R/W | Description |
|-----|---------------|-------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | RSSI_VAL[7:0] | 0x00 | R | RSSI estimate on a logarithmic scale, signed number in 2's complement. Unit is 1 dB, offset is TBD [depends on the absolute gain of the RX chain, including external components, and should be measured]. The RSSI value is averaged over 8 symbol periods. |

Table 52: Register RSSIL (0xDF07)

| Bit | Name | Reset | R/W | Description |
|-----|----------------|-------|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | SYNCWORD[15:8] | 0xA7 | R/W | <p>Synchronization word. The SYNCWORD is processed from the least significant nibble (F at reset) to the most significant nibble (A at reset).</p> <p>SYNCWORD is used both during modulation (where 0xF's are replaced with 0x0's) and during demodulation (where 0xF's are not required for frame synchronization). In reception an implicit zero is required before the first symbol required by SYNCWORD.</p> <p>The reset value is compliant with IEEE 802.15.4.</p> |

Table 53: Register SYNCWORDH (0xDF08)

| Bit | Name | Reset | R/W | Description |
|-----|---------------|-------|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | SYNCWORD[7:0] | 0x0F | R/W | <p>Synchronization word. The SYNCWORD is processed from the least significant nibble (F at reset) to the most significant nibble (A at reset).</p> <p>SYNCWORD is used both during modulation (where 0xF's are replaced with 0x0's) and during demodulation (where 0xF's are not required for frame synchronization). In reception an implicit zero is required before the first symbol required by SYNCWORD.</p> <p>The reset value is compliant with IEEE 802.15.4.</p> |

Table 54: Register SYNCWORDL (0xDF09)

| Bit | Name | Reset | R/W | Description |
|-----|----------------------|-------|-----|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:6 | TXMIXBUF_CUR[1:0] | 10 | R/W | <p>TX mixer buffer bias current.</p> <p>00 : 690 uA 01 : 980 uA 10 : 1.16 mA (nominal) 11 : 1.44 mA</p> |
| 5 | TX_TURNAROUND | 1 | R/W | <p>Sets the wait time after STXON before transmission is started.</p> <p>0 : 8 symbol periods (128 us) 1 : 12 symbol periods (192 us)</p> |
| 4:3 | TXMIX_CAP_ARRAY[1:0] | 0 | R/W | Selects varactor array settings in the transmit mixers. |
| 2:1 | TXMIX_CURRENT[1:0] | 0 | R/W | <p>Transmit mixers current:</p> <p>00 : 1.72 mA 01 : 1.88 mA 10 : 2.05 mA 11 : 2.21 mA</p> |
| 0 | PA_DIFF | 1 | R/W | <p>Power Amplifier (PA) output select. Selects differential or single-ended PA output.</p> <p>0 : Single-ended output 1 : Differential output</p> |

Table 55: Register TXCTRLH (0xDF0A)

| Bit | Name | Reset | R/W | Description |
|-----|-----------------|-------|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:5 | PA_CURRENT[2:0] | 011 | R/W | Current programming of the PA 000 : -3 current adjustment 001 : -2 current adjustment 010 : -1 current adjustment 011 : Nominal setting 100 : +1 current adjustment 101 : +2 current adjustment 110 : +3 current adjustment 111 : +4 current adjustment |
| 4:0 | PA_LEVEL[4:0] | 0x1F | R/W | Output PA level. (~0 dBm) |

Table 56: Register TXCTRL (0xDF0B)

| Bit | Name | Reset | R/W | Description |
|-----|--------------------|-------|-----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:6 | – | 00 | R0 | Reserved, read as 0. |
| 5:4 | RXMIXBUFF_CUR[1:0] | 01 | R/W | RX mixer buffer bias current. 00 : 690 μ A 01 : 980 μ A (nominal) 10 : 1.16 mA 11 : 1.44 mA |
| 3:2 | HIGH_LNA_GAIN[1:0] | 0 | R/W | Controls current in the LNA gain compensation branch in AGC High gain mode. 00 : Compensation disabled 01 : 100 μ A compensation current 10 : 300 μ A compensation current (Nominal) 11 : 1000 μ A compensation current |
| 1:0 | MED_LNA_GAIN[1:0] | 10 | R/W | Controls current in the LNA gain compensation branch in AGC Med gain mode. |

Table 57: Register RXCTRL0H (0xDF0C)

| Bit | Name | Reset | R/W | Description |
|-----|-----------------------|-------|-----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:6 | LOW_LNA_GAIN[1:0] | 11 | R/W | Controls current in the LNA gain compensation branch in AGC Low gain mode |
| 5:4 | HIGH_LNA_CURRENT[1:0] | 10 | R/W | Controls main current in the LNA in AGC High gain mode 00 : 240 μ A LNA current (x2) 01 : 480 μ A LNA current (x2) 10 : 640 μ A LNA current (x2) 11 : 1280 μ A LNA current (x2) |
| 3:2 | MED_LNA_CURRENT[1:0] | 01 | R/W | Controls main current in the LNA in AGC Med gain mode |
| 1:0 | LOW_LNA_CURRENT[1:0] | 01 | R/W | Controls main current in the LNA in AGC Low gain mode |

Table 58: Register RXCTRL0L (0xDF0D)

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|--------------------------------------------------------------------------------------------------------|
| 7:6 | – | 0 | R0 | Reserved, read as 0. |
| 5 | RXBPF_LOCUR | 1 | R/W | Controls reference bias current to RX band-pass filters: 0 : 4 μ A 1 : 3 μ A (Default) |
| 4 | RXBPF_MIDCUR | 0 | R/W | Controls reference bias current to RX band-pass filters: 0 : 4 μ A (Default) 1 : 3.5 μ A |
| 3 | LOW_LOWGAIN | 1 | R/W | LNA low gain mode setting in AGC low gain mode. |
| 2 | MED_LOWGAIN | 0 | R/W | LNA low gain mode setting in AGC medium gain mode. |
| 1 | HIGH_HGM | 1 | R/W | RX Mixers high gain mode setting in AGC high gain mode. |
| 0 | MED_HGM | 0 | R/W | RX Mixers high gain mode setting in AGC medium gain mode. |

Table 59: Register RXCTRL1H (0xDF0E)

| Bit | Name | Reset | R/W | Description |
|-----|--------------------|-------|-----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:6 | LNA_CAP_ARRAY[1:0] | 01 | R/W | Selects varactor array setting in the LNA 00 : OFF 01 : 0.1 pF (x2) (Nominal) 10 : 0.2 pF (x2) 11 : 0.3 pF (x2) |
| 5:4 | RXMIX_TAIL[1:0] | 01 | R/W | Control of the receiver mixers output current. 00 : 12 μ A 01 : 16 μ A (Nominal) 10 : 20 μ A 11 : 24 μ A |
| 3:2 | RXMIX_VCM[1:0] | 01 | R/W | Controls VCM level in the mixer feedback loop 00 : 8 μ A mixer current 01 : 12 μ A mixer current (Nominal) 10 : 16 μ A mixer current 11 : 20 μ A mixer current |
| 1:0 | RXMIX_CURRENT[1:0] | 10 | R/W | Controls current in the mixer 00 : 360 μ A mixer current (x2) 01 : 720 μ A mixer current (x2) 10 : 900 μ A mixer current (x2) (Nominal) 11 : 1260 μ A mixer current (x2) |

Table 60: Register RXCTRL1L (0xDF0F)

| Bit | Name | Reset | R/W | Description |
|-----|---------------|----------------------|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:6 | LOCK_THR[1:0] | 01 | R/W | Number of consecutive reference clock periods with successful sync windows required to indicate lock: 00 : 64 01 : 128 10 : 256 11 : 512 |
| 5 | CAL_DONE | 0 | R | Frequency synthesizer calibration done. 0 : Calibration not performed since the last time the FS was turned on. 1 : Calibration performed since the last time the FS was turned on. |
| 4 | CAL_RUNNING | 0 | R | Calibration status, '1' when calibration in progress. |
| 3 | LOCK_LENGTH | 0 | R/W | LOCK_WINDOW pulse width: 0: 2 CLK_PRE periods 1: 4 CLK_PRE periods |
| 2 | LOCK_STATUS | 0 | R | PLL lock status 0 : PLL is not in lock 1 : PLL is in lock |
| 1:0 | FREQ[9:8] | 01 (2405 MHz) | R/W | Frequency control word. Used directly in TX, in RX the LO frequency is automatically set 2 MHz below the RF frequency. $\text{Frequency division} = \frac{2048 + \text{FREQ}[9:0]}{4} \Leftrightarrow$ $f_{RF} = (2048 + \text{FREQ}[9:0]) \text{ MHz}$ $f_{LO} = (2048 + \text{FREQ}[9:0] - 2 \cdot \text{RXEN}) \text{ MHz}$ |

Table 61: Register FSCTRLH (0xDF10)

| Bit | Name | Reset | R/W | Description |
|-----|-----------|------------------------|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | FREQ[7:0] | 0x65 (2405 MHz) | R/W | Frequency control word. Used directly in TX, in RX the LO frequency is automatically set 2 MHz below the RF frequency. $\text{Frequency division} = \frac{2048 + \text{FREQ}[9:0]}{4} \Leftrightarrow$ $f_{RF} = (2048 + \text{FREQ}[9:0]) \text{ MHz}$ $f_{LO} = (2048 + \text{FREQ}[9:0] - 2 \cdot \text{RXEN}) \text{ MHz}$ |

Table 62: Register FSCTRLH (0xDF11)

| Bit | Name | Reset | R/W | Description |
|-----|------|-------|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | CSPT | 0x00 | R/W | CSP T Data register. Contents is decremented each time MAC Timer overflows while CSP program is running. CSP program stops when is about to count to 0. Setting T=0xFF disables decrement function. |

Table 63: Register CSPT (0xDF16)

| Bit | Name | Reset | R/W | Description |
|-----|------|-------|-----|-----------------------------------------------------------------------------|
| 7:0 | CSPX | 0x00 | R/W | CSP X Data register. Used by CSP WAITX, RANDXY and conditional instructions |

Table 64: Register CSPX (0xDF12)

| Bit | Name | Reset | R/W | Description |
|-----|------|-------|-----|-------------------------------------------------------------------------------------------|
| 7:0 | CSPY | 0x00 | R/W | CSP Y Data register. Used by CSP INCY, DECY, INCMAXY, RANDXY and conditional instructions |

Table 65: Register CSPY (0xDF13)

| Bit | Name | Reset | R/W | Description |
|-----|------|-------|-----|--------------------------------------------------------------------|
| 7:0 | CSPZ | 0x00 | R/W | CSP Z Data register. Used by CSP DECZ and conditional instructions |

Table 66: Register CSPZ (0xDF14)

| Bit | Name | Reset | R/W | Description |
|-----|----------|-------|-----|--------------------------------------------------------------|
| 7:1 | – | 0x00 | R0 | Reserved, read as 0 |
| 0 | CPU_CTRL | 0 | R/W | CSP CPU control input. Used by CSP conditional instructions. |

Table 67: Register CSPCTRL (0xDF15)

| Bit | Name | Reset | R/W | Description | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|-----------------|-----------------|-------|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|-------|-------|-----|---|----|-----|----|----|-----|----|----|-----|-----|----|-----|-----|----|-----|-----|----|-----|------|----|-----|------|----|
| 7:5 | – | 0 | R0 | Reserved, read as 0. | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | ADI_RADIO_PD | 0 | R | ADI_RADIO_PD is a delayed version of RREG_RADIO_PD. The delay is set by RREG_DELAY[2:0]. When ADI_RADIO_PD is 0, all analog modules in the radio are set in power down. ADI_RADIO_PD is read only. | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | RREG_RADIO_PD | 1 | R / W | Power down of the voltage regulator to the analog part of the radio. This signal is used to enable or disable the analog radio. 0 : Power up 1 : Power down | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2:0 | RREG_DELAY[2:0] | 100 | R / W | Delay value used in power-on for voltage regulator <table><thead><tr><th>VREG_DELAY[2:0]</th><th>Delay</th><th>Units</th></tr></thead><tbody><tr><td>000</td><td>0</td><td>μs</td></tr><tr><td>001</td><td>31</td><td>μs</td></tr><tr><td>010</td><td>63</td><td>μs</td></tr><tr><td>011</td><td>125</td><td>μs</td></tr><tr><td>100</td><td>250</td><td>μs</td></tr><tr><td>101</td><td>500</td><td>μs</td></tr><tr><td>110</td><td>1000</td><td>μs</td></tr><tr><td>111</td><td>2000</td><td>μs</td></tr></tbody></table> | VREG_DELAY[2:0] | Delay | Units | 000 | 0 | μs | 001 | 31 | μs | 010 | 63 | μs | 011 | 125 | μs | 100 | 250 | μs | 101 | 500 | μs | 110 | 1000 | μs | 111 | 2000 | μs |
| VREG_DELAY[2:0] | Delay | Units | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 000 | 0 | μs | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 001 | 31 | μs | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 010 | 63 | μs | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 011 | 125 | μs | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 100 | 250 | μs | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 101 | 500 | μs | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 110 | 1000 | μs | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 111 | 2000 | μs | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Table 68: Register RFPWR (0xDF17)

| Bit | Name | Reset | R/W | Description |
|-----|--------------------|-------|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:5 | TC_RXCHAIN2RX[2:0] | 011 | R/W | The time in 5 μs steps between the time the RX chain is enabled and the demodulator and AGC is enabled. The RX chain is started when the band pass filter has been calibrated (after 6.5 symbol periods). |
| 4:2 | TC_SWITCH2TX[2:0] | 110 | R/W | The time in advance the RXTX switch is set high, before enabling TX. Unit is μs. |
| 1:0 | TC_PAON2TX[3:2] | 10 | R/W | The time in advance the PA is powered up before enabling TX. Unit is μs. |

Table 69: Register FSMTCH (0xDF20)

| Bit | Name | Reset | R/W | Description |
|-----|----------------------|-------|-----|----------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:6 | TC_PAON2TX[1:0] | 10 | R/W | The time in advance the PA is powered up before enabling TX. Unit is μs. |
| 5:3 | TC_TXEND2SWITCH[2:0] | 010 | R/W | The time after the last chip in the packet is sent, and the rtx switch is disabled. Unit is μs. |
| 2:0 | TC_TXEND2PAOFF[2:0] | 100 | R/W | The time after the last chip in the packet is sent, and the PA is set in power-down. Also the time at which the modulator is disabled. Unit is μs. |

Table 70: Register FSMTCL (0xDF21)

| Bit | Name | Reset | R/W | Description |
|-----|-------------|-------|-----|---------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | VGA_RESET_N | 1 | R/W | The VGA_RESET_N signal is used to reset the peak detectors in the VGA in the RX chain. |
| 6 | BIAS_PD | 1 | R/W | Reserved, read as 0 |
| 5 | BALUN_CTRL | 1 | R/W | The BALUN_CTRL signal controls whether the PA should receive its required external biasing (1) or not (0) by controlling the RX/TX output switch. |
| 4 | RXTX | 1 | R/W | RXTX signal: controls whether the LO buffers (0) or PA buffers (1) should be used. |
| 3 | PRE_PD | 1 | R/W | Powerdown of prescaler. |
| 2 | PA_N_PD | 1 | R/W | Powerdown of PA (negative path). |
| 1 | PA_P_PD | 1 | R/W | Powerdown of PA (positive path). When PA_N_PD=1 and PA_P_PD=1 the up conversion mixers are in powerdown. |
| 0 | DAC_LPF_PD | 1 | R/W | Powerdown of TX DACs. |

Table 71: Register MANANDH (0xDF22)

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|-------------------------------------------------------------------------------|
| 7 | – | 0 | R0 | Reserved, read as 0 |
| 6 | RXBPF_CAL_PD | 1 | R/W | Powerdown control of complex band pass receive filter calibration oscillator. |
| 5 | CHP_PD | 1 | R/W | Powerdown control of charge pump. |
| 4 | FS_PD | 1 | R/W | Powerdown control of VCO, I/Q generator, LO buffers. |
| 3 | ADC_PD | 1 | R/W | Powerdown control of the ADCs. |
| 2 | VGA_PD | 1 | R/W | Powerdown control of the VGA. |
| 1 | RXBPF_PD | 1 | R/W | Powerdown control of complex band pass receive filter. |
| 0 | LNAMIX_PD | 1 | R/W | Powerdown control of LNA, down conversion mixers and front-end bias. |

Table 72: Register MANANDL (0xDF23)

| Bit | Name | Reset | R/W | Description |
|-----|-------------|-------|-----|---------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | VGA_RESET_N | 0 | R/W | The VGA_RESET_N signal is used to reset the peak detectors in the VGA in the RX chain. |
| 6 | BIAS_PD | 0 | R/W | Global Bias power down (1) |
| 5 | BALUN_CTRL | 0 | R/W | The BALUN_CTRL signal controls whether the PA should receive its required external biasing (1) or not (0) by controlling the RX/TX output switch. |
| 4 | RXTX | 0 | R/W | RXTX signal: controls whether the LO buffers (0) or PA buffers (1) should be used. |
| 3 | PRE_PD | 0 | R/W | Powerdown of prescaler. |
| 2 | PA_N_PD | 0 | R/W | Powerdown of PA (negative path). |
| 1 | PA_P_PD | 0 | R/W | Powerdown of PA (positive path). When PA_N_PD=1 and PA_P_PD=1 the up conversion mixers are in powerdown. |
| 0 | DAC_LPF_PD | 0 | R/W | Powerdown of TX DACs. |

Table 73: Register MANORH (0xDF24)

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|-------------------------------------------------------------------------------|
| 7 | – | 0 | R0 | Reserved, read as 0 |
| 6 | RXBPF_CAL_PD | 0 | R/W | Powerdown control of complex band pass receive filter calibration oscillator. |
| 5 | CHP_PD | 0 | R/W | Powerdown control of charge pump. |
| 4 | FS_PD | 0 | R/W | Powerdown control of VCO, I/Q generator, LO buffers. |
| 3 | ADC_PD | 0 | R/W | Powerdown control of the ADCs. |
| 2 | VGA_PD | 0 | R/W | Powerdown control of the VGA. |
| 1 | RXBPF_PD | 0 | R/W | Powerdown control of complex band pass receive filter. |
| 0 | LNAMIX_PD | 0 | R/W | Powerdown control of LNA, down conversion mixers and front-end bias. |

Table 74: Register MANORL (0xDF25)

| Bit | Name | Reset | R/W | Description |
|-----|---------------|-------|-----|-----------------------------------------------------------------------------------------------|
| 7 | VGA_GAIN_OE | 0 | R/W | Use the VGA_GAIN value during RX instead of the AGC value. |
| 6:0 | VGA_GAIN[6:0] | 0x7F | R/W | When written, VGA manual gain override value; when read, the currently used VGA gain setting. |

Table 75: Register AGCCTRLH (0xDF26)

| Bit | Name | Reset | R/W | Description |
|-----|-------------------------|-------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:4 | – | 0 | R0 | Reserved, read as 0. |
| 3:2 | LNAMIX_GAINMODE_O [1:0] | 00 | R/W | LNA / Mixer Gain mode override setting 00 : Gain mode is set by AGC algorithm 01 : Gain mode is always low-gain 10 : Gain mode is always med-gain 11 : Gain mode is always high-gain |
| 1:0 | LNAMIX_GAINMODE[1:0] | 00 | R | Status bit, defining the currently selected gain mode selected by the AGC or overridden by the LNAMIX_GAINMODE_O setting. |

Table 76: Register AGCCTRL (0xDF27)

| Bit | Name | Reset | R/W | Description |
|-----|-----------------------|-------|-----|--------------------------------------------------------------------------------------|
| 7:6 | – | 0 | R0 | Reserved, read as 0. |
| 5:0 | FSM_FFCTRL_STATE[5:0] | – | R | Gives the current state of the FIFO and Frame Control (FFCTRL) finite state machine. |

Table 77: Register FSMSTATE (0xDF39)

| Bit | Name | Reset | R/W | Function |
|-----|-------------------|-------|-----|-------------------------------------------------------------------------------------------------------|
| 7 | ADC_CLOCK_DISABLE | 0 | R/W | ADC Clock Disable 0 : Clock enabled when ADC enabled 1 : Clock disabled, even if ADC is enabled |
| 6:0 | ADC_I[6:0] | – | R | Returns the current ADC I-branch value. |

Table 78: Register ADCTSTH (0xDF3A)

| Bit | Name | Reset | R/W | Function |
|-----|------------|-------|-----|-----------------------------------------|
| 7 | – | 0 | R0 | Reserved, read as 0. |
| 6:0 | ADC_Q[6:0] | – | R | Returns the current ADC Q-branch value. |

Table 79: Register ADCTSTL (0xDF3B)

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7 | – | 0 | R0 | Reserved, read as 0. |
| 6:4 | DAC_SRC[2:0] | 000 | R/W | The TX DACs data source is selected by DAC_SRC according to: 000 : Normal operation (from modulator). 001 : The DAC_I_O and DAC_Q_O override values below.- 010 : From ADC, most significant bits 011 : I/Q after digital down mix and channel filtering. 100 : Full-spectrum White Noise (from CRC) 101 : From ADC, least significant bits 110 : RSSI / Cordic Magnitude Output 111 : HSSD module. This feature will often require the DACs to be manually turned on in MANOVR and PAMTST.ATESTMOD_MODE=4. |
| 3:0 | DAC_I_O[5:2] | 000 | R/W | I-branch DAC override value. |

Table 80: Register DACTSTH (0xDF3C)

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|------------------------------|
| 7:6 | DAC_I_O[1:0] | 00 | R/W | I-branch DAC override value. |
| 5:0 | DAC_Q_O[5:0] | 0x00 | R/W | Q-branch DAC override value. |

Table 81: Register DACTSTL (0xDF3D)

| Bit | Name | Reset | R/W | Description |
|-----|-----------------|-------|-----|------------------------|
| 7:0 | IEEE_ADDR0[7:0] | 0x00 | R/W | IEEE ADDR byte 0 (LSB) |

Table 82: Register IEEE_ADDR0 (0xDF43)

| Bit | Name | Reset | R/W | Description |
|-----|-----------------|-------|-----|------------------|
| 7:0 | IEEE_ADDR1[7:0] | 0x00 | R/W | IEEE ADDR byte 1 |

Table 83: Register IEEE_ADDR1 (0xDF44)

| Bit | Name | Reset | R/W | Description |
|-----|-----------------|-------|-----|------------------|
| 7:0 | IEEE_ADDR2[7:0] | 0x00 | R/W | IEEE ADDR byte 2 |

Table 84: Register IEEE_ADDR2 (0xDF45)

| Bit | Name | Reset | R/W | Description |
|-----|-----------------|-------|-----|------------------|
| 7:0 | IEEE_ADDR3[7:0] | 0x00 | R/W | IEEE ADDR byte 3 |

Table 85: Register IEEE_ADDR3 (0xDF46)

| Bit | Name | Reset | R/W | Description |
|-----|-----------------|-------|-----|------------------|
| 7:0 | IEEE_ADDR4[7:0] | 0x00 | R/W | IEEE ADDR byte 4 |

Table 86: Register IEEE_ADDR4 (0xDF47)

| Bit | Name | Reset | R/W | Description |
|-----|-----------------|-------|-----|------------------|
| 7:0 | IEEE_ADDR5[7:0] | 0x00 | R/W | IEEE ADDR byte 5 |

Table 87: Register IEEE_ADDR5 (0xDF48)

| Bit | Name | Reset | R/W | Description |
|-----|-----------------|-------|-----|------------------|
| 7:0 | IEEE_ADDR6[7:0] | 0x00 | R/W | IEEE ADDR byte 6 |

Table 88: Register IEEE_ADDR6 (0xDF49)

| Bit | Name | Reset | R/W | Description |
|-----|-----------------|-------|-----|------------------------|
| 7:0 | IEEE_ADDR7[7:0] | 0x00 | R/W | IEEE ADDR byte 7 (MSB) |

Table 89: Register IEEE_ADDR7 (0xDF4A)

| Bit | Name | Reset | R/W | Description |
|-----|-------------|-------|-----|--------------------------|
| 7:0 | PANIDH[7:0] | 0x00 | R/W | PAN identifier high byte |

Table 90: Register PANIDH (0xDF4B)

| Bit | Name | Reset | R/W | Description |
|-----|-------------|-------|-----|-------------------------|
| 7:0 | PANIDL[7:0] | 0x00 | R/W | PAN identifier low byte |

Table 91: Register PANIDL (0xDF4C)

| Bit | Name | Reset | R/W | Description |
|-----|-----------------|-------|-----|-------------------------|
| 7:0 | SHORTADDRH[7:0] | 0x00 | R/W | Short address high byte |

Table 92: Register SHORTADDRH (0xDF4D)

| Bit | Name | Reset | R/W | Description |
|-----|-----------------|-------|-----|------------------------|
| 7:0 | SHORTADDRL[7:0] | 0x00 | R/W | Short address low byte |

Table 93: Register SHORTADDRL (0xDF4E)

| Bit | Name | Reset | R/W | Description |
|-----|----------------|-------|-----|---------------------------------------------------------------------------|
| 7 | – | 0 | R0 | Reserved, read as 0. |
| 6:0 | FIFOP_THR[6:0] | 0x40 | R/W | Sets the number of bytes in RXFIFO that is required for FIFOP to go high. |

Table 94: Register IOCFG0 (0xDF4F)

| Bit | Name | Reset | R/W | Description |
|-----|------------|-------|-----|-----------------------------------------------------------------------------------------|
| 7 | – | 0 | R0 | Reserved, read as 0. |
| 6 | OE_CCA | 0 | R/W | CCA is output on P1.7 when this bit is 1 |
| 5 | IO_CCA_POL | 0 | R/W | Polarity of the IO_CCA signal. This bit is xor'ed with the internal CCA signal. |
| 4:0 | IO_CCA_SEL | 00000 | R/W | Multiplexer setting for the CCA signal. Must be 0x00 in order to output the CCA status. |

Table 95: Register IOCFG1 (0xDF50)

| Bit | Name | Reset | R/W | Description |
|-----|------------|-------|-----|----------------------------------------------------------------------------------------|
| 7 | – | 0 | R0 | Reserved, read as 0. |
| 6 | OE_SFD | 0 | R/W | SFD is output on P1.6 when this bit is 1 |
| 5 | IO_SFD_POL | 0 | R/W | Polarity of the IO_SFD signal. This bit is xor'ed with the internal SFD signal. |
| 4:0 | IO_SFD_SEL | 00000 | R/W | Multiplexer setting for the SFD signal. Must be 0x00 in order to output the SFD status |

Table 96: Register IOCFG2 (0xDF51)

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:6 | – | 00 | R0 | Reserved, read as 0. |
| 5:4 | HSSD_SRC | 00 | R/W | Configures the HSSD interface. Only the first 4 settings (compared to CC2420) are used. 00 : Off 01 : Output AGC status (gain setting/peak detector status/accumulator value) 10 : Output ADC I and Q values 11 : Output I/Q after digital down mix and channel filtering |
| 3 | OE_FIFOP | 0 | R/W | FIFOP is output on P1.5 when this bit is 1. |
| 2 | IO_FIFOP_POL | 0 | R/W | Polarity of the IO_FIFOP signal. This bit is xor'ed with the internal FIFOP signal |
| 1 | OE_FIFO | 0 | R/W | FIFO is output on P1.4 when this bit is 1 |
| 0 | IO_FIFO_POL | 0 | R/W | Polarity of the IO_FIFO signal. This bit is xor'ed with the internal FIFO signal |

Table 97: Register IOCFG3 (0xDF52)

| Bit | Name | Reset | R/W | Description |
|-----|----------------|-------|-----|--------------------------------|
| 7:0 | RXFIFOCNT[7:0] | 0x00 | R | Number of bytes in the RX FIFO |

Table 98: Register RXFIFOCNT (0xDF53)

| Bit | Name | Reset | R/W | Description |
|-----|------------------|-------|-----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:6 | – | 00 | R0 | Reserved, read as 0. |
| 5 | ABORTRX_ON_SRXON | 1 | R/W | Abort RX when SRXON strobe is issued 0 : Packet reception is not aborted when SRXON is issued 1 : Packet reception is aborted when SRXON is issued |
| 4 | RX_INTERRUPTED | 0 | R | RX interrupted by strobe command This bit is cleared when the next strobe is detected. 0 : Strobe command detected 1 : Packet reception was interrupted by strobe command |
| 3 | AUTO_TX2RX_OFF | 0 | R/W | Automatically go to RX after TX. Applies to both data packets and ACK packets. 0 : Automatic RX after TX 1 : No automatic RX after TX |
| 2 | RX2RX_TIME_OFF | 0 | R/W | Turns off the 12 symbol timeout after packet reception has ended. Active high. |
| 1 | PENDING_OR | 0 | R/W | This bit is OR'ed with the pending bit from FFCTRL before it goes to the modulator. |
| 0 | ACCEPT_ACKPKT | 1 | R/W | Accept ACK packet control. 0 : Reject all ACK packets 1 : ACK packets are received |

Table 99: Register FSMTTC1 (0xDF54)

| Bit | Name | Reset | R/W | Description |
|-----|--------------|-------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:0 | VERSION[7:0] | 0x03 | R | <p>Chip revision number. The relationship between the value in VERSION[7:0] and the die revision is as follows:</p> <p>0x03 : Die revision D</p> <p>The current number in VERSION[7:0] may not be consistent with past or future die revisions of this product</p> |

Table 100: Register CHVER (0xDF60)

| Bit | Name | Reset | R/W | Description |
|-----|-------------|-------|-----|--------------------------------------------------|
| 7:0 | CHIPID[7:0] | 0x85 | R | Chip identification number. Always read as 0x85. |

Table 101: Register CHIPID (0xDF61)

| Bit | Name | Reset | R/W | Description |
|-----|-----------|-------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:5 | – | 000 | R0 | Reserved, read as 0. |
| 4 | TX_ACTIVE | 0 | R | <p>TX active indicates transmission in progress</p> <p>0 : TX inactive</p> <p>1 : TX active</p> |
| 3 | FIFO | 0 | R | <p>RXFIFO data available</p> <p>0 : No data available in RXFIFO</p> <p>1 : One or more bytes available in RXFIFO</p> |
| 2 | FIFOP | 0 | R | <p>RXFIFO threshold flag</p> <p>0 : Number of bytes in RXFIFO is less or equal threshold set by IOCFG0.FIFOP_THR</p> <p>1 : Number of bytes in RXFIFO is greater than threshold set by IOCFG0.FIFOP_THR</p> <p>Note that if frame filtering/address recognition is enabled this bit is set only when the frame has passed filtering. This bit is also set when a complete frame has been received.</p> |
| 1 | SFD | 0 | R | <p>Start of Frame Delimiter status</p> <p>0 : SFD inactive</p> <p>1 : SFD active</p> |
| 0 | CCA | | R | Clear Channel Assessment |

Table 102: Register RFSTATUS (0xDF62)

| Bit | Name | Reset | R/W | Description |
|-----|------|-------|-----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:4 | – | 0000 | R0 | Reserved, read as 0. |
| 3:0 | TUNE | 1111 | R/W | 32 MHz Crystal Oscillator Tuning value. Adds load capacitance to XOSC_Q1 and XOSC_Q2 pins in linear steps from 0 pF to 15 pF in 16 steps. With reset value zero pF is added 0000 : 15 pF 1111 : 0 pF |

Table 103: Register XOSC32M (0xDF63)²⁰

| Bit | Name | Reset | R/W | Description |
|-----|-------|---------|-----|--------------------------------------------------------------------------------------------------------------------------------------------------|
| 7:1 | – | 0000000 | R0 | Reserved, read as 0. |
| 0 | TXACK | 0 | R/W | TX Acknowledge interrupt enable. 0 : RFIF interrupt is not set for acknowledge frames 1 : RFIF interrupt is set for acknowledge frames |

Table 104: Register IRQSRC (0xDF64)²¹

²⁰ Only for devices with Chip Version register, CHVER.VERSION equal to 0x02 or greater

²¹ Only for devices with Chip Version register, CHVER.VERSION equal to 0x02 or greater

15 Radio Test Output Signals

For debug purposes, the `RFSTATUS.SFD`, `RFSTATUS.FIFO`, `RFSTATUS.FIFOP` and `RFSTATUS.CCA` bits can be output onto P1.7 – P1.4 I/O pins to monitor the status of these signals. These test output signals are selected by the `IOCFG0`, `IOCFG1` and `IOCFG2` registers.

The debug signals are output to the following I/O pins:

- P1.4 – FIFO
- P1.5 – FIFOP
- P1.6 – SFD
- P1.7 - CCA

16 Voltage Regulators

The **CC2430** includes two low drop-out voltage regulators. These are used to provide a 1.8 V power supply to the **CC2430** analog and digital power supplies.

Note: The voltage regulators should not be used to provide power to external circuits because of limited power sourcing capability and also due to noise considerations.

The analog voltage regulator input pin AVDD_RREG is to be connected to the unregulated 2.0 to 3.6 V power supply. The regulated 1.8 V voltage output to the analog parts, is available on the RREG_OUT pin. The digital regulator input pin AVDD_DREG is also to be connected to the unregulated 2.0 to 3.6 V power supply. The output of the digital regulator is connected internally within the **CC2430** to the digital power supply.

The voltage regulators require external components as described in section 11 on page 30.

17 Evaluation Software

Texas Instruments provides users of **CC2430** with a software program, SmartRF® Studio, which may be used for radio performance and functionality evaluation. SmartRF® Studio runs on

16.1 Voltage Regulators Power-on

The analog voltage regulator is disabled by setting the RF register bit RFPWR.RREG_RADIO_PD to 1. When the analog voltage regulator is powered-on by clearing the RFPWR.RREG_RADIO_PD bit, there will be a delay before the regulator is enabled. This delay is programmable through the RFPWR RF register. The interrupt flag RFIF.IRQ_RREG_PD is set when the delay has expired. The delayed power-on can also be observed by polling the RF register bit RFPWR.ADI_RADIO_PD.

The digital voltage regulator is disabled when the **CC2430** is placed in power modes PM2 or PM3 (see section 13.10). When the voltage regulators are disabled, register and RAM contents will be retained while the unregulated 2.0 to 3.6 power supply is present.

Microsoft Windows 95/98 and Microsoft Windows NT/XP/2000. SmartRF® Studio can be downloaded from the Texas Instruments web page:
<http://www.ti.com/lpw>

18 Register overview


| | |
|-------------------------------------------------------------------------|-----|
| DPH0 (0x83) – Data Pointer 0 High Byte | 42 |
| DPL0 (0x82) – Data Pointer 0 Low Byte | 42 |
| DPH1 (0x85) – Data Pointer 1 High Byte | 42 |
| DPL1 (0x84) – Data Pointer 1 Low Byte | 42 |
| DPS (0x92) – Data Pointer Select | 42 |
| MPAGE (0x93) – Memory Page Select | 42 |
| PSW (0xD0) – Program Status Word | 48 |
| ACC (0xE0) – Accumulator | 48 |
| B (0xF0) – B Register | 48 |
| SP (0x81) – Stack Pointer | 49 |
| IEN0 (0xA8) – Interrupt Enable 0 | 55 |
| IEN1 (0xB8) – Interrupt Enable 1 | 56 |
| IEN2 (0x9A) – Interrupt Enable 2 | 57 |
| TCON (0x88) – Interrupt Flags | 58 |
| S0CON (0x98) – Interrupt Flags 2 | 59 |
| S1CON (0x9B) – Interrupt Flags 3 | 59 |
| IRCON (0xC0) – Interrupt Flags 4 | 60 |
| IRCON2 (0xE8) – Interrupt Flags 5 | 61 |
| IP1 (0xB9) – Interrupt Priority 1 | 62 |
| IP0 (0xA9) – Interrupt Priority 0 | 62 |
| MEMCTR (0xC7) – Memory Arbiter Control | 69 |
| FMAP (0x9F) – Flash Bank Map | 70 |
| P0 (0x80) – Port 0 | 75 |
| P1 (0x90) – Port 1 | 75 |
| P2 (0xA0) – Port 2 | 75 |
| PERCFG (0xF1) – Peripheral Control | 76 |
| ADCCFG (0xF2) – ADC Input Configuration | 76 |
| P0SEL (0xF3) – Port 0 Function Select | 76 |
| P1SEL (0xF4) – Port 1 Function Select | 76 |
| P2SEL (0xF5) – Port 2 Function Select | 77 |
| P0DIR (0xFD) – Port 0 Direction | 77 |
| P1DIR (0xFE) – Port 1 Direction | 77 |
| P2DIR (0xFF) – Port 2 Direction | 78 |
| P0INP (0x8F) – Port 0 Input Mode | 78 |
| P1INP (0xF6) – Port 1 Input Mode | 78 |
| P2INP (0xF7) – Port 2 Input Mode | 79 |
| P0IFG (0x89) – Port 0 Interrupt Status Flag | 79 |
| P1IFG (0x8A) – Port 1 Interrupt Status Flag | 79 |
| P2IFG (0x8B) – Port 2 Interrupt Status Flag | 79 |
| PICTL (0x8C) – Port Interrupt Control | 80 |
| P1IEN (0x8D) – Port 1 Interrupt Mask | 80 |
| DMAARM (0xD6) – DMA Channel Arm | 89 |
| DMAREQ (0xD7) – DMA Channel Start Request and Status | 90 |
| DMA0CFGH (0xD5) – DMA Channel 0 Configuration Address High Byte | 90 |
| DMA0CFLG (0xD4) – DMA Channel 0 Configuration Address Low Byte | 90 |
| DMA1CFGH (0xD3) – DMA Channel 1-4 Configuration Address High Byte | 91 |
| DMA1CFLG (0xD2) – DMA Channel 1-4 Configuration Address Low Byte | 91 |
| DMAIRQ (0xD1) – DMA Interrupt Flag | 91 |
| T1CNTH (0xE3) – Timer 1 Counter High | 100 |
| T1CNTL (0xE2) – Timer 1 Counter Low | 100 |
| T1CTL (0xE4) – Timer 1 Control and Status | 100 |

| | |
|--------------------------------------------------------------------|-----|
| T1CCTL0 (0xE5) – Timer 1 Channel 0 Capture/Compare Control | 101 |
| T1CC0H (0xDB) – Timer 1 Channel 0 Capture/Compare Value High | 101 |
| T1CC0L (0xDA) – Timer 1 Channel 0 Capture/Compare Value Low | 101 |
| T1CCTL1 (0xE6) – Timer 1 Channel 1 Capture/Compare Control | 102 |
| T1CC1H (0xDD) – Timer 1 Channel 1 Capture/Compare Value High | 102 |
| T1CC1L (0xDC) – Timer 1 Channel 1 Capture/Compare Value Low | 102 |
| T1CCTL2 (0xE7) – Timer 1 Channel 2 Capture/Compare Control | 103 |
| T1CC2H (0xDF) – Timer 1 Channel 2 Capture/Compare Value High | 103 |
| T1CC2L (0xDE) – Timer 1 Channel 2 Capture/Compare Value Low | 103 |
| T2CNF (0xC3) – Timer 2 Configuration | 107 |
| T2THD (0xA7) – Timer 2 Timer Value High Byte | 108 |
| T2TLD (0xA6) – Timer 2 Timer Value Low Byte | 108 |
| T2CMP (0x94) – Timer 2 Compare Value | 108 |
| T2OF2 (0xA3) – Timer 2 Overflow Count 2 | 108 |
| T2OF1 (0xA2) – Timer 2 Overflow Count 1 | 108 |
| T2OF0 (0xA1) – Timer 2 Overflow Count 0 | 109 |
| T2CAPHPH (0xA5) – Timer 2 Period High Byte | 109 |
| T2CAPLPL (0xA4) – Timer 2 Period Low Byte | 109 |
| T2PEROF2 (0x9E) – Timer 2 Overflow Capture/Compare 2 | 109 |
| T2PEROF1 (0x9D) – Timer 2 Overflow Capture/Compare 1 | 110 |
| T2PEROF0 (0x9C) – Timer 2 Overflow Capture/Compare 0 | 110 |
| ST2 (0x97) – Sleep Timer 2 | 111 |
| ST1 (0x96) – Sleep Timer 1 | 111 |
| ST0 (0x95) – Sleep Timer 0 | 111 |
| T3CNT (0xCA) – Timer 3 Counter | 115 |
| T3CTL (0xCB) – Timer 3 Control | 115 |
| T3CCTL0 (0xCC) – Timer 3 Channel 0 Compare Control | 116 |
| T3CC0 (0xCD) – Timer 3 Channel 0 Compare Value | 116 |
| T3CCTL1 (0xCE) – Timer 3 Channel 1 Compare Control | 117 |
| T3CC1 (0xCF) – Timer 3 Channel 1 Compare Value | 117 |
| T4CNT (0xEA) – Timer 4 Counter | 117 |
| T4CTL (0xEB) – Timer 4 Control | 118 |
| T4CCTL0 (0xEC) – Timer 4 Channel 0 Compare Control | 119 |
| T4CC0 (0xED) – Timer 4 Channel 0 Compare Value | 119 |
| T4CCTL1 (0xEE) – Timer 4 Channel 1 Compare Control | 120 |
| T4CC1 (0xEF) – Timer 4 Channel 1 Compare Value | 120 |
| TIMIF (0xD8) – Timers 1/3/4 Interrupt Mask/Flag | 121 |
| ADCL (0xBA) – ADC Data Low | 124 |
| ADCH (0xBB) – ADC Data High | 125 |
| ADCCON1 (0xB4) – ADC Control 1 | 125 |
| ADCCON2 (0xB5) – ADC Control 2 | 126 |
| ADCCON3 (0xB6) – ADC Control 3 | 127 |
| RNDL (0xBC) – Random Number Generator Data Low Byte | 129 |
| RNDH (0xBD) – Random Number Generator Data High Byte | 129 |
| ENCCS (0xB3) – Encryption Control and Status | 134 |
| ENCDI (0xB1) – Encryption Input Data | 134 |
| ENCDO (0xB2) – Encryption Output Data | 134 |
| PCON (0x87) – Power Mode Control | 138 |
| SLEEP (0xBE) – Sleep Mode Control | 139 |
| CLKCON (0xC6) – Clock Control | 140 |
| WDCTL (0xC9) – Watchdog Timer Control | 143 |
| U0CSR (0x86) – USART 0 Control and Status | 148 |
| U0UCR (0xC4) – USART 0 UART Control | 149 |
| U0GCR (0xC5) – USART 0 Generic Control | 150 |

| | |
|------------------------------------------------------------|-----|
| U0DBUF (0xC1) – USART 0 Receive/Transmit Data Buffer | 150 |
| U0BAUD (0xC2) – USART 0 Baud Rate Control..... | 150 |
| U1CSR (0xF8) – USART 1 Control and Status | 151 |
| U1UCR (0xFB) – USART 1 UART Control | 152 |
| U1GCR (0xFC) – USART 1 Generic Control..... | 153 |
| U1DBUF (0xF9) – USART 1 Receive/Transmit Data Buffer | 153 |
| U1BAUD (0xFA) – USART 1 Baud Rate Control | 153 |
| FCTL (0xAE) – Flash Control | 160 |
| FWDATA (0xAF) – Flash Write Data..... | 160 |
| FADDRH (0xAD) – Flash Address High Byte..... | 160 |
| FADDRL (0xAC) – Flash Address Low Byte | 160 |
| FWT (0xAB) – Flash Write Timing | 160 |
| RFIF (0xE9) – RF Interrupt Flags | 165 |
| RFIM (0x91) – RF Interrupt Mask | 166 |
| RFD (0xD9) – RF Data | 167 |
| RFST (0xE1) – RF CSMA-CA / Strobe Processor | 187 |

19 Package Description (QLP 48)

All dimensions are in millimeters, angles in degrees. NOTE: The **CC2430** is available in RoHS lead-free package only. Compliant with JEDEC MS-020.

**Figure 59: Package dimensions drawing**

| Quad Leadless Package (QLP) | | | | | | | | | | |
|---------------------------------------------|-----|-----|------|-----|------|-----|------|-----|------|------|
| | | D | D1 | E | E1 | e | b | L | D2 | E2 |
| QLP 48 | Min | 6.9 | 6.65 | 6.9 | 6.65 | | 0.18 | 0.3 | 5.05 | 5.05 |
| | | 7.0 | 6.75 | 7.0 | 6.75 | 0.5 | | 0.4 | 5.10 | 5.10 |
| | Max | 7.1 | 6.85 | 7.1 | 6.85 | | 0.30 | 0.5 | 5.15 | 5.15 |
| The overall package height is 0.85 +/- 0.05 | | | | | | | | | | |
| All dimensions in mm | | | | | | | | | | |

Table 105: Package dimensions

19.5 Carrier tape and reel specification

Carrier tape and reel is in accordance with EIA Specification 481.

| Tape and Reel Specification | | | | | |
|-----------------------------|------------|-----------------|------------|---------------|----------------|
| Package | Tape Width | Component Pitch | Hole Pitch | Reel Diameter | Units per Reel |
| QLP 48 | 16mm | 12mm | 4mm | 13 inches | 2500 |

Table 108: Carrier tape and reel specification

20 Ordering Information

| Ordering part number | Description | MOQ |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|
| CC2430F128RTC | CC2430, QLP48 package, RoHS compliant Pb-free assembly, trays with 260 pcs per tray, 128 Kbytes in-system programmable flash memory, System-on-chip RF transceiver. | 260 |
| CC2430F128RTCR | CC2430, QLP48 package, RoHS compliant Pb-free assembly, T&R with 2500 pcs per reel, 128 Kbytes in-system programmable flash memory, System-on-chip RF transceiver. | 2,500 |
| CC2430ZF128RTC | CC2430, QLP48 package, RoHS compliant Pb-free assembly, trays with 260 pcs per tray, 128 Kbytes in-system programmable flash memory, System-on-chip RF transceiver, including royalty for using TI's ZigBee Software Stack, Z-Stack™, in an end product | 260 |
| CC2430ZF128RTCR | CC2430, QLP48 package, RoHS compliant Pb-free assembly, T&R with 2500 pcs per reel, 128 Kbytes in-system programmable flash memory, System-on-chip RF transceiver, including royalty for using TI's ZigBee Software Stack, Z-Stack™, in an end product | 2,500 |
| CC2430F64RTC | CC2430, QLP48 package, RoHS compliant Pb-free assembly, trays with 260 pcs per tray, 64 Kbytes in-system programmable flash memory, System-on-chip RF transceiver. | 260 |
| CC2430F64RTCR | CC2430, QLP48 package, RoHS compliant Pb-free assembly, T&R with 2500 pcs per reel, 64 Kbytes in-system programmable flash memory, System-on-chip RF transceiver. | 2,500 |
| CC2430F32RTC | CC2430, QLP48 package, RoHS compliant Pb-free assembly, trays with 260 pcs per tray, 32 Kbytes in-system programmable flash memory, System-on-chip RF transceiver. | 260 |
| CC2430F32RTCR | CC2430, QLP48 package, RoHS compliant Pb-free assembly, T&R with 2500 pcs per reel, 32 Kbytes in-system programmable flash memory, System-on-chip RF transceiver. | 2,500 |
| CC2430DK | CC2430 ZigBee DK Development kit. | 1 |
| CC2430ZDK Pro | CC2430 ZigBee DK Development kit including support and training | 1 |

MOQ = Minimum Order Quantity

T&R = tape and reel

Table 109: Ordering Information

21 General Information

21.1 Document History

Table 110: Document History

| Revision | Date | Description/Changes |
|----------|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2.01 | 2006-12-19 | Updated section 7 tables with reviewed values, rearranged footnotes and measurement criteria. Changed header to reflect release to market. Add max time that Timer 2 can be stopped for synchronous start correct |
| 2.0 | 2006-12-04 | Deleted product status information in all page headers and footers Deleted product status information on first page Changed start address of locations and number of bytes in XDATA that are not retained in PM2/3 Clarifications made and figure added in section 13.10 Added information in SLEEP and CLKCON register descriptions Clarifications made in section 13.14 Added pull-up resistor for P2_2, in sections 11.5, 12.9.1 and 13.1.6, Table 24 Updated CHVER register value Clarified text and modified graphics in figures in sections 12.3.1 and 12.3.2 Added section 13.1.9, updated description for PICTL.PADSC Updated characteristics for RF receiver, Table 6, RF transmit, Table 7 and Frequency Synthesizer, Table 12 and Temperature sensor, Table 13 Updated characteristics, Table 4 Updated Address Information and Disclaimer sections Plastic tube is replaced by tray, section 19.4 Minimum order quantity is changed, Table 109 Watchdog counter reset in PM2/3 Updated flash DMA trigger from flash, and flash erase from flash memory Removed Timer 3/4 capture Updated Table 5 |

| Revision | Date | Description/Changes |
|----------|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1.04 | 2006-09-29 | SPI maximum bit rate Description of CSP WAITX and WAITW instructions Modified Timer 1 output compare mode figures (Figure 23, Figure 24 and Figure 25) Updated Table 35 Corrected register ADCTSTL bit numbers 16 MHz RC oscillator is referred to as High-Frequency RC oscillator instead of High-Speed RC oscillator Added FMAP register Removed Timer 1 RF capture event Updated ADC characteristics, Table 14. Address information, section 22 Correct register U0UCR/U1UCR bit D9 description, added 3-/4-wire interface description, section 13.13.2 Added RFSTATUS.SFD timing delay in section 14.9 Changed ADCCON2.SCH read value in section 13.7.2.5 Additional text about DMAARM, section 13.2.4 Added section 13.14.1, other added text in section 13.14 Added RX_INFINITE state in Figure 54 Updated UxCSR.RX_BYTE and UxCSR.TX_BYTE descriptions Expanded DMA VLEN description, section 13.2.2.4 Update MDMCTRL0H Updated descriptions for T2OF2:T2OF1:T2OF0 in section 13.4.1.7 Removed RXFIFO double-flushing, section 14.8 Updated CLKCON description Port registers P0 and P1 are reachable for DMA (section 13.1.3) 32 kHz RC oscillator calibration may be disabled, section 13.10.5 SLEEP_OSC_PD is not cleared when CLKCON.OSC toggles (section 13.10.8) Added 32 MHz crystal oscillator tuning (sections 11.3 and 12.8) Added registers XSOSC32M and IRQSRC Acknowledge frames generate interrupt, section 14.19 Added RF test registers in section 14.35 SPI slave MISO not tri-stated, section 13.13.3 Updated MDMCTRL0L.AUTOACK Updated RFSTATUS.FIFOP Updated output power levels, Table 43 Added note that USART baud rate must be set before other settings, section 13.13.4 Updated T2CNF.RUN description Updated differential balun inductor values, Table 24 Updated 32 kHz RC oscillator freq, Table 10 XDATA memory locations with no data retention increased with 4 bytes |
| 1.03.1 | 2006-09-27 | Updated first page header |

| Revision | Date | Description/Changes |
|----------|------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1.03 | 2006-05-12 | <p>Updated ADC characteristics, Table 14. Updated DMAREQ, DMAARM and changed section 13.2 first paragraph, section 13.2.4 and Figure 17 Registers UxBUF renamed as UxDBUF. EAL renamed as EA. Added code protection and encryption disclaimers. Clarified flash write description Updated DC characteristics (Table 20) Added information about clearing PxIFG in section 13.1.2 Removed T2CON Updated Table 45 Changed formatting of Table 25 STXCALN/ISTXCALN are intended for test only Modified Figure 39 Updated MDMCTRL0L.PREAMBLE_LENGTH Clarified use of ADC conversions triggered by ADCCON3 Clarified RNDL/RNDH descriptions, renamed Random Generator to Random Number Generator Expanded description and changed reset value for SLEEP.OSC_PD Corrected P0/P1/P2 reset values Changed reference to SXOSCON to CLKCON Changed RFSTATUS.SFD description</p> <p style="text-align: center;">Corrected references to</p> <p>Figure 44 and Figure 45 Corrected descriptions in FSMTCH/FSMTCL Corrected numbers in Table 32 Various clarifications in Timers, ADC and Power Management Changed typical start-up time for 32 MHz crystal oscillator Corrected T1CCTL1.CMP and T1CCTL2.CMP Updated address information Changed Random Number Generator seeding; modified ADCCON1.RCTRL and section 13.8.2.2 Changed descriptions for T2PEROF2, T2PEROF1 and T2PEROF0 Changed Figure 15 and section 12.3.2; unified CODE space uses memory banking Added CLKCON.CLKSPD bit, and altered descriptions in CLKCON Corrected RSSIL description Updated ordering information Added SSN description section 13.13.3 and updated Table 16 and Figure 2 Preliminary status updated</p> |
| 1.02 | 2005-10-03 | Added ADC external trigger (section 13.1.5 and 13.7.2). Updated sensitivity. Corrected Application circuit |
| 1.01 | 2005-09-15 | Updated Table 103, Units per reel |
| 1.0 | 2005-09-12 | First release, preliminary |

21.2 Product Status Definitions

| Data Sheet Identification | Product Status | Definition |
|---------------------------|---------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advance Information | Planned or Under Development | This data sheet contains the design specifications for product development. Specifications may change in any manner without notice. |
| Preliminary | Engineering Samples and Pre-Production Prototypes | This data sheet contains preliminary data, and supplementary data will be published at a later date. TI reserves the right to make changes at any time without notice in order to improve design and supply the best possible product. The product is not yet fully qualified at this point. |
| No Identification Noted | Full Production | This data sheet contains the final specifications. TI reserves the right to make changes at any time without notice in order to improve design and supply the best possible product. |
| Obsolete | Not In Production | This data sheet contains specifications on a product that has been discontinued by TI. The data sheet is printed for reference information only. |

Table 111: Product Status Definitions**22 Address Information**

Texas Instruments Norway AS
 Gaustadalléen 21
 N-0349 Oslo
 NORWAY
 Tel: +47 22 95 85 44
 Fax: +47 22 95 85 46
 Web site: <http://www.ti.com/lpw>

23 TI Worldwide Technical Support**Internet**

TI Semiconductor Product Information Center Home Page: support.ti.com
 TI Semiconductor KnowledgeBase Home Page: support.ti.com/sc/knowledgebase

Product Information Centers**Americas**

Phone: +1(972) 644-5580
Fax: +1(972) 927-6377
Internet/Email: support.ti.com/sc/pic/americas.htm

Europe, Middle East and Africa

Phone:
 Belgium (English) +32 (0) 27 45 54 32
 Finland (English) +358 (0) 9 25173948
 France +33 (0) 1 30 70 11 64
 Germany +49 (0) 8161 80 33 11
 Israel (English) 180 949 0107
 Italy 800 79 11 37
 Netherlands (English) +31 (0) 546 87 95 45
 Russia +7 (0) 95 363 4824
 Spain +34 902 35 40 28



CC2430

Sweden (English) +46 (0) 8587 555 22
United Kingdom +44 (0) 1604 66 33 99
Fax: +49 (0) 8161 80 2045
Internet: support.ti.com/sc/pic/euro.htm

Japan

| | | |
|-----------------------|---------------|--------------------------------------------------------------------------------------|
| Fax | International | +81-3-3344-5317 |
| | Domestic | 0120-81-0036 |
| Internet/Email | International | support.ti.com/sc/pic/japan.htm |
| | Domestic | www.tij.co.jp/pic |

Asia

| | | |
|-----------------|---------------|----------------------------------|
| Phone | International | +886-2-23786800 |
| | Domestic | <u>Toll-Free Number</u> |
| | Australia | 1-800-999-084 |
| | China | 800-820-8682 |
| | Hong Kong | 800-96-5941 |
| | India | +91-80-51381665 (Toll) |
| | Indonesia | 001-803-8861-1006 |
| | Korea | 080-551-2804 |
| | Malaysia | 1-800-80-3973 |
| | New Zealand | 0800-446-934 |
| | Philippines | 1-800-765-7404 |
| | Singapore | 800-886-1028 |
| | Taiwan | 0800-006800 |
| | Thailand | 001-800-886-0010 |
| Fax | | +886-2-2378-6808 |
| Email | | tiasia@ti.com or ti-china@ti.com |
| Internet | | support.ti.com/sc/pic/asia.htm |

Important Notice

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products

| | |
|--------------------|--------------------------------------------------------------------|
| Amplifiers | amplifier.ti.com |
| Data Converters | dataconverter.ti.com |
| DSP | dsp.ti.com |
| Interface | interface.ti.com |
| Logic | logic.ti.com |
| Power Mgmt | power.ti.com |
| Microcontrollers | microcontroller.ti.com |
| Low Power Wireless | www.ti.com/lpw |

Applications

| | |
|--------------------|--------------------------------------------------------------------------|
| Audio | www.ti.com/audio |
| Automotive | www.ti.com/automotive |
| Broadband | www.ti.com/broadband |
| Digital Control | www.ti.com/digitalcontrol |
| Military | www.ti.com/military |
| Optical Networking | www.ti.com/opticalnetwork |
| Security | www.ti.com/security |
| Telephony | www.ti.com/telephony |
| Video & Imaging | www.ti.com/video |
| Wireless | www.ti.com/wireless |

Mailing Address: Texas Instruments
Post Office Box 655303 Dallas, Texas 75265

© 2006, Texas Instruments. All rights reserved.